

Plain range: Excel sees cells, identified by column letters and row numbers

No name: formulas must refer to cell addresses

Formula copied by hand

	A	G	H	K	P
1	SalesInvoiceLineID	Quantity	BaseListPrice	LineTotal	ListAmount
10645	10644	6.00	374.22	2,177.94	2,245.32
10646	10645	2.00	382.45	688.42	764.90
10647	10646	3.74	856.08	2,817.53	3,201.74
10648	10647	0.68	563.52	344.88	383.19

Column formula, copied by hand:
P10646 holds =ROUND(G10646*H10646,2). The formula was typed in P2 and copied down, so every row has its own copy. Rows added below the data get no formula until you copy it again.

Total: =SUM(K2:K27934)
The formula names fixed cells. Rows added below row 27934 are left out of the total, and nothing warns you.

Excel Table: Excel sees a named dataset with named columns

Table name: SalesInvoiceLine

Calculated column

	A	G	H	K	P
1	SalesInvoiceLineID ▾	Quantity ▾	BaseListPrice ▾	LineTotal ▾	ListAmount ▾
10645	10644	6.00	374.22	2,177.94	2,245.32
10646	10645	2.00	382.45	688.42	764.90
10647	10646	3.74	856.08	2,817.53	3,201.74
10648	10647	0.68	563.52	344.88	383.19

Calculated column:
=ROUND([@Quantity]*[@BaseListPrice],2)
One formula for the whole column. Excel fills it into every row, including rows added later.

Total: =SUM(SalesInvoiceLine[LineTotal])
Includes every row the Table holds, however many there are.

Both views show the same cells. Shaded row: line 10645, the Alder Desk sold on invoice SI-2025-007947, which you traced in Tutorial 3.2. The selected cell holds the plain range's formula for that line.