

```
245 -- Tutorial 12.2, test P4: purchase order approvals
246 -- Population: all purchase orders; expected: no rows
247 WITH ApprovalExceptions AS (
248     SELECT 'Self-approved' AS Test, po.PONumber, po.OrderTotal
249     FROM PurchaseOrder AS po
250     WHERE po.CreatedByEmployeeID = po.ApprovedByEmployeeID
251     UNION ALL
252     SELECT 'Above approver limit', po.PONumber, po.OrderTotal
253     FROM PurchaseOrder AS po
254     INNER JOIN Employee AS e
255         ON e.EmployeeID = po.ApprovedByEmployeeID
256     WHERE po.OrderTotal > e.MaxApprovalAmount
257     UNION ALL
258     SELECT 'Approved after termination', po.PONumber, po.OrderTotal
259     FROM PurchaseOrder AS po
260     INNER JOIN Employee AS e
261         ON e.EmployeeID = po.ApprovedByEmployeeID
262     WHERE e.TerminationDate IS NOT NULL
263         AND po.OrderDate > e.TerminationDate
264 )
265 SELECT Test, COUNT(*) AS Orders, ROUND(SUM(OrderTotal), 2) AS OrderValue
266 FROM ApprovalExceptions
267 GROUP BY Test
268 ORDER BY Orders DESC;
```

	Test	Orders	OrderValue
1	Above approver limit	13	705779.39
2	Self-approved	9	651830.75
3	Approved after termination	3	15419.28

Execution finished without errors.
Result: 3 rows returned
At line 247:
WITH ApprovalExceptions AS (

Outlined: the three tests, with the number of purchase orders each flags and their value. Most of the fourteen orders fail two tests.