

New Database

Open Database ▾

Write Changes

Revert Changes

Database Structure

Browse Data

Edit Pragas

Execute SQL

Open SQL file(s)

Save SQL file ▾

▶ Execute all/selected SQL

Audit.sql

```
1  /* Audit.sql: internal audit query library
2     Engagement: records behind the manufacturing variance, fiscal 2026
3     Database: CharlesRiver_Work.sqlite (a copy of CharlesRiver.sqlite)
4     Prepared by: your name, date; reviewed by: name, date */
5
6  -- Test 1.1: journal entry population
7  -- Objective: JournalEntry holds every entry the ledger posted
8  -- Population: all journal entries; reconciled to GLEntry debits
9  -- Expected: counts and totals agree to the cent
10 SELECT
11     (SELECT COUNT(*) FROM JournalEntry) AS Entries,
12     (SELECT ROUND(SUM(TotalAmount), 2) FROM JournalEntry) AS EntryTotal,
13     (SELECT COUNT(DISTINCT SourceDocumentID) FROM GLEntry
14      WHERE SourceDocumentType = 'JournalEntry') AS PostedEntries,
15     (SELECT ROUND(SUM(Debit), 2) FROM GLEntry
16      WHERE SourceDocumentType = 'JournalEntry') AS PostedDebits;
17
18 -- Test 1.2: postings with no document, documents with no posting
19 -- Objective: existence and completeness of the ledger's postings
20 -- Population: GLEntry by SourceDocumentType; each document table
21 -- Expected: no rows. Found 6 PayrollPayment postings (finding 1)
22 SELECT 'Posting with no payroll payment' AS Test,
23     gl.GLEntryID AS RecordID, gl.PostingDate AS RecordDate,
24     gl.Debit + gl.Credit AS Amount
25 FROM GLEntry AS gl
26     LEFT JOIN PayrollPayment AS pp
27         ON pp.PayrollPaymentID = gl.SourceDocumentID
28 WHERE gl.SourceDocumentType = 'PayrollPayment'
29     AND pp.PayrollPaymentID IS NULL
30 UNION ALL
31 SELECT 'Posting with no supplier payment', gl.GLEntryID,
```

The header records the engagement, the data, and who prepared and reviewed the script. Each test states its objective, population, and expected result. The script continues below the lines shown.