B16 | *fx* | =IF(COUNTIFS(Account!A:A,A16)=0,"orphan","ok")

	A	B	C	D	E	F	G	H	I
1	**Child table**	**Foreign key**	**Parent table**	**Primary key**	**Rows**	**Blank**	**Orphans**	**Blank allowed because**	**Verdict**
2	SalesOrder	CustomerID	Customer	CustomerID	5819	0	0	never blank	Maintained
3	SalesOrderLine	ItemID	Item	ItemID	22269	0	0	never blank	Maintained
4	SalesOrderLine	SalesOrderID	SalesOrder	SalesOrderID	22269	0	0	never blank	Maintained
5	ShipmentLine	SalesOrderLineID	SalesOrderLine	SalesOrderLineID	27503	0	0	never blank	Maintained
6	SalesInvoice	CustomerID	Customer	CustomerID	20914	0	0	never blank	Maintained
7	SalesInvoiceLine	SalesInvoiceID	SalesInvoice	SalesInvoiceID	27933	0	0	never blank	Maintained
8	SalesInvoiceLine	ShipmentLineID	ShipmentLine	ShipmentLineID	27933	439	0	design services	Maintained
9	CashReceiptApplication	SalesInvoiceID	SalesInvoice	SalesInvoiceID	27117	0	0	never blank	Maintained
10	CashReceipt	SalesInvoiceID	SalesInvoice	SalesInvoiceID	7409	6878	0	the link is in the application table	Maintained
11	GLEntry	AccountID	Account	AccountID	815921	0	0	never blank	Maintained
12	GLEntry	CostCenterID	CostCenter	CostCenterID	815921	115623	0	balance sheet and other rows with no cost center	Maintained
13	Account	ParentAccountID	Account	AccountID	104	8	0	top-level accounts	Maintained
14									
15	**Row Labels**	**In Account?**							
16	2	ok							
17	3	ok							
18	5	ok							
19	6	ok							
			rows 20 to 85 are scrolled out of view						
86	104	ok							
87									
88	**Misses**	**0**							

Account | GLEntry | **Integrity Tests**

A finished answer: one row for each of the 12 relationships, with counts of rows, blanks and orphans and a reason for every blank. The PivotTable below the log lists the 71 AccountID values the ledger uses, and each is looked up in the AccountID column of Account (the formula bar shows the lookup of the first). Outlined: the Orphans and Verdict columns, and the lookup, whose 0 misses are counted in the last row.