meant → after the fill meant → after the fill

	J	K	M	O	P	Q
1	**Discount**	**LineTotal**	**PromotionID**	**PricingMethod**	**ListAmount**	**DiscountAmount**
2	0	182.99		Segment Price List	203.30	0.00
3	0	2,844.18		Segment Price List	3,025.71	0.00

Columns A to I, L and N of SalesInvoiceLine are hidden. ListAmount and DiscountAmount are the calculated columns of Tutorial 4.1.

1 **Typed in B16, as in Step 5 of Tutorial 4.2**

B16 shows 469

Counts the Approved Override lines with a discount of 0%.

B16 *fx* =COUNTIFS(SalesInvoiceLine[**PricingMethod**],$A16,SalesInvoiceLine[**Discount**],B$15)

2 **Filled one column to the right with the fill handle**

C16 shows 0

Each column name moved to the next column of the Table. No error appears, and the count is wrong.

C16 *fx* =COUNTIFS(SalesInvoiceLine[**ListAmount**],$A16,SalesInvoiceLine[**LineTotal**],C$15)

3 **Copied from B16 and pasted into C16**

C16 shows 10

The column names stayed; only $A16 and the rate cell moved, so C16 counts the 8% lines.

C16 *fx* =COUNTIFS(SalesInvoiceLine[**PricingMethod**],$A16,SalesInvoiceLine[**Discount**],C$15)

Two ways to keep the columns where they are

Paste instead of filling. Copy the cell and paste it: structured references stay as they are.

Lock the column by writing it with a column range, which a fill leaves alone:

=COUNTIFS(SalesInvoiceLine[**[PricingMethod]:[PricingMethod]**],$A16,SalesInvoiceLine[**[Discount]:[Discount]**],B$15)

Teal outline and teal names (bold): the columns the formula means. Coral outline and coral names (bold): the columns it reads after a fill across. Click a cell in the middle of the result and read the formula bar: that is how a drift shows.