DB Browser for SQLite - C:\Users\you\Documents\CharlesRiver_Work.sqlite

New Database | Open Database ▾ | Write Changes | Revert Changes

Database Structure | Browse Data | Edit Pragmas | **Execute SQL**

Open SQL file(s) | Save SQL file ▾ | ▶ **Execute all/selected SQL**

Ex 9.6.sql

```
40  -- Requirement (2): time clock entries with no ClockOutTime
41  -- Population: TimeClockEntry, ClockOutTime NULL; expected: 3 entries, employee 85, Pending
42  SELECT TimeClockEntryID, EmployeeID, WorkDate, ClockInTime,
43      COALESCE(ClockOutTime, 'missing') AS ClockOut,
44      RegularHours, OvertimeHours, ClockStatus
45  FROM TimeClockEntry
46  WHERE ClockOutTime IS NULL
47  ORDER BY WorkDate;
```

	TimeClockEntryID	EmployeeID	WorkDate	ClockInTime	ClockOut	RegularHours	OvertimeHours	ClockStatus
1	1	85	2024-01-01	2024-01-01 10:00:00	missing	7.66	1.44	Pending
2	17846	85	2025-01-01	2025-01-01 10:00:00	missing	7.89	0.75	Pending
3	36072	85	2026-01-01	2026-01-01 10:00:00	missing	8.23	0.74	Pending

Execution finished without errors.
Result: 3 rows returned
At line 42:
SELECT TimeClockEntryID, EmployeeID, WorkDate, ClockInTime,

Outlined: the word missing, which COALESCE shows where ClockOutTime is NULL. All 3 entries are for employee 85 and all are Pending, yet each records 8.64 to 9.1 hours. Pending is a related test, not the same one: 5 entries are Pending and 2 of them have a clock-out.