DB Browser for SQLite - C:\Users\you\Documents\CharlesRiver_Work.sqlite

New Database | Open Database ▾ | Write Changes | Revert Changes

Database Structure | Browse Data | Edit Pragmas | **Execute SQL**

Open SQL file(s) | Save SQL file ▾ | ▶ Execute all/selected SQL

Ex 10.3.sql

```
29  -- Requirement (2): the same analysis grouped by CustomerName
30  -- Population: as (1); expected: 210 rows, one fewer than (1)
31  SELECT c.CustomerName, COUNT(*) AS Orders,
32      ROUND(SUM(so.OrderTotal), 2) AS TotalOrdered,
33      ROUND(AVG(so.OrderTotal), 2) AS AverageOrder
34  FROM SalesOrder AS so
35      INNER JOIN Customer AS c ON c.CustomerID = so.CustomerID
36  GROUP BY c.CustomerName
37  ORDER BY AverageOrder DESC;
```

	CustomerName	Orders	TotalOrdered	AverageOrder
18	Willis and Sons	62	1321877.76	21320.61
19	Brady Group	60	1262710.46	21045.17
20	Patel, Nash and Hoffman	53	1087361.8	20516.26
21	Brown LLC	71	1443258.32	20327.58
22	Gillespie-Walker	36	704956.9	19582.14
23	Estrada, White and Keller	46	873580.51	18990.88
24	Walker Ltd	33	620346.58	18798.38

Execution finished without errors.
Result: 210 rows returned
At line 31:
SELECT c.CustomerName, COUNT(*) AS Orders,

Outlined: the Brown LLC row, 71 orders averaging 20,327.58, one row for two customers: customer 5 (Design Trade, 20 orders, 10,258.01) and customer 173 (Strategic, 51 orders, 24,276.43). The pane reports 210 rows, one fewer than the 211 of the grouping by CustomerID, and the grid is scrolled to rows 18 to 24, where the merged row ranks 21st; by key the two customers rank 8th and 137th.