DB Browser for SQLite - C:\Users\you\Documents\CharlesRiver_Work.sqlite

New Database | Open Database ▾ | Write Changes | Revert Changes

Database Structure | Browse Data | Edit Pragmas | **Execute SQL**

Open SQL file(s) | Save SQL file ▾ | ▶ **Execute all/selected SQL**

Ex 10.6.sql

```
43  -- Requirement (2): the fan-out of joining invoices to payments, supplier 1
44  -- Population: supplier 1's invoices and payments through 2026-12-31; expected: 152,880 rows, not 390 or 392
45  SELECT COUNT(*) AS JoinedRows
46  FROM PurchaseInvoice AS pi
47      INNER JOIN DisbursementPayment AS dp
48          ON dp.SupplierID = pi.SupplierID
49  WHERE pi.SupplierID = 1 AND pi.InvoiceDate <= '2026-12-31'
50      AND dp.PaymentDate <= '2026-12-31';
```

	JoinedRows
1	152880

Execution finished without errors.
Result: 1 rows returned
At line 45:
SELECT COUNT(*) AS JoinedRows

Outlined: 152,880 rows, which is 390 invoices times 392 payments of supplier 1: the two tables share only SupplierID, so every invoice meets every payment. Summing GrandTotal over this join gives $147,941,203.76 where the invoices total $377,401.03. Total each table on its own, then join the totals.