DB Browser for SQLite - C:\Users\you\Documents\CharlesRiver_Work.sqlite

New Database | Open Database | Write Changes | Revert Changes

Database Structure | Browse Data | Edit Pragmas | Execute SQL

Open SQL file(s) | Save SQL file | ▶ Execute all/selected SQL

SQL 1

```
1  -- Tied rows: the default window against ROWS UNBOUNDED PRECEDING
2  -- Population: the Furniture items, ten rows; expected: a tied pair shares a rank and a default total
3  SELECT ItemCode, StandardLaborHoursPerUnit AS Hours,
4      RANK() OVER w AS RankNum,
5      ROW_NUMBER() OVER w AS RowNum,
6      ROUND(SUM(StandardLaborHoursPerUnit) OVER w, 2) AS DefaultTotal,
7      ROUND(SUM(StandardLaborHoursPerUnit) OVER
8          (w ROWS UNBOUNDED PRECEDING), 2) AS FrameTotal
9  FROM Item
10 WHERE ItemGroup = 'Furniture'
11 WINDOW w AS (ORDER BY StandardLaborHoursPerUnit DESC)
12 ORDER BY StandardLaborHoursPerUnit DESC, ItemCode
13 LIMIT 10;
```

	ItemCode	Hours	RankNum	RowNum	DefaultTotal	FrameTotal
1	FUR-CTB-0027	2.14	1	1	2.14	2.14
2	FUR-TBL-0017	2.12	2	2	4.26	4.26
3	FUR-DSK-0011	2.1	3	3	6.36	6.36
4	FUR-DSK-0051	2.07	4	4	8.43	8.43
5	FUR-CTB-0014	2.05	5	5	10.48	10.48
6	FUR-CON-0077	2.04	6	6	12.52	12.52
7	FUR-DSK-0083	1.99	7	8	16.5	16.5
8	FUR-TBL-0008	1.99	7	7	16.5	14.51
9	FUR-SDB-0002	1.97	9	9	20.44	18.47
10	FUR-TBL-0033	1.97	9	10	20.44	20.44

Execution finished without errors.
Result: 10 rows returned
At line 3:
SELECT ItemCode, StandardLaborHoursPerUnit AS Hours,

Outlined: the first tied pair, FUR-DSK-0083 and FUR-TBL-0008, both 1.99 hours. They share rank 7 and the default running total 16.50, because the default window runs through the peers of the current row; ROW_NUMBER gives them 8 and 7, and the ROWS frame totals 16.50 and 14.51, in the order the window met the pair, which is not the order of the result and can differ between SQLite versions. The grid is the first 10 rows of the Furniture items.