DB Browser for SQLite - C:\Users\you\Documents\CharlesRiver_Work.sqlite

New Database | Open Database | Write Changes | Revert Changes

Database Structure | Browse Data | Edit Pragmas | **Execute SQL**

Open SQL file(s) | Save SQL file | **▶ Execute all/selected SQL**

Ex 11.6.sql

```
54  Runs AS (
55      SELECT RequisitionID AS MiddleID, PreviousID, NextID
56      FROM Neighbors
57      WHERE Amount = PreviousAmount AND Amount = NextAmount
58  )
59  SELECT r.MiddleID, a.RequisitionID, a.RequisitionNumber, a.RequestDate,
60      a.Amount, a.RequestedByEmployeeID, a.ApprovedByEmployeeID, a.Status
61  FROM Runs AS r
62      INNER JOIN Amounts AS a
63          ON a.RequisitionID BETWEEN r.PreviousID AND r.NextID
64  ORDER BY a.RequisitionID;
```

	MiddleID	RequisitionID	RequisitionNumber	RequestDate	Amount	RequestedByEmployeeID	ApprovedByEmployeeID	Status
1	4715	4714	PR-2025-004714	2025-01-01	4990.92	80	*NULL*	Converted to PO
2	4715	4715	PR-2025-004715	2025-01-01	4990.92	76	*NULL*	Converted to PO
3	4715	4716	PR-2025-004716	2025-01-01	4990.92	80	2	Converted to PO
4	13259	13258	PR-2026-013258	2026-01-01	4990.92	21	*NULL*	Converted to PO
5	13259	13259	PR-2026-013259	2026-01-01	4990.92	74	*NULL*	Converted to PO
6	13259	13260	PR-2026-013260	2026-01-01	4990.92	78	2	Converted to PO

Execution finished without errors.
Result: 6 rows returned
At line 40:
WITH Amounts AS (

Outlined: the four ApprovedByEmployeeID cells that are NULL. Each run of three requisitions for $4,990.92 has two with no approver, and the third was approved by employee 2, the chief financial officer; the runs are dated 2025-01-01 and 2026-01-01, and all six are Converted to PO. MiddleID names the one row that LAG and LEAD flag (4715 and 13259); the join back lists the neighbors on each side. The editor is scrolled to the foot of the query.