DB Browser for SQLite - C:\Users\you\Documents\CharlesRiver_Work.sqlite

New Database | Open Database ▾ | Write Changes | Revert Changes

Database Structure | Browse Data | Edit Pragmas | **Execute SQL**

Open SQL file(s) | Save SQL file ▾ | ▶ Execute all/selected SQL

Ex 12.2.sql

```
123 Ledger AS (
124     SELECT SUM(gl.Debit) - SUM(gl.Credit) AS Balance,
125         SUM(CASE WHEN gl.VoucherNumber = 'JE-2024-000001'
126             THEN gl.Debit - gl.Credit ELSE 0 END) AS OpeningLine
127     FROM GLEntry AS gl
128         INNER JOIN Account AS a ON a.AccountID = gl.AccountID
129     WHERE a.AccountNumber = 1020
130         AND gl.PostingDate <= (SELECT AsOfDate FROM Params)
131 )
132 SELECT ROUND(SUM(b.OpenBalance), 2) AS OpenInvoices,
133     ROUND((SELECT Balance FROM Ledger), 2) AS Account1020,
134     ROUND((SELECT Balance FROM Ledger) - SUM(b.OpenBalance), 2)
135         AS Difference,
136     ROUND((SELECT OpeningLine FROM Ledger), 2) AS OpeningEntryLine
137 FROM Balances AS b
138 WHERE b.OpenBalance > 0;
```

	OpenInvoices	Account1020	Difference	OpeningEntryLine
1	4418804.32	4798804.32	380000.0	380000.0

Execution finished without errors.
Result: 1 rows returned
At line 93:
WITH Params AS (

Outlined: Difference and OpeningEntryLine, both $380,000.00. The 1,079 open invoices total $4,418,804.32 and account 1020 holds $4,798,804.32; the whole difference is one line of JE-2024-000001, the opening balance that no invoice supports, a finding to investigate and not an error to correct. The editor is scrolled to the Ledger CTE and the final SELECT.