1 Filter context

A cell of a matrix

ItemGroup	2026-Q3	2026-Q4
Furniture		*Revenue*
Lighting		

The cell carries three filters:

Item
ItemGroup
= Furniture
from the row

Date
YearQuarter
= 2026-Q4
from the column

Customer
Region
= a selection
from a slicer

SalesInvoiceLine
the relationships carry the filters here; only the lines that pass all three remain

SUM (LineTotal) adds those lines: the cell shows one number

2 Row context

A calculated column on Customer

Customer	
CustomerID	**Revenue All**
…	all lines
current row	all lines
…	all lines

```
Revenue All =
SUM ( SalesInvoiceLine[LineTotal] )
```

No arrow. The row is not a filter, so nothing narrows the lines.

SalesInvoiceLine
every line, whatever the row

Every row reads the same number: the total of all the lines

3 Context transition

The same column inside CALCULATE

Customer	
CustomerID	**Revenue Own**
…	its lines
current row	its lines
…	its lines

```
Revenue Own =
CALCULATE (
    SUM ( SalesInvoiceLine[LineTotal] )
)
```

The current row becomes a filter on Customer, and the relationship carries it

SalesInvoiceLine
only the lines of the current customer

Each row reads its own number: that customer's lines only

A board sketch with no values, to draw while the class reads the three paragraphs of the section on evaluation context. The chapter's figures on the filter context of a cell and on row context with and without context transition show the same ideas with the numbers.