DB Browser for SQLite - C:\Users\you\Documents\CharlesRiver_Capstone.sqlite

New Database | Open Database | Write Changes | Revert Changes

Database Structure | Browse Data | Edit Pragmas | Execute SQL

Open SQL file(s) | Save SQL file | ▶ Execute all/selected SQL

LenderPackage.sql

```
675 SELECT pa.AsOfDate, ROUND(pa.Opening, 2) AS Opening,
676    ROUND(pa.Freight, 2) AS FreightNotSettled,
677    ROUND(pa.DecemberFreight, 2) AS DecemberFreight,
678    ROUND(SUM(CASE WHEN oa.IsOld = 0 THEN oa.OpenAmount ELSE 0 END), 2)
679       AS YoungAccruals,
680    ROUND(SUM(CASE WHEN oa.IsOld = 1 THEN oa.OpenAmount ELSE 0 END), 2)
681       AS OldAccruals,
682    ROUND(pa.Opening + pa.Freight + SUM(oa.OpenAmount), 2) AS Parts,
683    ROUND(pa.Ledger, 2) AS Ledger,
684    ROUND(pa.Opening + pa.Freight + SUM(oa.OpenAmount)
685       - pa.Ledger, 2) AS Difference
686 FROM Parts AS pa
687    INNER JOIN OpenAccruals AS oa ON oa.AsOfDate = pa.AsOfDate
688 GROUP BY pa.AsOfDate, pa.Opening, pa.Freight, pa.DecemberFreight,
689    pa.Ledger
690 ORDER BY pa.AsOfDate;
```

| | AsOfDate | Opening | FreightNotSettled | DecemberFreight | YoungAccruals | OldAccruals | Parts | Ledger | Difference |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 2024-12-31 | 85000.0 | 48797.21 | 45381.01 | 152347.13 | 39028.43 | 325172.77 | 325172.77 | -0.0 |
| 2 | 2025-12-31 | 85000.0 | 47290.49 | 41564.67 | 168648.64 | 96049.58 | 396988.71 | 396988.71 | -0.0 |
| 3 | 2026-12-31 | 85000.0 | 44423.87 | 40704.22 | 193781.7 | 157346.79 | 480552.36 | 480552.36 | 0.0 |

Execution finished without errors.
Result: 3 rows returned
At line 642:
WITH YearEnds AS (

*Outlined in coral: the Difference of each year-end, the parts less the ledger, which is zero at all three (-0.0 is a rounding residue). The editor is scrolled to the closing SELECT; its CTEs sum the opening entry, the freight and the ledger, and the view OpenAccruals holds the accruals still open.*