DB Browser for SQLite - C:\Users\you\Documents\CharlesRiver_Work.sqlite

New Database | Open Database ▾ | Write Changes | Revert Changes

Database Structure | Browse Data | Edit Pragmas | **Execute SQL**

Open SQL file(s) | Save SQL file ▾ | ▶ **Execute all/selected SQL**

Case.sql

```
217 -- Requirement 1: the two views reconciled to the surge days and entries of Tutorial 12.3
218 -- Population: SurgeDays and PlantEntries; expected: 12, 32, 49 surge days and 768, 2,048, 3,136 surge entries
219 SELECT strftime('%Y', pe.WorkDate) AS WorkYear,
220     (SELECT COUNT(*)
221      FROM SurgeDays AS sd
222      WHERE strftime('%Y', sd.WorkDate)
223          = strftime('%Y', pe.WorkDate)) AS SurgeDays,
224     SUM(CASE WHEN pe.DayType = 'Surge'
225         THEN 1 ELSE 0 END) AS SurgeEntries,
226     COUNT(DISTINCT CASE WHEN pe.DayType = 'Ordinary'
227         THEN pe.WorkDate END) AS OrdinaryDays,
228     SUM(CASE WHEN pe.DayType = 'Ordinary'
229         THEN 1 ELSE 0 END) AS OrdinaryEntries
230 FROM PlantEntries AS pe
231 GROUP BY WorkYear
232 ORDER BY WorkYear;
```

	WorkYear	SurgeDays	SurgeEntries	OrdinaryDays	OrdinaryEntries
1	2024	12	768	235	15033
2	2025	32	2048	223	14145
3	2026	49	3136	194	11796

Execution finished without errors.
Result: 3 rows returned
At line 219:
SELECT strftime('%Y', pe.WorkDate) AS WorkYear,

Outlined: SurgeDays and SurgeEntries, the figures that test H8 of Tutorial 12.3 counts: 12, 32 and 49 surge days and 768, 2,048 and 3,136 surge entries in 2024, 2025 and 2026. The two views must give them before any later test relies on them. The query reads the views SurgeDays and PlantEntries, which the script saved earlier with Write Changes.