DB Browser for SQLite - C:\Users\you\Documents\CharlesRiver_Work.sqlite

New Database | Open Database | Write Changes | Revert Changes

Database Structure | Browse Data | Edit Pragmas | Execute SQL

Open SQL file(s) | Save SQL file | ▶ Execute all/selected SQL

Ex 12.6.sql

```
161     SELECT 'Partial payments', Digit
162     FROM Payments
163     WHERE Amount < GrandTotal
164 ),
165 Observed AS (
166     SELECT PaymentGroup, Digit, COUNT(*) AS Payments,
167         COUNT(*) * 1.0 / SUM(COUNT(*)) OVER (PARTITION BY PaymentGroup)
168             AS Actual
169     FROM Groups
170     GROUP BY PaymentGroup, Digit
171 )
172 SELECT PaymentGroup, SUM(Payments) AS Payments, COUNT(*) AS Digits,
173     ROUND(AVG(ABS(Actual - LOG10(1 + 1.0 / Digit))), 5) AS MAD
174 FROM Observed
175 GROUP BY PaymentGroup
176 ORDER BY PaymentGroup;
```

	PaymentGroup	Payments	Digits	MAD
1	All payments	39864	9	0.01295
2	Full payments	34115	9	0.00755
3	Partial payments	5749	9	0.04496

Execution finished without errors.
Result: 3 rows returned
At line 145:
WITH Payments AS (

Outlined: the MAD column (teal) and the partial-payment row (coral). The values are Tutorial 8.1's: all payments 0.01295, marginally acceptable conformity; full payments (Amount = GrandTotal) 0.00755, acceptable conformity; partial payments 0.04496, nonconformity, plausibly because only invoices of $1,000 or more are paid in parts (the smallest, $1,000.24), a selection by size. Each group has 9 digits, so none is missing. The editor is scrolled to the last branch of the Groups CTE, the Observed CTE and the final SELECT.