meant → after the fill

meant → after the fill

| | J | K | M | O | P | Q |
|---|---|---|---|---|---|---|
| 1 | **Discount** | **LineTotal** | **PromotionID** | **PricingMethod** | **ListAmount** | **DiscountAmount** |
| 2 | 0 | 182.99 | | Segment Price List | 203.30 | 0.00 |
| 3 | 0 | 2,844.18 | | Segment Price List | 3,025.71 | 0.00 |

*Columns A to I, L and N of SalesInvoiceLine are hidden. ListAmount and DiscountAmount are the calculated columns of Tutorial 4.1.*

**1** **Typed in B16, as in Step 5 of Tutorial 4.2**

**B16 shows 469**

Counts the Approved Override lines with a discount of 0%.

B16 *fx* =COUNTIFS(SalesInvoiceLine[**PricingMethod**],$A16,SalesInvoiceLine[**Discount**],B$15)

**2** **Filled one column to the right with the fill handle**

**C16 shows 0**

Each column name moved to the next column of the Table. No error appears, and the count is wrong.

C16 *fx* =COUNTIFS(SalesInvoiceLine[**ListAmount**],$A16,SalesInvoiceLine[**LineTotal**],C$15)

**3** **Copied from B16 and pasted into C16**

**C16 shows 10**

The column names and $A16 stay as typed, and B$15 becomes C$15, so C16 counts the 8% lines.

C16 *fx* =COUNTIFS(SalesInvoiceLine[**PricingMethod**],$A16,SalesInvoiceLine[**Discount**],C$15)

**Two ways to keep the columns where they are**

**Paste instead of filling.** Copy the cell and paste it: structured references stay as they are.

**Lock the column** by writing it with a column range, which a fill leaves alone:

=COUNTIFS(SalesInvoiceLine[**[PricingMethod]:[PricingMethod]**],$A16,SalesInvoiceLine[**[Discount]:[Discount]**],B$15)

*Teal outline and teal names (bold): the columns the formula means. Coral outline and coral names (bold): the columns it reads after a fill across. Click a cell in the middle of the result and read the formula bar: that is how a drift shows.*