DB Browser for SQLite - C:\Users\you\Documents\CharlesRiver_Work.sqlite

New Database | Open Database | Write Changes | Revert Changes

Database Structure | Browse Data | Edit Pragmas | Execute SQL

Open SQL file(s) | Save SQL file | ▶ Execute all/selected SQL

Ex 10.5.sql

```
17  -- Requirement (2): ledger rows that point to no payroll payment
18  -- Population: GLEntry, PayrollPayment; expected: six rows, three pairs of 7,971.10
19  SELECT gl.GLEntryID, gl.PostingDate, gl.SourceDocumentID,
20      gl.Debit, gl.Credit, gl.Description
21  FROM GLEntry AS gl
22      LEFT JOIN PayrollPayment AS pp
23          ON pp.PayrollPaymentID = gl.SourceDocumentID
24  WHERE gl.SourceDocumentType = 'PayrollPayment'
25      AND pp.PayrollPaymentID IS NULL
26  ORDER BY gl.GLEntryID;
```

	GLEntryID	PostingDate	SourceDocumentID	Debit	Credit	Description
1	7231	2024-01-19	1	7971.1	0.0	Clear accrued payroll
2	7232	2024-01-19	1	0.0	7971.1	Disburse payroll cash
3	12521	2025-01-03	2646	7971.1	0.0	Clear accrued payroll
4	12522	2025-01-03	2646	0.0	7971.1	Disburse payroll cash
5	18069	2026-01-02	5420	7971.1	0.0	Clear accrued payroll
6	18070	2026-01-02	5420	0.0	7971.1	Disburse payroll cash

Execution finished without errors.
Result: 6 rows returned
At line 19:
SELECT gl.GLEntryID, gl.PostingDate, gl.SourceDocumentID,

Outlined: SourceDocumentID. The six rows are three pairs of $7,971.10, a debit "Clear accrued payroll" and a credit "Disburse payroll cash", posted on 2024-01-19, 2025-01-03 and 2026-01-02. They name payroll payments 1, 2646 and 5420, which are not in PayrollPayment, a referential-integrity failure in the extract. The query does not show how the rows arose, and a reference whose table depends on its source type needs a test that reads the type, which one ordinary foreign key cannot do.