

New Database

Open Database

Write Changes

Revert Changes

Database Structure

Browse Data

Edit Pragmas

Execute SQL

Open SQL file

Save SQL file

▶ Execute all/selected SQL

SQL 1

```
1 WITH ApprovalExceptions AS (  
2   SELECT 'Self-approved' AS Test, po.PONumber, po.OrderTotal  
3   FROM PurchaseOrder AS po  
4   WHERE po.CreatedByEmployeeID = po.ApprovedByEmployeeID  
5   UNION ALL  
6   SELECT 'Above approver limit', po.PONumber, po.OrderTotal  
7   FROM PurchaseOrder AS po  
8       INNER JOIN Employee AS e ON e.EmployeeID = po.ApprovedByEmployeeID  
9   WHERE po.OrderTotal > e.MaxApprovalAmount  
10  UNION ALL  
11  SELECT 'Approved after termination', po.PONumber, po.OrderTotal  
12  FROM PurchaseOrder AS po  
13      INNER JOIN Employee AS e ON e.EmployeeID = po.ApprovedByEmployeeID  
14  WHERE e.TerminationDate IS NOT NULL  
15      AND po.OrderDate > e.TerminationDate  
16 )  
17 SELECT Test, COUNT(*) AS Orders, ROUND(SUM(OrderTotal), 2) AS OrderValue  
18 FROM ApprovalExceptions  
19 GROUP BY Test  
20 ORDER BY Orders DESC;
```

	Test	Orders	OrderValue
1	Above approver limit	13	705779.39
2	Self-approved	9	651830.75
3	Approved after termination	3	15419.28

Execution finished without errors.
Result: 3 rows returned
At line 1:
WITH ApprovalExceptions AS (

Outlined: the three tests, with the number of purchase orders each flags and their value. Some orders fail more than one test.