


Plotting and Color in R

Roger D. Peng, Associate Professor of Biostatistics Johns Hopkins Bloomberg School of Public Health


Plotting and Color

- · The default color schemes for most plots in R are horrendous
 - I don't have good taste and even I know that
- Recently there have been developments to improve the handling/specifica1on of colors in plots/graphs/etc.
- There are functions in R and in external packages that are very handy

Colors 1, 2, and 3



Default Image Plots in R



Color U1li1es in R

- The grDevices package has two functions
 - colorRamp
 - colorRampPalette
- These functions take palettes of colors and help to interpolate between the colors
- The function colors() lists the names of colors you can use in any plotting function

Color Palette Utilities in R

- colorRamp: Take a palette of colors and return a function that takes valeus between 0 and 1, indicating the extremes of the color palette (e.g. see the 'gray' function)
- colorRampPalette: Take a palette of colors and return a function that takes integer arguments and returns a vector of colors interpolating the palette (like heat.colors or topo.colors)

colorRamp

[,1] [,2] [,3] corresponds to [Red] [Blue] [Green]

colorRamp

```
> pal(seq(0, 1, len = 10))
                 [,1] [,2]
                           [,3]
       [1,] 255.00000
                                   0
       [2,] 226.66667
                           28.33333
                           56.66667
       [3,] 198.33333
       [4,] 170.00000
                           85.00000
       [5,] 141.66667
                        0 113.33333
       [6,] 113.33333
                        0 141.66667
       [7,] 85.00000
                        0 170.00000
       [8,] 56.66667
                        0 198.33333
       [9,] 28.33333
                           226.66667
       [10,] 0.00000
                        0 255.00000
```


colorRampPalette

```
> pal <- colorRampPalette(c("red", "yellow"))
> pal(2)
[1] "#FF0000" "#FFFF00"

> pal(10)
[1] "#FF0000" "#FF1C00" "#FF3800" "#FF5500" "#FF7100"
[6] "#FF8D00" "#FFAA00" "#FFC600" "#FFE200" "#FFFF00"
```

RColorBrewer Package


- One package on CRAN that contains interes1ng/useful color palettes
- There are 3 types of palettes
 - Sequential
 - Diverging
 - Qualitative
- Palette informa1on can be used in conjunction with the colorRamp() and colorRampPalette()




RColorBrewer and colorRampPalette

```
> library(RColorBrewer)
> cols <- brewer.pal(3, "BuGn")
> cols
[1] "#E5F5F9" "#99D8C9" "#2CA25F"
> pal <- colorRampPalette(cols)
> image(volcano, col = pal(20))
```

RColorBrewer and colorRampPalette




The smoothScatter function




Some other plotting notes

- · The rgb function can be used to produce any color via red, green, blue proportions
- · Color transparency can be added via the alpha parameter to rgb
- The colorspace package can be used for a different control over colors

Scatterplot with no transparency



Scatterplot with transparency



Summary

- Careful use of colors in plots/maps/etc. can make it easier for the reader to get what you're trying to say (why make it harder?)
- The RColorBrewer package is an R package that provides color palettes for sequential, categorical, and diverging data
- The colorRamp and colorRampPalette functions can be used in conjunction with color palettes to connect data to colors
- Transparency can sometimes be used to clarify plots with many points