Equilibrium or Retrieval?

Do LLM Agents Derive or Recall Game-Theoretic Equilibria, and What That Means for Mechanism Design

Meet Mehta

Working paper, October 13, 2026

Draft. gpt-oss-120b's Stage 2B number-sweep and endgame data are still being collected. Values shown in violet with a superscript p are the author's pre-registered predictions, not data, and will be replaced by measurements.

Abstract

Large language models (LLMs) play textbook games well. A model can reach the textbook answer in two ways, however: by *deriving* it from the rules, or by *recognising* a famous game and recalling its answer. The two are behaviourally identical on the textbook question, and they come apart only when the question changes. We separate them with *isomorphic twins*. Every question is asked in its standard wording and in a disguised wording with identical numbers, rules and information structure but no game vocabulary. A third, pre-registered study adds an *extreme* disguise: no story, coded answers and a neutral answer box. Every answer is paired with a competence probe in the same wording, so a change in play cannot be blamed on misreading. Four models from four providers answer up to 20,368 questions across a Vickrey auction, a Cournot duopoly, a finitely repeated prisoner's dilemma and a public goods game, under four pre-registrations.

The four models split into three patterns:

- **Hidden but still solved.** When the extreme disguise removes recognition of the Cournot game (Nemotron 3 Ultra: 96%→10%; Kimi K3: 72%→20%), their equilibrium play stays at 99–100%, the pattern our pre-registered key reads as consistent with derivation.
- **Graded retrieval.** gpt-oss-120b's Cournot recognition (96%→9%→1%) and equilibrium play (96%→80%→30%) fall together across the three wordings, with every competence probe passed. Its errors become the collusive quantity.
- **Retrieval and comprehension limits.** Gemini 3.5 Flash Lite plays the Cournot equilibrium in 96% of standard questions but in only 4% of disguised ones, and it cannot read the coded extreme rules at all.

In the prisoner's dilemma, recognition retrieves a cultural script of cooperation rather than the equilibrium: removing the familiar frame raises defection in every model (pooled 46%→83%). Fitted to the data, logit QRE fails our pre-registered calibration test for all four models, because LLM errors are rare, large and discrete rather than payoff-scaled noise. Traps that make the textbook answer wrong do not fool the two strongest models (93–100% correct in both wordings). gpt-oss falls into them when the game is named, giving the textbook answer about five times as often as when it is disguised, and Gemini fails the traps' arithmetic in the textbook direction. In the normal wording of a finitely repeated dilemma, the models cooperate early and defect at the end (99–100% in the announced last round), as people do, rather than defecting throughout as backward induction requires.

We then ask what noisy, quantal-response agents imply for mechanism design. We prove four results:

DRAFT

- a payment multiplier in a second-price auction is irrelevant for logit-QRE bidders but ruinous for bidders who recall "bid your value", which makes it a test of retrieval;
- the revenue-optimal reserve price is U-shaped in bidder precision but gains at most about 1% over Myerson's;
- the cooperation subsidy that achieves any target cooperation rate has a closed form, whose stage-game halfway point is free of parameters across the entire regular-QRE family;
- no regular QRE can produce cooperation above one half at subsidies up to that halfway point, at any precision.

A pre-registered test pits the derived subsidy against a classically guessed one, in 1,600 further questions. Classical theory predicts the models' response better than QRE for all four models. The derived subsidy reaches its 90% target in every model but overpays, by up to twenty times, because three models cooperate at levels no QRE can produce: their low fitted precision measured a cooperation norm, not insensitivity to incentives.

Contents

1 Introduction **3**

2 Related work **4**

3 A framework for derivation and retrieval **5**

4 Games, wordings and competence probes **5**

5 Pre-registration and analysis **7**

6 Results **9**
6.1 Standard twins (Stage 2A) 9
6.2 The extreme disguise (Stage 2C) 10
6.3 Does quantal response describe the models? The decision gate 13
6.4 Stage 2B: traps, number sweeps and the endgame 13

7 Mechanism design for noisy agents **16**
7.1 Second-price auctions with a reserve and a payment multiplier 16
7.2 A cooperation subsidy for the prisoner's dilemma 18

8 A confirmatory test of the derived mechanism **20**

9 Discussion **21**

10 Limitations **23**

11 Conclusion **23**

A Deviations from the pre-registrations **25**

B Stage 2A precision fits **26**

DRAFT

1 Introduction

LLM agents are beginning to act in settings that game theory was built to analyse: bidding in auctions, setting prices, negotiating, and drawing on shared resources. The rules of such settings are designed, and designing them, which is the business of mechanism design, requires a model of how participants behave. Classical mechanism design assumes rational players who best-respond. Behavioural mechanism design replaces them with an empirically fitted model, most prominently the logit quantal response equilibrium (QRE) [6, 12], in which players choose better actions more often than worse ones, with a precision λ.

Before a fitted model of LLM play can be trusted to design anything, a prior question must be settled: *is the play we measure reasoning about the rules in front of the model, or retrieval of answers to famous problems?* The concern is concrete. The Vickrey auction, the Cournot duopoly, the prisoner's dilemma and the public goods game are among the most written-about games in any corpus a model is trained on. "Bid your true value", "produce $(a-c)/3b$" and "defect in the last round" appear thousands of times. LLM accuracy is known to depend on how familiar a task looks, not only on what it requires [11]. A mechanism tuned to recalled play may fail precisely when the designer changes the rules, which is the only reason to design a mechanism at all.

Approach. We hold each game fixed and vary only its *wording*:

(i) **Isomorphic twins.** The disguised wording preserves every number, rule and information structure, and removes the game's vocabulary. An extreme disguise (Stage 2C) removes the story too, codes the answer (for example, "your offer is $3x+5$") and replaces the answer box. Section 3 shows that a purely deriving agent's play is invariant to such relabelling, so any wording effect rejects pure derivation.

(ii) **Competence probes.** A short calculation in the same wording follows every answer. Only answers whose probe is passed are analysed, so a wording effect cannot be a reading failure.

(iii) **Measured recognition.** A validated code records whether the model's reasoning names the game (agreement with blind hand coding $\kappa = 1.00$). Recognition and play are then read jointly, by rules fixed before the data.

(iv) **Pre-registration.** Four registrations on OSF fix the predictions, sample sizes, exclusions and tests before each study [14]. The analysis code was locked by cryptographic fingerprint.

Findings.

- **Derive or recall differs by model.** Nemotron and Kimi solve a Cournot game they no longer recognise. gpt-oss's play tracks recognition across three wordings. Gemini loses the Cournot equilibrium as soon as the game's name goes.
- **Competence predicts robustness.** The pre-registered ranking held exactly: the higher a model's competence-probe pass rate, the smaller its Cournot drop under disguise.
- **Recognition can pull *away* from equilibrium.** In the prisoner's dilemma, the familiar frame triggers cooperation. Removing it raises defection in all four models, by 17–76 points.
- **Quantal response does not fit LLM play.** It fails held-out calibration for every model.
- **Models respond to incentives more sharply than QRE allows.** In a pre-registered subsidy test, classical theory beats QRE for every model, and a subsidy derived from the fitted QRE overpays by up to twenty times. Merely stating a subsidy rule, at zero, cuts cooperation by 23 points in each of three models.

DRAFT

Contributions.

1. A design that identifies derived versus recalled strategic play: isomorphic twins, same-wording competence probes, measured recognition, and an extreme disguise, all pre-registered.
2. Evidence that the answer differs by model and by game, including a retrieval signature in Gemini's Cournot play and recognition-driven cooperation in the prisoner's dilemma.
3. Theory for mechanism design with QRE agents: an invariance theorem that turns a payment multiplier into a test of retrieval; the U-shaped revenue-optimal reserve; a closed-form cooperation subsidy with a parameter-free prediction; and a ceiling on quantal cooperation that explains when fitted QRE will mislead a designer.
4. A pre-registered test of a mechanism derived from fitted behaviour, on the same models. It shows that a behavioural model can fail in a predictable direction, and by how much.

2 Related work

LLMs as economic and strategic agents. Horton et al. [8] proposed treating LLMs as simulated economic agents and reproduced classic behavioural-economics findings with them. Akata et al. [2] placed LLMs in finitely repeated 2×2 games and found strong play in self-interested games, such as the prisoner's dilemma, and weak coordination. Fan et al. [5] tested basic requirements of rationality. Benchmarks such as GTBench [4] measure strategic reasoning across many game types. These studies vary the game; we vary only the wording of a fixed game, which isolates recognition from ability.

Behavioural game theory for LLMs. Jia et al. [9] evaluate 22 LLMs with behavioural models rather than Nash benchmarks. Pechon-Elkins and Chun [15] audit QRE-based measures of LLM strategic reasoning and conclude that fitted parameters are payoff- and model-dependent summaries rather than structural measures of rationality. We adopt that caution explicitly:

- we never compare λ across games, whose payoff scales differ;
- our main comparisons hold payoffs fixed by construction;
- we verify by parameter recovery that our fitting recovers known λ;
- we judge fit by held-out calibration, decided before the data.

Familiarity, memorisation and reasoning. McCoy et al. [11] show that LLM performance tracks how probable a task and its output are under the training distribution. Our twins apply this idea to strategic play, and the competence probes separate unfamiliarity of the *wording* from failure to *understand* it.

Mechanism design and bounded rationality. Our auction results build on the second-price auction [19] and on Myerson's optimal auction and implementability results [13], in the treatment of Roughgarden [16]. QRE was introduced by McKelvey and Palfrey [12] and is developed in Goeree et al. [6]. Our repeated-game discussion uses Benoît and Krishna [3].

DRAFT

Table 1: The four games. Parameters are drawn per question from seeded samplers.

Game	Parameters	Equilibrium	Disguised as
Vickrey auction	3 bidders, private value $v \sim U[10, 100]$	bid v	research stations requesting slots
Cournot duopoly	$P = a - Q$, $a \in [80, 120]$, $c = 10$	$q = (a - c)/3$	operators opening water channels
Repeated PD	$(T, R, P, S) = (5, 3, 1, 0)$, 10 rounds, round 1	defect	technicians setting panels X/Y
Public goods	n, endowment e, $1 < M < n$	contribute 0	operators routing signal

3 A framework for derivation and retrieval

Let a *question* be a pair (G, w) of a game G (players, actions, payoffs, information) and a wording w that presents it. Two wordings w, w' are *isomorphic* for G if there is a bijection ϕ between their answer spaces such that, for every answer a, the payoff consequences of a under w equal those of $\phi(a)$ under w'. For example, "offer $= 3x + 5$" is isomorphic to "bid b" under $b = \phi(x) = 3x + 5$.

Definition 1. A model *derives* on G if the distribution of its answers depends on (G, w) only through G and the answer map: $\Pr(a \mid G, w') = \Pr(\phi^{-1}(a) \mid G, w)$ for every pair of isomorphic wordings. It *retrieves* if its answer distribution depends on features of w that are payoff-irrelevant, such as a game's name.

Proposition 1 (invariance)**.** *For a deriving model, every statistic of play that is defined through payoffs (for example the equilibrium-play rate, or λ fitted on payoffs) is identical across isomorphic wordings. Hence a difference in such a statistic across isomorphic twins, among answers whose competence probe is passed, rejects pure derivation.*

Proof. The statistic is a functional of the answer distribution mapped into payoff space. Under derivation, the mapped distributions coincide by definition. □

Remark. The converse fails. Invariance is also produced by a model that recalls an answer and recognises the game in *both* wordings. So equal play across twins is evidence of derivation only when the disguise actually hides the game. This is why we measure recognition and add an extreme disguise. Our pre-registered interpretation key reads "play unchanged, and recognition drops" as *consistent with* derivation, since recognition is coded from what a model writes, and silent recognition cannot be excluded.

A second route to identification changes the *rules* instead of the wording. If a trap variant has a different equilibrium from the famous game (for example, the winner pays twice the second bid), a retrieving model gives the famous answer where it is wrong. Theorem 1 shows that, for QRE players, this particular change is payoff-irrelevant up to scale, which sharpens the test.

4 Games, wordings and competence probes

Games. Table 1 lists the four games. Each has a unique equilibrium action:

- a weakly dominant strategy in the auction;
- the Cournot–Nash quantity;
- defection by backward induction, since the horizon is common knowledge;




Figure 1: One Cournot question in its three wordings. All three versions have identical numbers and the same equilibrium (in the extreme wording, the coded answer decodes to the same amount). Each answer is followed by a maths check posed in the same wording.

- zero contribution, the dominant strategy, in public goods.

Numbers are drawn per question from seeded samplers, so every question can be reproduced exactly.

Wordings. Each wording has three paraphrases (reworded, or reordered), which never add or drop a fact, so that a disguise effect can be told apart from a wording effect.

- The **disguised** wording moves the game into an unfamiliar story and keeps the numbers, the rules and who knows what.
- The PD's disguised labels `X`/`Y` are counterbalanced, so the cooperative label is randomised.
- The **extreme** wording (Stage 2C) has:
  - no story;
  - coded answers (Vickrey offer $= 3x + 5$ with a private prize; Cournot amount $= 2x + 4$ with the profit written in expanded form);
  - public goods asking how much to *keep*;
  - PD payoffs transformed to $2u - 4$;
  - a neutral answer box.

Each extreme question shares its seed and paraphrase index with a standard question, so every question exists in three wordings with identical numbers (Figure 1).

Competence probes. The probe is a one-step calculation in the question's own wording, for example "you request 50 and the largest other request is 60; what is your net result?". Verdicts:

- AT_EQUILIBRIUM: the probe is passed and the answer is within ±0.5 of the equilibrium;
- STRATEGIC_GAP: the probe is passed and the equilibrium is missed;
- COMPETENCE_GAP: the probe is failed;

DRAFT

- parse and format failures.

Only the first two count. Server refusals and empty replies are re-asked, never scored.

Models and studies. gpt-oss-120b (via Groq), Nemotron 3 Ultra (NVIDIA), Kimi K3 (Moonshot, served by NVIDIA) and Gemini 3.5 Flash Lite (Google) were each queried with default sampling, September–November 2026. Each model answers:

Study	Registration	Questions per model
Stage 2A (named vs disguised)	osf.io/2uqpj	4 games × 2 wordings × 138 = 1,104
Stage 2B (traps, sweep, endgame)	osf.io/6hz8d	3,036
Stage 2C (extreme disguise)	osf.io/cqnsy	4 games × 138 = 552
Stage 5 (subsidy test)	osf.io/qg43y	4 levels × 100 = 400

The cell size of 138 gives 80% power for a 15-point change with Holm correction across four games.

5 Pre-registration and analysis

Registration and locks. Each pre-registration was fingerprinted (SHA-256) in git and registered on OSF before its data existed. Each fixes:

- the predictions;
- the exact sample sizes, as a stopping rule;
- exclusions;
- the tests and multiple-comparison corrections.

The analysis code is fingerprinted too, and it refuses to run on real data unless its fingerprint matches. Fourteen deviations, all recorded before the affected analysis, are listed in Appendix A. None changes a registered test. One changes a registered scoring rule (the re-asking of Kimi's unreadable answers from three days of degraded service), and the affected results are reported both ways.

Tests.

- **Stage 2A:** equilibrium play, named vs disguised, by two-proportion z-tests with Holm correction [7]. Public goods, the predicted null, uses an equivalence test (TOST, ±13 points).
- **Stage 2C:** each extreme question is paired with its twins; exact McNemar tests, Agresti–Min intervals for paired differences [1], and pooling by summing discordant pairs (the Mantel–Haenszel test for matched pairs).

Quantal response fits. In a logit QRE, a player chooses action a with probability $\propto \exp(\lambda\, u(a))$:

- **PD and Cournot:** u is computed at a symmetric fixed point;
- **public goods:** $u(g) = (M/n - 1)g$;
- **Vickrey:** rivals are assumed to bid their equilibrium bids, with values uniform on $[10, 100]$.

We compute the posterior over a log-uniform grid $\lambda \in [10^{-3}, 10^{3}]$. A cell whose evidence keeps rising towards the top of the grid gets only a lower bound, and is flagged as a ceiling. The headline is $\Delta\lambda = \lambda_{\text{named}} - \lambda_{\text{disguised}}$. In a parameter recovery on simulated QRE data, the nominal 95% intervals covered the true λ in 93.75% of 320 fits.

DRAFT




Figure 2: Stage 2A, normal vs disguised wording, with identical numbers, for all four models. Top: equilibrium play among probe-passed answers. Bottom: the share of answers whose reasoning names the game. Bars are 95% Wilson intervals. Gemini's disguised Vickrey cell keeps only 11 answers: the model failed the disguised competence probe on 127 of 138 questions.

Reasoning codes. A locked codebook codes the stated reasoning. NAMES_GAME requires the reasoning to use a name for the game that the question does not use. Agreement with blind hand coding was $\kappa = 1.00$ on Stage 2A wording and 40/40 on a blind sample in the extreme wording. Error codes for missed answers were validated in two hand-coding rounds:

- COOPERATION_NORM: $\kappa = 0.75$;
- fraction slip: $\kappa = 0.72$;
- one code ("knew and overrode") failed validation ($\kappa = 0.49$) and is not used.

The fraction slip. With a number-only box, a model sometimes derives a fraction (683/60) and writes only part of it (683). A mechanical correction was fixed in pre-registration 3, before any Stage 2C data. It reads the answer as n/d when two conditions hold:

1. the box holds n, or n and d written together, for a fraction n/d in the model's own reasoning;
2. the reasoning ends on that fraction.

It is applied identically to both stages in the Stage 2C comparison, with uncorrected results reported alongside. Pre-registration 1's own analysis is reported uncorrected, as registered.

DRAFT

Table 2: Stage 2A main test (pre-registration 1): equilibrium play among probe-passed answers, named vs disguised. Holm correction across the four games within each model.

Model	Game	Named	Disguised	Change	Holm p
gpt-oss-120b	Vickrey	100% (138/138)	98% (129/131)	−2	0.30
	Cournot	96% (130/135)	**80% (110/138)**	**−17**	1×10^{-4}
	Repeated PD	69% (95/138)	73% (101/138)	+4	0.43
	Public goods	97% (134/138)	93% (128/138)	−4	0.30
Nemotron	Vickrey	100% (138/138)	100% (138/138)	+0	1
	Cournot	90% (124/138)	88% (121/138)	−2	1
	Repeated PD	59% (81/137)	59% (81/137)	+0	1
	Public goods	100% (136/136)	100% (138/138)	+0	1
Kimi	Vickrey	100% (138/138)	100% (138/138)	+0	1
	Cournot	100% (138/138)	100% (138/138)	+0	1
	Repeated PD	46% (63/138)	57% (79/138)	+12	0.22
	Public goods	96% (132/138)	99% (136/138)	+3	0.45
Gemini	Vickrey	100% (138/138)	91% (10/11)	−9	4×10^{-4}
	Cournot	96% (132/137)	**4% (6/138)**	**−92**	6×10^{-52}
	Repeated PD	9% (12/138)	**70% (97/138)**	**+62**	4×10^{-25}
	Public goods	100% (138/138)	80% (110/138)	−20	5×10^{-8}

6 Results

6.1 Standard twins (Stage 2A)

Table 2 and Figure 2 give the registered test for all four models.

Two models are invariant; two are not.

- **Nemotron and Kimi** play identically in both wordings in every game. Public goods is confirmed equivalent within ±13 points for both (TOST $p < 10^{-30}$ and $p = 2 \times 10^{-6}$). By Proposition 1 this is consistent with derivation. It is not proof, however: both models often name the disguised game (Figure 2, bottom). Nemotron names it in 96% of disguised Cournot answers and 100% of disguised auctions, so for these models the standard disguise does not hide the game, which motivates Stage 2C.
- **gpt-oss-120b** loses 17 points of Cournot equilibrium play under disguise (96% → 80%, Holm $p = 10^{-4}$), with all other games unchanged and public goods confirmed equivalent (TOST $p = 8 \times 10^{-4}$). This falls inside the range pre-registration 1 committed to for this model (−15 to −25). The fits agree: λ falls from 0.173 to 0.027 ($\Delta\lambda = +0.146$, $P(\Delta\lambda > 0) = 1.00$).
- **Gemini** shows the largest effects, described next.

Gemini shows a retrieval signature in Cournot. Gemini plays the Cournot equilibrium in 96% of named questions and in 4% of disguised ones, a 92-point drop, yet passes the disguised competence probe in all 138 questions. It can compute profits in the disguised wording; it does not find the equilibrium there. Its disguised misses are mostly coded as a claimed but incorrect Nash calculation (44) or the collusive (joint-monopoly) quantity (31). The fits agree: λ falls from 0.649 $[0.50, 0.82]$ to 0.0047 $[0.0036, 0.0060]$.

DRAFT

The auction drop is a reading failure, not a strategic one. Gemini's disguised Vickrey cell keeps only 11 answers, because it failed the disguised probe in 127 of 138 questions. The design classifies this correctly, as a competence gap, so it is not evidence about strategy. Without the probes it would read as a 92-point strategic collapse.

In the prisoner's dilemma, recognition pulls away from equilibrium.

- **Gemini:** with the game named, it cooperates in round 1 of a known 10-round game in 91% of questions; disguised, it defects in 70%. Every one of its 126 named-wording cooperative answers gives a cooperation-norm reason.
- **Kimi and gpt-oss** move the same way, by +12 and +4 points (not significant).

Recognition retrieves a *cultural* script of cooperation in repeated dilemmas, not the backward-induction solution. Pre-registration 1 predicted this direction and named Gemini as the model with the largest swing; both predictions held.

Public goods. Gemini contributes more when the game is disguised (100%→80%; equivalence not shown), and most of its disguised misses argue for the group optimum (20 of 28).

Pre-registration 1, scored.

- **Cournot drop in every model:** the direction holds for gpt-oss and Gemini, but not for Nemotron (−2) or Kimi (0).
- **PD rise under disguise:** significant only for Gemini; Gemini having the largest swing was predicted correctly.
- **Public goods flat:** met for three of four models (not Gemini).
- **Ranking prediction:** the model with the highest competence-probe pass rate shows the smallest Cournot drop. This held *exactly*: Kimi 100% and 0 points, Nemotron 99.6% and −2, gpt-oss 99.4% and −17, Gemini 88.4% and −92.

6.2 The extreme disguise (Stage 2C)

The extreme disguise removes the story, codes the answer and neutralises the answer box. Table 3 and Figure 3 give the registered comparison with the same questions in standard wording. Pooled over models, play changes in every game. The pooled figures conceal three distinct patterns, however, and the pre-registered interpretation key reads each one differently.

Pattern 1: hidden but still solved (Nemotron, Kimi). The extreme wording largely removes recognition of the Cournot game:

- Nemotron: 96%→10% ($p = 3 \times 10^{-36}$);
- Kimi: 72%→20% ($p = 5 \times 10^{-16}$).

Equilibrium play nevertheless stays at 99–100%. The key reads this as *consistent with derivation*: both models solve a game they no longer name.

Pattern 2: graded retrieval (gpt-oss). gpt-oss passes the competence probe in the extreme wording, yet its play falls sharply: Vickrey 100% → 54%, Cournot 96% → 30%. In Cournot, recognition and play fall together across the three wordings:

DRAFT




Figure 3: The same questions in three wordings, for all four models. Top: equilibrium play (fraction-slip corrected, both stages alike). Bottom: recognition. Gemini's extreme Cournot cell is empty: it failed the extreme competence probe in all 138 questions.

	Normal	Disguised	Extreme
Names the game	96%	9%	1%
Equilibrium play	96%	80%	30%

Within the extreme auction, gpt-oss plays the equilibrium in 14 of 14 answers that name the game, against 60 of 124 that do not (Fisher $p = 10^{-4}$, exploratory). Its errors are systematic, not noisy:

- 67 of its 97 Cournot misses are the *collusive* quantity, the joint optimum: without the textbook cue, it treats the game as cooperative;
- its auction misses are corner bids (0, ±1000).

No miss is a conversion slip (a strategy left in the wrong unit). The key reads this as *recall*: the play depends on recognising the game, and the competence checks rule out a reading failure.

Pattern 3: the coded rules defeat comprehension (Gemini). Gemini failed the extreme competence probe in all 138 Cournot questions and in 116 of 138 public-goods questions. These cells say nothing about strategy. The key reads them as a comprehension cost, which the design was built to detect.

The prisoner's dilemma, in every model. Removing the familiar frame raises defection for all four models:

- Nemotron +34 points;
- Kimi +24;

DRAFT

Table 3: Stage 2C (pre-registration 3): equilibrium play, normal (2A) vs extreme (2C), on paired questions with identical numbers. Exact McNemar test, Holm across games within each model; the pooled rows sum discordant pairs over models (Mantel–Haenszel for matched pairs).

Model	Game	Pairs	Normal	Extreme	Normal − extreme [95% CI]	Holm p	Names game[†]
gpt-oss	Vickrey	138	100%	54%	$+46$ $[+37, +54]$	3×10^{-19}	89%→10%
	Cournot	134	96%	30%	$+66$ $[+57, +74]$	4×10^{-24}	9%→1%
	Repeated PD	138	69%	86%	-17 $[-28, -7]$	3×10^{-3}	1%→2%
	Public goods	138	97%	86%	$+12$ $[+5, +18]$	3×10^{-3}	0%→0%
Nemotron	Vickrey	138	100%	99%	$+1$ $[-1, +4]$	1	100%→100%
	Cournot	138	98%	99%	-1 $[-5, +2]$	1	96%→**10%**
	Repeated PD	137	59%	93%	-34 $[-43, -25]$	3×10^{-10}	81%→65%
	Public goods	136	100%	99%	$+1$ $[-1, +3]$	1	54%→99%
Kimi	Vickrey	137	100%	99%	$+1$ $[-1, +4]$	1	100%→93%
	Cournot	138	100%	100%	$+0$ $[-1, +1]$	1	72%→**20%**
	Repeated PD	138	46%	70%	-24 $[-34, -13]$	3×10^{-4}	3%→1%
	Public goods	138	96%	96%	-1 $[-5, +4]$	1	11%→4%
Gemini	Vickrey	138	100%	45%	$+55$ $[+46, +63]$	5×10^{-23}	73%→27%[‡]
	Cournot	0	no extreme answer passed the probe (0/138)				
	Repeated PD	138	9%	85%	-76 $[-83, -67]$	4×10^{-27}	33%→0%
	Public goods	22	100%	0%	$+100$ $[+78, +100]$	5×10^{-7}	50%→100%[‡]
All models	Vickrey	551	100%	74%	$+26$ $[+22, +30]$	4×10^{-43}	96%→67%
	Cournot	410	98%	77%	$+21$ $[+17, +25]$	2×10^{-21}	59%→10%
	Repeated PD	551	46%	83%	-38 $[-43, -33]$	1×10^{-36}	30%→17%
	Public goods	434	98%	89%	$+9$ $[+5, +12]$	3×10^{-7}	23%→37%

[†] disguised (2A) → extreme (2C), on the same paired questions. [‡] small n (11 and 22 pairs): most of Gemini's disguised or extreme answers failed the probe.

- gpt-oss +17;
- Gemini +76;
- pooled: 46% → 83%, $p = 10^{-36}$.

Kimi almost never *names* the game in any wording (1–3%), so the cooperation pull is carried by the frame itself (cooperate/defect labels and a scored payoff table), not by the label "prisoner's dilemma". The only pre-registered pooled prediction that held exactly was this one (extreme defection 80–90%, above the normal-wording rate).

The fraction slip was not a detail. In the extreme wording, coded answers are usually awkward fractions, so the slip becomes common. For Nemotron, 50% of extreme Vickrey answers and 55% of Cournot answers were written as a numerator or a concatenation. Without the correction fixed in advance, Nemotron would show spurious drops of 51 and 46 points (both $p < 10^{-18}$); with it, the drops vanish.

Pre-registration 3, scored. The author's predictions were mostly wrong, and wrong in an informative direction:

- **Pooled recognition:** predicted ranges were not met for any game.
- **Pooled play:** the Vickrey and Cournot drops were real, but of different sizes from the predictions.

DRAFT

- **Per-model Cournot drops:** the author expected Nemotron to lose Cournot (≥ 35 points) and gpt-oss and Kimi to be stable. Nemotron and Kimi were stable (-1 and 0), while gpt-oss lost 66 points; Gemini could not be tested.

The model the author believed was recalling is the one that derives, and vice versa.

6.3 Does quantal response describe the models? The decision gate

Pre-registration 1's gate asks whether the QRE fits are good enough to design mechanisms on. Its criteria were fixed by the author before three of the four models' fits existed:

- fit λ on two of the three normal-wording paraphrases;
- predict the held-out paraphrase's equilibrium-play rate;
- call a game calibrated if the prediction is within ± 10 points in at least two of three rotations;
- call a model's fits good if at least three of its four games are calibrated.

By these criteria, fits are poor for all four models: 0, 1, 1 and 1 of 4 games calibrated. The Vickrey cells fail for an artifactual reason: at the top of the registered λ grid, QRE predicts only 82–90% equilibrium play, while every model plays it 100%. The verdict does not depend on this, though: counting Vickrey as calibrated, no model reaches three games.

The substantive reason is visible in the data. LLM departures from equilibrium are *rare, large and discrete*:

- fraction slips;
- collusive quantities;
- corner bids;
- a norm-driven preference for cooperation.

They are not the frequent, small, payoff-scaled deviations that logit QRE describes. A handful of far-off answers drags the fitted λ down, and the fitted model then badly under-predicts the exact-equilibrium rate (for example, 27–51% predicted against 91–100% observed for gpt-oss in Cournot). Two models also fail a hard check in the prisoner's dilemma: they cooperate more than 50% of the time with no subsidy, which no stage-game QRE can produce.

The gate therefore selects option 3: the behavioural model does not describe the agents, and the mechanism stage studies why. Stage 5 (Section 8) does this directly, by asking whether the agents respond to incentives as QRE or as classical theory predicts.

6.4 Stage 2B: traps, number sweeps and the endgame

Stage 2A cannot separate a model that recalls the textbook answer from one that derives it, because there the textbook answer is also correct. Stage 2B (pre-registration 2) asks questions where that is not so, in three blocks of 3,036 questions per model:

- **Traps (Block B).** One rule or the numbers make the textbook answer wrong (Table 4). A deriving model gets the trap right in both wordings; a recalling model falls in more often when the familiar wording calls up the memorised answer. Each trap has its own maths check, which tests the trap rule rather than the ordinary one.
- **Number sweep (Block C).** Each game at three sizes. Does the wording effect survive a change of scale?

DRAFT

Table 4: Stage 2B traps: share correct (%), normal → disguised wording, among answers whose trap-specific maths check was passed. "–": no answer passed the check.

Trap	What changes (correct answer)	gpt-oss	Nemotron	Kimi	Gemini
Vickrey	winner pays *twice* the second bid (bid $v/2$)	56→65	100→100	99→94	–→56
Cournot	three firms (produce $(a-c)/4$)	71→40	100→100	99→99	–→–
Prisoner's dilemma	$R > T$ and $S > P$ (cooperate)	59→93	100→100	99→100	–→100
Public goods	$M = 5 > n = 4$ (contribute all)	75→95	93→100	96→96	67→61

- **Endgame (Block E).** The prisoner's dilemma at round 5, 9 or 10 of 10, after mutual cooperation in every earlier round. Backward induction says defect in every round.

In this draft, the traps (Block B) are measured for all four models and analysed as registered. For the number sweep and the endgame (Blocks C and E), gpt-oss's entries (marked p) are the pre-registered predictions, which were stated for all models jointly and are shown at the midpoint of each registered range; pooled tests there use the three complete models and are provisional.

Traps: the strong models are not fooled. The registered prediction was that recall would make the normal wording a trap: 15–40% correct, against 40–85% disguised. Nemotron and Kimi instead answer every trap correctly 93–100% of the time in *both* wordings, and almost never give the textbook answer (at most 7% in any cell). A model that recalled "bid your value" or "defect" would have fallen into these traps; these two re-derive the answer when one rule changes.

gpt-oss falls into the traps when the game is named. gpt-oss shows the recall signature the traps were built to detect. In the normal wording it gives the textbook answer in 24% of Vickrey answers ("bid your value"), 41% of prisoner's dilemma answers ("defect") and 23% of public goods answers ("contribute nothing"), against 4%, 7% and 5% disguised. Its correct rate rises under disguise accordingly: from 59% to 93% in the prisoner's dilemma and from 75% to 95% in public goods (both $p < 10^{-5}$), and from 56% to 65% in the auction (not significant). The Cournot trap runs the other way (71% named, 40% disguised), with no textbook answers in either wording. Here the disguised version demands the three-firm first-order condition from scratch, which pre-registration 2 expected to be harder. This matches gpt-oss's graded retrieval in Stage 2C: the same model, by an independent test, again answers from memory when it recognises the game.

The registered test, pooled. Pooled over all four models (Cochran–Mantel–Haenszel by model, Holm across the four traps), two traps show a significant wording effect. In the prisoner's dilemma trap, disguise raises correct answers by 12 points (Holm $p = 6 \times 10^{-10}$) and cuts textbook answers from 14% to 2% (Holm $p = 6 \times 10^{-10}$). In the Cournot trap, disguise lowers correct answers by 10 points (Holm $p = 3 \times 10^{-6}$). Public goods (+5 under disguise, Holm $p = 0.055$) and Vickrey (-3, $p = 0.52$) are not significant. The predicted direction (more traps fallen into in the normal wording) holds for the prisoner's dilemma and public goods, reverses for Cournot, and is absent for Vickrey. The predicted levels were far too low: pooled correct rates are 79–98% in every cell. The predicted most-caught trap, the double-payment auction, held narrowly (83% correct over both

Table 5: Stage 2B number sweep: share correct (%), normal / disguised, pooled over the three complete models. Interaction: wording × size in a logistic regression with model fixed effects, Holm across games.

Game (sizes)	Small	Medium	Large	Interaction, Holm p
Vickrey (2, 4, 8 bidders)	100 / 99	100 / 100	100 / 100	not estimable (ceiling)
Cournot ($a \approx 60$, 100, 200)	96 / 68	95 / 65	93 / 65	0.71
Public goods (3, 4, 8 players)	100 / 83	99 / 89	99 / 99	0.17
Prisoner's dilemma (2, 10, 50 rounds)	78 / 79	37 / 64	28 / 61	0.0005

Table 6: Stage 2B endgame: defection (%) in round 5, 9 or 10 of a 10-round prisoner's dilemma after mutual cooperation in every earlier round. Theory: 100% in every cell.

	Normal wording			Disguised wording		
Model	5	9	10	5	9	10
gpt-oss-120b	35[P]	48[P]	60[P]	82[P]	82[P]	88[P]
Nemotron 3 Ultra	22	96	100	16	93	96
Kimi K3	7	59	99	10	60	95
Gemini 3.5 Flash Lite	0	68	100	5	11	27
Three models pooled	10	74	100	10	55	73

wordings, against 84–93% for the others).

Gemini fails the traps' maths, in the textbook direction. Gemini passed no maths check in the normal wording of the Vickrey, Cournot and prisoner's dilemma traps (0 of 138 each), so its play there cannot be scored. The failures are themselves informative (exploratory). In the Vickrey trap's check ("the winner pays twice the second-highest bid; what is your payoff?"), 71 of Gemini's 138 normal-wording answers are exactly the single-payment payoff, $v - H$ rather than $v - 2H$: the familiar rule overrides the stated one even in arithmetic. In the disguised wording it passes about half of the Vickrey and prisoner's dilemma checks and then plays correctly 56% and 100% of the time.

The wording effect does not depend on scale, except in the prisoner's dilemma. Table 5 gives the sweep. As registered, the Cournot gap is constant across sizes (28–30 points; interaction $p = 0.71$). It comes almost entirely from Gemini (95% normal against 14% disguised over all sizes), while Nemotron and Kimi lose at most 9 points. The prisoner's dilemma is the registered exception, and it behaves as predicted: equilibrium defection in the normal wording falls with the horizon (78% at 2 rounds, 28% at 50) and the gap widens from 0 to 33 points (Holm $p = 0.0005$). A long, recognised dilemma reads as an invitation to cooperate. gpt-oss's sweep is still in collection; its registered prediction is no wording × size interaction except a positive one in the prisoner's dilemma[P].

The endgame: cooperate early, defect at the end. None of the three complete models follows backward induction from the start: after four rounds of mutual cooperation, at most 22% defect in round 5 (Table 6, Figure 4). Defection then rises sharply, and in the normal wording it reaches 99–100% in the announced last round for all three complete models. This is the pattern

DRAFT




Figure 4: Stage 2B endgame: defection after mutual cooperation in every earlier round, by round and wording, for the three models whose Block E is complete (95% Wilson intervals; dashed: backward induction). Nemotron and Kimi trace the same curve in both wordings. Gemini defects at the end only when the game is named.

of human play in finitely repeated dilemmas [17], not the backward-induction solution. The author's registered expectation was the opposite: weak, "warm" named endgame behaviour and high disguised defection throughout. The registered discriminator, named defection in round 10 minus round 9, was predicted at +10 to +15 points and is +26. Pre-registration 2 named near-theory round-10 defection in the normal wording as "the most surprising single result Stage 2B could produce"; it occurred. Read as registered, the models' cooperation in the named game is strategic, not warmth: it ends exactly when the future ends.

The wording difference in rounds 9 and 10 (pooled +20 and +27 points, Holm $p < 10^{-7}$) is almost entirely Gemini's. Nemotron and Kimi defect at nearly the same rates in both wordings (within 6 points), so their endgame reasoning does not depend on recognising the game. Gemini defects in the last round 100% of the time when the game is named and 27% when it is not: it applies the folk rule "defect at the end" only to a game it recognises. This matches its retrieval signature in Cournot.

Robustness to the re-asked answers. Kimi's Block C and E results above include the 219 answers re-asked after NVIDIA's degraded days (Appendix A). Under the registered scoring, which drops them, Kimi's rate in every Block C and E cell moves by at most 5 points, and no conclusion changes.

7 Mechanism design for noisy agents

We now treat each player as a logit-QRE player with precision λ and ask how rules should change. All results are verified numerically: the code accompanies the paper, and every claim has a test.

7.1 Second-price auctions with a reserve and a payment multiplier

Let $M(r, \alpha)$ be the rule under which the highest bid wins if it is at least r, and the winner pays $\alpha \cdot \max(\text{second bid}, r)$. The Vickrey auction is $M(0, 1)$, and under $M(0, \alpha)$ the dominant strategy

is $b = v/\alpha$. In a symmetric logit QRE, each bidder's bid density is $\propto \exp(\lambda U(b \mid v))$, where U is the expected payoff against the other bidders' QRE bids.

Theorem 1 (α is irrelevant for QRE bidders)**.** *If $(B_1, \ldots, B_n)$ is a QRE of $M(r, 1)$ on bid space $[0, \bar{B}]$, then $(B_1/\alpha, \ldots, B_n/\alpha)$ is a QRE of $M(r/\alpha, \alpha)$ on $[0, \bar{B}/\alpha]$, with the same winner, the same revenue and the same payoffs.*

Proof. Against a highest rival bid H, $U_\alpha(b \mid v) = \mathbb{E}[(v - \alpha \max(H, r/\alpha))\mathbf{1}\{H < b,\ b \geq r/\alpha\}]$. Suppose rivals play $H = H_1/\alpha$, and substitute $b = \beta/\alpha$. Then $U_\alpha(\beta/\alpha \mid v) = \mathbb{E}[(v - \max(H_1, r))\mathbf{1}\{H_1 < \beta,\ \beta \geq r\}] = U_1(\beta \mid v)$. So the M_α bid has density $\propto \exp(\lambda U_1(\alpha b \mid v))$. By a change of variables, αB has density $\propto \exp(\lambda U_1(x \mid v))$, which is the M_1 QRE density, and the normalising constants agree because both integrate to one. The scaled profile is therefore self-consistent, which makes it a QRE. Dividing every bid by α preserves their order, and revenue is $\alpha \cdot B_{(2)}/\alpha = B_{(2)}$. □

The invariance needs the bid space to scale with α. Our solver lays the bid grid out in value units and confirms the identity to 10^{-9}.

A test of retrieval. For a deriving QRE bidder, $\alpha \cdot b$ has the same distribution at every α. A bidder that recalls "bid your value" bids v regardless. Under $\alpha = 2$, three such bidders leave the winner with $\mathbb{E}[v_{(1)}] - 2\,\mathbb{E}[v_{(2)}] = 77.5 - 110 = -32.5$. Any dependence of $\alpha \cdot b$ on α therefore cannot be QRE noise; it is the fingerprint of recall. Stage 2B's "winner pays twice" trap implements exactly this test (Table 4). Nemotron bids half its value in 100% of answers in both wordings and Kimi in 99% and 94%: the rational response, which is also the QRE-consistent one. gpt-oss bids its full value, the recalled answer, in 24% of normal-wording answers against 4% disguised: exactly the fingerprint the theorem identifies. Gemini cannot pass the trap's maths check in the normal wording, and half of its failed checks apply the single-payment rule, the arithmetic signature of recall.

Theorem 2 (a reserve never raises efficiency)**.** *For any λ, expected efficiency (the winner's value, or 0 without a sale) cannot be increased by $r > 0$.*

Proof. For fixed bids, r never changes who has the highest bid; it can only cancel the sale, replacing a value of at least 10 by 0. Under QRE the bids also respond to r. That strategic effect is verified numerically: efficiency falls in r at every λ tested. □

The originally planned problem, maximising efficiency over (r, α), therefore has a trivial answer. For *revenue*, with values uniform on $[10, 100]$, rational bidders have $\varphi(v) = 2v - 100$, so Myerson's reserve is $r^* = 50$. For QRE bidders we solve the full symmetric fixed point, in which each bidder responds to the others' noisy bids, and optimise r (Figure 5).

The optimal reserve $r^*(\lambda)$ is U-shaped:

- **Moderate noise** ($\lambda \approx 0.2$): 21% of bidders with $v > 50$ bid below a reserve of 50 and are excluded, so lowering r wins those sales back ($r^* = 41$).
- **Extreme noise** ($\lambda \approx 0.02$): bids barely track values (a bidder worth 20 bids 59 on average), so the reserve acts as a floor under random overbids, and r^* rises above 50.

The revenue gain over Myerson's reserve never exceeds about 1%. Moreover, all four models bid at the ceiling of precision in the standard (named) auction (Appendix B). For these agents the auction leaves little to design, so we turn to the game where they are genuinely noisy.

DRAFT




Figure 5: The revenue-optimal reserve for three logit-QRE bidders (values uniform on $[10, 100]$). It is U-shaped in precision and returns to Myerson's 50 as $\lambda \to \infty$.

7.2 A cooperation subsidy for the prisoner's dilemma

Under $S(\tau)$, every player who cooperates is paid an extra τ per round. Against an opponent who cooperates with probability p, defecting pays more by $\Delta U(p) = p(T-R)+(1-p)(P-S)$. Under $S(\tau)$ the advantage becomes $\Delta U(p) - \tau$, and the symmetric logit QRE satisfies $p = 1/(1 + e^{\lambda(\Delta U(p)-\tau)})$.

Theorem 3 (closed-form subsidy)**.** *The subsidy at which the symmetric logit-QRE cooperation rate equals p^* is*

$$\tau(p^*, \lambda) = \Delta U(p^*) + \frac{\operatorname{logit}(p^*)}{\lambda}.$$

Since $d\tau/dp = (T - R) - (P - S) + 1/(\lambda p(1 - p)) > 0$, each τ gives exactly one QRE.

Proof. Rearranging, $(1 - p)/p = e^{\lambda(\Delta U(p)-\tau)}$, so $-\operatorname{logit}(p) = \lambda(\Delta U(p) - \tau)$. Solve for τ. □

Corollary 1 (a parameter-free halfway point)**.** *In the stage game, at $\tau_{1/2} = \Delta U(\frac{1}{2}) = \frac{1}{2}[(T - R) + (P - S)]$ (that is, 1.5 for our payoffs), every regular QRE population cooperates with probability exactly $\frac{1}{2}$, whatever its precision and whatever its symmetric error distribution.*

Proof. At $p = \frac{1}{2}$ and $\tau = \tau_{1/2}$ the player is indifferent, so a regular quantal responder randomises evenly. Uniqueness holds because $\Delta U(p) - \tau$ rises in p, while the response falls in it. □

Proposition 2 (a ceiling on quantal cooperation)**.** *In the stage game, for every subsidy $\tau \le \tau_{1/2}$, every symmetric regular QRE has cooperation $p \le \frac{1}{2}$, at every precision. Cooperation above one half at $\tau \le \tau_{1/2}$ is therefore outside the whole regular-QRE family.*

Proof. Suppose $p > \frac{1}{2}$. Since ΔU is increasing in p (because $T - R > P - S$), $\Delta U(p) - \tau > \Delta U(\frac{1}{2}) - \tau_{1/2} = 0$, so defection is strictly better than cooperation against p. A regular quantal responder then cooperates with probability below $\frac{1}{2}$, contradicting $p > \frac{1}{2}$. □

The fitting consequence is immediate. A population that cooperates more than half the time without a subsidy can only be approached by QRE from below, as $\lambda \to 0$. The maximum likelihood λ is




Figure 6: Cooperation under a subsidy τ for logit-QRE players. Every precision passes through 50% at $\tau = 1.5$ (Corollary 1), as does the rational mixed equilibrium. The dotted line is Theorem 3's subsidy for 90% cooperation at Nemotron's fitted $\lambda = 0.154$.

then driven to the floor of the grid, and Theorem 3 turns a near-zero λ into an enormous "required" subsidy. Section 8 shows this happening.

Rational players and the repeated game.

- **Rational stage game:** players defect for $\tau < P - S = 1$ and cooperate for $\tau > T - R = 2$. In between, the subsidised stage game is chicken, whose symmetric equilibrium mixes with $p = \tau - 1$, so it too passes through $\frac{1}{2}$ at $\tau = 1.5$.
- **Repeated game:** chicken has two pure equilibria that pay each player differently, so in the 10-round game, round-1 cooperation can be subgame-perfect: play (C, C), and punish a deviator in the last round with the equilibrium worst for them [3]. At $\tau = 1.5$, deviating gains 0.5, while the punishment costs at least 1.5. So cooperation above 50% at $\tau = 1.5$ is consistent with rational repeated-game play as well as with a cooperation norm, and the reasoning codes separate the two.

Noisy players are cheap to nudge towards partial cooperation and expensive to push towards certainty (Figure 6). At Nemotron's $\lambda = 0.154$:

- 50% cooperation costs $\tau = 1.5$;
- the classical choice of $\tau = 2.5$, just above dominance, yields only about 54%;
- 90% requires $\tau \approx 16.2$.

DRAFT

Table 7: Stage 5: round-1 cooperation (%) under the subsidy τ, 100 questions per cell, against each theory's prediction. QRE is evaluated at the model's fitted Stage 2A precision $\hat{\lambda}$ (posterior median). Classical is the stage-game equilibrium. The last column is Stage 2A's identical question without the subsidy rule. †At the registered cap.

			Cooperation at subsidy τ				No rule
Model	$\hat{\lambda}$	τ^*	0	1.5	2.5	τ^*	(2A)
gpt-oss-120b	0.579	5.7	8	57	84	98	31
Nemotron 3 Ultra	0.154	16.2	18	96	100	100	41
Kimi K3	0.0075	50†	31	95	99	99	54
Gemini 3.5 Flash Lite	0.0032	50†	94	100	100	100	91
Classical prediction			0	50	100	100	
QRE prediction, gpt-oss			32	50	62	90	
QRE prediction, Nemotron			44	50	54	90	
QRE prediction, Kimi / Gemini			50	50	50	59 / 54	

8 A confirmatory test of the derived mechanism

Stage 5 asks each model the Stage 2A prisoner's dilemma (round 1, standard wording) with the subsidy stated as a separate rule for both players. There are 100 questions per level, balanced across the paraphrases, at four levels:

- $\tau = 0$: the baseline;
- $\tau = 1.5$: Corollary 1;
- $\tau = 2.5$: the classical guess;
- $\tau^* = 1.9 + \ln 9/\hat{\lambda}_m$: Theorem 3's subsidy for 90%, at model m's fitted precision; the derived mechanism.

Because $\tau^* > 2.5$ whenever $\lambda < 3.66$, "the derived subsidy yields more cooperation" would test nothing. The registered comparison is between the theories' *predictions*:

- at $\tau = 2.5$, is QRE's prediction closer to the observed rate than classical theory's 100%?
- at τ^*, is the observed rate within 90 ± 15%?

Decision-gate criteria (held-out calibration) and an interpretation key for every pattern were fixed before the remaining fits existed. The pre-registered prediction is that classical theory will predict better than QRE at $\tau = 2.5$ for Nemotron and Kimi, because their low prisoner's dilemma λ reflects a cooperation norm, not insensitivity to payoffs.

All 1,600 Stage 5 answers were collected after pre-registration 4 was filed (first answer two minutes after the registration time stamp). Table 7 and Figure 7 give the results. The four registered tests read as follows.

Test 1: at $\tau = 2.5$, classical theory predicts better than QRE, for every model. The difference in absolute error (classical minus QRE) is -46 points for Nemotron, -48 for Kimi and -50 for Gemini, with bootstrap intervals far from zero. For gpt-oss it is -6 points $[-20, +8]$: classical theory is closer, but not decisively. Every model cooperates at least 84% once cooperation is dominant, where QRE at the fitted precision predicts 50–62%.

DRAFT

Test 2: the derived mechanism reaches its target, and overshoots it. At τ^*, cooperation is 98–100% for every model, inside the registered band of 90 ± 15. For every model, though, the 95% interval lies wholly above 90%: the mechanism worked, but it overpaid. The overpayment is largest where Proposition 2 predicts it. Kimi and Gemini cooperate more than half the time with no subsidy (54% and 91% in Stage 2A), so their fitted λ sits at the floor of the grid and τ^* hits the cap of 50, twenty times the 2.5 at which they already cooperate 99–100%. Only for gpt-oss did the derived subsidy earn its cost: the classical guess of 2.5 reached 84%, short of the 90% target, and $\tau^* = 5.7$ reached 98%.

Test 3: the parameter-free halfway point holds for one model. Corollary 1 predicts exactly 50% at $\tau = 1.5$ for any regular quantal responder. gpt-oss cooperates 57% $[47, 66]$ (exact binomial $p = 0.19$), consistent with the prediction. The other three cooperate 95–100% (Holm-adjusted $p < 10^{-21}$), which by Proposition 2 no regular QRE can produce. Cooperation this high at $\tau = 1.5$ is consistent with the subgame-perfect repeated-game cooperation described in Section 7 and with a cooperation norm; Stage 5 alone does not separate the two.

Test 4: calibration. Only 3 of 16 cells are within ± 10 points of QRE: gpt-oss at $\tau = 1.5$ and τ^*, and Nemotron at τ^*, where QRE's 90% and the observed 100% are both near the ceiling.

Stating the rule changes play. The registered comparison of $\tau = 0$ with Stage 2A isolates the effect of merely stating a subsidy rule, with a subsidy of zero. Cooperation falls for three models: gpt-oss from 31% to 8%, Nemotron from 41% to 18% and Kimi from 54% to 31% (each $p < 0.001$). Gemini is unchanged (91% vs 94%, $p = 0.44$). A payoff rule on the page seems to move these models from the cooperative script towards the payoff calculation. That is itself a mechanism-design effect: the framing of an incentive matters even when the incentive is zero.

Pre-registration 4, scored. The amended headline prediction was that classical theory would beat QRE at $\tau = 2.5$ for Nemotron and Kimi, that τ^* would overshoot, and that QRE would be closest only for Gemini. The first two parts held; the third failed, because classical theory was also closer for Gemini. The author's level-by-level forecasts were closer to the data than either theory for gpt-oss and Kimi (mean absolute error 6.5 and 13 points, against 8.3 and 19.5 for classical theory and 15.3 and 38.3 for QRE). For Nemotron they were as close as classical theory (16.5 against 16.0 points). They missed badly for Gemini (43.5 points), whose near-universal cooperation at $\tau = 0$ the author did not foresee. This comparison is descriptive and was not registered.

What Stage 5 shows. The models are not insensitive to incentives, which is what a low fitted λ would suggest. They are *more* responsive than QRE allows, and three of them more responsive than even the classical stage-game equilibrium at $\tau = 1.5$. The low prisoner's dilemma λ measured a cooperation norm on the unsubsidised question, not noise in responding to payoffs. A designer who took it at face value would set subsidies up to twenty times larger than needed.

9 Discussion

"Derive or recall" has no single answer. The same question receives different answers across models and games:

- Nemotron's and Kimi's Cournot play survives the removal of every cue that could trigger recall, and both re-derive the answer when a trap changes one rule;

- gpt-oss's play degrades step by step as the cues are removed, its errors become the cooperative (collusive) answer, and in the traps it gives the textbook answer about five times as often when the game is named;
- Gemini's Cournot play does not survive the removal of the game's name;
- for games whose rules are their fingerprint (the second-price auction, public goods), no wording hid the game from the strongest models, so derivation and recall remain observationally equivalent there.

The last point is a limit of the method, not a failure of it: recognising a game's structure is itself a form of reasoning. More striking is that the author's own pre-registered expectations about *which* models recall were reversed. Intuition about which LLMs "really reason" is unreliable, and that is a reason to measure it.

Competence buys robustness. The pre-registered ranking held exactly: models that pass more competence probes lose less when the game is disguised. A model that can reliably execute the rules has less need to lean on recognising them. This suggests a practical screen for agents that will face unfamiliar rules: probe pass rates under paraphrase are a cheap proxy for robustness to rule changes.

Recognition can pull away from equilibrium. The usual worry is that recall makes models look more rational than they are. In the prisoner's dilemma we find the reverse. Recognising the game lowers equilibrium play: Gemini by 62 points under the standard disguise, and every model by 17–76 points relative to the extreme wording. The retrieved content is the folk lesson of repeated dilemmas (trust, reciprocity, establishing cooperation), not the backward-induction solution, much as calling a human prisoner's dilemma the "Community Game" raises cooperation [10]. For mechanism design this matters directly: an agent's behaviour depends on which famous game the designer's rules resemble.

Probes change conclusions. Without competence probes, Gemini's disguised auction would read as a 92-point strategic collapse. With them, it is correctly a reading failure. Without a registered slip rule, Nemotron's extreme-wording Cournot and auction results would read as 46- and 51-point drops. Both safeguards altered headline numbers, which is the strongest argument for building them in before the data.

Implications for designing mechanisms for AI agents. Theorem 1 gives a cheap diagnostic: rescale the payment rule and check whether bids rescale. Theorem 3 shows that noise makes high compliance expensive, so subsidies should be set from measured responsiveness rather than from dominance thresholds. And the decision gate warns against borrowing the behavioural model wholesale. Logit QRE fails held-out calibration for every model, because LLM errors are rare, large and discrete: slips, collusive answers and norms. A fitted λ then encodes a norm or a slip rate rather than noise. Stage 5 shows the cost: a subsidy derived from the fitted λ reached its target but overpaid by up to twenty times, while the classical dominance threshold was enough for three of four models.

When does a fitted behavioural model mislead? Proposition 2 gives a check that needs no new data: if a population cooperates more than half the time where every regular QRE predicts at most half, the population is outside the model, and any λ fitted to it will be pushed towards

zero. Three of our four models fail this check in Stage 5 (95–100% cooperation at $\tau = 1.5$), and Gemini already fails it without any subsidy (91–94%). The general lesson is that a precision parameter fitted to one setting (here, the unsubsidised game) can measure something other than responsiveness (here, a norm), and then extrapolates badly to the setting a designer cares about. Checking a behavioural model's qualitative restrictions before trusting its parameters is cheap, and it would have prevented the overpayment.

Framing is part of the mechanism. Stating a subsidy rule of zero cut cooperation by 23 points in three models. Framing effects are well documented in people [18]; in the prisoner's dilemma, merely renaming the game changes human cooperation [10]. For LLM agents, the text of a rule, and not only its payoffs, is a design variable.

10 Limitations

- **Disguises can fail.** The standard disguise did not hide the games from two of the four models (Nemotron and Kimi), and no wording hid the auction or public goods. Recognition is coded from written reasoning, so silent recognition cannot be excluded.
- **A leaky answer box.** In Stage 2A's disguised wording the answer field still carried the named game's field names ("bid", "quantity", "contribution"). This was found after collection, is recorded as deviation 8, and was removed in Stage 2C.
- **Timing.** Stage 2C was collected weeks after Stage 2A, so a provider updating a model in between would appear as a difference.
- **The behaviour model.** QRE treats every departure from equilibrium as payoff-scaled noise. Our models' departures are often slips or norms instead, so λ is a summary, not a structural parameter [15], and it is never compared across games.
- **The λ grid.** The registered grid tops out at $\lambda = 1000$, where QRE cannot reproduce 100% equilibrium play in the auction. This affects the calibration of those cells, but not the gate's verdict.
- **The stage-game QRE in the prisoner's dilemma.** It ignores continuation play, which is harmless when the stage equilibrium is unique but not at $\tau = 1.5$.
- **Stage 5 is one game.** The subsidy test uses the prisoner's dilemma only, with one wording, and 100 questions per level. Cooperation above one half at $\tau = 1.5$ is consistent with both a norm and subgame-perfect repeated-game play, and Stage 5 does not separate them.
- **Data collection on NVIDIA's degraded days.** Kimi returned scrambled replies on 7–9 October 2026; 219 unreadable Stage 2B answers from those days were re-asked at the author's decision (Appendix A). Only unreadable answers were re-asked, so the re-ask is selective; results are reported both ways.
- **Scope.** Four models, four games and free API tiers with default sampling. Cross-model patterns are rankings, not estimates of population effects.

11 Conclusion

Whether an LLM agent derives or recalls a game's equilibrium is an empirical property of the model and the game, and it can be measured. Isomorphic twins with same-wording competence probes,

DRAFT

measured recognition and an extreme disguise separate the two wherever the game can be hidden at all. On that evidence:

- two frontier models solve a Cournot game they no longer recognise, and are not fooled by traps that make the textbook answer wrong;
- a third loses the equilibrium step by step as the cues are removed;
- a fourth loses it as soon as the name goes;
- in the prisoner's dilemma, recognising the game pulls every model away from equilibrium, towards cooperation;
- the standard behavioural model, logit QRE, does not describe any of them.

For mechanism design these are not curiosities. They determine whether a rule tuned to observed play will survive a change in the rules. In a pre-registered test, a subsidy derived from fitted quantal response did reach its target, but overpaid by up to twenty times, because the models respond to incentives more sharply than the fitted model allows. Before designing for AI agents from a behavioural model, the model itself should be tested on them.

Acknowledgements

Claude (Anthropic) assisted with code, typesetting and drafting. The research questions, predictions and decisions are the author's.

Data and code availability

Code, prompts, seeds, raw answers, analysis outputs and the locked analysis plans are available at https://github.com/mmehta4/llm-mechanism-design (public on release). Pre-registrations: osf.io/2uqpj, osf.io/6hz8d, osf.io/cqnsy, osf.io/qg43y.

References

[1] Alan Agresti and Yongyi Min. Simple improved confidence intervals for comparing matched proportions. *Statistics in Medicine*, 24(5):729–740, 2005.

[2] Elif Akata, Lion Schulz, Julian Coda-Forno, Seong Joon Oh, Matthias Bethge, and Eric Schulz. Playing repeated games with large language models. *Nature Human Behaviour*, 2025. doi: 10.1038/s41562-025-02172-y.

[3] Jean-Pierre Benoît and Vijay Krishna. Finitely repeated games. *Econometrica*, 53(4):905–922, 1985.

[4] Jinhao Duan et al. GTBench: Uncovering the strategic reasoning capabilities of LLMs via game-theoretic evaluations. In *Advances in Neural Information Processing Systems*, 2024.

[5] Caoyun Fan, Jindou Chen, Yaohui Jin, and Hao He. Can large language models serve as rational players in game theory? a systematic analysis. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pages 17960–17967, 2024. doi: 10.1609/aaai.v38i16.29751.

[6] Jacob K. Goeree, Charles A. Holt, and Thomas R. Palfrey. *Quantal Response Equilibrium: A Stochastic Theory of Games*. Princeton University Press, 2016.

DRAFT

[7] Sture Holm. A simple sequentially rejective multiple test procedure. *Scandinavian Journal of Statistics*, 6(2):65–70, 1979.

[8] John J. Horton, Apostolos Filippas, and Benjamin S. Manning. Large language models as simulated economic agents: What can we learn from homo silicus? Working Paper 31122, National Bureau of Economic Research, 2023.

[9] Jingru Jia, Zehua Yuan, Junhao Pan, Paul E. McNamara, and Deming Chen. LLM strategic reasoning: Agentic study through behavioral game theory. In *Advances in Neural Information Processing Systems*, 2025. arXiv:2502.20432.

[10] Varda Liberman, Steven M. Samuels, and Lee Ross. The name of the game: Predictive power of reputations versus situational labels in determining prisoner's dilemma game moves. *Personality and Social Psychology Bulletin*, 30(9):1175–1185, 2004.

[11] R. Thomas McCoy, Shunyu Yao, Dan Friedman, Matt Hardy, and Thomas L. Griffiths. Embers of autoregression show how large language models are shaped by the problem they are trained to solve. *Proceedings of the National Academy of Sciences*, 121(41):e2322420121, 2024. doi: 10.1073/pnas.2322420121.

[12] Richard D. McKelvey and Thomas R. Palfrey. Quantal response equilibria for normal form games. *Games and Economic Behavior*, 10(1):6–38, 1995.

[13] Roger B. Myerson. Optimal auction design. *Mathematics of Operations Research*, 6(1):58–73, 1981.

[14] Brian A. Nosek, Charles R. Ebersole, Alexander C. DeHaven, and David T. Mellor. The preregistration revolution. *Proceedings of the National Academy of Sciences*, 115(11):2600–2606, 2018.

[15] Mateo Pechon-Elkins and Jon Chun. Auditing game-theoretic measures of strategic reasoning in LLMs, 2026. arXiv:2603.10029.

[16] Tim Roughgarden. *Twenty Lectures on Algorithmic Game Theory*. Cambridge University Press, 2016.

[17] Reinhard Selten and Rolf Stoecker. End behavior in sequences of finite prisoner's dilemma supergames: A learning theory approach. *Journal of Economic Behavior & Organization*, 7 (1):47–70, 1986.

[18] Amos Tversky and Daniel Kahneman. The framing of decisions and the psychology of choice. *Science*, 211(4481):453–458, 1981.

[19] William Vickrey. Counterspeculation, auctions, and competitive sealed tenders. *The Journal of Finance*, 16(1):8–37, 1961.

A Deviations from the pre-registrations

1. **PD scoring error in practice runs.** Named answers were scored against the disguised labels; fixed before Stage 2.
2. **Gemini 3.8 Flash replaced** by Gemini 3.5 Flash Lite, because of a 20-request daily cap.

DRAFT

3. **Empty replies** (bursts of "!!!!") are re-asked rather than scored as unreadable.
4. **gpt-oss's daily token cap** slows its collection; this does not affect the design.
5. **A 10-minute NVIDIA access outage.** Its 4,454 refused requests were relabelled as infrastructure failures and re-asked.
6. **The fraction slip.** Recorded as an exploratory observation, and corrected only in the pre-registration-3 comparison.
7. **Block D (reasoning effort)** was dropped before any of its data existed, so that all models answer the same questions.
8. **The disguised answer boxes** carried the named game's field names (a limitation).
9. **Ten questions re-asked** that should have been scored as the model's own (1 Kimi Stage 2A; 2 Nemotron Stage 2A; 7 Nemotron Stage 2B traps). The re-asked answers stand.
10. **The pilot answer form** sent explanatory text that leaked words; fixed before Stage 2C.
11. **A second provider for gpt-oss** (Cerebras, same open weights) was recorded as an option for Stage 2B and never used. Every gpt-oss answer comes from Groq.
12. **Additional API keys.** A second Gemini key and three further Groq keys, each from a different person's account, were used after the providers' support teams confirmed in writing that this is permitted. Same models and settings. Remaining work was split into disjoint slices of the registered question list, so no question was asked twice.
13. **One NVIDIA refusal** ("DEGRADED function cannot be invoked") had been scored as an unreadable Kimi answer; it was relabelled a server refusal and re-asked.
14. **Kimi's unreadable answers from NVIDIA's degraded days** (7–9 October 2026) were re-asked at the author's decision: 219 answers, 16% of that window against about 3% on other days. Only unreadable answers were re-asked; the originals remain in the data, and affected results are reported both ways.

B Stage 2A precision fits

Nemotron's Stage 2A Cournot fit is dominated by uncorrected fraction slips (answers such as 683 for 683/60), which are scored as they were written, as pre-registration 1 requires. With the slip correction fixed in pre-registration 3, its Cournot λ is 0.0082 $[0.0063, 0.0103]$ (Table 3). Kimi's Cournot difference arises entirely within the ± 0.5 tolerance: both wordings are at 100% equilibrium play.

DRAFT

Table 8: Posterior λ (median and 95% interval), named vs disguised. "$\geq$" marks a cell at the ceiling of the grid, where only a lower bound is identified. λ is on each game's payoff scale and is not comparable across games.

Model	Game	λ named	λ disguised	$\Delta\lambda$
gpt-oss	Vickrey	≥ 944	1.12 $[0.87, 1.45]$	$\geq +943$
	Cournot	0.173 $[0.13, 0.22]$	0.027 $[0.022, 0.035]$	$+0.146$, $P(>0) = 1.00$
	PD	0.579 $[0.27, 0.92]$	0.772 $[0.45, 1.12]$	-0.19, $P(>0) = 0.20$
	Public goods	3.76 $[3.07, 4.34]$	1.19 $[1.00, 1.37]$	$+2.53$, $P(>0) = 1.00$
Nemotron	Vickrey	≥ 944	≥ 944	both at ceiling
	Cournot	0.0012	0.0010	$+0.0001$, $P(>0) = 0.82$
	PD	0.154 $[0.002, 0.47]$	0.188 $[0.002, 0.50]$	-0.02, $P(>0) = 0.44$
	Public goods	≥ 21.8	≥ 21.8	both at ceiling
Kimi	Vickrey	≥ 944	≥ 944	both at ceiling
	Cournot	≥ 299	19.4 $[14.1, 26.6]$	$\geq +272$
	PD	0.0075 $[0.001, 0.11]$	0.079 $[0.001, 0.39]$	-0.06, $P(>0) = 0.21$
	Public goods	2.51 $[2.11, 2.90]$	3.98 $[3.35, 4.73]$	-1.51, $P(>0) = 0.00$
Gemini	Vickrey	≥ 944	3.98 $[1.5, 7.7]$ $(n = 11)$	$\geq +936$
	Cournot	0.649 $[0.50, 0.82]$	0.0047 $[0.004, 0.006]$	$+0.645$, $P(>0) = 1.00$
	PD	0.0032 $[0.001, 0.023]$	0.631 $[0.33, 0.97]$	-0.629, $P(>0) = 0.00$
	Public goods	≥ 21.8	0.434 $[0.36, 0.53]$	$\geq +21.2$

DRAFT




Figure 7: Stage 5: round-1 cooperation against the subsidy τ, one panel per model. Orange: observed rate with 95% Wilson interval (100 questions per level). Blue: logit QRE at the model's fitted Stage 2A precision $\hat{\lambda}$ (posterior median), with the 95% band over λ's posterior. Dashed: the classical stage-game equilibrium (all defect below $\tau = 1$, the mixed equilibrium $p = \tau - 1$ of the chicken game between 1 and 2, all cooperate above 2). Dotted: the 90% target and the derived subsidy τ^* (capped at 50).