

		Women		Men	
		Score	Confidence	Score	Confidence
Geometry	trig5	8.2	0.91	7.8	0.88
	trig8	7.4	0.87	6.9	0.81
	vision	6.7	0.84	7.3	0.89
Other	semtest	9.1	0.95	8.6	0.92
	align	5.9	0.76	6.5	0.80

tabularray by example

A compact tutorial for modern and powerful $\text{\LaTeX}$ tables

Author: **melepe** (mmelepe@gmail.com)
Version 1.1 ■ Compiled September 23, 2026

Product	Category	Price
Widget A	Tools	19.95
	Books	29.50
Widget C	Software	49.00
Widget D	Hardware	12.75

Lastest version on Github: https://github.com/mmelepe/tabularray_tutorial/blob/master/latest_compact.pdf
Long, beginner-friendly version: https://github.com/mmelepe/tabularray_tutorial/blob/master/latest_compact.pdf

Feature	Basic	Pro	Elite
Private rooms	✓	✓	✓
Customization	✓	✓	✓
Software updates	–	✓	✓
Customer support	–	✓	✓
Advanced monitoring	–	–	✓

Year	Attendance	City
2023	72%	The Hague
2024	81%	Ho Chi Minh City
2025	94%	Milano
2026	86%	Córdoba

Introduction

Creating tables in $\text{\LaTeX}$ can be difficult. Luckily, in 2021 the `tabularray` package was created, offering a simple united interface for most functionalities you will ever need, and then some.

Target audience

This short version, non-official tutorial, is aimed at people who already have some experience in Latex and just want a quick reference to learn `tabularray`. It showcases examples of `tabularray` uses, with a small explanation.

A more detailed tutorial for beginners (or people who wish to understand this package more in depth) is available at https://github.com/mmelepe/tabularray_tutorial/blob/master/latest.pdf.

Contents

1	Simple tables without hassle	4
1.1	A basic table	4
1.2	Column control	5
1.2.1	Control column width and vertical alignment	5
1.2.2	Multiline cells	6
1.2.3	Variable width column	6
1.2.4	Merged cells	7
2	More hassle with less simple tables	8
2.1	Manage separations and spacing	8
2.1.1	Add all separation lines	8
2.1.2	Manage row and column spacing	8
2.1.3	Manage merged cell expansion	9
2.2	Let's add some styling	10
2.2.1	A bit of colour and formatting	10
2.2.2	Style in the header, style in the body	10
2.2.3	Style of a row, style of a column	11
2.2.4	Border style	12
2.2.5	Advanced selectors	12
2.2.6	Smart selections with class and id	13
2.3	Multipage tables	14
2.4	Tabularray's libraries	16
2.4.1	Drawing in your table with Tikz	16
2.4.2	Diagonal separations with diagbox	17
2.4.3	Automatic in-cell computing with functional	17

Chapter 1

Simple tables without hassle

1.1 A basic table

All tables shown in this tutorial must load the tabularray package in the preamble: `\usepackage{tabularray}`.

Let us continue with the first example:

```
% \usepackage{tabularray} in the preamble
\begin{tblr}{|l|c|r|}
\hline
Hello & tabularray & world! \\
\hline
cell & cell & last table cell \\
\hline
\end{tblr}
```

Hello	tabularray	world!
cell	cell	last table cell



A tabularray environment has a mandatory argument between curly braces, that contains (among others) the column specification. A column specification, or colspec, specifies:

- the horizontal alignment of each column (left `l`, center `c`, right `r` or justified `j` for multiline columns). Default value is `j`
- vertical borders with the pipe character `|`

The body of the table separates cells by `&`, rows by `\\`. Horizontal lines are indicated in the body of the table by `\hline`. Space character between cells are ignored. As for line breaks, tabularray might behave incorrectly if there is more than one consecutive line break.

1.2 Column control

1.2.1 Control column width and vertical alignment

```
\begin{tblr}{|Q[1,2cm,b]|Q[r,2cm,t]|Q[2cm,m]|Q[2cm,m]|Q[2cm,h]|Q[2cm,f]|}
\hline
Column set to \texttt{Q[1,2cm,b]} & Column set to \texttt{Q[r,2cm,t]} & Column set
to \texttt{Q[2cm,m]} & Column set to \texttt{Q[2cm,m]} with a lot of text that
is going on forever to show the difference between \texttt{t} and \texttt{f}
alignment & Column set to \texttt{Q[2cm,h]} & Column set to \texttt{Q[2cm,f]}\
\hline
\end{tblr}
```

Column set to Q[1,2cm,b]	Column set to Q[r,2cm,t]	Column set to Q[2cm,m]	Column set to Q[2cm,m] with a lot of text that is going on forever to show the difference between t and f align- ment	Column set to Q[2cm,h]	Column set to Q[2cm,f]
--------------------------------	--------------------------------	---------------------------	---	---------------------------	---------------------------

Columns are technically all of `Q` type. A `Q` column can take optional arguments in any order, such as:

- The horizontal alignment¹ (`l`, `c`, `r`, `j`). Default value is `j`.
- The column width (in the example above, in `cm` but any unit of length, see e.g. <https://en.wikibooks.org/wiki/LaTeX/Lengths>, is valid). By default, a column will extend as much as possible so that all cells text fit on one line, which might cause the table to overflow.
- The vertical alignment. The possible values are: `h` (head, positions the text at the top of the cell), `f` (foot, positions the text at the bottom of the cell), `t` (sets the baseline of the cell at the top of the text block), `m` (sets the baseline at the middle of the text block), `b` (sets the baseline at the bottom of the text block). Default value is `m`.

Other options are available, and we will see some of these below.

Note that `h` and `b` options are not equivalent, neither are `f` and `t`.

¹A `Q[l]` column is equivalent to a `l` column, and so on. However, an `l` column cannot receive additional arguments, whereas a `Q` column can: `Q[1,2cm,f]`.

1.2.2 Multiline cells

```
\begin{tblr}{lQ[l,m]Q[l,m]}
Country & Capital(s) & Comment \\ \hline
Belize & Belmopan & N/A \\
Bénin & {Porto-Novo \\ Cotonou} & {Official capital \\ De facto administrative capital} \\
Bhutan & Thimphu & N/A \\
\end{tblr}
```

Country	Capital(s)	Comment
Belize	Belmopan	N/A
Bénin	Porto-Novo Cotonou	Official capital De facto administrative capital
Bhutan	Thimphu	N/A

Multiline cells must be delimited by {}. They can be vertically centered, by selecting the desired alignment in the colspec.

1.2.3 Variable width column

```
\begin{tblr}{
width=0.9\linewidth,
colspec={l|X|X[2,r]|},
}
Furniture & Price & Shop & Grade \\ \hline
Bed & 150 & MOBILI & 6/10 \\
Table & 800 & LUXTABLE & 8/10 \\
Desk & 300 & LBC & 7/10 \\
\end{tblr}
```

Furniture	Price	Shop	Grade
Bed	150	MOBILI	6/10
Table	800	LUXTABLE	8/10
Desk	300	LBC	7/10

Multiple arguments in a tabularray header

The example above passes another argument to tabularray (namely, the table width). Consequently, the colspec *must* be specified by using the keyword `colspec`. Keywords must be separated by a comma ,.

There can be no empty lines in the tabularray header. This would cause a compilation error.

`X` columns are columns of varying width. tabularray will automatically adjust their width so the table spans the whole line width, or whatever value is the header attribute `width` set to (if the attribute `width` is not set, it defaults to the line width).

`X` columns can receive any other argument that `Q` columns can receive, e.g. `X[r]` is a right-aligned `X` column².

²Technically, an `X[n]` column, with `n` a coefficient, is an alias to a `Q[co=n]` column.

In case there are several `X` columns, the extra width is equally distributed among them. This distribution can be weighted by passing any number value (a coefficient) as an argument to the `X` column. In the example above, the fourth column is twice as large as the third. Default coefficient for an `X` column is 1.

The coefficient in the `X` column can be any value (possibly decimal). It can also be negative. For instance, `X[-2.5]` means that the column will expand *at maximum* with coefficient 2.5, but will be smaller if the text in the column does not require that much space and other `X` columns can fill the remaining space.

```
\begin{tblr}{|X|X[-2.5]|}
\hline
coeff +1 & coeff -2.5 \\ \hline
\end{tblr}
```

coeff +1	coeff -2.5
----------	------------

1.2.4 Merged cells

```
\begin{tblr}{|l|l|l|l|l|}
\hline
1 & 2 & & & & & 3 & & \SetCell[c=2]{ } 4,5 & & hidden! \\ \hline
1 & & \SetCell[r=2,c=3]{r,m,4cm} 2,3,4 & & 0 & & 0 & & & 5 \\ \hline
\SetCell[r=2]{f} 1 & & & & & & & & & 5 \\ \hline
0 & 2 & & & 3 & & 4 & & & 5 \\ \hline
\end{tblr}
```

1	2	3	4,5	
1			2,3,4	5
				5
1	2	3	4	5

To merge cells, you have to use the command `\SetCell` and specify the merging within the optional argument. For instance, `\SetCell[r=2]{ }` says that the cell will span two rows, starting from the current cell. `\SetCell[c=4]{ }` will span the current cell over 4 columns.

Merged cells must still be specified in the table body with the ampersands `&`, even though their contents will be overwritten. Their contents may be empty.

The mandatory argument of `\SetCell[]{}` can receive any cell formatting instruction, e.g. a width, horizontal/vertical alignment, etc. For instance, `\SetCell[r=2,c=3]{r,m,4cm}` merges the cells on the next 2 rows and 3 columns, and the resulting merged cell will be right aligned, vertically centered, and 4 cm wide.

Most tables do not need more functionalities than what you have seen so far. Feel free to browse the rest of the document for more advanced features.

Chapter 2

More hassle with less simple tables

2.1 Manage separations and spacing

2.1.1 Add all separation lines

```
\begin{tblr}{hlines, vlines, colspec = {ccccccc}}
    & Monday & & Tuesday & & Wednesday & & Thursday & & Friday & & Saturday & & Sunday \\
Lunch & Potatoes & & Potatoes & & Potatoes & & Potatoes & & Potatoes & & Potatoes & & Potatoes \\
too! \\
Dinner & Rice & & Stir-fry & & Soup & & Eat out & & Fish & & Pizza & & Leftovers \\
\end{tblr}
```

	Monday	Tuesday	Wednesday	Thursday	Friday	Saturday	Sunday
Lunch	Potatoes	Potatoes	Potatoes	Potatoes	Potatoes	Potatoes	Potatoes too!
Dinner	Rice	Stir-fry	Soup	Eat out	Fish	Pizza	Leftovers



2.1.2 Manage row and column spacing

```
\begin{tblr}{
    colspec = {l1l}, hlines,
    rowsep = {8pt}, % default tabularray value is 2pt
    colsep = {1pt}, % default tabularray value is 6pt
}
    cell 1 & cell 2 & & cell  $\frac{3}{3}$  \\
    cell 4 & cell  $\frac{5}{6}$  & & cell 6 \\
\end{tblr}
```

cell 1 cell 2 cell $\frac{3}{3}$

cell 4 cell $\frac{5}{6}$ cell 6



2.1.3 Manage merged cell expansion

By default, merged cells will try to fit the contents of the merged cell on one line. If needed, only the last column (or last row) will be extended, but you can change this behaviour.

```
\begin{tblr}{
  colspec={llll},
  vlines,
  hlines,
  hspan=minimal,
  vspan=even,
}
\SetCell[r=2]{m} {Mur, ville, \ \ Et port, \ \ Asile \ \ De mort, \ \ Mer grise \ \ OÙ
  brise \ \ La brise, \ \ Tout dort.} & Les Djinns & Victor Hugo & 1829 \ \
& \SetCell[c=3]{l} A beautiful poem in which each stanza has a different metrical
  structure. & & \ \
\end{tblr}
```

Mur, ville, Et port, Asile De mort, Mer grise Où brise La brise, Tout dort.	Les Djinns	Victor Hugo	1829
	A beautiful poem in which each stanza has a different metrical structure.		

The possible values for `hspan` are `default` (only the last column is extended), `even` (all the columns covering a merged cell will be extended by the same amount), or `minimal` (the columns will not be extended, the text of the merged cell will wrap on several lines).

The values for `vspan` are `default` and `even`.

Compare the above example with e.g.

```
\begin{tblr}{
  colspec={llll},
  vlines,
  hlines,
  hspan=even,
  vspan=default,
}
\SetCell[r=2]{m} {Mur, ville, \ \ Et port, \ \ Asile \ \ De mort, \ \ Mer grise \ \ OÙ
  brise \ \ La brise, \ \ Tout dort.} & Les Djinns & Victor Hugo & 1829 \ \
& \SetCell[c=3]{l} A beautiful poem in which each stanza has a different metrical
  structure. & & \ \
\end{tblr}
```

Mur, ville, Et port, Asile De mort, Mer grise Où brise La brise, Tout dort.	Les Djinns	Victor Hugo	1829
	A beautiful poem in which each stanza has a different metrical structure.		

2.2 Let's add some styling

2.2.1 A bit of colour and formatting

Until tabularray version 2025C, you need to load the package `xcolor` in your preamble to add colors to your table.

```
\begin{tblr}{l|l|l|l|l|l}
Company & Q1 & Q2 & Q3 & Q4 & Total \\ \hline
COSTO & +150k & -300k & +210k & +150k & 
\SetCell{font={\small\ttfamily},green!80!black} +210k \\
McDalle & -120k & -200k & -200k & +250k & \SetCell{font={\small\ttfamily},red!60}
-270k \\
FireCar & +150k & +300k & +450k & +150k & 
\SetCell{font={\small\ttfamily},green!80!black} +1050k \\
\end{tblr}
```

Company	Q1	Q2	Q3	Q4	Total
COSTO	+150k	-300k	+210k	+150k	+210k
McDalle	-120k	-200k	-200k	+250k	-270k
FireCar	+150k	+300k	+450k	+150k	+1050k

Since we are not merging cells, we do not need to write the optional argument of `\SetCell`.

2.2.2 Style in the header, style in the body

The styling of the above table can also be specified in the header of the table. This allows to fully separate the data from its formatting and is a major functionality from tabularray.

```
\begin{tblr}{
  colspec={l|l|l|l|l|l},
  cell{2,4}{6} = {green!80!black},
  cell{3}{6} = {red!60},
  cell{2-4}{1} = {font={\ttfamily\small}},
}
Company & Q1 & Q2 & Q3 & Q4 & Total \\ \hline
COSTO & +150k & -300k & +210k & +150k & +210k \\
McDalle & -120k & -200k & -200k & +250k & -270k \\
FireCar & +150k & +300k & +450k & +150k & +1050k \\
\end{tblr}
```

The cell from row `i` and column `j` is selected by the keyword `cell{i}{j}`. Several indexes can be selected with a comma: `{2,4}`, or by a range `{3-8}`. Applying the same style to two cells with very different coordinates is possible: `cell{1}{2}, {3}{5}` will select both `cell{1}{2}` and `cell{3}{5}`.

Cells can also be merged from the header: `cell{i}{j} = {r=2,c=3}{m, red}`. You can leave the second mandatory argument empty `{}` if no further styling, besides the merging, is required.

2.2.3 Style of a row, style of a column

```

\begin{tblr}{
  colspec = {rllllll},
  cells = {font=\itshape},
  columns = {2cm, m},
  column{1} = {1cm},
  row{1} = {ht=1cm,blue!50},
  colsep=4pt,
  rowsep=1pt,
  cell{1}{2} = {c=6}{c},
  cell{2}{1} = {r=4}{m,blue!70},
}

& Alphabets & & & & & \hline
Greek & {Alpha \\\ $\\alpha$} & {Beta \\\ $\\beta$} & {Gamma \\\ $\\gamma$} & {Delta \\\ $\\delta$} & {Epsilon \\\ $\\varepsilon$} & {Zeta \\\ $\\zeta$} \\\
& {Eta \\\ $\\eta$} & {Theta \\\ $\\theta$} & {Iota \\\ $\\iota$} & {Kappa \\\ $\\kappa$} & {Lambda \\\ $\\lambda$} & {Mu \\\ $\\mu$} \\\
& {Nu \\\ $\\nu$} & {Xi \\\ $\\xi$} & {Omikron \\\ o} & {Pi \\\ $\\pi$} & {Rho \\\ $\\rho$} & {Sigma \\\ $\\sigma$, $\\varsigma$} \\\
& {Tau \\\ $\\tau$} & {Upsilon \\\ $\\upsilon$} & {Phi \\\ $\\varphi$} & {Chi \\\ $\\chi$} & {Psi \\\ $\\psi$} & {Omega \\\ $\\omega$} \\\
\end{tblr}

```

Alphabets						
Greek	Alpha	Beta	Gamma	Delta	Epsilon	Zeta
	α	β	γ	δ	ε	ζ
	Eta	Theta	Iota	Kappa	Lambda	Mu
	η	θ	ι	κ	λ	μ
	Nu	Xi	Omikron	Pi	Rho	Sigma
	ν	ξ	o	π	ρ	σ, ς
	Tau	Upsilon	Phi	Chi	Psi	Omega
	τ	υ	φ	χ	ψ	ω

The example above illustrates how priority rules apply to styling: for a given property, the last written instruction (either in the header or in the body) will be the one applied. Here, the column 1 will be 1cm wide, because the instruction for `column{1}` was written after the instruction `columns`. If the instructions would be permuted, the column would be 2cm wide.

2.2.4 Border style

```
\begin{tblr}{
  hline{1} = {2-8}{dashed},
  hline{2-4} = {1-8}{},
  vline{1} = {2-3}{red, dotted, 2pt},
  vline{2-9} = {1-3}{green},
  colspec = {cccccccc},
}
& Monday & Tuesday & Wednesday & Thursday & Friday & Saturday & Sunday \\
Lunch & Potatoes & Potatoes & Potatoes & Potatoes & Potatoes & Potatoes & Potatoes \\
too! & \\
Dinner & Rice & Stir-fry & Soup & Eat out & Fish & Pizza & Leftovers\\
\end{tblr}
```

	Monday	Tuesday	Wednesday	Thursday	Friday	Saturday	Sunday
Lunch	Potatoes	Potatoes	Potatoes	Potatoes	Potatoes	Potatoes	Potatoes too!
Dinner	Rice	Stir-fry	Soup	Eat out	Fish	Pizza	Leftovers

Similarly to columns and rows, horizontal lines (**hlines**) and vertical lines (**vlines**) can be individually selected, or by group or range. Thus `hline{1} = {red}` will make the first horizontal line red. Note that the first horizontal line is situated above the first row.

Lines can be **solid** (default), **dotted** or **dashed**. Thickness can be personalized (for instance, **2pt**).

Lines do not have to run through the whole table. For instance, `vline{1} = {2-3}{red, dotted}` is drawing a vertical red line before the first column, from hline index 2 to hline index 3. Note that if a line is partial, the second styling argument must be specified, even if no styling is applied. The default styling instructions for a line are **1pt, solid, black**.

You can give the same style to all vlines/hlines: `hlines = {green, 2pt}`.

2.2.5 Advanced selectors

```
\begin{tblr}{
  colspec = {l1l1},
  hline{1,Z[2]} = {2-Z}{2pt, red},
  row{odd[3]} = {gray!20},
  row{Z} = {font=\bfseries},
}
Subject & {Reaction time (s)} & {Pain (EVA scale)} \\ \hline
Subjet 1 & 0:03 & 3 \\
Subjet 2 & 0:08 & 7 \\
Subjet 3 & 0:01 & 4 \\
AVERAGE & 0:04 & 4.67
\end{tblr}
```

Subject	Reaction time (s)	Pain (EVA scale)
Subjet 1	0:03	3
Subjet 2	0:08	7
Subjet 3	0:01	4
AVERAGE	0:04	4.67

The last index can be selected with `Z`. Since `tabularray` 2025A and later, the one before last can be selected with `Z[2]`, etc. Odd/even indexes can be selected with `odd`, `even`. The selection can start at index, say 5, with `odd[5]`.

2.2.6 Smart selections with class and id

```
\begin{tblr}{
  colspec = {l|l|l|l|l|l|l},
  row{1} = {c, font=\bfseries\large},
  cell{personalbest} = {font=\bfseries},
  cell{Gold} = {yellow!90!black},
  cell{Silver} = {gray!80},
  cell{Bronze} = {brown},
}

Athlete & \#1 & \#2 & \#3 & \#4 & \#5 & \#6 \\ \hline
Chase Jackson & 19.55 & x & 19.43 & 19.67 & x & 
  \SetChild{class=personalbest,id=Silver} 20.21 \\
Fanny Roos & 19.33 & 19.07 & 18.99 & 18.91 & 18.83 & 
  \SetChild{class=personalbest} 19.54 \\
Jessica Schilder & 18.23 & 18.68 & 19.24 & 19.51 & 18.76 & 
  \SetChild{class=personalbest,id=Gold} 20.29 \\
Maddi Wesche & & \SetChild{class=personalbest,id=Bronze} 20.06 & x & 19.90 & x & 
  18.87 & x \\
Sarah Mitton & 19.76 & 19.18 & & \SetChild{class=personalbest} 19.81 & 19.75 & 
  19.80 & 19.62 \\
Yemisi Ogunleye & & \SetChild{class=personalbest} 19.33 & x & x & 18.62 & 18.73 & 
  18.89 \\
\end{tblr}
```

Athlete	#1	#2	#3	#4	#5	#6
Chase Jackson	19.55	x	19.43	19.67	x	20.21
Fanny Roos	19.33	19.07	18.99	18.91	18.83	19.54
Jessica Schilder	18.23	18.68	19.24	19.51	18.76	20.29
Maddi Wesche	20.06	x	19.90	x	18.87	x
Sarah Mitton	19.76	19.18	19.81	19.75	19.80	19.62
Yemisi Ogunleye	19.33	x	x	18.62	18.73	18.89

Minimal `tabularray` version

class and id are only available if your `tabularray` version is 2025A or above.

A class name must be alphabetic, full lowercase. An id name must be alphabetic, and the first letter must be uppercase, the rest lowercase. There can be several times the same class in a table, but only the last use of a given id will be kept in memory.

Styling a non-existing class or id

If you add a styling instruction for a class or id that is not present in the table body, until version 2026A the compilation will fail with a cryptic error message, e.g.: `Undefined control sequence. \l__tl_tmpa_tl ->\__tblr_child_selector_missingclass`

2.3 Multipage tables

```

\DeclareTblrTemplate{contfoot-text}{default}{(The table continues on the next page)}
\DeclareTblrTemplate{conthead-text}{default}{(Continued from the previous page)}
% Only if you want to change the default text

\begin{longtblr}[
  caption={First 40 UN countries by alphabetical order and their official capital},
  label={table:all_countries},
  halign=l,
]{
  colspec={ll},
  rowhead=1,
  rowfoot=1,
  row{odd}= {gray!30},
  row{1} = {font=\bfseries, blue!30},
  row{Z} = {font=\itshape, blue!30},
}
Country & Capital \\ \hline
Afghanistan & Kabul \\
% ...
Costa Rica & San Jose \\
Country & Capital \\ \hline % Repeating bottom row thanks to rowfoot
\end{longtblr}

```



Table 2.1: First 40 UN countries by alphabetical order and their official capital

Country	Capital
Afghanistan	Kabul
Albania	Tirana
Algeria	Algiers
Andorra	Andorra la Vella
Angola	Luanda
Antigua and Barbuda	Saint John's
Argentina	Buenos Aires
Armenia	Yerevan
Australia	Canberra
Austria	Vienna
Azerbaijan	Baku
Bahamas	Nassau
Bahrain	Manama
Bangladesh	Dhaka
Barbados	Bridgetown
Belarus	Minsk
Belgium	Brussels
<i>Country</i>	<i>Capital</i>

(The table continues on the next page)

Table 2.1: First 40 UN countries by alphabetical order and their official capital (Continued from the previous page)

Country	Capital
Belize	Belmopan
Benin	Porto-Novo
Bhutan	Thimphu
Bolivia	Sucre
Bosnia and Herzegovina	Sarajevo
Botswana	Gaborone
Brazil	Brasília
Brunei	Bandar Seri Begawan
Bulgaria	Sofia
Burkina Faso	Ouagadougou
Burundi	Gitega
Cabo Verde	Praia
Cambodia	Phnom Penh
Cameroon	Yaounde
Canada	Ottawa
Central African Republic	Bangui
Chad	N'Djamena
Chile	Santiago
China	Beijing
Colombia	Bogotá
Comoros	Moroni
Congo Republic of the	Brazzaville
Costa Rica	San Jose
<i>Country</i>	<i>Capital</i>

Multipage tables are defined with the `longtblr` environment. Its horizontal alignment can be defined with `halign` (default is `c`) and is automatically included as a floating table element. The `caption` and `label` are defined as outer attributes.

To repeat rows at the beginning and end of the table on each page, use `rowhead` and `rowfoot`. You can repeat more than 1 row at the beginning or end. The repeating row(s) at the bottom must be written at the end of the table.

Continuation text can be personalized in the `default` templates of `tabularray` (otherwise the default values apply). You can also use named templates, see the documentation for more details.

Long tables are significantly slower at compilation than normal `tabularray` tables, which themselves are significantly slower at compilation than native LaTeX tables. Do not use `longtblr` if the table can fit on one page.

2.4 Tabularray's libraries

2.4.1 Drawing in your table with Tikz

Minimal tabularray version

The tikz library is only available from tabularray version 2025A or more recent.

```
% \UseTblrLibrary{tikz} % in the preamble

\begin{tblrtikzbelow}
  \path[fill=blue!15,draw=blue!80, ultra thick, rounded corners]
    (table.north west) rectangle (table.south east);
\end{tblrtikzbelow}

\begin{tblrtikzabove}
  \draw[red!70, thick]
    (2-2.north west) -- (2-3.south east)
    (2-2.south west) -- (2-3.north east);
  \draw[color=green,thick]
    (h1-|v1) -- (h1-|v2) -- (h2-|v2) -- (h2-|v3) -- (h3-|v3) -- (h3-|v4)
    -- (h4-|v4) -- (h4-|v5) -- (h2-|v5) -- (h2-|v6) -- (h1-|v6);
\end{tblrtikzabove}

\begin{tblr}{
  colspec={ccccc},
  hlines={4pt},
  vlines={3pt},
  hline{1,Z} = {0pt},
  vline{1,Z} = {0pt},
}
  1-1 & 1-2 & 1-3 & 1-4 & 1-5 \\
  2-1 & some text & other text & 2-4 & 2-5 \\
  3-1 & 3-2 & 3-3 & 3-4 & 3-5
\end{tblr}
```

1-1	1-2	1-3	1-4	1-5
2-1	some text	other text	2-4	2-5
3-1	3-2	3-3	3-4	3-5

The tikz library allows to draw on (or under) the table, with any valid tikz instruction, once the size of each cell has been computed¹. The environment `tblrtikzabove` allows to draw on top of the table, and `tblrtikzbelow` under the table. These environments must be defined before the table they relate to.

Each cell is given a named tikz node: the cell at row i and column j is named `(i-j)`. Similarly, each border intersection has a name: the intersection of hline i with vline j is named `(hi-|vj)`.

¹Note that you can insert tikz images in a table cell. But these images will increase the cell's width.

2.4.2 Diagonal separations with diagbox

```
% \UseTblrLibrary{diagbox} % in the preamble

\begin{tblr}{
  colspec={c|ccc},
}
  \diagbox{Day}{Roommate} & Martin & Emma & Julie\\ \hline
Monday & Dishes & & Cooking\\
Tuesday & Cooking & Dishes & \\
Wednesday & & Cooking & Dishes \\
Thursday & Dishes & & Cooking \\
Friday & Cooking & Dishes & \\
Saturday & & Cooking & Dishes \\
Sunday & & & \\
\end{tblr}
```

Day \ Roommate	Martin	Emma	Julie
Monday	Dishes		Cooking
Tuesday	Cooking	Dishes	
Wednesday		Cooking	Dishes
Thursday	Dishes		Cooking
Friday	Cooking	Dishes	
Saturday		Cooking	Dishes
Sunday			

`\diagboxthree{}{}{}` is also available.