

21. jQuery HTML / CSS Methods

The following table lists all the methods used to manipulate the HTML and CSS.

The methods below work for both HTML and XML documents. Exception: the `html()` method.

Method	Description
<code>addClass()</code>	Adds one or more class names to selected elements
<code>after()</code>	Inserts content after selected elements
<code>append()</code>	Inserts content at the end of selected elements
<code>appendTo()</code>	Inserts HTML elements at the end of selected elements
<code>attr()</code>	Sets or returns attributes/values of selected elements
<code>before()</code>	Inserts content before selected elements
<code>clone()</code>	Makes a copy of selected elements
<code>css()</code>	Sets or returns one or more style properties for selected elements
<code>detach()</code>	Removes selected elements (keeps data and events)
<code>empty()</code>	Removes all child nodes and content from selected elements
<code>hasClass()</code>	Checks if any of the selected elements have a specified class name
<code>height()</code>	Sets or returns the height of selected elements
<code>html()</code>	Sets or returns the content of selected elements
<code>innerHeight()</code>	Returns the height of an element (includes padding, but not border)
<code>innerWidth()</code>	Returns the width of an element (includes padding, but not border)
<code>insertAfter()</code>	Inserts HTML elements after selected elements
<code>insertBefore()</code>	Inserts HTML elements before selected elements

offset()	Sets or returns the offset coordinates for selected elements (relative to the document)
offsetParent()	Returns the first positioned parent element
outerHeight()	Returns the height of an element (includes padding and border)
outerWidth()	Returns the width of an element (includes padding and border)
position()	Returns the position (relative to the parent element) of an element
prepend()	Inserts content at the beginning of selected elements
prependTo()	Inserts HTML elements at the beginning of selected elements
prop()	Sets or returns properties/values of selected elements
remove()	Removes the selected elements (including data and events)
removeAttr()	Removes one or more attributes from selected elements
removeClass()	Removes one or more classes from selected elements
removeProp()	Removes a property set by the prop() method
replaceAll()	Replaces selected elements with new HTML elements
replaceWith()	Replaces selected elements with new content
scrollLeft()	Sets or returns the horizontal scrollbar position of selected elements
scrollTop()	Sets or returns the vertical scrollbar position of selected elements
text()	Sets or returns the text content of selected elements
toggleClass()	Toggles between adding/removing one or more classes from selected elements
unwrap()	Removes the parent element of the selected elements
val()	Sets or returns the value attribute of the selected elements (for form elements)
width()	Sets or returns the width of selected elements

<code>wrap()</code>	Wraps HTML element(s) around each selected element
<code>wrapAll()</code>	Wraps HTML element(s) around all selected elements
<code>wrapInner()</code>	Wraps HTML element(s) around the content of each selected element