



Lecture 2: Data Processing

Outline of this lecture

- What is Data?
- Data types
- Data Quality
- Data Pre-processing (methods)

Outline of this lecture

- What is Data?
- Data types
- Data Quality
- Data Pre-processing (methods)

What is Data?

- Collection of data objects and their attributes
- An attribute is a property or characteristic of an object
 - Examples: eye color of a person, temperature, etc.
 - Attribute is also known as variable, field, characteristic, or feature
- A collection of attributes describe an object
 - Object is also known as record, point, case, sample, entity, or instance

Attributes

<i>Tid</i>	Refund	Marital Status	Taxable Income	Cheat
1	Yes	Single	125K	No
2	No	Married	100K	No
3	No	Single	70K	No
4	Yes	Married	120K	No
5	No	Divorced	95K	Yes
6	No	Married	60K	No
7	Yes	Divorced	220K	No
8	No	Single	85K	Yes
9	No	Married	75K	No
10	No	Single	90K	Yes

Objects

Attribute Values

- Attribute values are numbers or symbols assigned to an attribute
- Distinction between attributes and attribute values
 - Same attribute can be mapped to different attribute values
 - ◆ Example: height can be measured in feet or meters
 - Different attributes can be mapped to the same set of values
 - ◆ Example: Attribute values for ID and age are integers
 - ◆ But properties of attribute values can be different
 - ID has no limit but age has a maximum and minimum value

Types of Attributes

- There are different types of attributes
 - **Nominal**
 - ◆ Examples: ID numbers, eye color, zip codes
 - **Ordinal**
 - ◆ Examples: rankings (e.g., taste of potato chips on a scale from 1-10), grades, height in {tall, medium, short}
 - **Interval**
 - ◆ Examples: calendar dates, temperatures in Celsius or Fahrenheit.
 - **Ratio**
 - ◆ Examples: temperature in Kelvin, length, time, counts

Properties of Attribute Values

- The type of an attribute depends on which of the following properties it possesses:
 - Distinctness: $= \neq$
 - Order: $< >$
 - Addition: $+ -$
 - Multiplication: $* /$

Quiz

Link every attribute type and its properties.

1. Nominal attribute

a. Distinctness

2. Interval attribute

b. distinctness & order

3. Ratio attribute

c. distinctness, order & addition

4. Ordinal attribute

d. distinctness, order, addition & Multiplication

Discrete and Continuous Attributes

- Discrete Attribute

- Has only a finite or countably infinite set of values
- Examples: zip codes, counts, or the set of words in a collection of documents
- Often represented as integer variables.
- Note: binary attributes are a special case of discrete attributes

- Continuous Attribute

- Has real numbers as attribute values
- Examples: temperature, height, or weight.
- Practically, real values can only be measured and represented using a finite number of digits.
- Continuous attributes are typically represented as floating-point variables.

Outline of this lecture

- What is Data?
- Data types
- Data Quality
- Data Pre-processing (methods)

Types of data sets

● Record

- Data Matrix
- Document Data
- Transaction Data

● Graph

- World Wide Web
- Molecular Structures

● Ordered

- Spatial Data
- Temporal Data
- Sequential Data
- Genetic Sequence Data

Record Data

- Data that consists of a collection of records, each of which consists of a fixed set of attributes

<i>Tid</i>	Refund	Marital Status	Taxable Income	Cheat
1	Yes	Single	125K	No
2	No	Married	100K	No
3	No	Single	70K	No
4	Yes	Married	120K	No
5	No	Divorced	95K	Yes
6	No	Married	60K	No
7	Yes	Divorced	220K	No
8	No	Single	85K	Yes
9	No	Married	75K	No
10	No	Single	90K	Yes

Conti.

- If data objects have the same fixed set of numeric attributes, then the data objects can be thought of as points in a multi-dimensional space, where each dimension represents a distinct attribute
- Such data set can be represented by an m by n matrix, where there are m rows, one for each object, and n columns, one for each attribute

Projection of x Load	Projection of y load	Distance	Load	Thickness
10.23	5.27	15.22	2.7	1.2
12.65	6.25	16.22	2.2	1.1

Document Data

- Each document becomes a 'term' vector,
 - each term is a component (attribute) of the vector,
 - the value of each component is the number of times the corresponding term occurs in the document.

	team	coach	play	ball	score	game	win	lost	timeout	season
Document 1	3	0	5	0	2	6	0	2	0	2
Document 2	0	7	0	2	1	0	0	3	0	0
Document 3	0	1	0	0	1	2	2	0	3	0

Transaction Data

- A special type of record data, where
 - each record (transaction) involves a set of items.


Example: grocery store.

The set of products purchased by a customer during one shopping trip constitute a transaction, while the individual products that were purchased are the items.

<i>TID</i>	<i>Items</i>
1	Bread, Coke, Milk
2	Beer, Bread
3	Beer, Coke, Diaper, Milk
4	Beer, Bread, Diaper, Milk
5	Coke, Diaper, Milk

Graph Data

- Examples: Generic graph and HTML Links




```
<a href="papers/papers.html#bbbb">  
Data Mining </a>  
<li>  
<a href="papers/papers.html#aaaa">  
Graph Partitioning </a>  
<li>  
<a href="papers/papers.html#aaaa">  
Parallel Solution of Sparse Linear System of Equations </a>  
<li>  
<a href="papers/papers.html#ffff">  
N-Body Computation and Dense Linear System Solvers
```

Ordered Data

- Sequences of transactions

Items/Events




An element of
the sequence

Ordered Data

- Spatio-Temporal Data

**Average Monthly
Temperature of
land and ocean**

Jan



Important Characteristics of Structured Data

- **Dimensionality**
 - ◆ **Curse of Dimensionality**
- **Sparsity**
 - ◆ **Only presence counts**
- **Resolution**
 - ◆ **Patterns depend on the scale**

Outline of this lecture

- What is Data?
- Data types
- Data Quality
- Data Pre-processing (methods)


Data Quality

- Three Questions about data quality
 - What kinds of data quality problems?
 - How can we detect problems with the data?
 - What can we do about these problems?


- Examples of data quality problems:
 - Noise and outliers
 - missing values
 - duplicate data

Noise

- Noise refers to modification of original values
 - Examples: distortion of a person's voice when talking on a poor phone and “snow” on television screen




Two Sine Waves



Two Sine Waves + Noise

Outliers

- Outliers are data objects with characteristics that are considerably different than most of the other data objects in the data set



Missing Values

- Reasons for missing values

- Information is not collected
(e.g., people decline to give their age and weight)
- Attributes may not be applicable to all cases
(e.g., annual income is not applicable to children)

- Handling missing values

- Eliminate Data Objects
- Estimate Missing Values
- Ignore the Missing Value During Analysis
- Replace with all possible values (weighted by their probabilities)

Duplicate Data

- Data set may include data objects that are duplicates, or almost duplicates of one another
 - Major issue when merging data from heterogeneous sources
- Examples:
 - Same person with multiple email addresses
- Data cleaning
 - Process of dealing with duplicate data issues

Outline of this lecture

- What is Data?
- Data types
- Data Quality
- Data Pre-processing (methods)

Data Preprocessing


- a. Aggregation
- b. Sampling
- c. Dimensionality Reduction
- d. Feature subset selection
- e. Feature creation
- f. Discretization and Binarization
- g. Attribute Transformation

a. Aggregation


- Combining two or more attributes (or objects) into a single attribute (or object)
- Purpose
 - Data reduction
 - ◆ Reduce the number of attributes or objects
 - Change of scale
 - ◆ Cities aggregated into regions, states, countries, etc
 - More “stable” data
 - ◆ Aggregated data tends to have less variability

a. Aggregation

Variation of Precipitation in Australia



**Standard Deviation of Average
Monthly Precipitation**



**Standard Deviation of Average
Yearly Precipitation**

B. Sampling

- Sampling is the main technique employed for data selection.
 - It is often used for both the preliminary investigation of the data and the final data analysis.
- Statisticians sample because **obtaining** the entire set of data of interest is too expensive or time consuming.
- Sampling is used in data mining because **processing** the entire set of data of interest is too expensive or time consuming.


b. Sampling ...

- The key principle for effective sampling is the following:
 - using a sample will work almost as well as using the entire data sets, if the sample is representative
 - A sample is representative if it has approximately the same property (of interest) as the original set of data


Types of Sampling

- Simple Random Sampling
 - There is an equal probability of selecting any particular item
- Sampling without replacement
 - As each item is selected, it is removed from the population
- Sampling with replacement
 - Objects are not removed from the population as they are selected for the sample.
 - ◆ In sampling with replacement, the same object can be picked up more than once
- Stratified sampling
 - Split the data into several partitions; then draw random samples from each partition


Sample Size



8000 points




2000 Points



500 Points


Sample Size

- What sample size is necessary to get at least one object from each of 10 groups.



c. Dimensionality Reduction

- Curse of Dimensionality:
When dimensionality increases, data becomes increasingly sparse in the space that it occupies
- Definitions of density and distance between points, which is critical for clustering and outlier detection, become less meaningful



- Randomly generate 500 points
- Compute difference between max and min distance between any pair of points

c. Dimensionality Reduction

- Purpose:


- Avoid curse of dimensionality
- Reduce amount of time and memory required by data mining algorithms
- Allow data to be more easily visualized
- May help to eliminate irrelevant features or reduce noise

- Techniques

- Principle Component Analysis
- Singular Value Decomposition
- Others: supervised and non-linear techniques


Dimensionality Reduction: PCA

- Goal is to find a projection that captures the largest amount of variation in data




Dimensionality Reduction: PCA

- Find the eigenvectors of the covariance matrix
- The eigenvectors define the new space



Dimensionality Reduction: ISOMAP

By: Tenenbaum, de Silva,
Langford (2000)



- Construct a neighbourhood graph
- For each pair of points in the graph, compute the shortest path distances – geodesic distances

Dimensionality Reduction: PCA

Dimensions = 206



d. Feature Subset Selection

- Another way to reduce dimensionality of data
- Redundant features
 - duplicate much or all of the information contained in one or more other attributes
 - Example: purchase price of a product and the amount of sales tax paid
- Irrelevant features
 - contain no information that is useful for the data mining task at hand
 - Example: students' ID is often irrelevant to the task of predicting students' GPA

d.Feature Subset Selection

- Techniques:


- Brute-force approach:
 - ◆ Try all possible feature subsets as input to data mining algorithm
- Embedded approaches:
 - ◆ Feature selection occurs naturally as part of the data mining algorithm
- Filter approaches:
 - ◆ Features are selected before data mining algorithm is run
- Wrapper approaches:
 - ◆ Use the data mining algorithm as a black box to find best subset of attributes

e. Feature Creation


- Create new attributes that can capture the important information in a data set much more efficiently than the original attributes
- Three general methodologies:
 - Feature Extraction
 - ◆ domain-specific
 - Mapping Data to New Space
 - Feature Construction
 - ◆ combining features

f. Discretization Using Class Labels

● Entropy based approach




3 categories for both x and y




5 categories for both x and y


Discretization Without Using Class Labels




Data



Equal interval width




Equal frequency



K-means

g. Attribute Transformation

- A function that maps the entire set of values of a given attribute to a new set of replacement values such that each old value can be identified with one of the new values
 - Simple functions: x^k , $\log(x)$, e^x , $|x|$
 - Standardization and Normalization



Review: Data Preprocessing

- a. Aggregation
- b. Sampling
- c. Dimensionality Reduction
- d. Feature subset selection
- e. Feature creation
- f. Discretization and Binarization
- g. Attribute Transformation