intrum

Documentation: CI-WS (Credit Information Web Services)

Author: Silvan Suremann

Date: 2024-09-05

Version: 0.0.27

intrum

Version history

Version	Changes	Author	Date
0.0.0	- created	S. Suremann	2020-11-12
0.0.1	- added new service person/workflow (2.3.3) - added more matching profiles (4.3.2) - added attribute descriptions (4.3.5, 4.3.12, 4.3.17) - small corrections	S. Suremann	2020-11-26
0.0.2	- added new report types (4.3.1) - added reportData attribute in person/info (2.3.2) - added further detail collectionData attributes to person/info (2.3.2) incl. descriptions (4.3.17, 4.3.18, 4.3.19, 4.3.20) - minor corrections	S. Suremann	2021-01-07
0.0.3	- revised company services (see 2.2.2 & 2.2.3) - minor corrections	S. Suremann	2021-02-02
0.0.4	- added address/normalisation service (2.1.2) - added address/check service (2.1.3) - changed zipCode to swissZipCode in address/autocomplete service (2.1.1) - removed name from address/name/autocomplete service (2.1.1) - added bankruptcyData to person/info (2.3.2) - changed pursuitData from person/info (2.3.2) - added eCH-0097 docu to organisationIdCategory (4.2.4) - added rubric (4.3.5) and subrubric (4.3.10) - minor corrections and enhancements	S. Suremann	2021-02-18
0.0.5	- removed name from company/name/autocomplete service (2.2.1) - added compliance/search (2.4.1) and compliance/info services (2.4.2)	S. Suremann	2021-03-29
0.0.6	- small corrections - change example requests to test env and changed format to hyperlinks	S. Suremann	2021-04-29
0.0.7	- corrected example request for compliance/search (2.4.1) - corrected contact mail address (4.2.1, 4.3.1) - new codes and description (4.2.9, 4.2.10, 4.2.11, 4.3.18, 4.3.19, 4.3.20)	S.Suremann	2021-05-26
0.0.8	- removed old and added new attributes in company/info (2.2.3) and person/info (2.3.2) - changed swissZipCode to zipCode for person/info (2.3.2) & workflow (2.3.3) - added xmlServices (2.6) - added company/workflow (2.2.4)	S.Suremann	2021-08-27
0.0.9	- added new service person/search (2.3.1) - changed response structure of company/search (2.2.2) to dictionary - changed attribute name matching_results to matchingResults for company/autocomplete (2.2.1)	S.Suremann	2021-09-23
0.0.10	- added option of searching by birth year for person services (4.3.2) - changed url for testing purposes (1.2) - changed example requests - small corrections	S.Suremann	2021-10-07
0.0.11	- added fraudData (tbd) to person/info (2.3.2) and company/info (2.2.3)	S.Suremann	2021-10-22
0.0.12	- added kremo service (2.5) - small corrections	M.Hannay	2021-11-15
0.0.13	- added hitScore to person/search (2.3.1) and person/info (2.3.2)	S.Suremann	2021-12-14

	- added sortType to person/info (2.3.2) and person/workflow (2.3.3) - updated fraudData for person/info (2.3.2) and company/info (2.2.3) - small corrections		
0.0.14	- added scoreDate, houseoldScoreDate to person/info (2.3.2) - added blacklistData to person/info (2.3.2) - removed riData and wfData from person/info (2.3.2) - removed responseId and requestId from sub tag in company/search (2.2.2) - corrected format of formerNames in company/search (2.2.2) - added plsClothingRequirementIncreased to kremo (2.5) - added blacklistData and industryCodeProbabilities to company/info (2.2.3) - corrected fraudData in company/info (2.2.3) - changed type of pursuitData and shabData from list to container including new tag "details" for company/info (2.2.3) - changed type of bankruptcyData and pursuitData from list to container including new tag "details" for person/info (2.3.2) - adapted types openapi definition (float to number, int to integer) - corrected types of IDs in company/search (2.4.1) - added cas description (4.3.5) - changed industryCode to nogaCode and added description (4.2.12) - several small corrections	S.Suremann	2022-02-07
0.0.15	- added orderingPerson attributes to company/info (2.2.3) and company/workflow (2.2.4) - added email, phone, idNumber, ipAddress, productCategory to company/info (2.2.3), company/workflow (2.2.4), person/info (2.3.2) and person/workflow (2.3.3)	S.Suremann	2022-02-24
0.0.16	- removed v.0.0 from base url (1.2) - added company/orderRegistration (2.2.5) and person/orderRegistration (2.3.4) - added orderRegistration (3.2) to xmlServices - added payment methods (4.2.23, 4.3.22) - added hit type via external Swiss Post service CP and PP (4.2.18, 4.3.13) - added response codes (4.2.20, 4.3.15) - added delivery address fields to company/workflow (2.2.4) and person/workflow (2.3.3)	M.Hannay, S.Suremann	2022-04-06
0.0.17	- removed note regarding order for matchingProfile (4.3.2) - several small corrections - added sortType to person/search (2.3.1) - changed contractNumber to contractId (2.2.3, 2.3.2) - changed ccliAparSerialNumber to sourceId (2.2.3, 2.3.2)	M.Hannay, S.Suremann	2022-05-25
0.0.18	- added ZEK services chapter - added zek/person/search	L. Müller	2023-01-16
0.0.19	- added zek/person/info - added zek/person/workflow - added zek code and status tables	L. Müller, M. Hannay	2023-01-25
0.0.20	- updated table of content - zek/workflow changes	L. Müller, M. Hannay	2023-02-01
0.0.21	- change sourceCanton to canton in the zek services - added zek/person/rejectCreditApplication - changed contractStatus LOGGED_OUT to CANCELLED	L. Müller	2023-03-09
0.0.22	- added premiumConsumerScoreData to /person/info	H. Schaller	2023-05-11
0.0.23	- added net Income to the kremo service	M. Hannay	2023-08-22
0.0.24	- added missing response fields for kremo	M. Hannay	2023-10-02
0.0.27	- added advanced scores (4.2.6, 4.3.5)	S. Suremann	2024-09-05

intrum

Table of Contents

1. Introduction 7
1.1. Technology 7
1.2. URL 7
1.3. Authorization 7
1.4. HTTP Status Codes 7
1.5. Date Format 9
2. RestServices 10
2.1. Address 10
2.1.1. Autocomplete 10
2.1.2. Normalisation 10
2.1.3. Check 11
2.2. Company 11
2.2.1. Autocomplete 11
2.2.2. Search 12
2.2.3. Info 13
2.2.4. Workflow 19
2.2.5. OrderRegistration 20
2.3. Person 21
2.3.1. Search 21
2.3.2. Info 22
2.3.3. Workflow 27
2.3.4. OrderRegistration 29
2.4. Compliance 30
2.4.1. Search 30
2.4.2. Info 31
2.5. Kremo 33
2.6. ZEK 39
2.6.1. Search 39
2.6.2. Info 40
2.6.3. Workflow 44
2.6.4. RejectCreditApplication 48
3. XML Services 51
3.1. Workflow 51
3.2. OrderRegistration 52
4. Detailed Attribute Description 56
4.1. Address 56

4.1.1. hitScore 56
4.1.2. valid 56
4.1.3. check 56
4.2. Company 56
4.2.1. reportType 56
4.2.2. matchingProfile 56
4.2.3. hitScoreCutoff 56
4.2.4. organisationIdCategory 56
4.2.5. bcs 56
4.2.6. abcs 57
4.2.7. status 57
4.2.8. legalForm 57
4.2.9. eventCode 58
4.2.10. closingCode 58
4.2.11. industryCode 59
4.2.12. nogaCode 59
4.2.13. industryCodeProbabilities 59
4.2.14. isBranch 60
4.2.15. hitScore 60
4.2.16. Signature 60
4.2.17. workflowName 60
4.2.18. hitType 60
4.2.19. remainingLimit 61
4.2.20. responseCode 61
4.2.21. riskIndicator 61
4.2.22. productCategory 61
4.2.23. paymentMethod 61
4.3. Person 61
4.3.1. reportType 61
4.3.2. matchingProfile 62
4.3.3. sortType 62
4.3.4. ccs 62
4.3.5. accs 63
4.3.6. cas 63
4.3.7. hitScore 63
4.3.8. status 63

4.3.9. rubric 63
4.3.10. sub Rubric 64
4.3.11. workflowName 64
4.3.12. creditRecommendation 64
4.3.13. hitType 65
4.3.14. remainingLimit 65
4.3.15. responseCode 65
4.3.16. riskIndicator 65
4.3.17. aadsCode 65
4.3.18. eventCode 66
4.3.19. closingCode 66
4.3.20. industryCode 66
4.3.21. productCategory 67
4.3.22. paymentMethod 67
4.4. Compliance 67
4.4.1. lists 67
4.4.2. accuracy 67
4.5. ZEK 67
4.5.1. TargetOrganisation 67
4.5.2. RequestReason 68
4.5.3. CardEventCode 68
4.5.4. CardTypeCode 68
4.5.5. OfficeInformationCode 68
4.5.6. Canton 69
4.5.7. CreditRequestStatus 69
4.5.8. RejectionReason 69
4.5.9. DeletionReason 70
4.5.10. ContractStatus 70
4.5.11. CreditRatingCode 70
4.5.12. Safeguarding 70
4.5.13. PersonStatus 71
4.5.14. ZekScore 71
4.5.15. WorkflowName 71

intrum

1. Introduction

The following document describes the Credit Information Web Services.

1.1. Technology

The interface is provided as a REST/JSON API.

1.2. URL

Environment	URL
Test	https://test-credit-information-ws.ch/
Production	https://credit-information-ws.ch/

1.3. Authorization

The API uses Basic HTTP authentication. To get access to the service, a username and a password must be passed in the HTTP header. The user must be registered for the specific service.

Autorisation	Basic username:password encoded via base64

1.4. HTTP Status Codes

The following basic HTTP status codes can be received.

Category	Code	Message	Description
Informational Response	100	Continue	Only a part of the request has been received by the server, but as long as it has not been rejected, the client should continue with the request.
	101	Switching Protocols	The server switches protocol.
Success	200	OK	The request is OK.
	201	Created	The request is complete, and a new resource is created.
	202	Accepted	The request is accepted for processing, but the processing is not complete.
	203	Non-authoritative Information	The information in the entity header is from a local or third-party copy, not from the original server.
	204	No Content	A status code and a header are given in the response, but there is no entity-body in the reply.
	205	Reset Content	The browser should clear the form used for this transaction for additional input.
	206	Partial Content	The server is returning partial data of the size requested. Used in response to a request specifying a Range header. The server must specify the range included in the response with the Content-Range header.
Redirection	300	Multiple Choices	A link list: The user can select a link and go to that location. Maximum five addresses.
	301	Moved Permanently	The requested page has moved to a new URL.
	302	Found	The requested page has moved temporarily to a new URL.
	303	See Other	The requested page can be found under a different URL.
	304	Not Modified	This is the response code to an If-Modified-Since or If-None-

			Match header, where the URL has not been modified since the specified date.
	305	Use Proxy	The requested URL must be accessed through the proxy mentioned in the Location header.
	307	Temporary Redirect	The requested page has moved temporarily to a new URL.
Client Errors	400	Bad Request	The server did not understand the request.
	401	Unauthorized	The requested page needs a username and a password.
	402	Payment Required	You cannot use this code yet.
	403	Forbidden	Access is forbidden to the requested page.
	404	Not Found	The server cannot find the requested page.
	405	Method Not Allowed	The method specified in the request is not allowed.
	406	Not Acceptable	The server can only generate a response that is not accepted by the client.
	407	Proxy Authentication Required	You must authenticate with a proxy server before this request can be served.
	408	Request Timeout	The request took longer than the server was prepared to wait.
	409	Conflict	The request could not be completed because of a conflict.
	410	Gone	The requested page is no longer available.
	411	Length Required	The "Content-Length" is not defined. The server will not accept the request without it.
	412	Precondition Failed	The pre-condition given in the request evaluated to false by the server.
	413	Request Entity Too Large	The server will not accept the request, because the request entity is too large.
	414	Request-url Too Long	The server will not accept the request, because the URL is too long. Occurs when you convert a "post" request to a "get" request with a long query information.
	415	Unsupported Media Type	The server will not accept the request, because the mediatype is not supported.
	416	Requested Range Not Satisfiable	The requested byte range is not available and is out of bounds.
	417	Expectation Failed	The expectation given in an Expect request-header field could not be met by this server.
	422	Unprocessable Entity	The server understands the content type of the request entity, and the syntax of the request entity is correct but was unable to process the contained instructions.
Server Errors	500	Internal Server Error	The request was not completed. The server met an unexpected condition.
	501	Not Implemented	The request was not completed. The server did not support the functionality required.
	502	Bad Gateway	The request was not completed. The server received an invalid response from the upstream server.
	503	Service Unavailable	The request was not completed. The server is temporarily overloading or down.
	504	Gateway Timeout	The gateway has timed out.
	505	HTTP Version Not Supported	The server does not support the "http protocol" version.

1.5. Date Format

Unless explicitly defined otherwise, all dates used in this API are of the following format: YYYY-MM-DD.

intrum

2. RestServices

2.1. Address

2.1.1. Autocomplete

This service can be used to obtain suggestions for complete addresses by providing an incomplete address. The user can decide between sending a full address (fullAddress) or splitting the request parameters. When using the fullAddress approach, the following structure must be followed: street houseNumber swissZipCode town. When using the separate parameters, the fullAddress should not be sent, otherwise these parameters will be overwritten. The response is a list containing all possible addresses.

Endpoint	restServices/v.0.0/address/autocomplete?		
Method	GET		
Request Parameter	**Name**	**Type**	**Description**
	requestId	string	Request ID
	fullAddress	string	(Parts of)an address
	street	string	Street
	houseNumber	string	House number
	swissZipCode	string	Postal code for swiss addresses
	town	string	Town
Example Request	https://test-credit-information-ws.ch/restServices/v.0.0/address/autocomplete?fullAddress=Eschenstrasse 12 8		
Response Attributes	**Name**	**Type**	**Description**
	fullAddress	string	(Parts of)an address in the following order and structure: street houseNumber swissZipCode town
	houseNumber	string	House number
	street	string	Street
	swissZipCode	string	Postal Code
	town	string	Town

2.1.2. Normalisation

This service can be used to normalise a given address by providing a full address. The precision of the normalisation improves as the number of attributes (street, houseNumber, swissZipCode, town, countryCode) increases. The order of the attributes does not matter. The response is a list containing normalised addresses sorted by the highest hitScore.

Endpoint	restServices/v.0.0/address/normalisation?		
Method	GET		
Request Parameter	**Name**	**Type**	**Description**
	requestId	string	Request ID
	fullAddress	string	A full address (street houseNumber swissZipCode town countryCode)
Example Request	https://test-credit-information-ws.ch/restServices/v.0.0/address/normalisation?fullAddress=Zentralstrasse 55 2502 biel		

Response Attributes	Name	Type	Description
	addressAddition	string	Any additional information
	canton	string	Canton
	coAddress	string	c/o address
	countryCode	string	Country Code
	fullAddress	string	The normalised full address in the following order and structure: street houseNumber swissZipCode town canton countryCode
	hitScore	number	Grade of match (see 4.1.1)
	houseNumber	string	House number
	id	string	Unique ID of the found address
	street	string	Street
	swissZipCode	string	Postal Code
	town	string	Town
	valid	integer	Status of normalisation (see 4.1.2)

2.1.3. Check

This service can be used to check if a person is registered at a given address or not according to the post. The user can decide between sending a full address (fullAddress) or splitting the request parameters.

Endpoint	restServices/v.0.0/address/check?		
Method	GET		
Request Parameter	Name	Type	Description
	requestId	string	Request ID
	firstName	string	First name
	lastName	string	Last name
	fullAddress	string	A full address (street houseNumber swissZipCode town)
	street	string	Street
	houseNumber	string	House number
	swissZipCode	string	Postal Code
	town	string	Town
Example Request	https://test-credit-information-ws.ch/restServices/v.0.0/address/check?firstName=Peter&lastName=Muster&fullAddress=Bahnstrasse 10 8000 Zürich		
Response Attributes	Name	Type	Description
	check	integer	Indicator if person is registered or not (see 4.1.3)
	requestId	string	Request ID (the one sent in the request)
	responseId	integer	Unique Response ID

2.2. Company

2.2.1. Autocomplete

This service can be used to obtain suggestions for company names by providing an uncomplete company name.

Endpoint	restServices/v.0.0/company/autocomplete?		
Method	GET		
Request Parameter	**Name**	**Type**	**Description**
	requestId	string	Request ID
	organisationName	string	Beginning of the company name
Example Request	https://test-credit-information-ws.ch/restServices/v.0.0/company/autocomplete?organisationName=Holding		
Response Attributes	**Name**	**Type**	**Description**
	matchingResults	list	List of organisation name(s)
	requestId	string	Request ID (the one sent in the request)
	responseId	integer	Unique Response ID

2.2.2. Search

This service can be used to obtain companies with basic details by a few search parameters.

Endpoint	restServices/v.0.0/company/search?		
Method	GET		
Request Parameter	**Name**	**Type**	**Description**
	requestId	string	Request ID
	iid	string	Intrum ID
	uid	string	UID number
	refNr	string	HR ref number
	organisationName	string	Full company name
	street	string	Street
	houseNumber	string	House number
	town	string	Town
	swissZipCode	string	Postal Code
	matchingProfile	integer	Matching profile to use (see 4.2.2)
Example Request	https://test-credit-information-ws.ch/restServices/v.0.0/company/search?organisationName=Holding		
Response Attributes	**Name**	**Type**	**Description**
	matchingResults	list	Container for all matched Companies
	formerName	list	List of former company name(s)
	hitScore	number	Grade of match (see 4.2.15)
	houseNumber	string	House number
	iid	string	Intrum ID
	isBranch	string	Indicates if organisation is branch or headquarter (see 4.2.9)
	legalForm	container	Container for legal form related information (see 4.2.8)
	code	integer	Legal form value (see 4.2.8)
	description	string	Legal form description (see 4.2.8)
	organisationIdCategory	string	Indicates if Organisation is listed in commercial register (see 4.2.4)
	organisationName	string	Company name
	refNr	string	HR ref number
	status	container	Container for status related information (see

			4.2.6)
	code	integer	Status value (see 4.2.6)
	description	string	Status description (see 4.2.6)
	street	string	Street
	swissZipCode	string	Postal code
	town	string	Town
	uid	string	Full UID
	uidOrganisationId	integer	UID number
	requestId	string	Request ID (the one sent in the request)
	responseId	integer	Unique Response ID

2.2.3. Info

This service can be used to obtain detailed information about a specific company by providing either a company name or an identifiying number. Additionally, the report type can be used to specify how detailed the response should be. The matchingProfile defines which profile should be used to match.

Endpoint	restServices/v.0.0/company/info?		
Method	GET		
Request Parameter	**Name**	**Type**	**Description**
	requestId	string	Request ID
	iid	string	Intrum ID
	uid	string	UID number
	refNr	string	HR ref number
	organisationName	string	Full company name
	street	string	Street
	houseNumber	string	House number
	town	string	Town
	swissZipCode	string	Postal Code
	phone	string	Phone number
	email	string	e-mail address
	ipAddress	string	IP address
	idNumber	string	ID number
	productCategory	string	Product Category (see 4.2.22)
	orderingPersonFirstName	string	First name of ordering person
	orderingPersonLastName	string	Last name of ordering person
	orderingPersonBirthdate	string	Birthdate of ordering person (e.g. 1980-01-01)
	reportType	string	Type of report (see 4.2.1)
	hitScoreCutoff	number	Minimal hitScore to be considered a hit (see 4.2.3)
	matchingProfile	integer	Matching profile to use (see 4.2.2)
Example Request	https://test-credit-information-ws.ch/restServices/v.0.0/company/info?requestId=123abc&organisationName=HoldingGalleria&reportType=b2bCreditDetails&hitScoreCutoff=85&matchingProfile=1&phone=0441234567&email=c.bösch@holdingalleria.ch&idNumber=C1234567&ipAddress=127.		

	12.34.5&orderingPersonFirstName=Caspar&orderingPersonLastName=Bösch&orderingPersonBirthdate=1960-12-08		
Response Attributes	**Name**	**Type**	**Description**
	addressData	container	Address related information
	formerAddresses	list	Former address related information
	addressLine	string	c/o address
	houseNumber	string	House number
	swissZipCode	string	Postal code
	street	string	Street
	town	string	town
	newestAddress	container	Current address related information
	addressLine	string	c/o address
	houseNumber	string	House number
	swissZipCode	string	Postal code
	street	string	Street
	town	string	town
	blacklistData	container	Blacklist data related information
	lists	list	Detailed blacklist data related information
	email	string	E-mail of blacklist hit
	ext1	string	Ext1 attribute of blacklist hit
	ext2	string	Ext2 attribute of blacklist hit
	hcbtCode	integer	Code of blacklist hit
	houseNumber	string	House number of blacklist hit
	info	string	Info attribute of blacklist hit
	initials	string	Initial attribute of blacklist hit
	ipAddress	string	IP address of blacklist hit
	modifiedDate	string	Modified date of blacklist hit
	phone	string	Phone number of blacklist hit
	sourceId	integer	Source id of blacklist hit
	sourceName	string	Source name of blacklist hit
	sourceParty	integer	Source party of blacklist hit
	street	string	Street of blacklist hit
	swissZipCode	string	Postal code of blacklist hit
	town	string	Town of blacklist hit
	collectionData	container	Collection data related information
	aggregated	container	Aggregated data related information
	firstOpeningDate	string	Opening date of first case
	latestOpeningDate	string	Opening date of latest case
	latestPaymentAmount	number	Amount of latest payment
	latestPaymentDate	string	Date of latest payment
	openCasesNum	integer	Number of open cases
	totalAmount	number	Total amount
	totalCasesNum	integer	Number of total cases
	totalOpenAmount	number	Open amount
	details	list	Detailed collection data related information

	amount	number	Amount
	caseRef	string	Case reference
	closingCode	integer	Closing code (see 4.2.10)
	closingDate	string	Closing date
	eventCode	integer	Event (see 4.2.9)
	industryCode	integer	Industry Code (see 4.2.11)
	latestPaymentAmount	number	Amount of latest payment
	latestPaymentDate	string	Date of latest payment
	legalState	integer	Indicates if prelegal (0) or legal (1) case
	openAmount	number	Open amount
	openingDate	string	Opening date
	sourceName	string	Indicates source name
	status	integer	Indicates if case is closed (0) or still open (1)
	creditData	container	Credit data data related information
	bcsAlpha	string	bcsAlpha (see 4.2.5)
	bcsNum	number	bcsNum (see 4.2.5)
	abcsAlpha	string	abcsAlpha (see 4.2.6)
	abcsNum	number	abcsNum (see 4.2.6)
	scoreDate	string	Date of last score change
	eCommerceData	container	E-Commerce data related information
	aggregated	container	Aggregated eCommerce data related information
	lastMonthContractsAmount	number	Amount of last month’s contracts
	lastMonthContractsNum	integer	Number of contracts last month
	latestContractDate	string	Date of latest contract
	latestPaymentDate	string	Date of latest payment
	totalContractsAmount	number	Total amount of all contracts
	totalContractsNum	integer	Number of total contracts
	totalPaymentAmount	number	Total amount of all payments
	details	list	Detailed eCommerce data related information
	sourceId	integer	Source ID
	contractAmount	number	Contract amount
	contractDate	string	Contract date
	contractId	string	Contract ID
	latestPaymentDate	string	Latest payment date
	paymentAmount	number	Payment amount
	fraudData	container	Fraud data related information
	fraudScore	number	Fraud score
	hits	list	Fraud hit related information
	id	string	ID of hit
	latestEntryDate	string	Latest entry date of hit
	registrationDate	string	Registration date of hit
	source	string	Source of hit
	type	string	Type of hit

	value	string	Value of hit
	identityQuality	list	Identity quality related information
	hitScore	number	Hit score of identity match
	latestEntryDate	string	Latest entry date of hit
	numPayments	integer	Number of payments of identity
	registrationDate	string	Registration date of hit
	type	string	Type of identity
	lists	list	Detailed blacklist data related information
	blacklistId	string	Id of blacklist entry
	countryCode	string	Country code
	email	string	E-mail of blacklist hit
	ext1	string	Ext1 attribute of blacklist hit
	ext2	string	Ext2 attribute of blacklist hit
	hcbtCode	integer	Code of blacklist hit
	houseNumber	string	House number of blacklist hit
	info	string	Info attribute of blacklist hit
	initials	string	Initial attribute of blacklist hit
	ipAddress	string	IP address of blacklist hit
	modifiedDate	string	Modified date of blacklist hit
	organisationName	string	Organisation name of blacklist hit
	phone	string	Phone number of blacklist hit
	sourceName	string	Source name of blacklist hit
	street	string	Street of blacklist hit
	swissZipCode	string	Postal code of blacklist hit
	town	string	Town of blacklist hit
	numAddresses	container	Number of addresses related information
	bankruptcies	integer	Number of bankrupted organisations on same address
	organisations	integer	Number of organisations on same address
	suspectList	list	Suspects related information
	id	string	ID of suspect
	registrationDate	string	Registration Date of suspect
	source	string	Source of suspect
	type	string	Type of suspect
	value	string	Value of suspect
	generalData	container	General data related information
	auditor	string	Details of auditor
	capital	string	Amount of capital
	hitScore	number	Grade of match (see 4.2.15)
	hrDeletionDate	string	Date of HR deletion
	hrRegistrationDate	string	Date of HR registration
	iid	string	Intrum ID
	legalForm	integer	Legal form value (see 4.2.8)
	legalSeat	string	Town where organisation is registered in
	organisationIdCategory	string	Indicates if Organisation is listed in commercial register (see 4.2.4)

	organisationName	string	Organisation name
	purpose	string	Purpose of company
	refNr	string	HR ref number
	requestId	string	Request ID (the one sent in the request)
	responseId	integer	Unique Response ID
	status	integer	Status value (see 4.2.6)
	uid	string	Full UID
	uidOrganisationId	integer	UID number
	industryData	container	Industry related information
	industryCodeProbabilities	container	Industry code probability related information (see 4.2.13)
	A	number	Probability of industry code category A
	B	number	Probability of industry code category B
	C	number	Probability of industry code category C
	D	number	Probability of industry code category D
	E	number	Probability of industry code category E
	F	number	Probability of industry code category F
	G	number	Probability of industry code category G
	H	number	Probability of industry code category H
	I	number	Probability of industry code category I
	J	number	Probability of industry code category J
	K	number	Probability of industry code category K
	L	number	Probability of industry code category L
	M	number	Probability of industry code category M
	N	number	Probability of industry code category N
	O	number	Probability of industry code category O
	P	number	Probability of industry code category P
	Q	number	Probability of industry code category Q
	R	number	Probability of industry code category R
	S	number	Probability of industry code category S
	T	number	Probability of industry code category T
	U	number	Probability of industry code category U
	nogaCode	string	Current official noga code (see 4.2.12)
	managerData	container	Manager related information
	currentManagement	list	Current management related information
	activeMandatesNum	integer	Number of active mandates of manager
	ccsAlpha	string	Alphanumeric score (see 4.3.4)
	ccsNum	number	Numeric score (see 4.3.4)
	companyFailuresNum	integer	Number of company failures of manager
	domicile	string	Domicile
	endDate	string	End date
	function	string	Function of manager
	iid	string	Identification number
	name1	string	Last name
	name2	string	First name

	origin	string	Origin
	positions	list	Position related information
	classCode	integer	Class code
	classDescription	string	Class description
	positionCode	integer	Position code
	positionDescription	string	Position Description
	scoreDate	string	Date of last score change
	signature	string	Signature description (see 4.2.16)
	signatureCode	integer	Signature value (see 4.2.16)
	startDate	string	Start date
	numberSigningPeople	integer	Number of people with signing authority
	pursuitData	container	Pursuit data related information
	details	list	Detailed pursuit data related information
	amountOfGarnishments	number	amount of garnishments
	amountOfObjections	number	amount of objections
	amountOfOpenProsecutions	number	amount of open prosecutions
	amountOfPaidProsecutions	number	amount of paid prosecutions
	amountOfThreatedProsecutions	number	amount of threated prosecutions
	amountOfUnpaidDebtsCertificates	number	amount of unpaid debt certificates
	controlDate	string	Collection date
	controlLocation	string	Town of responsible authority
	controlYear	integer	Year of entry
	numberOfGarnishments	integer	number of garnishments
	numberOfObjections	integer	number of objections
	numberOfOpenProsecutions	integer	number of open prosecutions
	numberOfPaidProsecutions	integer	number of paid prosecutions
	numberOfThreatedProsecutions	integer	number of threated prosecutions
	numberOfUnpaidDebtsCertificates	integer	number of unpaid debt certificates
	pursuitId	integer	Identifier of pursuit entry
	status	integer	Status (0=empty, 1=at least one negative entry)
	reportData	container	Report data related information
	base64	string	Report as base64
	url	string	URL of report
	shabData	container	SHAB message related information
	details	list	Detailed SHAB message related information
	canton	string	Canton

	messageDetails	string	Message details
	publicationDate	string	Publication date
	publicationNumber	string	Publication number
	rubric	string	Rubric
	subRubric	string	Sub rubric
	swissZipCode	string	Postal code
	title	string	Message title
	town	string	Town

2.2.4. Workflow

This service can be used to obtain various attributes which are subject to a workflow (e.g. credit recommendations, risk indicator). The scale of the response depends on the chosen workflow name and the client specific stored parameter. For further information please contact information.services@intrum.com.

Endpoint	restServices/v.0.0/company/workflow?		
Method	GET		
Request Parameter	**Name**	**Type**	**Description**
	requestId	string	Request ID
	iid	string	Intrum ID
	uid	string	UID number
	refNr	string	HR ref number
	organisationName	string	Full company name
	street	string	Street
	houseNumber	string	House number
	town	string	Town
	swissZipCode	string	Postal code
	phone	string	Phone number
	email	string	e-mail address
	ipAddress	string	IP address
	idNumber	string	ID number
	productCategory	string	Product Category (see 4.2.22)
	orderingPersonFirstName	string	First name of ordering person
	orderingPersonLastName	string	Last name of ordering person
	orderingPersonBirthdate	string	Birthdate of ordering person (e.g. 1980-01-01)
	hitScoreCutoff	number	Minimal hitScore to be considered a hit (see 4.2.3)
	workflowName	string	Workflow (see 4.2.17)
	amount	number	Order amount (only for b2bECommerce)
	deliveryOrganisationName	string	Delivery company name
	deliveryFirstName	string	Delivery first name
	deliveryLastName	string	Delivery last name
	deliveryStreet	string	Delivery street

	deliveryHouseNumber	string	Delivery house number
	deliveryZipCode	string	Delivery postal code
	deliveryTown	string	Delivery town
	matchingProfile	integer	Matching profile to use (see 4.2.2)
Example Request	https://test-credit-information-ws.ch/restServices/v.0.0/company/workflow?requestId=123abc&uid=100046244&workflowName=b2bECommerce&amount=500&matchingProfile=1&phone=0441234567&email=c.b%C3%B6sch@holdingalleria.ch&idNumber=C1234567&ipAddress=127.12.34.5&orderingPersonFirstName=Caspar&orderingPersonLastName=B%C3%B6sch&orderingPersonBirthdate=1960-12-08		
Response Attributes	**Name**	**Type**	**Description**
	bcsAlpha	string	Numeric score (see 4.2.5)
	bcsNum	number	Alphanumeric score (see 4.2.5)
	abcsAlpha	string	Numeric score (see 4.2.6)
	abcsNum	number	Alphanumeric score (see 4.2.6)
	hitType	string	Hit type
	iid	string	Intrum ID
	remainingLimit	number	Remaining limit (see 4.2.18)
	requestId	string	Request ID (the one sent in the request)
	responseCode	integer	Response code (see 4.2.19)
	responseId	integer	Unique Response ID
	riskIndicator	integer	Risk indicator (see 4.2.20)
	scoreDate	string	Date of last score change

2.2.5. OrderRegistration

This service can be used to register an order made by one of your customers. This information is important for correct limit handling and helps Intrum maintain good quality data.

Endpoint	restServices/v.0.0/company/orderRegistration		
Method	POST		
Request Parameter	**Name**	**Type**	**Description**
	requestId	string	Request ID
	workflowResponseId	integer	Response ID from workflow used to check company
	orderId	string	Identifier of Order
	paymentMethod	string	Payment Method (see 4.2.23)
	amount	number	Order amount in CHF
	organisationName	string	Full company name
	street	string	Street
	houseNumber	string	House number
	town	string	Town
	zipCode	string	Postal Code
	countryCode	string	Country Code
	phone	string	Phone number
	email	string	e-mail address

	ipAddress	string	IP address
	iid	string	Intrum ID
	uid	string	UID number
	refNr	string	HR ref number
	deliveryOrganisationName	string	Full company name of delievery
	deliveryStreet	string	Street of delivery address
	deliveryTown	string	Town of delivery address
	deliveryZipCode	string	Postal code of delivery address
	deliveryCountryCode	string	Country code of delivery address
	extraInfo	string	Extra information about the order
Example Request URL	https://test-credit-information-ws.ch/restServices/v.0.0/company/orderRegistration		
Example Request DATA	{"requestId":"37_626fe19c00cd2", "workflowResponseId":5247001, "orderId":"000000037", "paymentMethod":"checkmo", "amount":18.00, "organisationName":"Intrum AG", "street":"infostrasse 12", "town":"infocity", "zipCode":"1000", "countryCode":"CH", "phone":"1234", "email":"hello@world.com", "ipAddress":"194.11.129.242", "deliveryOrganisationName":"Intrum AG", "deliveryStreet":"infostrasse 12", "deliveryTown":"infocity", "deliveryZipCode":"1000", "deliveryCountryCode":"CH", "extraInfo":"Magento_Plug_in"}		
Response Attributes	**Name**	**Type**	**Description**
	registrationId	integer	Registration ID

2.3. Person

2.3.1. Search

This service can be used to search for individuals in Switzerland. Different details must be given depending on the chosen matchingProfile. A full request contains the attributes fullName (or firstName, lastName), birthdate and fullAdress (or street, houseNumber, zipCode, town). If fullName and/or fullAddress is given the corresponding separate attributes are ignored.

Endpoint	restServices/v.0.0/person/search?		
Method	GET		
Request Parameter	**Name**	**Type**	**Description**
	requestId	string	Request ID

	fullName	string	Full Name (e.g. Peter Muster)
	firstName	string	First name
	lastName	string	Last name
	birthdate	string	Birth date (e.g. 1980-01-01)
	fullAddress	string	Full address (e.g. Bahnstrasse 1 8000 Zürich)
	street	string	Street
	houseNumber	string	House number
	town	string	Town
	zipCode	string	Postal code
	matchingProfile	integer	Matching profile to use (see 4.3.2)
	sortType	string	Sorting Type (see 4.3.3)
Example Request	https://test-credit-information-ws.ch/restServices/v.0.0/person/search?requestId=123abc&fullName=Christian Behrens&birthdate=1970-03-17&fullAddress=St. Gallerstrasse 59 9300 Wittenbach&matchingProfile=1		
Response Attributes	**Name**	**Type**	**Description**
	matchingResults	list	Container for all matched individuals
	birthdate	string	Birth date (e.g. 1980-01-01)
	firstName	string	First Name
	fullAddress	string	Full address
	hitScore	number	Grade of match (see 4.3.7)
	iid	string	Intrum ID
	lastName	string	Last Name
	personId	integer	Unique party identifier
	requestId	string	Request ID
	responseId	integer	Unique Response ID

2.3.2. Info

This service can be used to obtain detailed information about a person by providing a full name and either a birth date or a complete address. To be considered a complete address, at least street and zip code or street and town must be passed.

Endpoint	restServices/v.0.0/person/info?		
Method	GET		
Request Parameter	**Name**	**Type**	**Description**
	requestId	string	Request ID (the one sent in the request)
	firstName	string	First name
	lastName	string	Last name
	birthdate	string	Birth date (e.g. 1980-01-01)
	street	string	Street
	houseNumber	string	House number
	town	string	Town
	zipCode	string	Postal code
	countryCode	string	Country code
	phone	string	Phone number
	email	string	e-mail address

	ipAddress	string	IP address
	idNumber	string	ID number
	productCategory	string	Product Category (see 4.3.21)
	reportType	string	Type of report (see 4.3.1)
	matchingProfile	integer	Matching profile to use (see 4.3.2)
	sortType	string	Sorting Type (see 4.3.3)
Example Request	https://test-credit-information-ws.ch/restServices/v.0.0/person/info?requestId=123abc&firstName=Caspar&lastName=Bosch&birthdate=1960-12-08&street=Bachstrasse&houseNumber=9&town=Herisau&zipCode=9100&countryCode=CH&matchingProfile=1&reportType=b2cCreditDetails&phone=0441234567&email=c.bösch@holdingalleria.ch&idNumber=C1234567&ipAddress=127.12.34.5		
Response Attributes	**Name**	**Type**	**Description**
	addressData	container	Address data related information
	formerAddresses	list	Former address related information
	aadsCode	integer	Address status code (see 4.3.17)
	aadsDate	string	Address status date
	addressId	string	Unique address identification number
	countryCode	string	Country code
	houseNumber	string	House number
	street	string	Street
	swissZipCode	string	Postal code for swiss addresses
	town	string	Town
	zipCode	string	Postal code
	newestAddress	container	Newest address related information
	aadsCode	integer	Address status code (see 4.3.17)
	aadsDate	string	Address status date
	addressId	string	Unique address identification number
	countryCode	string	Country code
	houseNumber	string	House number
	street	string	Street
	swissZipCode	string	Postal code for swiss addresses
	town	string	Town
	zipCode	string	Postal code
	bankruptcyData	container	Bankruptcy data related information (from SHAB)
	details	list	Detailed bankruptcy data related information
	messageDetails	string	Message content
	publicationDate	string	Publication Date
	publicationNumber	string	Publication number
	rubric	string	Rubric value (see 4.3.9)
	subRubric	string	Subrubric value (see 4.3.10)
	title	string	Title of publication
	blacklistData	container	Blacklist data related information
	lists	list	Detailed blacklist data related information
	birthdate	string	Birth date of blacklist hit
	email	string	E-mail of blacklist hit
	ext1	string	Ext1 attribute of blacklist hit

	ext2	string	Ext2 attribute of blacklist hit
	firstName	string	First name of blacklist hit
	hcbtCode	integer	Code of blacklist hit
	houseNumber	string	House number of blacklist hit
	info	string	Info attribute of blacklist hit
	initials	string	Initial attribute of blacklist hit
	ipAddress	string	IP address of blacklist hit
	lastName	string	Last name of blacklist hit
	modifiedDate	string	Modified date of blacklist hit
	phone	string	Phone number of blacklist hit
	sourceKey	integer	Source key of blacklist hit
	sourceName	string	Source name of blacklist hit
	street	string	Street of blacklist hit
	swissZipCode	string	Postal code of blacklist hit
	town	string	Town of blacklist hit
	collectionData	container	Collection data related information
	aggregated	container	Aggregated collection data related information
	firstOpeningDate	string	Opening date of first case
	latestOpeningDate	string	Opening date of latest case
	latestPaymentAmount	number	Amount of latest payment
	latestPaymentDate	string	Date of latest payment
	openCasesNum	integer	Number of open cases
	totalAmount	number	Total amount
	totalCasesNum	integer	Number of total cases
	totalOpenAmount	number	Open amount
	details	list	Detailed collection data related information
	amount	number	Amount
	caseRef	string	Case reference
	closingCode	integer	Closing code (see 4.3.19)
	closingDate	string	Closing date
	eventCode	integer	Event (see 4.3.18)
	industryCode	integer	Industry Code (see 4.3.20)
	latestPaymentAmount	number	Amount of latest payment
	latestPaymentDate	string	Date of latest payment
	legalState	integer	Indicates if prelegal (0) or legal (1) case
	openAmount	number	Open amount
	openingDate	string	Opening date
	sourceName	string	Source Name
	status	integer	Indicates if case is closed (0) or still open (1)
	creditData	container	Credit data related information
	casAlpha	string	Alphanumeric score of address hit (see 4.3.5)
	casNum	number	Numeric score of address hit (see 4.3.5)
	householdCcsAlpha	string	Alphanumeric score of household hit (see 4.3.4)
	householdCcsNum	number	Numeric score of household hit (see 4.3.4)

	householdScoreDate	string	Date of last score change
	personCcsAlpha	string	Alphanumeric score (see 4.3.4)
	personCcsNum	number	Numeric score (see 4.3.4)
	personAccsAlpha	string	Alphanumeric advanced score (see 4.3.5)
	personAccsNum	number	Numeric advanced score (see 4.3.54.3.4)
	scoreDate	string	Date of last score change
	eCommerceData	container	E-Commerce data related information
	aggregated	container	Aggregated eCommerce data related information
	lastMonthContractsAmount	number	Amount of last month's contracts
	lastMonthContractsNum	integer	Number of contracts last month
	latestContractDate	string	Date of latest contracts
	latestPaymentDate	string	Latest payment date
	totalContractsAmount	number	Total amount of all contracts
	totalContractsNum	integer	Number of total contracts
	totalPaymentAmount	number	Total amount of all payment
	details	list	Detailed eCommerce data related information
	sourceId	integer	Source ID
	contractAmount	number	Contract amount
	contractDate	string	Contract date
	contractId	string	Contract ID
	latestPaymentDate	string	Date of latest payment
	paymentAmount	number	Payment amount
	fraudData	container	Fraud data related information
	fraudScore	number	Fraud score
	hits	list	Fraud hit related information
	id	string	ID of hit
	latestEntryDate	string	Latest date of entry
	registrationDate	string	Registration date of hit
	source	string	Source of hit
	type	string	Type of hit
	value	string	Value of hit
	identityQuality	list	Identity quality related information
	hitScore	number	Hit score of identity match
	latestEntryDate	string	Latest Date of entry
	numPayments	integer	Number of payments of identity
	registrationDate	string	Registration date
	type	string	Type of identity
	lists	list	Blacklist related information
	birthdate	string	Birth date of blacklist hit
	blacklistId	string	ID of blacklist hit
	countryCode	String	Country code of blacklist hit
	email	string	E-mail of blacklist hit
	ext1	string	Ext1 attribute of blacklist hit

	ext2	string	Ext2 attribute of blacklist hit
	firstName	string	First name of blacklist hit
	hcbtCode	integer	Code of blacklist hit
	houseNumber	string	House number of blacklist hit
	info	string	Info attribute of blacklist hit
	initials	string	Initial attribute of blacklist hit
	ipAddress	string	IP address of blacklist hit
	lastName	string	Last name of blacklist hit
	modifiedDate	string	Modified date of blacklist hit
	phone	string	Phone number of blacklist hit
	sourceName	string	Source name of blacklist hit
	street	string	Street of blacklist hit
	swissZipCode	string	Postal code of blacklist hit
	town	string	Town of blacklist hit
	suspectList	list	Suspect related information
	id	string	ID of suspect
	registrationDate	string	Registration Date
	source	string	Source of suspect
	type	string	Type of suspect
	value	string	Value of suspect
	generalData	container	General data related information
	birthdate	string	Birth date (e.g. 1980-01-01)
	firstName	string	First name
	hitScore	number	Grade of match (see 4.3.7)
	lastName	string	Last name
	personId	integer	Unique party identifier
	requestId	string	Request ID (the one sent in the request)
	responseId	integer	Unique Response ID
	managerData	container	Manager data related information
	activeMandatesNum	integer	Number of active mandates
	companies	list	Company related information
	organisationName	string	Company Name
	uidOrganisationId	integer	Uid in integer format
	companyFailuresNum	integer	Number of company failures
	iid	string	Manager id
	pursuitData	container	Pursuit data related information
	details	list	Detailed pursuit data related information
	amountOfGarnishments	number	amount of garnishments
	amountOfObjections	number	amount of objections
	amountOfOpenProsecutions	number	amount of open prosecutions
	amountOfPaidProsecutions	number	amount of paid prosecutions
	amountOfThreatedProsecutions	number	amount of threated prosecutions

	amountOfUnpaidDebtsCertificates	number	amount of unpaid debt certificates
	controlDate	string	Collection date
	controlLocation	string	Town of responsible authority
	controlYear	integer	Year of entry
	numberOfGarnishments	integer	number of garnishments
	numberOfObjections	integer	number of objections
	numberOfOpenProsecutions	integer	number of open prosecutions
	numberOfPaidProsecutions	integer	number of paid prosecutions
	numberOfThreatedProsecutions	integer	number of threated prosecutions
	numberOfUnpaidDebtsCertificates	integer	number of unpaid debt certificates
	pursuitId	integer	Identification number
	status	integer	Status value (see 4.3.8)
	premiumConsumerScoreData	container	Premium consumer score related information
	personPcsNum	integer	Premium consumer score value
	pcsHitType	string	Premium consumer score hit type - PHO: Person known in house, PST: Person known in street, PCI: Person known in city, PCO: Person known in Switzerland, LAA: Household known in house, OAF: (Only) address known, NAF: Address unknown
	pcsScoreType	string	Premium consumer score type
	reportData	container	Report data related information
	base64	string	Report as base64
	url	string	URL of report of found person

2.3.3. Workflow

This service can be used to obtain various attributes which are subject to a workflow (e.g. credit recommendations, risk indicator) about a person by providing a full name and either a birth date or a complete address. To be considered a complete address, at least street and zip code or street and town must be passed. The scale of the response depends on the chosen workflow name and the client specific stored parameter. For further information please contact information.services@intrum.com.

Endpoint	restServices/v.0.0/person/workflow?		
Method	GET		
Request Parameter	**Name**	**Type**	**Description**
	requestId	string	Request ID
	firstName	string	First name
	lastName	string	Last name
	birthdate	string	Birth date (e.g. 1980-01-01)
	street	string	Street
	houseNumber	string	House number

	town	string	Town	
	zipCode	string	Postal code	
	countryCode	string	Country code	
	phone	string	Phone number	
	email	string	e-mail address	
	ipAddress	string	IP address	
	idNumber	string	ID number	
	productCategory	string	Product category (see 4.3.21)	
	workflowName	string	Workflow (see 4.3.11)	
	amount	number	Order amount (only for b2cECommerce)	
	sortType	string	Sorting Type (see 4.3.3)	
	deliveryFirstName	string	Delivery first name	
	deliveryLastName	string	Delivery last name	
	deliveryStreet	string	Delivery street	
	deliveryHouseNumber	string	Delivery house number	
	deliveryZipCode	string	Delivery postal code	
	deliveryTown	string	Delivery town	
	deliveryCountryCode	string	Delivery country code	
	matchingProfile	integer	Matching profile to use (see 4.3.2)	
Example Request (simpleCreditRecommendation)	https://test-credit-information-ws.ch/restServices/v.0.0/person/workflow?requestId=123abc&lastName=Behrens&firstName=Christian&birthdate=1970-03-17&street=St.Gallerstrasse&houseNumber=59&town=Wittenbach&zipCode=9300&countryCode=CH&matchingProfile=1&workflowName=simpleCreditRecommendation&phone=0441234567&email=c.bösch@holdingalleria.ch&idNumber=C1234567&ipAddress=127.12.34.5			
Example Request (trafficLight)	https://test-credit-information-ws.ch/restServices/v.0.0/person/workflow?requestId=123abc&lastName=Behrens&firstName=Christian&birthdate=1970-03-17&street=St.Gallerstrasse&houseNumber=59&town=Wittenbach&zipCode=9300&countryCode=CH&matchingProfile=1&workflowName=trafficLight&phone=0441234567&email=c.bösch@holdingalleria.ch&idNumber=C1234567&ipAddress=127.12.34.5			
Example Request (b2cECommerce)	https://test-credit-information-ws.ch/restServices/v.0.0/person/workflow?requestId=123abc&amount=10.00&lastName=Behrens&firstName=Christian&birthdate=1970-03-17&street=St.%20Gallerstrasse&houseNumber=59&town=Wittenbach&zipCode=9300&countryCode=CH&matchingProfile=1&workflowName=b2cECommerce&phone=0441234567&email=c.b%C3%B6sch@holdingalleria.ch&idNumber=C1234567&ipAddress=127.12.34.5			
Response Attributes	**Name**	**Type**	**Description**	**wN**
	birthdate	string	Birth date (e.g. 1980-01-01)	1,2
	ccsAlpha	string	Alphanumeric score (see 4.3.4)	3
	ccsNum	number	Numeric score (see 4.3.4)	3
	accsAlpha	string	Alphanumeric advanced score (see 4.3.5)	3
	accsNum	number	Numeric advanced score (see 4.3.54.3.4)	3
	creditRecommendation	integer	Credit Recommendation (see 4.3.11)	1,2
	firstName	string	First name	1,2

	hitScore	number	Hit score of identity match	1,2
	hitType	string	Hit type (see 4.3.12)	3
	lastName	string	Last name	1,2
	newestAddress	container	Newest address related information	2
	aadsCode	integer	Address status code (see 4.3.16)	2
	aadsDate	string	Address status date	2
	addressId	string	Unique address identification number	2
	countryCode	string	Country code	2
	houseNumber	string	House number	2
	street	string	Street	2
	town	string	Town	2
	zipCode	string	Postal code	2
	personId	integer	Unique party identifier	1,2, 3
	remainingLimit	number	Remaining limit (see 4.3.13)	3
	requestId	string	Request ID (the one sent in the request)	1,2
	responseCode	integer	Response code (see 4.3.14)	1,2, 3
	responseId	integer	Unique Response ID	1,2
	riskIndicator	integer	Risk indicator (see 4.3.16)	3
	scoreDate	string	Date of last score change	3

2.3.4. OrderRegistration

This is the person equivalent to the company orderRegistration.

Endpoint	restServices/v.0.0/person/orderRegistration		
Method	POST		
Request Parameter	**Name**	**Type**	**Description**
	requestId	string	Request ID
	workflowResponseId	integer	Response ID from workflow used to check person
	orderId	string	ID Order
	paymentMethod	string	Payment Method (see 4.3.22)
	amount	number	Order amount
	birthdate	string	Birth date (e.g. 1980-01-01)
	firstName	string	First name
	lastName	string	Last name
	street	string	Street
	houseNumber	string	House number
	town	string	Town
	zipCode	string	Postal Code
	countryCode	string	Country Code
	phone	string	Phone number
	email	string	e-mail address
	ipAddress	string	IP address
	idNumber	string	ID number
	deliveryFirstName	string	First name at delivery address

	deliveryLastName	string	Last name at delivery address
	deliveryStreet	string	Street for delivery address
	deliveryHouseNumber	string	Housenumber for delivery address
	deliveryTown	string	Town for delivery address
	deliveryZipCode	string	Postal code for delivery address
	deliveryCountryCode	string	Country code for delivery address
	extraInfo	string	Extra information about the order
Example Request URL	https://test-credit-information-ws.ch/restServices/v.0.0/person/orderRegistration		
Example Request DATA	{"requestId":"123a", "firstName":"Christian", "lastName":"Behrens", "birthdate":"1970-03-17", "street":"St. Gallerstrasse", "houseNumber":"59", "town":"Wittenbach", "zipCode":"9300", "countryCode":"CH", "phone":"0441234567", "email":"c.behrens@holdingalleria.ch", "idNumber":"C1234567", "ipAddress":"127.12.34.5", "orderId":"103245a", "paymentMethod ":"invoice", "amount":12.2, "workflowResponseId":123}		
Response Attributes	**Name**	**Type**	**Description**
	registrationId	integer	Registration ID

2.4. Compliance

2.4.1. Search

This service can be used to search for entities listed on PEP (Political exposed People) Desk, Sanctions List or Watchlist&Blacklist.

Endpoint	restServices/v.0.0/compliance/search?		
Method	GET		
Request Parameter	**Name**	**Type**	**Description**
	requestId	string	Request ID
	lists	string	Which lists should be searched separated by commas (see 4.4.1)
	terms	string	Search terms (e.g. Christoph Blocher)
	accuracy	integer	Search Profile (see 4.4.2)
	max_hits_per_list	integer	Number of maximal hits to be responded
Example	https://test-credit-information-		

Request	ws.ch/restServices/v.0.0/compliance/search?accuracy=3&lists=PEP,SL,WLBL&terms=christoph blocher&max_hits_per_list=10		
Response Attributes	**Name**	**Type**	**Description**
	status	string	Status (OK or NOK)
	totalCount	integer	Number of hits
	hits	container	Container for indicating hits
	PEP	integer	Indicates if hit on PEP
	SL	integer	Indicates if hit on SL
	WLBL	integer	Indicates if hit on WLBL
	entries	container	Container for all entries
	PEP	container	Container for all hits on PEP
	ID	container	ID holding all details about hit
	ID	string	Unique Identification number (same as container)
	Country	string	Country
	First_Name	string	First name
	Last_Name	string	Last name
	Full_Name	string	Full name
	DOB	string	Birth date or Birth year (e.g. 1980-01-01 or 1980)
	SL	container	Container for all hits on SL
	ID	container	ID holding all details about hit
	ID	string	Unique Identification number (same as container)
	First_Name	string	First name
	Last_Name	string	Last name
	Full_Name	string	Full name
	DOB	string	Birth date or Birth year (e.g. 1980-01-01 or 1980)
	Name_of_the_List	string	Name of the list
	WLBL	container	Container for all hits on WLBL
	ID	container	ID holding all details about hit
	ID	string	Unique Identification number (same as container)
	First_Name	string	First name
	Last_Name	string	Last name
	Full_Name	string	Full name
	DOB	string	Birth date or Birth year (e.g. 1980-01-01 or 1980)
	Name_of_the_List	string	Name of the list

2.4.2. Info

This service can be used to get detailed information of entities listed on PEP (Political exposed People) Desk, SL (Sanctions List) or WLBL (Watchlist & Blacklist).

Endpoint	restServices/v.0.0/compliance/info?		
Method	GET		
Request Parameter	**Name**	**Type**	**Description**
	requestId	string	Request ID
	id	integer	ID from search response (see 2.4.1)
Example	https://test-credit-information-		

Request (PEP)	ws.ch/restServices/v.0.0/compliance/info?id=10101046122			
Example Request (SL)	https://test-credit-information-ws.ch/restServices/v.0.0/compliance/info?id=10120017297			
Example Request (WLBL)	https://test-credit-information-ws.ch/restServices/v.0.0/compliance/info?id=20200022102			
Response Attributes	**Name**	**Type**	**Description**	**List**
	Additional_Information	string	Additional information	all
	Address	string	Full address	SL, WLBL
	Address_Country	string	Address country	WLBL
	Alternative_Script	list	Alternative script	all
	Authority	string	Authority (e.g. FBI)	SL, WLBL
	Case	string	Reason why entity is listed	WLBL
	Category	list	Compliance Category	PEP, WLBL
	Code	string	Country Code (e.g. CHE)	PEP
	Country	string	Country	PEP, WLBL
	Country_Of_Activity	string	Country of activity	PEP
	Country_Of_Origin	string	Country of origin	PEP
	DOB	string	Birth date (e.g. 01.01.1980)	all
	Date_of_Information	string	Date of information (01.01.2020)	WLBL
	Date_of_Publication	string	Date of publication (01.01.2020)	WLBL
	Date_of_Publication_of_the_List	string	Date of publication (01.01.2020)	SL
	Entity_Type	string	Entity type (e.g. I)	WLBL
	First_Name	string	First name	all
	Full_Name	string	Full name	all
	Function	list	Functions of entity	PEP
	Gender	string	Gender	PEP
	ID	string	List specific unique Identification number	all
	Last_Name	string	Last name	all
	Name_of_the_List	string	Name of the list	SL, WLBL
	No_longer_on_List	string	Indicates if no longer on list (e.g. "")	WLBL
	Other_Names	list	Possible other names	all
	POB	string	Place of birth	all
	Passport_Nr	string	Passport Number	SL, WLBL
	Relative_ID	string	Relative ID	PEP, WLBL
	Relatives	list	Container for information about relatives	PEP

	ID	string	Unique identification number of relative	PEP
	Full_Name	string	Full name of relative	PEP
	DOB	string	Birth date of relative (e.g. 01.01.1980)	PEP
	Country	string	Country of relative	PEP
	Title	string	Title (e.g. Mr.)	all
	Type_SDN_or_Entity	string	Entity type (e.g. individual)	SL
	Type_of_List	string	Type of list	SL
	Whitelist	string	Indicates if whitelist entry (e.g. No)	SL
	list	string	Type of list (PEP, SL, WLBL)	all
	status	string	Status (OK or NOK)	all

2.5. Kremo

This service can be used to obtain information on the budget calculation, which abide to the Swiss Consumer Credit Act (KKG) law. In order to set this up as a REST service, some string input parameters need to follow certain structures. This is especially true for the input parameters childrenList, openCreditList, individualExpensesList, pOpenCreditList and pIndividualExpensesList.

Endpoint	restServices/v.0.0/kremo?		
Method	GET		
Request Parameter	**Name**	**Type**	**Description**
	substituteExistingCredit	number	Credit amount to be substituted in CHF
	creditType	string	Type of credit being applied for (CREDIT, LEASING or PARTIAL)
	creditAmount	number	Credit amount being applied for in CHF
	creditRecurringFee	number	Monthly recurring fee in CHF
	creditNonRecurringFee	number	One-time fee in CHF
	creditDecliningBalance	number	Remaining value in CHF
	creditFirstRateAmount	number	First big rate in CHF
	creditInterestRateAmount	number	Interest rate of credit being applied for
	creditInterestRateType	string	Credit interest rate type (NOMINAL or EFFECTIVE)
	creditterm	integer	Credit duration in Months
	birthDate	string	Birthdate of applicant
	gender	string	Gender of applicant (MALE or FEMALE)
	civilStatusType	string	Civil status type of applicant (SINGLE, MARRIED, DIVORCED, JURIDICAL_SEPARATED, WIDOWED, JURIDICAL_REGISTERED or JURIDICAL_RESOLVED)
	zip	string	Swisszipcode of applicant
	canton	string	Canton of applicant
	grossIncomeMain	number	Monthly main gross income in CHF of applicant
	grossIncomeExtra	number	Monthly extra gross income in CHF of applicant

	netIncomeMain	number	Monthly main net income in CHF of applicant
	netIncomeExtra	number	Monthly extra net income in CHF of applicant
	alimony	number	Monthly alimony expenses in CHF of applicant
	educationCost	number	Monthly expenses for education in CHF of applicant
	oneTimeExpenses	number	One-time expenses in CHF of applicant
	professionalOrganizationFee	number	Monthly expenses for organisational membership in CHF of applicant
	isFoodIntakeIncreased	boolean	(true or false)
	isFoodBoardingExternal	boolean	(true or false)
	isClothingRequirementIncreased	boolean	(true or false)
	transportationEffectiveAmount	number	Monthly expenses for transportation in CHF of applicant
	otherFixExpenses	number	Monthly other fixed expenses in CHF of applicant
	transportationType	string	Transportation type of applicant (NONE, BICYCLE, MOPED, MOTORCYCLE, CAR or PUBLIC)
	housingCost	number	Monthly rental or mortgage costs in CHF of applicant
	openCreditList	string	List of open credits in CHF of applicant, e.g. 350.0,CREDIT,NOMINAL,5,5;150.0,CREDIT,NOMINAL,5,39 represents 2 credits. The first one is a credit of type CREDIT with NOMIAL interest rate type and 5 percent interest rate of 350 CHF over 5 months while the second is a credit of type CREDIT with NOMIAL interest rate type and 5 percent interest rate of 150 CHF over 39 months.
	individualExpensesList	string	List of individual expenses in CHF of applicant separated by ';', e.g. 350.0,Kita Kosten;100.0,stamp collection represents 2 expenses. The first one is an expense for CHF 350 CHF for 'Kita Kosten' and the other one is for CHF 100 for 'stamp collection'
	isTaxAtSourceObligatory	boolean	(true or false)
	isChurchTaxObligatory	boolean	(true or false)
	workingDaysPerMonth	integer	Applicant's number of working days per month
	pBirthDate	string	Birthdate of partner
	pGender	string	Gender of partner (MALE or FEMALE)
	pCivilStatusType	string	Civil status type of partner (SINGLE, MARRIED, DIVORCED, JURIDICAL_SEPARATED, WIDOWED, JURIDICAL_REGISTERED or

			JURIDICAL_RESOLVED)
	pZip	string	Swisszipcode of partner
	pCanton	string	Canton of partner
	pGrossIncomeMain	number	Monthly main gross income in CHF of partner
	pGrossIncomeExtra	number	Monthly extra gross income in CHF of partner
	pNetIncomeMain	number	Monthly main net income in CHF of partner
	pNetIncomeExtra	number	Monthly extra net income in CHF of partner
	pAlimony	number	Monthly alimony expenses in CHF of partner
	pEducationCost	number	Monthly expenses for education in CHF of partner
	pOneTimeExpenses	number	One-time expenses in CHF of partner
	pProfessionalOrganizationFee	number	Monthly expenses for organisational membership in CHF of partner
	pIsFoodIntakeIncreased	boolean	(true or false)
	pIsFoodBoardingExternal	boolean	(true or false)
	pIsClothingRequirementIncreased	boolean	(true or false)
	pTransportationEffectiveAmount	number	Monthly expenses for transportation in CHF of partner
	pOtherFixExpenses	string	Monthly other fixed expenses in CHF of partner
	pTransportationType	string	Transportation type of partner (NONE, BICYCLE, MOPED, MOTORCYCLE, CAR or PUBLIC)
	pHousingCost	number	Monthly rental or mortgage costs in CHF of partner
	pOpenCreditList	string	List of open credits in CHF of partner, e.g. 350.0,CREDIT,NOMINAL,5,5;150.0,CREDIT,NOMINAL,5,39 represents 2 credits. The first one is a credit of type CREDIT with NOMIAL interest rate type and 5 percent interest rate of 350 CHF over 5 months while the second is a credit of type CREDIT with NOMIAL interest rate type and 5 percent interest rate of 150 CHF over 39 months.
	pIndividualExpensesList	string	List of individual expenses in CHF of the partner separated by ';', e.g. 350.0,Kita Kosten;100.0,stamp collection represents 2 expenses. The first one is an expense for CHF 350 CHF for 'Kita Kosten' and the other one is for CHF 100 for 'stamp collection'
	pIsTaxAtSourceObligatory	boolean	(true or false)
	pIsChurchTaxObligatory	boolean	(true or false)
	pWorkingDaysPerMonth	integer	Partner's number of working days per month
	childrenList	string	List of children and their ages in household separated by ';', e.g. '6;5;3' represents 3

			children aged 6,5 and 3 years old
	healthInsuranceFee	number	Monthly health insurance fee of household
	numberOfSupportableGrownUps	integer	Number of adults being taken care of in the household
	householdType	string	Type of household (SINGLE, MARRIED_COUPLE, SINGLE_HOUSEHOLD_COMMUNITY, SINGLE_PARENT, SINGLE_PARENT_HOUSEHOLD_COMMUNITY or SINGLE_SUPPORTING_GROWNUP_IN_SAME_HOUSEHOLD)
Example Request	https://test-credit-information-ws.ch/restServices/v.0.0/kremo?substituteExistingCredit=600&creditType=LEASING&creditAmount=75000&creditRecurringFee=50&creditNonRecurringFee=100&creditDecliningBalance=3000&creditFirstRateAmount=8000&creditInterestRateAmount=5&creditInterestRateType=NOMINAL&creditterm=48&birthDate=1995-03-17&gender=MALE&civilStatusType=MARRIED&zip=5400&canton=AG&grossIncomeMain=8000&grossIncomeExtra=700.0&alimony=350.0&educationCost=120&oneTimeExpenses=60&professionalOrganizationFee=50.0&isFoodIntakeIncreased=false&isFoodBoardingExternal=false&isClothingRequirementIncreased=true&transportationEffectiveAmount=350&otherFixExpenses=15&transportationType=BICYCLE&housingCost=2500.0&openCreditList=350.0,CREDIT,NOMINAL,5,5;150.0,CREDIT,NOMINAL,5,39;220,CREDIT,NOMINAL,5,39&individualExpensesList=100.0,stamp collection;100.0,Kita Kosten&isTaxAtSourceObligatory=false&isChurchTaxObligatory=true&workingDaysPerMonth=21&pBirthDate=1990-03-17&pGender=FEMALE&pCivilStatusType=MARRIED&pZip=5400&pCanton=AG&pGrossIncomeMain=3000.0&pGrossIncomeExtra=500.0&pAlimony=80.0&pEducationCost=130&pOneTimeExpenses=90&pProfessionalOrganizationFee=50.0&pIsFoodIntakeIncreased=false&pIsFoodBoardingExternal=false&pIsClothingRequirementIncreased=true&pTransportationEffectiveAmount=120&pOtherFixExpenses=100&pTransportationType=CAR&pHousingCost=0.0&pOpenCreditList=150.0,CREDIT,NOMINAL,5,39&pIndividualExpensesList=230.0,Kita Kosten&pIsTaxAtSourceObligatory=false&pIsChurchTaxObligatory=false&pWorkingDaysPerMonth=22&childrenList=6;6;12;13;13;13&healthInsuranceFee=0&numberOfSupportableGrownUps=0&householdType=MARRIED_COUPLE		
Response Attributes	**Name**	**Type**	**Description**
	calculateOut	container	Container for calculation output
	application	container	Container for calculated application
	exemptAmountList	list	Container for list of amounts
	amount	number	Amount in CHF
	exemptAmountType	string	Type (AFTER_TAX_AT_SOURCE, AFTER_CURRENT_LIABILITIES or AFTER_APPLICATION_DATA)
	isCorrected	string	(true or false)
	firstRateAmount	number	first rate amount
	interestRateAmount	number	interest rate amount
	interestEffectiveRate	number	interest effective rate
	interestEffectiveRateAmo	number	interest effective rate amount

	unt		
	seizableQuoteAmount	number	seizable quote amount
	term	number	Number of months
	calculationMode	string	Calculation mode (STANDARD_MODE or REFINANCE_MODE)
	household	container	Container for household
	applicant	container	Container for applicant
	exemptAmountList	list	Container for list of amounts
	amount	number	Amount in CHF
	exemptAmountType	string	Type (AFTER_TAX_AT_SOURCE, AFTER_CURRENT_LIABILITIES or AFTER_APPLICATION_DATA)
	isCorrected	string	(true or false)
	expenditures	container	Container for expenditure information
	alimony	number	Alimony in CHF
	educationCost	number	Educational costs in CHF
	externalFoodBoardingDeduction	number	Food deductions in CHF
	increasedClothingRequirementDeduction	number	Clothing deductions in CHF
	increasedFoodIntakeDeduction	number	Additional food deductions in CHF
	individualExpensesList	list	Container of individual expenses
	amount	number	Amount in CHF
	label	string	Label of specific labelled amount
	professionalOrganizationFee	number	Membership fee in CHF
	socialCharges	number	Social charges in CHF
	taxAtSource	number	Amount taxed at source
	taxAtSourceMainIncomeTarif	container	Amount taxed on main income
	isChurchTaxObligatory	string	(true or false)
	numberOfChildren	number	Number of children in household
	tarifCode	string	Tarif code
	tarifType	string	Tarif type (A:single, B:married with one person working ,C:married with both persons working, D:additional income, H:Single parent with person to be supported)
	transportationCost	number	Transportation costs in CHF
	grossIncome	container	Container for income information
	extra	number	Extra gross income in CHF
	main	number	Main gross income in CHF
	liabilities	container	Container of liabilities
	openCreditAmount	number	Amount in CHF of open credit amount
	openLeasingRateAmount	number	Amount in CHF of leasing rate amount
	personBasicData	container	Container of person data

	address	container	Container of address data
	canton	string	Canton
	zip	string	Swisszipcode
	ageAtEndOfYear	number	Age at the end of the year
	birthDate	string	Birthdate
	civilStatusType	string	Civil status (SINGLE, MARRIED, DIVORCED, JURIDICAL_SEPARATED, WIDOWED, JURIDICAL_REGISTERED or JURIDICAL_RESOLVED)
	childrenList	list	Container with list of children
	ageAtEndOfYear	number	Age at the end of the year
	subsistenceMinimum	number	Minimal subsistence in CHF
	healthInsuranceFee	number	Health insurance fees in CHF
	healthInsuranceFeeReference	number	Reference value of health insurance fee in CHF
	partner	container	Container for applicant
	exemptAmountList	list	Container for list of amounts
	amount	number	Amount in CHF
	exemptAmountType	string	Type (AFTER_TAX_AT_SOURCE, AFTER_CURRENT_LIABILITIES or AFTER_APPLICATION_DATA)
	isCorrected	string	(true or false)
	expenditures	container	Container for expenditure information
	alimony	number	Alimony in CHF
	educationCost	number	Educational costs in CHF
	externalFoodBoardingDeduction	number	Food deductions in CHF
	increasedClothingRequirementDeduction	number	Clothing deductions in CHF
	increasedFoodIntakeDeduction	number	Additional food deductions in CHF
	individualExpensesList	list	Container of individual expenses
	amount	number	Amount in CHF
	label	string	Label of specific labelled amount
	professionalOrganizationFee	number	Membership fee in CHF
	socialCharges	number	Social charges in CHF
	taxAtSource	number	Amount taxed at source
	taxAtSourceMainIncomeTarif	container	Amount taxed on main income
	isChurchTaxObligatory	string	(true or false)
	numberOfChildren	number	Number of children in household
	tarifCode	string	Tarif code
	tarifType	string	Tarif type (A:single, B:married with one person working ,C:married with both persons working, D:additional income, H:Single parent with person to be supported)

	transportationCost	number	Transportation costs in CHF
	grossIncome	container	Container for income information
	extra	number	Extra gross income in CHF
	main	number	Main gross income in CHF
	liabilities	container	Container of liabilities
	openCreditAmount	number	Amount in CHF of open credit amount
	openLeasingRateAmount	number	Amount in CHF of leasing rate amount
	personBasicData	container	Container of person data
	address	container	Container of address data
	canton	string	Canton
	zip	string	Swisszipcode
	ageAtEndOfYear	number	Age at the end of the year
	birthDate	string	Birthdate
	civilStatusType	string	Civil status (SINGLE, MARRIED, DIVORCED, JURIDICAL_SEPARATED, WIDOWED, JURIDICAL_REGISTERED or JURIDICAL_RESOLVED)
	subsistenceMinimum	number	Minimal subsistence in CHF
	clientReference	string	Client reference string
	requestIdentifier	string	Kremo request Identifier
	warningList	list	List of warnings
	area	string	Area of application to warning
	description	string	Description
	type	string	Type

2.6. ZEK

2.6.1. Search

This service can be used to seach for individuals registerd in ZEK. The request must contain the attributes firstName, lastName, targetOrganisation and requestReason. Additionally the birthdate or the address must be defined.

Endpoint	restServices/v.0.0/zek/person/search?		
Method	GET		
Request Parameter	**Name**	**Type**	**Description**
	requestId	string	Request ID (the one sent in the request)
	firstName	string	First name
	lastName	string	Last name
	birthdate	string	Birth date (e.g. 1980-01-01)
	gender	string	Gender (M: Male, F:Female, U:Unknown)
	nationality	string	Nationality
	street	string	Street
	houseNumber	string	House number
	town	string	Town
	zipCode	string	Postal code
	countryCode	string	Country code

	targetOrganisation	string	Target Organisation (see 4.5.1)
	requestReason	string	Request Reason (4.5.2)
Example Request	https://test-credit-information-ws.ch/restServices/v.0.0/zek/person/search?requestId=asdasdsa&lastName=Meier&firstName=James&street=haggenstrasse&houseNumber=6&town=Nesslau&zipCode=9650&countryCode=CH&targetOrganisation=BOTH&requestReason=NEW_BUSINESS		
Response Attributes	**Name**	**Type**	**Description**
	matchingResults	list	List for all matched individuals
	birthdate	string	Birth date (e.g. 1980-01-01)
	clientId	integer	Client ID
	firstName	string	First Name
	fullAddress	string	Full address
	gender	string	Gender (M: Male, F:Female, U:Unknown)
	hitScore	number	Grade of match
	lastName	string	Last Name
	nationality	string	Nationality (as country code ISO)
	personStatus	string	Person status (see 4.5.13)
	requestId	string	Request ID
	responseId	integer	Unique Response ID

2.6.2. Info

This service can be used to obtain detailed information about a person by providing clientId, targetOrganisation and requestReason. RequestId ist optional.

Endpoint	restServices/v.0.0/zek/person/info?		
Method	GET		
Request Parameter	**Name**	**Type**	**Description**
	requestId	string	Request ID (the one sent in the request)
	clientId	integer	Client Id
	targetOrganisation	string	Target Organisation (see 4.5.1)
	requestReason	string	Request Reason (see 4.5.2)
Example Request	https://test-credit-information-ws.ch/restServices/v.0.0/zek/person/info?requestId=asdasdsa&clientId=211091190088&targetOrganisation=BOTH&requestReason=NEW_BUSINESS		
Response Attributes	**Name**	**Type**	**Description**
	addressData	container	Address data related information
	formerAddresses	list	Former address related information
	aadsCode	integer	Address status code
	aadsDate	string	Address status date (e.g. 1980-01-01)
	addressId	string	Unique address identification number
	countryCode	string	Country Code
	houseNumber	string	House number
	street	string	Street
	town	string	Town
	zipCode	string	Postal code

	newestAddress	container	Newest address related information
	aadsCode	integer	Address status code
	aadsDate	string	Address status date (e.g. 1980-01-01)
	addressId	string	Unique address identification number
	countryCode	string	Country Code
	houseNumber	string	House number
	street	string	Street
	town	string	Town
	zipCode	string	Postal Code
	bankOverdraftData	list	Bank overdraft data
	dateSaldoDueDate	string	Date of due date (e.g. 1980-01-01)
	elementId	integer	Unique element ID
	referenceDate	string	Reference date (e.g. 1980-01-01)
	saldoBankStatement	number	Reported balance
	targetOrganisation	string	Target Organisation (see 4.5.1)
	cardCommitmentData	list	Card commitment data
	dateSaldoDueDate	string	Date of due date (e.g. 1980-01-01)
	elementId	integer	Unique element ID
	referenceDate	string	Reference date (e.g. 1980-01-01)
	saldoAccountingDay	number	Reported balance
	targetOrganisation	string	Target Organisation (see 4.5.1)
	cardMessageData	list	Card message data
	annulmentDate	string	Annulment date (e.g. 1980-01-01)
	cardEventCode	string	Card event code (see 4.5.3)
	cardMessageDate	string	Card message date (e.g. 1980-01-01)
	cardTypeCode	string	Card type Code (see 4.5.4)
	elementId	integer	Unique element ID
	negativeEventDate	string	Negative event date (e.g. 1980-01-01)
	cashLoanData	list	Cash loan data
	contractStatus	string	Contract status (see 4.5.10)
	creditAmount	number	Credit Amount
	creditRatingCode	string	Credit Rating of client at this contract (see 4.5.11)
	creditRatingDate	string	Credit rating date (e.g. 1980-01-01)
	elementId	integer	Unique element ID
	firstPaymentDate	string	First payment date (e.g. 1980-01-01)
	lastPaymentDate	string	Last payment date (e.g. 1980-01-01)
	monthlyPayments	number	Amount of monthly payments
	numberOfMonthlyPayments	integer	Number of monthly payments
	safeguarding	string	Specification for safeguarding the credit (see 4.5.12)
	targetOrganisation	string	Target Organisation (see 4.5.1)
	creditData	container	Credit data related information (see 4.5.14)
	scoreDate	string	Score date (e.g. 1980-01-01)

	zekAlpha	string	Alphanumeric ZEK score
	zekNum	integer	Numeric ZEK score
	creditApplicationData	list	Credit request data
	creditApplicationDate	string	Credit request date (e.g. 1980-01-01)
	creditApplicationStatus	string	Credit request status (see 4.5.7)
	deletionReason	string	Deletion reason (see 4.5.9)
	elementId	integer	Unique element ID
	rejectionDate	string	Rejection date of credit request (e.g. 1980-01-01)
	rejectionReason	string	Rejection reason of credit request (see 4.5.8)
	requestReason	string	Request reason (see 4.5.2)
	targetOrganisation	string	Target Organisation (see 4.5.1)
	validToDate	string	Validity period of credit request (e.g. 1980-01-01)
	fixedCreditData	list	Fixed credit data
	contractEndDate	string	Contract end date (e.g. 1980-01-01)
	contractStartDate	string	Contract start date (e.g. 1980-01-01)
	contractStatus	string	Contract status (see 4.5.10)
	creditAmount	number	Credit Amount
	creditRatingCode	string	Credit Rating of client at this contract (see 4.5.11)
	creditRatingDate	string	Credit rating date (e.g. 1980-01-01)
	elementId	integer	Unique element ID
	safeguarding	string	Specification for safeguarding the credit (see 4.5.12)
	targetOrganisation	string	Target Organisation (see 4.5.1)
	generalData	container	General data related information
	birthdate	string	Birth date (e.g. 1980-01-01)
	clientId	integer	Client ID
	firstName	string	First Name
	gender	string	Gender (M: Male, F:Female, U:Unknown)
	lastName	string	Last Name
	nationality	string	Nationality (as country code ISO)
	personStatus	string	Person status (see 4.5.13)
	requestId	string	Request ID (the one sent in the request)
	responseId	integer	Unique Response ID
	instalmentCreditData	list	Instalment credit
	contractStatus	string	Contract status (see 4.5.10)
	creditAmount	number	Credit Amount
	creditRatingCode	string	Credit Rating of client at this contract (see 4.5.11)
	creditRatingDate	string	Credit rating date (e.g. 1980-01-01)
	elementId	integer	Unique element ID
	firstPaymentDate	string	First payment date (e.g. 1980-01-01)
	lastPaymentDate	string	Last payment date (e.g. 1980-01-01)
	monthlyPayments	number	Amount of monthly payments
	numberOfMonthlyPay	integer	Number of monthly payments

	ments		
	safeguarding	string	Specification for safeguarding the credit (see 4.5.12)
	targetOrganisation	string	Target Organisation (see 4.5.1)
	jointSeveralDebtorContractData	list	Joint several debtor contract
	contractStatus	string	Contract status (see 4.5.10)
	creditAmount	number	Credit Amount
	creditRatingCode	string	Credit Rating of client at this contract (see 4.5.11)
	creditRatingDate	string	Credit rating date (e.g. 1980-01-01)
	elementId	integer	Unique element ID
	firstPaymentDate	string	First payment date (e.g. 1980-01-01)
	lastPaymentDate	string	Last payment date (e.g. 1980-01-01)
	monthlyPayments	number	Amount of monthly payments
	numberOfMonthlyPayments	integer	Number of monthly payments
	safeguarding	string	Specification for safeguarding the credit (see 4.5.12)
	targetOrganisation	string	Target Organisation (see 4.5.1)
	officeInformationData	list	Office information data
	elementId	integer	Unique element ID
	officeInformationCode	string	Office information code (see 4.5.5)
	canton	string	Canton of office information (see 4.5.6)
	sourceDate	string	Publishing date of office information (e.g. 1980-01-01)
	submissionDate	string	Date until actions have to be made (e.g. 1980-01-01)
	zipCode	string	Zip Code of publishing office
	overdraftCreditData	list	Overdraft credit
	contractEndDate	string	Contract end date (e.g. 1980-01-01)
	contractStartDate	string	Contract start date (e.g. 1980-01-01)
	contractStatus	string	Contract status (see 4.5.10)
	creditLimit	number	Credit limit
	creditRatingCode	string	Credit Rating of client at this contract (see 4.5.11)
	creditRatingDate	string	Credit rating date (e.g. 1980-01-01)
	elementId	integer	Unique element ID
	safeguarding	string	Specification for safeguarding the credit (see 4.5.12)
	targetOrganisation	string	Target Organisation (see 4.5.1)
	usedCreditPercent	integer	Percentage of used credit limit
	rentLeasingData	list	Rent leasing data
	contractStatus	string	Contract status (see 4.5.10)
	creditAmount	number	Credit Amount incl. interest and VAT
	creditRatingCode	string	Credit Rating of client at this contract (see 4.5.11)

	creditRatingDate	string	Credit rating date (e.g. 1980-01-01)
	elementId	integer	Unique element ID
	firstBigPayment	number	Amount of first payment incl. VAT
	firstPaymentDate	string	First payment date (e.g. 1980-01-01)
	lastPaymentDate	string	Last payment date (e.g. 1980-01-01)
	monthlyPayments	number	Amount of monthly payments incl. VAT
	numberOfMonthlyPayments	integer	Number of monthly payments
	residualValue	number	Amount of residual payments incl. VAT
	safeguarding	string	Specification for safeguarding the credit (see 4.5.12)
	targetOrganisation	string	Target Organisation (see 4.5.1)

2.6.3. Workflow

This service can be used to register a new credit application without the prior knowledge of the clientId. Typically, within the workflow, two calls are made to the target-organisation. The first call checks if the client is already known to target-organisation. If the client is known, the second call uses with previous call's clientId to register the new credit application. Otherwise the second call registers the new client and the new credit application. The workflowName describes the configuration, when more than one client is returned from the first call. If workflowName = MULTIPLE_HITS_ALLOWED then, regardless of the number of clients returned, the new credit application is registered to the one with the biggest hitScore. If workflowName = MULTIPLE_HITS_NOT_ALLOWED then no credit application is registered, in case of multiple client returns.

Endpoint	restServices/v.0.0/zek/person/workflow?		
Method	GET		
Request Parameter	**Name**	**Type**	**Description**
	requestId	string	Request ID (the one sent in the request)
	firstName	string	First name
	lastName	string	Last name
	birthdate	string	Birth date (e.g. 1980-01-01)
	gender	string	Gender (M: Male, F:Female, U:Unknown)
	nationality	string	Nationality
	street	string	Street
	houseNumber	string	House number
	town	string	Town
	zipCode	string	Postal code
	countryCode	string	Country code
	workflowName	string	Workflow Name (see 4.5.15)
	aadsDate	string	Address status date
	targetOrganisation	string	Target Organisation (see 4.5.1)
	requestReason	string	Request Reason (4.5.2)
Example Request	https://test-credit-information-ws.ch/restServices/v.0.0/zek/person/workflow?requestId=asdasdsa&lastName=Bourne&firstName=Jason&birthdate=1974-08-20&gender=M&nationality=CH&street=Bains, rue des&houseNumber=43&town=Genève&zipCode=1205&countryCode=CH&aadsDate=20		

	20-10-01&workflowName=MULTIPLE_HITS_NOT_ALLOWED&targetOrganisation=BOTH&requestReason=NEW_BUSINESSS		
Response Attributes	**Name**	**Type**	**Description**
	addressData	container	Address data related information
	formerAddresses	list	Former address related information
	aadsCode	integer	Address status code
	aadsDate	string	Address status date (e.g. 1980-01-01)
	addressId	string	Unique address identification number
	countryCode	string	Country Code
	houseNumber	string	House number
	street	string	Street
	town	string	Town
	zipCode	string	Postal code
	newestAddress	container	Newest address related information
	aadsCode	integer	Address status code
	aadsDate	string	Address status date (e.g. 1980-01-01)
	addressId	string	Unique address identification number
	countryCode	string	Country Code
	houseNumber	string	House number
	street	string	Street
	town	string	Town
	zipCode	string	Postal Code
	bankOverdraftData	list	Bank overdraft data
	dateSaldoDueDate	string	Date of due date (e.g. 1980-01-01)
	elementId	integer	Unique element ID
	referenceDate	string	Reference date (e.g. 1980-01-01)
	saldoBankStatement	number	Reported balance
	targetOrganisation	string	Target Organisation (see 4.5.1)
	cardCommitmentData	list	Card commitment data
	dateSaldoDueDate	string	Date of due date (e.g. 1980-01-01)
	elementId	integer	Unique element ID
	referenceDate	string	Reference date (e.g. 1980-01-01)
	saldoAccountingDay	number	Reported balance
	targetOrganisation	string	Target Organisation (see 4.5.1)
	cardMessageData	list	Card message data
	annulmentDate	string	Annulment date (e.g. 1980-01-01)
	cardEventCode	string	Card event code (see 4.5.3)
	cardMessageDate	string	Card message date (e.g. 1980-01-01)
	cardTypeCode	string	Card type Code (see 4.5.4)
	elementId	integer	Unique element ID
	negativeEventDate	string	Negative event date (e.g. 1980-01-01)
	cashLoanData	list	Cash loan data
	contractStatus	string	Contract status (see 4.5.10)
	creditAmount	number	Credit Amount

	creditRatingCode	string	Credit Rating of client at this contract (see 4.5.11)
	creditRatingDate	string	Credit rating date (e.g. 1980-01-01)
	elementId	integer	Unique element ID
	firstPaymentDate	string	First payment date (e.g. 1980-01-01)
	lastPaymentDate	string	Last payment date (e.g. 1980-01-01)
	monthlyPayments	number	Amount of monthly payments
	numberOfMonthlyPayments	integer	Number of monthly payments
	safeguarding	string	Specification for safeguarding the credit (see 4.5.12)
	targetOrganisation	string	Target Organisation (see 4.5.1)
	creditData	container	Credit data related information (see 4.5.14)
	scoreDate	string	Score date (e.g. 1980-01-01)
	zekAlpha	string	Alphanumeric ZEK score
	zekNum	integer	Numeric ZEK score
	creditApplicationData	list	Credit request data
	creditApplicationDate	string	Credit request date (e.g. 1980-01-01)
	creditApplicationStatus	string	Credit request status (see 4.5.7)
	deletionReason	string	Deletion reason (see 4.5.9)
	elementId	integer	Unique element ID
	rejectionDate	string	Rejection date of credit request (e.g. 1980-01-01)
	rejectionReason	string	Rejection reason of credit request (see 4.5.8)
	requestReason	string	Request reason (see 4.5.2)
	targetOrganisation	string	Target Organisation (see 4.5.1)
	validToDate	string	Validity period of credit request (e.g. 1980-01-01)
	fixedCreditData	list	Fixed credit data
	contractEndDate	string	Contract end date (e.g. 1980-01-01)
	contractStartDate	string	Contract start date (e.g. 1980-01-01)
	contractStatus	string	Contract status (see 4.5.10)
	creditAmount	number	Credit Amount
	creditRatingCode	string	Credit Rating of client at this contract (see 4.5.11)
	creditRatingDate	string	Credit rating date (e.g. 1980-01-01)
	elementId	integer	Unique element ID
	safeguarding	string	Specification for safeguarding the credit (see 4.5.12)
	targetOrganisation	string	Target Organisation (see 4.5.1)
	generalData	container	General data related information
	birthdate	string	Birth date (e.g. 1980-01-01)
	clientId	integer	Client ID
	firstName	string	First Name
	gender	string	Gender (M: Male, F:Female, U:Unknown)
	lastName	string	Last Name
	nationality	string	Nationality (as country code ISO)
	newCreditApplication	integer	Unique credit application identification number

	Id		of new credit application
	personStatus	string	Person status (see 4.5.13)
	requestId	string	Request ID (the one sent in the request)
	responseId	integer	Unique Response ID
	instalmentCreditData	list	Instalment credit
	contractStatus	string	Contract status (see 4.5.10)
	creditAmount	number	Credit Amount
	creditRatingCode	string	Credit Rating of client at this contract (see 4.5.11)
	creditRatingDate	string	Credit rating date (e.g. 1980-01-01)
	elementId	integer	Unique element ID
	firstPaymentDate	string	First payment date (e.g. 1980-01-01)
	lastPaymentDate	string	Last payment date (e.g. 1980-01-01)
	monthlyPayments	number	Amount of monthly payments
	numberOfMonthlyPayments	integer	Number of monthly payments
	safeguarding	string	Specification for safeguarding the credit (see 4.5.12)
	targetOrganisation	string	Target Organisation (see 4.5.1)
	jointSeveralDebtorContractData	list	Joint several debtor contract
	contractStatus	string	Contract status (see 4.5.10)
	creditAmount	number	Credit Amount
	creditRatingCode	string	Credit Rating of client at this contract (see 4.5.11)
	creditRatingDate	string	Credit rating date (e.g. 1980-01-01)
	elementId	integer	Unique element ID
	firstPaymentDate	string	First payment date (e.g. 1980-01-01)
	lastPaymentDate	string	Last payment date (e.g. 1980-01-01)
	monthlyPayments	number	Amount of monthly payments
	numberOfMonthlyPayments	integer	Number of monthly payments
	safeguarding	string	Specification for safeguarding the credit (see 4.5.12)
	targetOrganisation	string	Target Organisation (see 4.5.1)
	matchingResults	list	List for all matched individuals
	birthdate	string	Birth date (e.g. 1980-01-01)
	clientId	integer	Client ID
	firstName	string	First Name
	fullAddress	string	Full address
	gender	string	Gender (M: Male, F:Female, U:Unknown)
	hitScore	number	Grade of match
	lastName	string	Last Name
	nationality	string	Nationality (as country code ISO)
	personStatus	string	Person status (see 4.5.13)
	officeInformationData	list	Office information data
	elementId	integer	Unique element ID
	officeInformationCod	string	Office information code (see 4.5.5)

	e		
	canton	string	Canton of office information (see 4.5.6)
	sourceDate	string	Publishing date of office information (e.g. 1980-01-01)
	submissionDate	string	Date until actions have to be made (e.g. 1980-01-01)
	zipCode	string	Zip Code of publishing office
	overdraftCreditData	list	Overdraft credit
	contractEndDate	string	Contract end date (e.g. 1980-01-01)
	contractStartDate	string	Contract start date (e.g. 1980-01-01)
	contractStatus	string	Contract status (see 4.5.10)
	creditLimit	number	Credit limit
	creditRatingCode	string	Credit Rating of client at this contract (see 4.5.11)
	creditRatingDate	string	Credit rating date (e.g. 1980-01-01)
	elementId	integer	Unique element ID
	safeguarding	string	Specification for safeguarding the credit (see 4.5.12)
	targetOrganisation	string	Target Organisation (see 4.5.1)
	usedCreditPercent	integer	Percentage of used credit limit
	rentLeasingData	list	Rent leasing data
	contractStatus	string	Contract status (see 4.5.10)
	creditAmount	number	Credit Amount incl. interest and VAT
	creditRatingCode	string	Credit Rating of client at this contract (see 4.5.11)
	creditRatingDate	string	Credit rating date (e.g. 1980-01-01)
	elementId	integer	Unique element ID
	firstBigPayment	number	Amount of first payment incl. VAT
	firstPaymentDate	string	First payment date (e.g. 1980-01-01)
	lastPaymentDate	string	Last payment date (e.g. 1980-01-01)
	monthlyPayments	number	Amount of monthly payments incl. VAT
	numberOfMonthlyPayments	integer	Number of monthly payments
	residualValue	number	Amount of residual payments incl. VAT
	safeguarding	string	Specification for safeguarding the credit (see 4.5.12)
	targetOrganisation	string	Target Organisation (see 4.5.1)

2.6.4. RejectCreditApplication

This service can be used to reject a registered creditApplication in ZEK. The request body must contain the attributes clientId, elementId, and rejectionReason. Additionally the requestId can be given.

Endpoint	restServices/v.0.0/zek/person/rejectCreditApplication		
Method	PUT		
Request Parameter	**Name**	**Type**	**Description**
	clientId	string	Client Id
	elementId	string	Element Id
	rejectionReason	string	Rejection reason of credit request (see 4.5.8)
	requestId	string	Request ID (the one sent in the request)

Example Request	https://test-credit-information-ws.ch/restServices/v.0.0/zek/person/rejectCreditApplication		
Example Request DATA	{"clientId": 211091190108, "elementId": 230511010948, "rejectionReason": "PARTIAL_OR_TOTAL_LOSS", "requestId": "asdasdsa"}		
Response Attributes	**Name**	**Type**	**Description**
	addressData	container	Address data related information
	formerAddresses	list	Former address related information
	aadsCode	integer	Address status code
	aadsDate	string	Address status date (e.g. 1980-01-01)
	addressId	string	Unique address identification number
	countryCode	string	Country Code
	houseNumber	string	House number
	street	string	Street
	town	string	Town
	zipCode	string	Postal code
	newestAddress	container	Newest address related information
	aadsCode	integer	Address status code
	aadsDate	string	Address status date (e.g. 1980-01-01)
	addressId	string	Unique address identification number
	countryCode	string	Country Code
	houseNumber	string	House number
	street	string	Street
	town	string	Town
	zipCode	string	Postal Code
	creditApplicationData	list	Credit request data
	creditApplicationDate	string	Credit request date (e.g. 1980-01-01)
	creditApplicationStatus	string	Credit request status (see 4.5.7)
	deletionReason	string	Deletion reason (see 4.5.9)
	elementId	integer	Unique element ID
	rejectionDate	string	Rejection date of credit request (e.g. 1980-01-01)
	rejectionReason	string	Rejection reason of credit request (see 4.5.8)
	requestReason	string	Request reason (see 4.5.2)
	targetOrganisation	string	Target Organisation (see 4.5.1)
	validToDate	string	Validity period of credit request (e.g. 1980-01-01)
	generalData	container	General data related information
	birthdate	string	Birth date (e.g. 1980-01-01)
	clientId	integer	Client ID
	firstName	string	First Name
	gender	string	Gender (M: Male, F:Female, U:Unknown)
	lastName	string	Last Name
	nationality	string	Nationality (as country code ISO)

	personStatus	string	Person status (see 4.5.13)
	requestId	string	Request ID (the one sent in the request)
	responseId	integer	Unique Response ID

intrum

3. XML Services

3.1. Workflow

This service accepts POST requests holding the XML as a string in the REQUEST field.

Endpoint	xmlServices/v.0.0/xml/workflow		
Method	POST		
Request Parameter	**Name**	**Type**	**Description**
	REQUEST	string	whole XML
Request XSD	https://test-credit-information-ws.ch/xmlServices/v.0.0/schemas/workflow/request.xsd		
Example Request	https://test-credit-information-ws.ch/xmlServices/v.0.0/xml/workflow		
Example Request Body (Person)	<?xml version="1.0" encoding="UTF-8"?> <Request ClientId="123456" Password="XXX" UserID="example_test" Version="1.0" RequestId="111zzz"> <Customer Reference="123abc"> <Person> <LastName>Bösch</LastName> <FirstName>Caspar</FirstName> <CurrentAddress> <FirstLine>Bachstrasse</FirstLine> <HouseNumber>9</HouseNumber> <CountryCode>CH</CountryCode> <PostCode>9100</PostCode> <Town>Herisau</Town> </CurrentAddress> <ExtraInfo> <Name>ORDERCLOSED</Name> <Value>NO</Value> </ExtraInfo> <ExtraInfo> <Name>ORDERAMOUNT</Name> <Value>100</Value> </ExtraInfo> <ExtraInfo> <Name>ORDERCURRENCY</Name> <Value>CHF</Value> </ExtraInfo> </Person> </Customer> </Request>		
Example Request Body (Company)	<?xml version="1.0" encoding="UTF-8"?> <Request ClientId="123456" Password="XXX" UserID="example_test" Version="1.0" RequestId="111zzz"> <Customer Reference="123abc"> <Company> <CompanyName1>Holding Galleria</CompanyName1>		

	<CurrentAddress> <FirstLine>Bahnhofplatz</FirstLine> <HouseNumber>1</HouseNumber> <CountryCode>CH</CountryCode> <PostCode>8001</PostCode> <Town>Zürich</Town> </CurrentAddress> <ExtraInfo> <Name>ORDERCLOSED</Name> <Value>NO</Value> </ExtraInfo> <ExtraInfo> <Name>ORDERAMOUNT</Name> <Value>100</Value> </ExtraInfo> <ExtraInfo> <Name>ORDERCURRENCY</Name> <Value>CHF</Value> </ExtraInfo> </Company> </Customer> </Request>
Response XSD	https://test-credit-information-ws.ch/xmlServices/v.0.0/schemas/workflow/response.xsd

3.2. OrderRegistration

This service accepts POST requests holding the XML as a string in the REQUEST field.

Endpoint	xmlServices/v.0.0/xml/workflow		
Method	POST		
Request Parameter	**Name**	**Type**	**Description**
	REQUEST	string	whole XML
Request XSD	https://test-credit-information-ws.ch/xmlServices/v.0.0/schemas/workflow/request.xsd		
Example Request	https://test-credit-information-ws.ch/xmlServices/v.0.0/xml/workflow		
Example Request Body (Person)	<?xml version="1.0" encoding="UTF-8"?> <Request ClientId="123456" Password="XXX" UserID="example_test" Version="1.0" RequestId="111zzz"> <Customer Reference="123abc"> <Person> <LastName>Bösch</LastName> <FirstName>Caspar</FirstName> <CurrentAddress> <FirstLine>Bachstrasse</FirstLine> <HouseNumber>9</HouseNumber> <CountryCode>CH</CountryCode> <PostCode>9100</PostCode> <Town>Herisau</Town> </CurrentAddress>		

<table>
<tr><td></td><td>
<ExtraInfo>
<Name>TRANSACTIONNUMBER</Name>
<Value>305057454</Value>
</ExtraInfo>
<ExtraInfo>
<Name>ORDERCLOSED</Name>
<Value>YES</Value>
</ExtraInfo>
<ExtraInfo>
<Name>ORDERAMOUNT</Name>
<Value>79.07</Value>
</ExtraInfo>
<ExtraInfo>
<Name>ORDERCURRENCY</Name>
<Value>CHF</Value>
</ExtraInfo>
<ExtraInfo>
<Name>IP</Name>
<Value>213.55.220.25</Value>
</ExtraInfo>
<ExtraInfo>
<Name>DELIVERY_FIRSTLINE</Name>
<Value>Rue de Zurich 32</Value>
</ExtraInfo>
<ExtraInfo>
<Name>DELIVERY_HOUSENUMBER</Name>
<Value>32</Value>
</ExtraInfo>
<ExtraInfo>
<Name>DELIVERY_COUNTRYCODE</Name>
<Value>CH</Value>
</ExtraInfo>
<ExtraInfo>
<Name>DELIVERY_POSTCODE</Name>
<Value>1201</Value>
</ExtraInfo>
<ExtraInfo>
<Name>DELIVERY_TOWN</Name>
<Value>Genève</Value>
</ExtraInfo>
<ExtraInfo>
<Name>DELIVERY_FIRSTNAME</Name>
<Value>Myriam</Value>
</ExtraInfo>
<ExtraInfo>
<Name>DELIVERY_LASTNAME</Name>
<Value>Hagberg</Value>
</ExtraInfo>
<ExtraInfo>
<Name>ORDERID</Name>
</td></tr>
</table>

	<Value>811692390</Value> </ExtraInfo> <ExtraInfo> <Name>PAYMENTMETHOD</Name> <Value>INVOICE</Value> </ExtraInfo> </Person> </Customer> </Request>
Example Request Body (Company)	<?xml version="1.0" encoding="UTF-8"?> <Request ClientId="123456" Password="XXX" UserID="example_test" Version="1.0" RequestId="111zzz"> <Customer Reference="123abc"> <Company> <CompanyName1>Holding Galleria</CompanyName1> <CurrentAddress> <FirstLine>Bahnhofplatz</FirstLine> <HouseNumber>1</HouseNumber> <CountryCode>CH</CountryCode> <PostCode>8001</PostCode> <Town>Zürich</Town> </CurrentAddress> <ExtraInfo> <Name>ORDERCLOSED</Name> <Value>YES</Value> </ExtraInfo> <ExtraInfo> <Name>ORDERAMOUNT</Name> <Value>770.05</Value> </ExtraInfo> <ExtraInfo> <Name>ORDERCURRENCY</Name> <Value>CHF</Value> </ExtraInfo> <ExtraInfo> <Name>IP</Name> <Value>213.55.220.26</Value> </ExtraInfo> <ExtraInfo> <Name>DELIVERY_FIRSTLINE</Name> <Value>Manesastrasse 130</Value> </ExtraInfo> <ExtraInfo> <Name>DELIVERY_HOUSENUMBER</Name> <Value/> </ExtraInfo> <ExtraInfo> <Name>DELIVERY_COUNTRYCODE</Name> <Value>CH</Value> </ExtraInfo>

	<ExtraInfo> <Name>DELIVERY_POSTCODE</Name> <Value>8045</Value> </ExtraInfo> <ExtraInfo> <Name>DELIVERY_TOWN</Name> <Value>Zürich</Value> </ExtraInfo> <ExtraInfo> <Name>DELIVERY_COMPANYNAME</Name> <Value>Holding Galleria</Value> </ExtraInfo> <ExtraInfo> <Name>DELIVERY_FIRSTNAME</Name> <Value/> </ExtraInfo> <ExtraInfo> <Name>DELIVERY_LASTNAME</Name> <Value>Holding Galleria</Value> </ExtraInfo> <ExtraInfo> <Name>ORDERID</Name> <Value>90030028335</Value> </ExtraInfo> <ExtraInfo> <Name>PAYMENTMETHOD</Name> <Value>INVOICE</Value> </ExtraInfo> </Company> </Customer> </Request>
Response XSD	https://test-credit-information-ws.ch/xmlServices/v.0.0/schemas/workflow/response.xsd

intrum

4. Detailed Attribute Description

4.1. Address

4.1.1. hitScore

The hitScore varies from 80.0 to 100.0, where 100.0 represents a perfect match.

4.1.2. valid

Value	Description
1	this address is normalised
0	this address cannot be normalised

4.1.3. check

Value	Description
1	the person is registered at this address
0	the person is not registered at this address

4.2. Company

4.2.1. reportType

Which report type contains which attributes is defined client specific. Possible report types are "b2bCreditCheck" and "b2bCreditDetails". Please contact information.services@intrum.com for further information.

4.2.2. matchingProfile

Value	matching logic
1	if iid, uid, and refNr are not given → match with given attributes (organisationName, swissZipCode, etc.)

4.2.3. hitScoreCutoff

The minimum hitscore to be considered a hit. The default value is 85.0, which is applied if the hitScoreCutoff is missing in the request.

4.2.4. organisationIdCategory

The most common categories are listed below. For further information see eCH-0097.

Value	Description
CH.HR	Listed in CH commercial register
FL.HR	Listed in FL commercial register
WW.LEI	Listed in other country

4.2.5. bcs

BCS stands for Business Credit Score. The following numeric and alphanumeric scores are possible.

bcsNum	bcsAlpha	Description
6	A	Very good

5		
4	B	Good
3		
2		
1	C	Neutral
0		
-1		
-2	D	Bad
-3		
-4		
-5	E	Very bad
-6		
	X	Not known
	Z	Cancelled

4.2.6. abcs

ABCS stands for Advanced (AI) Business Credit Score. The following numeric and alphanumeric scores are possible.

abcsNum	abcsAlpha	Description
543 – 1000	A	Very good
457 – 542	B	Good
396 – 456	C	Neutral
363 – 395	D	Bad
0 – 362	E	Very Bad
	X	Not known
	Z	Cancelled

4.2.7. status

Value	Description
1	active
2	beingCancelled
3	cancelled

4.2.8. legalForm

Value	Description in German
101	Einzelunternehmen
103	Kollektivgesellschaft
104	Kommanditgesellschaft
105	Kommanditaktiengesellschaft
106	Aktiengesellschaft
107	Gesellschaft mit beschränkter Haftung GMBH / SARL
108	Genossenschaft
109	Verein (hier werden auch staatlich anerkannte Kirchen geführt)
110	Stiftung
111	Ausländische Niederlassung im Handelsregister eingetragen
113	Besondere Rechtsform

114	Kommanditgesellschaft für kollektive Kapitalanlagen
115	Investmentgesellschaft mit variablem Kapital (SICAV)
116	Investmentgesellschaft mit festem Kapital (SICAF)
117	Institut des öffentlichen Rechts
118	Nichtkaufmännische Prokuren
119	Haupt von Gemeinderschaften
151	Schweizerische Zweigniederlassung im Handelsregister eingetragen
220	Verwaltung des Bundes
221	Verwaltung des Kantons
222	Verwaltung des Bezirks
223	Verwaltung der Gemeinde
224	öffentlich-rechtliche Körperschaft (Verwaltung)
230	Unternehmen des Bundes
231	Unternehmen des Kantons
232	Unternehmen des Bezirks
233	Unternehmen der Gemeinde
234	öffentlich-rechtliche Körperschaft
302	Einfache Gesellschaft
312	Ausländische Niederlassung nicht im Handelsregister eingetragen
327	Ausländisches öffentliches Unternehmen
328	Ausländische öffentliche Verwaltung
329	Internationale Organisation
355	Übrige Genossenschaften
361	Trust
362	Fonds
441	Ausländische Unternehmen (Entreprise étrangère, impresa straniera)
0	unbekannt

4.2.9. eventCode

Value	Description
1000	Collection
1004	Claim not legally recognised
1008	Order for payment
1009	Continuation of the order for payment
1010	Debt collection Bankruptcy
1011	Certificate of loss
* a missing eventCode means that the case is closed	

4.2.10. closingCode

Value	Description in German
1001	Cases Paid in full
1002	Cases Partially Paid / Successful
1004	Requested Actions/Instructions have not been received
1005	Negative Information of debtor’s paying capabilities
1007	Bankruptcy
1009	Other
1012	Accord payment received

1013	Debtor deceased
1014	Debtor cannot be reached
1015	Debtor cannot be identified
1017	Debtor has moved abroad
1022	Statute-barred claim (limitation)
1023	Direct payment has been received
1024	No assets
1028	Company liquidated under duress
1029	Case transferred for legal action
1030	Closed during Reminder Service
1046	Closure - others
1053	No address
* a missing closingCode means that the case is still open	

4.2.11. industryCode

Value	Description
1000	Other
1001	Manufacturing & Construction
1002	Utilities
1003	Retail
1004	Transport
1005	Publishing
1006	TIME (Telecom, Internet, Media, Entertainment)
1007	Banking
1008	Other financial services
1009	Insurance
1010	Real Estate
1011	Public Administration
1012	Health & Education
1013	Unknown

4.2.12. nogaCode

The General Classification of Economic Activities (Nomenclature Générale des Activités économiques - NOGA) is the Swiss version of the European classification of economic activities NACE. For more information see https://www.kubb-tool.bfs.admin.ch/en.

4.2.13. industryCodeProbabilities

Value	Description
A	agriculture, forestry and fishing
B	mining and quarrying
C	manufacturing
D	electricity, gas, steam and air conditioning supply
E	water supply; sewerage, waste management and remediation activities
F	construction
G	wholesale and retail trade; repair of motor vehicles and motorcycles
H	transportation and storage
I	accommodation and food service activities
J	information and communication
K	financial and insurance activities
L	real estate activities

M	professional, scientific and technical activities
N	administrative and support service activities
O	public administration and defence; compulsory social security
P	education
Q	human health and social work activities
R	arts, entertainment and recreation
S	other service activities
T	activities of households as employers; undifferentiated goods- and services-producing activities of households for own use
U	activities of extraterritorial organisations and bodies

4.2.14. isBranch

Value	Description
false	This organisation is a headquarter
true	This organisation is a branch

4.2.15. hitScore

The hitScore varies from 80.0 to 100.0, where 100.0 represents a perfect match.

4.2.16. Signature

Value	Description
1	Einzelunterschrift
2	Kollektivunterschrift zu zweien
3	ohne Zeichnungsberechtigung
4	Kollektivprokura zu zweien
5	Prokura zu zweien
6	Einzelprokura
7	Einzelunterschrift als Liquidator
8	Kollektivunterschrift zu zweien als Liquidator
9	Anderes
10	Kollektivunterschrift zu dreien
11	Kollektivprokura zu dreien

4.2.17. workflowName

Depending on the selected workflow name, different attributes are responded. At the moment only one workflow is available. For some calculation steps (e.g. score cut-off) the parameters set by the client are used.

Value	Description
b2bECommerce	Returns various optional attributes (incl. responseCode & riskIndicator if requested)

4.2.18. hitType

Depending on the client specific setup, the following hit types are possible:

Value	Description
C	Organisation is found
CP	Organisation is found via external Swiss Post Service
X	Organisation is not found with the given request attributes

4.2.19. remainingLimit

This is the remaining limit after subtracting the orderAmount from the different limits. At the moment limits can be set for the following types:

- customerType (regular, new)
- hitType (see 4.2.18)
- bcsAlpha (see 4.2.5)

The lowest remaining limit of these is the final remainingLimit.

4.2.20. responseCode

Depending on the client specific setup, the following response codes are possible:

Value	Description
1	Business Credit Score (see 4.2.5) is below defined cutoff
2	Everything ok or organisation is on a Whitelist
3	Legal form is not accepted
4	Invalid address
5	Order amount is below defined cutoff
7	Remaining limit is negative (see 4.2.19)
9	Delivery address differs from billing address
10	Organisation is not found with given input attributes
11	Country not allowed
14	Fraud possibility
19	Organisation is on a Blacklist

4.2.21. riskIndicator

To be defined.

4.2.22. productCategory

ID of product category according to Google Taxonomy.

4.2.23. paymentMethod

The following payment methods are available:

Value	Description
checkmo	Check / Money
banktransfer	Bank Transfer
cashondelivery	Cash On Delivery
invoice	Invoice
epayment	E-Payment
creditcard	Cedit Card

4.3. Person

4.3.1. reportType

Which report type contains which attributes is defined client specific. Possible report types are "b2cCreditCheck" and "b2cCreditDetails". Please contact information.services@intrum.com for further information.

4.3.2. matchingProfile

When choosing a matching profile, the following notes should be considered:

- swissZipCode is always excluded from fuzziness logic if it is applied on the address
- the matching profiles are so called "downward compatible" - i.e. if a person is found with profile 0, they will also be found with profile 1, 2, 3 or 4
- if no birthdate is given from client side, matching profile 1 and 2 become equal and matching profile 3 and 4 become equal
- it is possible to search only by birth year (e.g. 1980) instead of the full birthdate for matching profile 4 (still use attribute birthdate for specifying the year)

Value	Matching Logic	Fuzzy
0	firstName & lastName & full address & birthdate (if given)	no fuzzy
1	firstName & lastName & birthdate or firstName & lastName & full address	full address
2	firstName & lastName & birthdate	firstName, lastName
3	firstName & lastName & full address (birthdate is missing)	firstName, lastName, full address
4	firstName & lastName & full address (birthdate is different) or firstName & lastName & birthdate (year)	firstName, lastName, full address

4.3.3. sortType

This is an optional input field where the requestor can choose between different sorting types. Only one hit is returned sorted by this attribute if multiple hits are found with the specified input attributes. If sortType is not given or another than one of the below is used, the hits are sorted by “score”.

Value	Description
score	The one with the lowest ccsNum (see 4.3.4) is returned. (default)
hitScore	The one that most closely matches the input fields (see 4.3.5) is returned.

4.3.4. ccs

CCS stands for Consumer Credit Score. The following numeric and alphanumeric scores are possible.

ccsNum	ccsAlpha	Description
6	A	Very good
5		
4	B	Good
3		
2		
1	C	Neutral
0		
-1		
-2	D	Bad
-3		
-4		
-5	E	Very bad
-6		
	M	Minor
	X	Not known
	Z	Deceased

4.3.5. accs

ACCS stands for Advanced (AI) Consumer Credit Score. The following numeric and alphanumeric scores are possible.

ccsNum	ccsAlpha	Description
725 – 1000	A	Very good
682 – 724	B	Good
578 – 681	C	Neutral
365 – 577	D	Bad
1 – 364	E	Very Bad
	M	Minor
	X	Not known
	Z	Deceased

4.3.6. cas

CAS stands for Consumer Address Score. The following numeric and alphanumeric scores are possible.

casNum	casAlpha	Description
6	A	Very good
5		
4	B	Good
3		
2		
1	C	Neutral
0		
-1		
-2	D	Bad
-3		
-4		
-5	E	Very bad
-6		

4.3.7. hitScore

The hitScore varies from 80.0 to 100.0, where 100.0 represents a perfect match.

4.3.8. status

Value	Description
0	Pursuit data is negative (person has at least one entry)
1	Pursuit data is positive (person does not have any entries)

4.3.9. rubric

Value	Description
KK	Bankruptcies
NA	Composition proceedings
SB	Debt enforcement

4.3.10. sub Rubric

Value	Description
KK01	Prior notification of launch of bankruptcy proceedings
KK02	Notification of bankruptcy proceedings/Call to creditors
KK03	Suspension of bankruptcy proceedings
KK04	Schedule of claims and inventory
KK05	Distribution plan and the final counting
KK06	Closing of bankruptcy proceedings
KK07	Revocation of bankruptcy proceedings
KK08	Property auction initiated by the bankruptcy office
KK09	Schedule of charges
KK10	Other public notice
KK11	Recognition of a foreign bankruptcy (Art. 166 et seq. IPLA)
KK12	Waiver of an IPLA bankruptcy proceeding (Art. 174a IPLA)
NA01	Provisional composition moratorium
NA02	Definitive composition moratorium
NA03	Call to creditors as part of composition proceedings/creditors meeting
NA04	Extension of the composition moratorium
NA05	Bankruptcy during composition proceedings
NA06	Approval hearing on the composition agreement
NA07	Approval of the composition agreement
NA08	Lifting of composition moratorium following restructuring
NA09	Schedule of claims in the composition proceedings, including assignment of assets
NA10	Report of activities/distribution plan and the final counting in the composition proceedings, including assignment of assets
NA11	Other public notice
SB01	Property auction initiated by the debt enforcement office
SB02	Payment order
SB03	Sequestration order and report
SB04	Seizure notice and report
SB05	Purging of the retention of title register
SB06	Other public notice

4.3.11. workflowName

Depending on the selected workflow name, different attributes are responded. The column wN in the response attributes table shows which attribute can be included in the response of which report type (1 = simpleCreditRecommendation, 2 = trafficLight, 3=b2cECommerce). For some calculation steps (e.g. score cut-off) the parameters set by the client are used.

Value	Description
simpleCreditRecommendation	Returns simple credit recommendation
trafficLight	Returns a credit recommendation and the newest address
b2cECommerce	Returns various optional attributes (incl. responseCode & riskIndicator if requested)

4.3.12. creditRecommendation

Value	Description

1	ccsNum of found person is higher or equal than cut-off
0	person is not found
-1	ccsNum of found person is lower than cut-off

For more details about ccsNum see 4.3.4.

4.3.13. hitType

Depending on the client specific setup, the following hit types are possible:

Value	Description
P	Person is found with the selected matchingProfile
H	Only matching household is found (lastName and address match but not first name)
PP	Person is found via external Swiss Post service
X	Person is not found with the selected matchingProfile

4.3.14. remainingLimit

This is the remaining limit after subtracting the orderAmount from the different limits. At the moment limits can be set for the following types:

- customerType (regular, new)
- hitType (see 4.3.13)
- ccsAlpha (see 4.3.4)

The lowest remaining limit of these is the final remainingLimit.

4.3.15. responseCode

Depending on the client specific setup, the following response codes are possible:

Value	Description
1	Consumer Credit Score (see 4.3.4) is below defined cutoff
2	Everything ok or person is on a Whitelist
4	Address is invalid
5	Order amount is below defined cutoff
7	Remaining limit is negative (see 4.3.14)
8	Persons age is not accepted
9	Delivery address differs from billing address
10	Person is not found with given input attributes
11	Country not accepted
12	Name of ordering person indicates a company
14	Fraud possibility
19	Person is on a Blacklist

4.3.16. riskIndicator

To be defined.

4.3.17. aadsCode

Value	Description
10	confirmed
20	unconfirmed
27	person deceased
28	address insufficient

29	delivery problem
30	undeliverable - address unknown
31	undeliverable -departed
32	undeliverable - redirection deadline expired

4.3.18. eventCode

Value	Description
1000	Collection
1004	Claim not legally recognised
1008	Order for payment
1009	Continuation of the order for payment
1010	Debt collection Bankruptcy
1011	Certificate of loss
* a missing eventCode means that the case is closed	

4.3.19. closingCode

Value	Description in German
1001	Cases Paid in full
1002	Cases Partially Paid / Successful
1004	Requested Actions/Instructions have not been received
1005	Negative Information of debtor’s paying capabilities
1007	Bankruptcy
1009	Other
1012	Accord payment received
1013	Debtor deceased
1014	Debtor cannot be reached
1015	Debtor cannot be identified
1017	Debtor has moved abroad
1022	Statute-barred claim (limitation)
1023	Direct payment has been received
1024	No assets
1028	Company liquidated under duress
1029	Case transferred for legal action
1030	Closed during Reminder Service
1046	Closure - others
1053	No address
* a missing closingCode means that the case is still open	

4.3.20. industryCode

Value	Description in German
1000	Other
1001	Manufacturing & Construction
1002	Utilities
1003	Retail
1004	Transport
1005	Publishing
1006	TIME (Telecom, Internet, Media, Entertainment)
1007	Banking
1008	Other financial services

1009	Insurance
1010	Real Estate
1011	Public Administration
1012	Health & Education
1013	Unknown

4.3.21. productCategory

ID of product category according to Google Taxonomy.

4.3.22. paymentMethod

The following payment methods are available:

Value	Description
checkmo	Check / Money
banktransfer	Bank Transfer
cashondelivery	Cash On Delivery
invoice	Invoice
epayment	E-Payment
creditcard	Cedit Card

4.4. Compliance

4.4.1. lists

Value	Description
PEP	Politically Exposed Person Desk
SL	Sanctions Lists
WLBL	Watchlists and Blacklists

4.4.2. accuracy

Value	Description
1	Liberal search
3	Standard search
5	Strict search

4.5. ZEK

4.5.1. TargetOrganisation

Value	Description
ZEK	TargetOrganisation is only ZEK
IKO	TargetOrganisation is only IKO
BOTH	TargetOrganisation is both ZEK and IKO

4.5.2. RequestReason

Value	Description
NEW_BUSINESS	New business
REEXAMINATION	Re-examination of an own customer:
CLARIFICATION	Clarification, for example: Verification of an executed message
SUSPECTED_FORGERY	Suspected forgery
COMPLAINTS	Complaints
CREDITWORTHINESS_OF_APPLICANT_INFLUENCED_BY_PERSON	Credithworthiness of applicant influenced by person
DEBT_COLLECTION	Debt collection
SUPPORT_ACTIVITIES	Support activites

4.5.3. CardEventCode

Value	Description
BLOCKED_BANK_CARD	Blocked bank card
BLOCKED_CARD	Blocked card (security measure based on various information)
ONGOING_DEBT_COLLECTION_MEASURES	Ongoing debt collection measures
PARTIAL_OR_TOTAL_LOSS	Partial or total loss (garnishment loss certificate, bankruptcy loss certificate)
DEBT_RESTRUCTURING	Debt restructuring
WHEREABOUTS_UNKNOWN	Whereabouts unknown
OTHER_REASONS	Other reasons
INFORMATION_IN_DOUBT	Information in doubt
CONTRACTOR_PROBLEM	Contractor problem

4.5.4. CardTypeCode

Value	Description
UNKNOWN	Unknow, CardTypeCode not specified
TE-CARD_CARD_PRIVILEGED	TE-Card privileged
TE-CARD_STANDARD	TE-Card standard
TE-CARD_BANK	TE-Card bank
CREDIT_CARD_WITH_CREDIT_OPTION	Credit card with credit option
CREDIT_CARD_BANK_ISSUER	Credit card bank issuer
SHOPPING_CARD	Shopping card
OTHER_CARDS	Other cards

4.5.5. OfficeInformationCode

Value	Description
BANKRUPTCY	Bankruptcy
PROBATE_PROCEEDINGS	Probate proceedings
PATERNALISM	Paternalism
ASSISTANCE	Assistance
DECLARATION_OF_MATURITY	Declaration of maturity

4.5.6. Canton

Value	Description
ZH	Zürich
BE	Bern
LU	Luzern
UR	Uri
SZ	Schwyz
OW	Obwalden
NW	Nidwalden
GL	Glarus
ZG	Zug
FR	Freiburg
SO	Solothurn
BS	Basel-Stadt
BL	Basel-Land
SH	Schaffhausen
AR	Appenzell Ausser-Rhoden
AI	Appenzell Inner-Rhoden
SG	St. Gallen
GR	Graubünden
AG	Aargau
TG	Thurgau
TI	Tessin
VD	Waadt
VS	Wallis
NE	Neuenburg
GE	Genf
JU	Jura
FL	Fürstentum Liechtenstein

4.5.7. CreditRequestStatus

Value	Description
OPEN	Open
REJECTED	Rejected
APPROVED	Approved
DELETED	Deleted

4.5.8. RejectionReason

Value	Description
NOT_REJECTED	Not rejected
SPECIAL_MEASURES	Special measures
PARTIAL_OR_TOTAL_LOSS	Partial or total loss
LEGAL_AMBIGUITIES	Legal ambiguities
DEBT_RATIO	Debt ratio
PATERNALISM	Paternalism

ACCURACY_OF_INFORMATION_IS_QUESTIONABLE	Accuracy of information is questionable
OTHER_PARTICULAR_NON-PERSON_REASONS	Other particular non-person reasons
CREDIT_REQUEST_TOO_HIGH	Credit request too high
REFUSAL_ON_LEGAL_GROUNDS	Refusal on legal grounds
OTHER_REASON_FOR_CREDITWORTHINESS-ABILITY	Other reason for creditworthiness-ability

4.5.9. DeletionReason

Value	Description
NO_DELETION	No deletion
MEMBER_REQUESTED_DELETION	Member requested deletion
CLIENT_REQUESTED_DELETION	Client requested deletion

4.5.10. ContractStatus

Value	Description
RUNNING	No deletion
CANCELLED	Member requested deletion

4.5.11. CreditRatingCode

Value	Description
NO_INFORMATION_POSITIVE_RATING	No information positive rating
BALANCE_WITH_NEW_LOAN_OFFSET	Balance with new loan offset
REGULAR_REPAYMENT	Regular repayment
SLUGGISH_REPAYMENT	Sluggish repayment
SPECIAL_MEASURES_OR_LATE_PAYMENT	Special measures or late payment
PARTIAL_OR_TOTAL_LOSS	Partial or total loss
LEGAL_AMBIGUITIES	Legal ambiguities
TERMINATION_OF_LEASING_CONTRACTS	Termination of leasing contracts
PAYMENT_AGREEMENT_FOR_CREDIT_CONTRACT	Payment agreement for credit contract
PAYMENT_AGREEMENT_FOR_LEASING_CONTRACT	Payment agreement for leasing contract
MESSAGE_DISCONTINUED	Message discontinued
IMMEDIATE_ARCHIVING_DELETED_BY_FUNCTION	Immediate archiving deleted by function
BY_ADMINISTRATOR_DELETED	By administrator deleted

4.5.12. Safeguarding

Value	Description
NO_INFORMATION	No information
WAGE_GARNISHMENT	Wage garnishment (valid until end of 1994 only)
LIFE_INSURANCE_POLICY	Life insurance policy
RESIDUAL_DEBT_INSURANCE	Residual debt insurances
GUARANTEE_AND_JOINT_AND_SE	Guarantee and joint and savings book

VERAL_LIABILITY	
SECURITIES_AND_SAVINGS_BOOK	Securities and savings book
TRADER_LIABILITY	Trader liability
RESERVATION_OF_OWNERSHIP	Reservation of ownership
MATERIAL_ASSETS_FAUST_PLEDGE _REAL_ESTATE_PLEDGE	Material assets, faus pledge, real estate pledge

4.5.13. PersonStatus

PersonStatus can also be empty if field is not given in ZEK Response.

Value	Description
NOT_BLOCKED	Not blocked
BLOCKED	Blocked

4.5.14. ZekScore

The following numeric (zekNum) and alphanumeric (zekAlpha) values for scores are possible.

zekNum	zekAlpha	Description
6	A	Positive payment method
5		No refusals
4	B	Neutral payment method
3		Neutral rejection history
2		unidentified
1	C	Neutral card messages
0		Sluggish payment
-1		Completed special measures
-2	D	Negative rejection history
-3		Running special measures
-4		Person-related reasons
-5	E	Report of loss
-6		Office information

4.5.15. WorkflowName

Value	Description
MULTIPLE_HITS_ALLOWED	Multiple hits in search are allowed and workflow proceeds sucessfully
MULTIPLE_HITS_NOT_ALLOWED	Multiple hits in search are not allowed. Worflow returns an error