

# Содержание

1	centroids	1
1.1	centroid_decomposition.cpp	1
2	fft	1
2.1	fft_advanced_integer.h	1
2.2	fft_double.h	3
2.3	fft_integer.h	3
2.4	fft_mod_10_9_7.h	4
3	flows	4
3.1	dinic.h	4
3.2	hungarian.cpp	5
3.3	min_cost_bellman_queue.h	5
3.4	min_cost_dijkstra.h	6
3.5	min_cost_ford_bellman.h	7
3.6	min_cost_negative_cycles.h	7
4	geometry	8
4.1	halfplane_intersection.cpp	8
4.2	segments_and_circles.cpp	10
5	graphs	10
5.1	components.cpp	10
5.2	directed_mst.cpp	11
5.3	dominator_tree.h	12
5.4	edmonds_matching.h	13
5.5	euler_cycle.h	13
6	maths	13
6.1	berlekamp.h	13
6.2	crt.h	14
6.3	gauss_bitset_inverse.h	14
6.4	gauss_bitset_solve_slv.h	14
6.5	gauss_double_inverse.h	15
6.6	gauss_double_solve_slv.h	15
6.7	millar_rabin_test.h	15
7	misc	16
7.1	ch_trick_with_binary_summation_struct.cpp	16
7.2	cht_stl.cpp	16
7.3	tree_bidirectional_dp.h	17
7.4	tree_order_statistics.cpp	17
8	numeric	17
8.1	integration.cpp	17
8.2	simplex.cpp	17
9	strings	19
9.1	aho_corasick.h	19
9.2	manacher.h	19
9.3	palindromes_on_subsegment.h	19
9.4	prefix_function.h	21
9.5	suffix_array.cpp	21
9.6	suffix_automaton_kostroma.h	22
9.7	suffix_tree_from_automaton.cpp	23
9.8	z_function.h	23
10	templates	23
10.1	template.cpp	23
11	treap	23
11.1	treap.cpp	23

## 1 centroids

### 1.1 centroid\_decomposition.cpp

```
vector<vector<int>>> g;
vector<int> cnt, max_cnt;
vector<int> comp;

void dfs1(int v, int p) {
    cnt[v] = 1;
    max_cnt[v] = 0;
    comp.push_back(v);
    for (int to : g[v]) {
        if (to == p || used[to]) continue;
        dfs1(to, v);
        max_cnt[v] = max(max_cnt[v], cnt[to]);
        cnt[v] += cnt[to];
    }
}
```

```
}

void kill_center(int v, int depth) {
    if (used[v]) {
        return;
    }
    comp.clear();
    dfs1(v, v);
    int center = -1;
    for (int x : comp) {
        if (max_cnt[x] <= cnt[v] / 2 && cnt[v] -
            cnt[x] <= cnt[v] / 2) {
            center = x;
            break;
        }
    }
    assert(center != -1);
    v = center;
    // perform actions with center v
    used[v] = true;
    for (int to : g[v]) {
        kill_center(to, depth + 1);
    }
}
```

```
void solve(__attribute__((unused)) bool read) {
    int n;
    cin >> n;

    used.assign(n, false);
    cnt.assign(n, 0);
    max_cnt.assign(n, 0);
    kill_center(0, 0);
}
```

## 2 fft

### 2.1 fft\_advanced\_integer.h

```
Poly derivative(Poly a) {
    if (a.empty()) {
        return a;
    }
    for (int i = 0; i < (int)a.size(); ++i) {
        a[i] = a[i] * i % mod;
    }
    a.erase(a.begin());
    return a;
}
```

```
// returns  $b(x) = \int_0^x a(t) dt$ 
Poly primitive(Poly a) {
    if (a.empty()) {
        return a;
    }
    for (int i = 0; i < (int)a.size(); ++i) {
        a[i] = a[i] * pw(i + 1, mod - 2) % mod;
    }
    a.insert(a.begin(), 0);
    return a;
}
```

```
Poly add(Poly a, const Poly& b) {
    a.resize(max(a.size(), b.size()));
    for (int i = 0; i < (int)b.size(); ++i) {
        a[i] = (a[i] + b[i]) % mod;
    }
    return a;
}
```

```
Poly sub(Poly a, const Poly& b) {
    a.resize(max(a.size(), b.size()));
    for (int i = 0; i < (int)b.size(); ++i) {
        a[i] = (a[i] + mod - b[i]) % mod;
    }
    return a;
}
```

```
Poly normalize(Poly a) {
    while (!a.empty() && a.back() == 0) {
        a.pop_back();
    }
}
```

```

    }
    return a;
}

// get such b that  $a \cdot b = 1 \pmod{x^{prec}}$ 
Poly getInversed(Poly a, int prec) {
    assert(a[0]);

    Poly res = {pw(a[0], mod - 2)};
    int k = 1;
    while (k < prec) {
        k *= 2;
        Poly tmp = multiply(res, Poly({a.begin(),
            ↪ a.begin() + min(k, (int)a.size())}));
        for (auto& x : tmp) {
            x = x ? mod - x : 0;
        }
        tmp[0] = (tmp[0] + 2) % mod;

        res = multiply(tmp, res);
        res.resize(k);
    }
    res.resize(prec);
    return res;
}

// get such q and r that  $a = b * q + r$ ,  $\deg(r) < \deg(b)$ 
pair<Poly, Poly> divMod(Poly a, Poly b) {
    int n = a.size();
    int m = b.size();
    if (n < m) {
        return {{0}, a};
    }
    reverse(all(a));
    reverse(all(b));
    auto quotient = multiply(a, getInversed(b, n - m
    ↪ + 1));
    quotient.resize(n - m + 1);
    reverse(all(a));
    reverse(all(b));
    reverse(all(quotient));
    auto remainder = sub(a, multiply(b, quotient));
    while (!remainder.empty() && remainder.back() ==
    ↪ 0) {
        remainder.pop_back();
    }
    return {quotient, remainder};
}

// this is for multipoint and interpolate functions
vector<Poly> getSegmentProducts(const vector<long
    ↪ long>& pts) {
    vector<Poly> segment_polys;
    function<int(int, int)> fill_polys = [&](int l,
    ↪ int r) {
        if (l + 1 == r) {
            segment_polys.push_back({(mod - pts[l])
            ↪ % mod, 1});
            return (int)segment_polys.size() - 1;
        }
        int m = (l + r) / 2;
        int i = fill_polys(l, m);
        int j = fill_polys(m, r);
        auto new_poly = multiply(segment_polys[i],
        ↪ segment_polys[j]);
        segment_polys.push_back(new_poly);
        return (int)segment_polys.size() - 1;
    };
    fill_polys(0, pts.size());

    return segment_polys;
}

// get p and {x1, x2, ..., xn}, return {p(x1),
    ↪ p(x2), ..., p(xn)}
vector<long long> multipoint(const Poly& poly, const
    ↪ vector<long long>& pts) {
    if (pts.empty()) {
        return {};
    }

    vector<Poly> segment_polys =
    ↪ getSegmentProducts(pts);

    vector<long long> ans;
    function<void(const Poly&)> fill_ans = [&](const
    ↪ Poly& p) {
        if ((int)segment_polys.back().size() <= 2) {
            ans.push_back(p.empty() ? 0 : p[0]);
            segment_polys.pop_back();
            return;
        }
        segment_polys.pop_back();
        fill_ans(divMod(p,
            ↪ segment_polys.back()).second);
        fill_ans(divMod(p,
            ↪ segment_polys.back()).second);
    };
    fill_ans(poly);
    reverse(all(ans));

    return ans;
}

// get {x1, ..., xn} and {y1, ..., yn}, return such
    ↪ p that  $p(x_i) = y_i$ 
Poly interpolate(const vector<long long>& xs, const
    ↪ vector<long long>& ys) {
    assert(xs.size() == ys.size());
    if (xs.empty()) {
        return {0};
    }

    vector<Poly> segment_polys = getSegmentProducts(xs);
    auto der = derivative(segment_polys.back());
    auto coeffs = multipoint(der, xs);
    for (auto& c : coeffs) {
        c = pw(c, mod - 2);
    }
    for (int i = 0; i < (int)ys.size(); ++i) {
        coeffs[i] = coeffs[i] * ys[i] % mod;
    }

    function<Poly()> get_ans = [&]() {
        Poly res;
        if (segment_polys.back().size() <= 2) {
            segment_polys.pop_back();
            res = {coeffs.back()};
            coeffs.pop_back();
        } else {
            segment_polys.pop_back();

            auto p1 = segment_polys.back();
            auto q1 = get_ans();

            auto p2 = segment_polys.back();
            auto q2 = get_ans();

            res = add(multiply(p1, q2), multiply(p2,
            ↪ q1));
        }
        return res;
    };
    return normalize(get_ans());
}

// takes 1 + b, returns  $b - b^2/2 + b^3/3 - \dots \pmod{x^{prec}}$ 
    ↪  $x^{\{prec\}}$ 
// ofc b must be divisible by x
Poly logarithm(Poly a, int prec) {
    assert(a[0] == 1);
    auto res = primitive(multiply(derivative(a),
    ↪ getInversed(a, prec)));
    res.resize(prec);
    return res;
}

// returns  $1 + a + a^2/2 + a^3/6 + \dots \pmod{x^{\{prec\}}}$ 
    ↪ ofc a must be divisible by x
Poly exponent(Poly a, int prec) {
    assert(a[0] == 0);

    Poly res = {1};
    int k = 1;
    while (k < prec) {
        k *= 2;

```

```

    Poly tmp = {a.begin(), a.begin() + min(k,
    ↪ (int)a.size())};
    tmp[0] += 1;
    tmp = sub(tmp, logarithm(res, k));

    res = multiply(tmp, res);
    res.resize(k);
}
res.resize(prec);
return res;
}

```

## 2.2 fft\_double.h

```

const int L = 22;
const int N = 1 << L;
bool fft_initialized = false;

using ld = long double;
using base = complex<ld>;
using Poly = vector<ld>;

const ld pi = acosl(-1);
base angles[N + 1];
int bitrev[N];

// don't know why such eps, may be changed
const ld eps = 1e-7;

inline bool eq(ld x, ld y) {
    return abs(x - y) < eps;
}

void fft_init() {
    for (int i = 0; i <= N; ++i) {
        angles[i] = {cosl(2 * pi * i / N), sinl(2 *
        ↪ pi * i / N)};
    }

    for (int i = 0; i < N; ++i) {
        int x = i;
        for (int j = 0; j < L; ++j) {
            bitrev[i] = (bitrev[i] << 1) | (x & 1);
            x >>= 1;
        }
    }

    fft_initialized = true;
}

inline int revBit(int x, int len) {
    return bitrev[x] >> (L - len);
}

void fft(vector<base>& a, bool inverse = false) {
    assert(fft_initialized &&
    ↪ "you fucking cunt just write fft_init()");
    int n = a.size();
    assert(!(n & (n - 1))); // work only with
    ↪ powers of two
    int l = __builtin_ctz(n);

    for (int i = 0; i < n; ++i) {
        int j = revBit(i, l);
        if (i < j) {
            swap(a[i], a[j]);
        }
    }

    for (int len = 1; len < n; len *= 2) {
        for (int start = 0; start < n; start += 2 *
        ↪ len) {
            for (int i = 0; i < len; ++i) {
                base x = a[start + i], y = a[start +
                ↪ len + i];
                int idx = N / 2 / len * i;
                base w = y * angles[inverse ? N -
                ↪ idx : idx];
                a[start + i] = x + w;
                a[start + len + i] = x - w;
            }
        }
    }
}

```

```

    if (inverse) {
        for (auto& x : a) {
            x /= n;
        }
    }
}

Poly multiply(Poly a, Poly b) {
    int n = 1;
    while (n < (int)a.size() || n < (int)b.size()) {
        n *= 2;
    }
    vector<base> ar(n + n), br(n + n);
    for (int i = 0; i < (int)a.size(); ++i) {
        ar[i] = a[i];
    }
    for (int i = 0; i < (int)b.size(); ++i) {
        br[i] = b[i];
    }
    fft(ar);
    fft(br);
    for (int i = 0; i < n + n; ++i) {
        ar[i] = ar[i] * br[i];
    }
    fft(ar, true);
    while (!ar.empty() && eq(norm(ar.back()), 0)) {
        ar.pop_back();
    }
    a.resize(ar.size());
    for (int i = 0; i < (int)a.size(); ++i) {
        a[i] = real(ar[i]);
    }
    return a;
}

```

## 2.3 fft\_integer.h

```

const int mod = 998244353;
const int L = 22; // can be 23 for 998244353
const int N = 1 << L;
bool fft_initialized = false;

using Poly = vector<long long>;

long long pw(long long a, long long b) {
    long long res = 1;
    while (b) {
        if (b & 1ll) {
            res = res * a % mod;
        }
        b >>= 1;
        a = a * a % mod;
    }
    return res;
}

int getRoot() {
    int root = 1;
    while (pw(root, 1 << L) != 1 || pw(root, 1 << (L
    ↪ - 1)) == 1) {
        ++root;
    }
    return root;
}

const int root = getRoot();

long long angles[N + 1];
int bitrev[N];

void fft_init() {
    angles[0] = 1;
    for (int i = 1; i <= N; ++i) {
        angles[i] = angles[i - 1] * root % mod;
    }

    for (int i = 0; i < N; ++i) {
        int x = i;
        for (int j = 0; j < L; ++j) {
            bitrev[i] = (bitrev[i] << 1) | (x & 1);
            x >>= 1;
        }
    }
}

```

```

    fft_initialized = true;
}

inline int revBit(int x, int len) {
    return bitrev[x] >> (L - len);
}

void fft(vector<long long>& a, bool inverse = false) {
    assert(fft_initialized &&
        ↪ "you fucking cunt just write fft_init()");
    int n = a.size();
    assert(!(n & (n - 1))); // work only with
    ↪ powers of two
    int l = __builtin_ctz(n);

    for (int i = 0; i < n; ++i) {
        int j = revBit(i, l);
        if (i < j) {
            swap(a[i], a[j]);
        }
    }

    for (int len = 1; len < n; len *= 2) {
        for (int start = 0; start < n; start += 2 *
            ↪ len) {
            for (int i = 0; i < len; ++i) {
                long long x = a[start + i], y =
                ↪ a[start + len + i];
                int idx = N / 2 / len * i;
                long long w = angles[inverse ? N -
                ↪ idx : idx];
                w = w * y % mod;
                a[start + i] = x + w;
                if (a[start + i] >= mod) {
                    a[start + i] -= mod;
                }
                a[start + len + i] = x - w;
                if (a[start + len + i] < 0) {
                    a[start + len + i] += mod;
                }
            }
        }

        if (inverse) {
            int rev_deg = 1;
            for (int i = 0; i < l; ++i) {
                rev_deg = (rev_deg % 2) ? ((rev_deg +
                    ↪ mod) / 2) : (rev_deg / 2);
            }
            for (auto& x : a) {
                x = x * rev_deg % mod;
            }
        }
    }

    Poly multiply(Poly a, Poly b) {
        int n = 1;
        while (n < (int)a.size() || n < (int)b.size()) {
            n *= 2;
        }
        a.resize(n + n);
        b.resize(n + n);
        fft(a);
        fft(b);
        for (int i = 0; i < n + n; ++i) {
            a[i] = a[i] * b[i] % mod;
        }
        fft(a, true);
        while (!a.empty() && a.back() == 0) {
            a.pop_back();
        }
        return a;
    }

    Poly multiply(const Poly& a, const Poly& b) {
        ....
        for (int i = 0; i < n; ++i) {
            answer[i] = (li)(res[i].real() + 0.5);
            answer[i] %= mod;
        }
    }

    }
    return answer;
}

const int shift = 15;
const int first_mod = 1 << shift;

Poly large_part(const Poly& a) {
    Poly res(a.size());
    for (int i = 0; i < a.size(); ++i) {
        res[i] = a[i] >> shift;
    }
    return res;
}

Poly small_part(const Poly& a) {
    Poly res(a.size());
    for (int i = 0; i < a.size(); ++i) {
        res[i] = a[i] & (first_mod - 1);
    }
    return res;
}

Poly add(const Poly& q, const Poly& w) {
    auto res = q;
    res.resize(max(q.size(), w.size()));
    for (int i = 0; i < w.size(); ++i) {
        res[i] += w[i];
    }
    return res;
}

Poly multiply_large(const Poly& a, const Poly& b,
    ↪ int k) {
    Poly largeA = large_part(a), largeB = large_part(b);
    Poly smallA = small_part(a), smallB = small_part(b);
    Poly large_mult = multiply(largeA, largeB);
    Poly small_mult = multiply(smallA, smallB);
    Poly middle_mult = multiply(add(smallA, largeA),
    ↪ add(smallB, largeB));

    Poly result(large_mult.size());
    for (int i = 0; i < result.size(); ++i) {
        result[i] = ((large_mult[i] * first_mod) %
            ↪ mod * first_mod + small_mult[i] +
            ↪ first_mod * (middle_mult[i] -
            ↪ large_mult[i] -
            ↪ small_mult[i]) % mod) %
            ↪ mod;
    }
    if (result.size() > k + 1) {
        result.resize(k + 1);
    }
    return result;
}
}

3 flows

3.1 dinic.h

struct Edge {
    int from, to, cap, flow;
};

const int INF = (int)2e9;

struct Dinic {
    int n;
    vector<Edge> edges;
    vector<vector<int>> g;

    Dinic(int n) : n(n) {
        g.resize(n);
    }

    void add_edge(int from, int to, int cap) {
        Edge e = {from, to, cap, 0};
        g[from].push_back(edges.size());
        edges.push_back(e);
        e = {to, from, 0, 0};
        g[to].push_back(edges.size());
        edges.push_back(e);
    }
}

```

## 2.4 fft\_mod\_10\_9\_7.h

```

Poly multiply(const Poly& a, const Poly& b) {
    ....
    for (int i = 0; i < n; ++i) {
        answer[i] = (li)(res[i].real() + 0.5);
        answer[i] %= mod;
    }
}

```

```

void add_edge(int from, int to, int cap) {
    Edge e = {from, to, cap, 0};
    g[from].push_back(edges.size());
    edges.push_back(e);
    e = {to, from, 0, 0};
    g[to].push_back(edges.size());
    edges.push_back(e);
}

```

```
using cost_type = li;
const cost_type COST_INF = (int)1e18;
const int FLOW_INF = (int)1e9;

struct MinCost {
    explicit MinCost(int n) {
        g.resize(n);
    }

    struct edge {
        int from, to;
        int cap;
        cost_type cost;
        int flow;
    };

    vector<edge> edges;
    vector<vector<int>> g;

    void add_edge(int from, int to, cost_type cost,
        ↪ int cap) {
        edge e = {from, to, cap, cost, 0};
        g[from].push_back(edges.size());
        edges.push_back(e);
        edge e2 = {to, from, 0, -cost, 0};
        g[to].push_back(edges.size());
        edges.push_back(e2);
    }

    pair<int, cost_type> min_cost(int n, int s, int
    ↪ t, bool need_max_flow, int max_flow_value =
    ↪ FLOW_INF) {
        cost_type cost = 0;
        int flow = 0;
        while (flow < max_flow_value) {
            queue<int> q;
            q.push(s);
            vector<int> in_q(n, 0);
            in_q[s] = 1;
            vector<int> p(n, -1);
            vector<cost_type> d(n);
            d[s] = 0;
            p[s] = s;
            while (!q.empty()) {
                int v = q.front();
                q.pop();
                in_q[v] = false;
                for (size_t i: g[v]) {
                    edge& e = edges[i];
                    if (e.cap == e.flow || p[e.from]
                    ↪ == -1)
                        continue;
                    if (p[e.to] == -1 || d[e.to] >
                    ↪ d[e.from] + e.cost) {
                        d[e.to] = d[e.from] + e.cost;
                        p[e.to] = e.from;
                        q.push(e.to);
                    }
                }
            }
            cost += d[t];
            if (!need_max_flow) return {cost, flow};
            flow += d[t];
            vector<int> f(n, 0);
            f[t] = d[t];
            while (t != s) {
                int v = p[t];
                f[v] += f[t];
                t = v;
            }
            for (int i = 0; i < edges.size(); ++i) {
                edge& e = edges[i];
                e.flow += f[e.from] - f[e.to];
            }
        }
        return {cost, flow};
    }
};
```

```

while (changed) {
    changed = false;
    for (size_t i = 0; i < edges.size(); ++i) {
        edge &e = edges[i];
        if (e.cap == e.flow || p[e.from] == -1) continue;
        if (p[e.to] == -1 || d[e.to] > d[e.from] + e.cost) {
            d[e.to] = d[e.from] + e.cost;
            p[e.to] = i;
            changed = true;
        }
    }
}
potential = std::move(d);
}

while (flow < max_flow_value) {
    vector<cost_type> d(n);
    vector<int> p(n, -1);

    using queue_type = pair<cost_type, int>;
    priority_queue<queue_type, vector<queue_type>, greater<queue_type>> q;

    q.push({0, s});

    while (!q.empty()) {
        int v = q.top().second;
        cost_type oldD = q.top().first;
        q.pop();
        if (oldD != d[v]) continue;
        for (int id: g[v]) {
            edge &e = edges[id];
            if (e.to == s) continue;
            if (e.cap > e.flow) {
                cost_type newd = d[v] + e.cost + potential[e.from] - potential[e.to];
                if (p[e.to] == -1 || d[e.to] > newd) {
                    d[e.to] = newd;
                    p[e.to] = id;
                    q.push({d[e.to], e.to});
                }
            }
        }
    }

    if (p[t] == -1) break;

    if (d[t] + potential[t] >= 0 && !need_max_flow) break;

    int cur = t;
    int maxAdd = max_flow_value - flow;
    while (cur != s) {
        edge &e = edges[p[cur]];
        cur = e.from;
        maxAdd = min(maxAdd, e.cap - e.flow);
    }

    flow += maxAdd;
    cost += (potential[t] + d[t]) * maxAdd;
    cur = t;
    while (cur != s) {
        int id = p[cur];
        edges[id].flow += maxAdd;
        edges[id ^ 1].flow -= maxAdd;
        cur = edges[id].from;
    }

    for (int i = 0; i < n; ++i) {
        if (i != s && p[i] == -1) {

```



```

        potential[i] = COST_INF;
    } else
        potential[i] = min(potential[i]
        ↪ + d[i], COST_INF);
    }
}

return make_pair(flow, cost);
};

```

### 3.5 min\_cost\_ford\_bellman.h

```

using cost_type = li;
const cost_type COST_INF = (int)1e18;
const int FLOW_INF = (int)1e9;

struct MinCost {
    explicit MinCost(int n) {
        g.resize(n);
    }

    struct edge {
        int from, to;
        int cap;
        cost_type cost;
        int flow;
    };

    vector<edge> edges;
    vector<vector<int>>> g;

    void add_edge(int from, int to, cost_type cost,
    ↪ int cap) {
        edge e = {from, to, cap, cost, 0};
        g[from].push_back(edges.size());
        edges.push_back(e);
        edge e2 = {to, from, 0, -cost, 0};
        g[to].push_back(edges.size());
        edges.push_back(e2);
    }

    pair<int, cost_type> min_cost(int n, int s, int
    ↪ t, bool need_max_flow, int max_flow_value =
    ↪ FLOW_INF) {
        cost_type cost = 0;
        int flow = 0;
        while(flow < max_flow_value) {
            vector<int> p(n, -1);
            vector<cost_type> d(n);
            d[s] = 0;
            p[s] = s;
            bool changed = true;
            while(changed) {
                changed = false;
                for(size_t i = 0; i < edges.size();
                ↪ ++i) {
                    edge& e = edges[i];
                    if(e.cap == e.flow || p[e.from]
                    ↪ == -1)
                        continue;
                    if(p[e.to] == -1 || d[e.to] >
                    ↪ d[e.from] + e.cost) {
                        d[e.to] = d[e.from] + e.cost;
                        p[e.to] = i;
                        changed = true;
                    }
                }
            }
            if(p[t] == -1)
                break;

            if(d[t] >= 0 && !need_max_flow) {
                break;
            }

            int cur = t;
            int maxAdd = max_flow_value - flow;
            while(cur != s) {
                edge& e = edges[p[cur]];
                cur = e.from;
                maxAdd = min(maxAdd, e.cap - e.flow);
            }

```

```

        flow += maxAdd;
        cost += d[t] * maxAdd;
        cur = t;
        while(cur != s) {
            int id = p[cur];
            edges[id].flow += maxAdd;
            edges[id ^ 1].flow -= maxAdd;
            cur = edges[id].from;
        }
    }
    return make_pair(flow, cost);
};

```

### 3.6 min\_cost\_negative\_cycles.h

```

using cost_type = int;
const cost_type COST_INF = (cost_type)1e9;
const int FLOW_INF = (int)1e9;

struct MinCost {
    explicit MinCost(int n) {
        g.resize(n);
    }

    struct edge {
        int from, to;
        int cap;
        cost_type cost;
        int flow;
    };

    vector<edge> edges;
    vector<vector<int>>> g;

    void add_edge(int from, int to, cost_type
    ↪ cur_cost, int cap) {
        edge e = {from, to, cap, cur_cost, 0};
        g[from].push_back(edges.size());
        edges.push_back(e);
        edge e2 = {to, from, 0, -cur_cost, 0};
        g[to].push_back(edges.size());
        edges.push_back(e2);
    }

    pair<int, cost_type> min_cost(int n, int s, int
    ↪ t, int max_flow_value = FLOW_INF) {
        cost_type cost = 0;
        int flow = 0;

        vector<int> p(n);
        vector<cost_type> d(n, 0);
        vector<int> to_add;
        while (flow < max_flow_value) {
            p.assign(n, -1);
            d.assign(n, COST_INF);
            d[s] = 0;
            set<pair<cost_type, int>> q;
            q.insert({0, s});
            vector<char> used(n, false);
            while (!q.empty()) {
                int v = q.begin()->second;
                q.erase(q.begin());
                used[v] = true;
                for (int i : g[v]) {
                    auto& e = edges[i];
                    if (e.cap == e.flow || used[e.to]) {
                        continue;
                    }
                    cost_type new_d = d[v] + e.cost;
                    if (d[e.to] > new_d) {
                        q.erase({d[e.to], e.to});
                        d[e.to] = new_d;
                        q.insert({d[e.to], e.to});
                        p[e.to] = i;
                    }
                }
            }
            if (p[t] == -1) {
                return {-1, 0};
            }
            int add_flow = max_flow_value - flow;

```

```

int cur = t;
to_add.clear();
int add_cost = 0;
while (cur != s) {
    auto& e = edges[p[cur]];
    add_flow = min(add_flow, e.cap -
        ↪ e.flow);
    to_add.push_back(p[cur]);
    cur = e.from;
    add_cost += e.cost;
}
assert(add_flow > 0);
flow += add_flow;
cost += add_flow * add_cost;
for (int x : to_add) {
    edges[x].flow += add_flow;
    edges[x ^ 1].flow -= add_flow;
}
}

int TIMER = 0;
vector<int> used_timer(n, 0);
vector<char> used(n, false);
vector<int> cur_edges;
vector<int> edges_to_add;
while (true) {
    p.assign(n, -1);
    d.assign(n, COST_INF);
    bool found = false;
    int iter = 0;
    for (int st = 0; st < s; ++st) {
        if (d[st] != COST_INF) {
            continue;
        }
        ++iter;
        d[st] = 0;
        vector<int> q, new_q;
        q.push_back(st);
        for (int it = 0; it < n; ++it) {
            ++TIMER;
            int changed = -1;
            for (int v : q) {
                for (int i : g[v]) {
                    edge &e = edges[i];
                    if (e.cap == e.flow)
                        continue;
                    cost_type new_d = d[v] +
                        ↪ e.cost;
                    if (d[e.to] > new_d) {
                        d[e.to] = new_d;
                        p[e.to] = i;
                        changed = e.to;
                        if (used_timer[e.to]
                            ↪ != TIMER) {
                            used_timer[e.to]
                                ↪ = TIMER;
                        }
                    }
                    ↪ new_q.push_back(e.to);
                }
            }
        }
        if (changed == -1) {
            break;
        }
        sort(all(new_q));
        q.swap(new_q);
        new_q.clear();
        if (d[st] < 0) {
            changed = st;
            it = n - 1;
        }
        if (it == n - 1) {
            found = true;
            int bad_end = changed;
            used.assign(n, false);
            int cur = bad_end;
            cur_edges.clear();
            while (!used[cur]) {
                used[cur] = true;
                cur_edges.push_back(p[cur]);
                cur = edges[p[cur]].from;
            }
            edges_to_add.clear();

```

```

while
    ↪ (edges[cur_edges.back()].to
    ↪ != cur) {
        ↪ edges_to_add.push_back(cur_edges.back());
        cur_edges.pop_back();
    }
    ↪ edges_to_add.push_back(cur_edges.back());
    int add_cost = 0, add_flow =
    ↪ FLOW_INF;
    for (auto e_id : edges_to_add) {
        add_flow = min(add_flow,
            ↪ edges[e_id].cap -
            ↪ edges[e_id].flow);
        add_cost +=
            ↪ edges[e_id].cost;
    }
    cost += add_cost * add_flow;
    assert(add_flow > 0);
    assert(add_cost < 0);
    for (auto e_id : edges_to_add) {
        edges[e_id].flow +=
            ↪ add_flow;
        edges[e_id ^ 1].flow -=
            ↪ add_flow;
    }
}
}
}
if (!found) {
    break;
}
return make_pair(flow, cost);
};

```

## 4 geometry

### 4.1 halfplane\_intersection.cpp

```

using ld = double;
const ld eps = 1e-9;

struct point {
    ld x, y;

    point(ld x = 0, ld y = 0): x(x), y(y) {}

    point operator+(const point& p) const { return
        ↪ point(x + p.x, y + p.y); }
    point operator-(const point& p) const { return
        ↪ point(x - p.x, y - p.y); }

    point operator*(ld t) const { return point(x *
        ↪ t, y * t); }
    point operator/(ld t) const { return point(x /
        ↪ t, y / t); }

    point rot() const { return point(-y, x); }

    ld vprod(const point& p) const { return x * p.y
        ↪ - y * p.x; }
    ld sprod(const point& p) const { return x * p.x
        ↪ + y * p.y; }

    int half() const {
        if (y)
            return y < -eps;
        else
            return x < -eps;
    }

    ld sql() const { return x * x + y * y; }
    ld len() const { return sqrt(sql()); }

    bool operator<(const point& p) const { return
        ↪ make_pair(x, y) < make_pair(p.x, p.y); }
};

int sign(ld x) {

```



```

    return abs(x) > eps ? (x > 0 ? 1 : -1) : 0;
}

int vecLess(const point& a, const point& b) {
    if (a.half() != b.half())
        return a.half() < b.half() ? 1 : -1;
    else {
        return sign(a.vprod(b));
    }
}

struct halfplane {
    // ax + by + c >= 0
    ld a, b, c;
    int type;

    tuple<ld, ld, ld> get() const { return
        ↪ make_tuple(a, b, c); }
    bool operator<(const halfplane& rhs) const {
        ↪ return get() < rhs.get(); }

    point norm() const { return point(a, b); }

    point intersect(const halfplane& h) const {
        ld x = -c * h.b + b * h.c;
        ld y = a * -h.c + c * h.a;
        ld denum = a * h.b - b * h.a;
        return point(x / denum, y / denum);
    }
};

// does intersection of a and c belong to b?
// assumes that a.vprod(c) > 0!
bool interAccepted(const halfplane& a, const
    ↪ halfplane& b, const halfplane& c) {
    // Determinant of 3x3 matrix formed by a, b, c
    return a.a * (b.b * c.c - b.c * c.b) - a.b *
        ↪ (b.a * c.c - b.c * c.a) + a.c * (b.a * c.b -
        ↪ b.b * c.a) < 0;
}

void sanitizeHalfplanes(vector<halfplane>& planes,
    ↪ bool doAdd, bool doSort) {
    // Add bounding box
    const ld INF = 1e9;
    if (doAdd) {
        planes.push_back(halfplane { 1, 0, INF });
        planes.push_back(halfplane { -1, 0, INF });
        planes.push_back(halfplane { 0, 1, INF });
        planes.push_back(halfplane { 0, -1, INF });
    }

    // Normalize halfplanes. This is used when
    ↪ selecting strictest of parallel halfplanes
    // NOT NEEDED if there are no collinear (and not
    ↪ antiparallel) normals, but may improve
    ↪ precision
    for (halfplane& h: planes) {
        ld len = h.norm().len();
        h.a /= len;
        h.b /= len;
        h.c /= len;
    }

    if (doSort)
        sort(all(planes), [&](halfplane& a,
            ↪ halfplane& b) { return vecLess(a.norm(),
            ↪ b.norm()) > 0; });
}

class polygon {
public:
    vector<point> pts;

    polygon(const vector<point>& pts =
        ↪ vector<point>(): pts(pts) {}

    ld getDoubleSquare() const {
        ld result = 0;
        int n = pts.size();
        for (int i = 1; i < n - 1; ++i) {
            result += (pts[i] - pts[0]).vprod(pts[i]
                ↪ + 1] - pts[0]);
        }
    }
};

}

return abs(result);
}

// Returns halfplane through points a and b,
// inner part is counter-clockwise from a->b segment
halfplane byPoints(point a, point b) {
    // rot counter clockwise, n points to area
    ↪ inside halfplane intersection
    point n = (b - a).rot();
    return halfplane { n.x, n.y, -n.sprod(a) };
}

// empty return polygon/vector denotes empty
    ↪ intersection
    ↪ degenerate intersections are reported as empty

// CALL sanitizeHalfplanes WITH SORT AND/OR ADD
    ↪ BOUNDING BOX BEFORE USING!
polygon getPolygon(const vector<halfplane>& planes) {
    int l = 0, r = 0;
    static vector<halfplane> ans;
    ans.clear();
    ans.reserve(planes.size());

    for (int L = 0; L < planes.size(); ) {
        int R = L + 1;
        while (R < planes.size() &&
            ↪ abs(planes[L].norm().vprod(planes[R].norm()))
            ↪ < eps) ++R;

        // choose most powerful inequality among
        ↪ those with equal normals
        // assumes that normals are identity!
        const halfplane& h =
            ↪ *min_element(planes.begin() + L,
            ↪ planes.begin() + R, [](const halfplane&
            ↪ a, const halfplane& b) { return a.c <
            ↪ b.c; });
        L = R;

        while (r - l > 1 && !interAccepted(ans[r -
            ↪ 2], h, ans[r - 1])) {
            ans.pop_back();
            --r;
        }

        while (r - l > 1 && !interAccepted(ans[l],
            ↪ h, ans[l + 1])) {
            ++l;
        }

        // WATCH OUT: you may need to tweak eps here
        ↪ for severe problems
        if (r - l > 0 && ans[r -
            ↪ 1].norm().vprod(h.norm()) <= -1e-7) {
            return polygon();
        }

        if (r - l < 2 || interAccepted(ans[r - 1],
            ↪ ans[l], h)) {
            ans.push_back(h);
            r++;
        }
    }

    assert(r == ans.size());

    // IF YOU NEED HALFPLANES:
    // return vector<halfplane>(ans.begin() + 1,
        ↪ ans.end());

    int n = r - 1;

    polygon poly;
    poly.pts.reserve(n);
    for (int i = 0; i < n; ++i) {
        poly.pts.push_back(ans[l +
            ↪ i].intersect(ans[l + (i + 1) % n]));
    }

    return poly;
}

```

}

## 4.2 segments\_and\_circles.cpp

```

struct point {
    ld x, y;

    point(ld x = 0, ld y = 0): x(x), y(y) {}

    point operator+(const point& p) const { return
    ↪ point(x + p.x, y + p.y); }
    point operator-(const point& p) const { return
    ↪ point(x - p.x, y - p.y); }

    point operator*(ld t) const { return point(x *
    ↪ t, y * t); }
    point operator/(ld t) const { return point(x /
    ↪ t, y / t); }

    ld vprod(const point& p) const { return x * p.y
    ↪ - y * p.x; }
    ld sprod(const point& p) const { return x * p.x
    ↪ + y * p.y; }

    point rot() const { return point(-y, x); }

    point norm() const { return *this / len(); }
    bool valid() const { return isfinite(x); }

    ld len() const { return hypot(x, y); }
    ld sql() const { return x * x + y * y; }

    int half() const {
        if (abs(y) > eps)
            return y < 0;
        else
            return x < -eps;
    }
};

point invalid(INFINITY, INFINITY);

point segmentIntersect(point a, point b, point c,
    ↪ point d) {
    b = b - a;
    d = d - c;

    if (abs(b.vprod(d)) < eps) return invalid;

    // a + bu = c + dv
    ld u = (c - a).vprod(d) / b.vprod(d);
    ld v = (a - c).vprod(b) / d.vprod(b);

    if (u >= -eps && v >= -eps && u <= 1 + eps && v
    ↪ <= 1 + eps)
        return a + b * u;

    return invalid;
}

vector<point> lineCircleIntersect(point a, point b,
    ↪ point c, ld r) {
    point n = (b - a).norm().rot();
    ld d = n.sprod(a - c);
    if (abs(d) > r + eps) return {};

    if (abs(abs(d) - r) < eps)
        return { c + n * d };

    ld x = sqrt(max<ld>(0, r * r - d * d));
    return { c + n * d + n.rot() * x, c + n * d -
    ↪ n.rot() * x };
}

vector<point> segmentCircleIntersect(point a, point
    ↪ b, point c, ld r) {
    auto pts = lineCircleIntersect(a, b, c, r);

    vector<point> ans;
    for (point& p: pts) {
        assert(abs((p - c).len() - r) < eps);
        assert(abs((p - a).vprod(b - a)) < eps);
    }
}

```

```

        if ((p - a).sprod(p - b) <= eps)
            ans.push_back(p);
    }

    return ans;
}

vector<point> circleCircleIntersect(point c1, ld r1,
    ↪ point c2, ld r2) {
    //  $r_1^2 - h^2 = x^2$ 
    //  $r_2^2 - h^2 = (d - x)^2 = x^2 - 2dx + d^2$ 
    //  $d^2 - 2dx = r_2^2 - r_1^2$ 

    ld d = (c2 - c1).len();

    if (d > r1 + r2 + eps || d < abs(r2 - r1) - eps
    ↪ || abs(d) < eps) return {};

    ld x = (d * d - r2 * r2 + r1 * r1) / (2 * d);
    point dir = (c2 - c1).norm();

    ld h = sqrt(max<ld>(r1 * r1 - x * x, 0));

    if (h < eps)
        return { c1 + dir * x };
    else
        return { c1 + dir * x + dir.rot() * h, c1 +
    ↪ dir * x - dir.rot() * h };
}

```

## 5 graphs

### 5.1 components.cpp

```

struct Graph {
    void read() {
        int m;
        cin >> n >> m;

        e.resize(n);

        for (int i = 0; i < m; ++i) {
            int u, v;
            cin >> u >> v;
            --u; --v;
            e[u].push_back(v);
            e[v].push_back(u);
        }

        /* COMMON PART */

        int n;
        vector<vector<int>> e;

        int counter = 1;
        vector<int> inTime, minInTime;

        void dfs(int v, int p = -1) {
            minInTime[v] = inTime[v] = counter++;

            for (int u: e[v]) {
                if (u == p) continue;

                if (!inTime[u]) {
                    dfs(u, v);
                    minInTime[v] = min(minInTime[v],
                    ↪ inTime[u]);
                }
                else {
                    minInTime[v] = min(minInTime[v],
                    ↪ inTime[u]);
                }
            }
        }

        vector<char> used;

        /* COMPONENTS SEPARATED BY BRIDGES (COLORING) */

        int nColors;
    }
}

```

```

vector<int> color;

void colorDfs(int v, int curColor) {
    color[v] = curColor;

    for (int u: e[v]) {
        if (color[u] != -1) continue;

        colorDfs(u, minInTime[u] > inTime[v] ?
            ↪ nColors++ : curColor);
    }
}

void findVertexComponents() {
    inTime.assign(n, 0);
    minInTime.assign(n, 0);
    counter = 1;

    for (int i = 0; i < n; ++i)
        if (!inTime[i])
            dfs(i);

    nColors = 0;
    color.assign(n, -1);
    for (int i = 0; i < n; ++i)
        if (color[i] == -1) {
            colorDfs(i, nColors++);
        }
}

/* COMPONENTS SEPARATED BY JOINTS (EDGE ↪
   ↪ COMPONENTS) */

struct Edge {
    int u, v;
};

// Cactus loops can be parsed as .u of every edge
vector<vector<Edge>> edgeComps;

vector<int> colorStack;

void edgeCompDfs(int v, int p = -1) {
    used[v] = true;

    for (int u: e[v]) {
        if (used[u]) {
            if (inTime[u] < inTime[v] && u != p) {
                // NOTE: && u != p makes ↪
                ↪ one-edge components contain ↪
                ↪ exactly one edge;
                // if you need them as two-edge ↪
                ↪ loops, remove this part of ↪
                ↪ if condition
                ↪
                ↪ edgeComps[colorStack.back()].push_back({v,
                ↪ u});
            }
            continue;
        }

        bool newComp = minInTime[u] >= inTime[v];

        if (newComp) {
            colorStack.push_back(edgeComps.size());
            edgeComps.emplace_back();
        }

        ↪ edgeComps[colorStack.back()].push_back({v,
        ↪ u});
        edgeCompDfs(u, v);

        if (newComp) {
            colorStack.pop_back();
        }
    }
}

void findEdgeComponents() {
    inTime.assign(n, 0);
    minInTime.assign(n, 0);
    counter = 1;

```

```

    for (int i = 0; i < n; ++i)
        if (!inTime[i])
            dfs(i);

    used.assign(n, false);
    colorStack.clear();
    edgeComps.clear();
    for (int i = 0; i < n; ++i)
        if (!used[i]) {
            assert(colorStack.empty());
            edgeCompDfs(i);
        }
}
};

```

## 5.2 directed\_mst.cpp

```

vector<int> min_edges;

// RETURNS: value of directed MST with root in root
// ids of min edges are pushed into min_edges
// WARNING: DO NOT FORGET TO FILL edge.id !!! ↪
↪ (algorithm reports these values)
li findMst(vector<edge>& edges, int n, int root) {
    li res = 0;

    const li INF = 1e18;
    vector<li> minCost(n, INF);
    vector<int> id_edge(n, -1);

    for (int i = 0; i < edges.size(); i++)
        edges[i].local_id = i;

    for (edge& e: edges) {
        if (e.from == e.to || e.to == root) continue;

        if (minCost[e.to] > e.cost) {
            minCost[e.to] = e.cost;
            id_edge[e.to] = e.id;
        }
    }

    for (int v = 0; v < n; v++)
        if (v != root) {
            res += minCost[v];
        }

    vector<edge> zero;
    for (edge& e: edges) {
        if (e.from == e.to || e.to == root) continue;

        e.cost -= minCost[e.to];
        if (e.cost == 0)
            zero.push_back(e);
    }

    vector<vector<tuple<int, int, int>>> zero_to(n), ↪
    ↪ zero_to_rev(n);
    for (edge& e: zero) {
        zero_to[e.from].emplace_back(e.to, e.id, ↪
        ↪ e.local_id);
        zero_to_rev[e.to].emplace_back(e.from, e.id, ↪
        ↪ e.local_id);
    }

    vector<char> used(n, false);
    vector<int> out_order;

    vector<int> can_min;
    function<void(int)> dfs = [&](int v) {
        used[v] = true;
        for (auto ed: zero_to[v]) {
            int u = get<0>(ed);

            if (!used[u]) {
                dfs(u);
                can_min.push_back(get<1>(ed));
            }
        }
        out_order.push_back(v);
    };

```

```

dfs(root);

bool fail = false;
for (int v = 0; v < n; v++)
    if (!used[v]) {
        fail = true;
        dfs(v);
    }

if (!fail) {
    min_edges = can_min;
    answer += res;
    return res;
}

reverse(all(out_order));

vector<int> color(n, -1);

int curColor = 0;

function<void(int)> colorDfs = [&](int v) {
    color[v] = curColor;

    for (auto ed: zero_to_rev[v]) {
        int u = get<0>(ed);
        if (color[u] == -1) {
            colorDfs(u);
            min_edges.push_back(get<2>(ed));
        }
    }
};

for (int v: out_order) {
    if (color[v] == -1) {
        colorDfs(v);
        curColor++;
    }
}

vector<edge> new_edges;
for (int i = 0; i < edges.size(); i++) {
    edge& e = edges[i];
    if (e.from == e.to || e.to == root) continue;

    if (color[e.to] != color[e.from]) {
        edge new_e = edge { color[e.from],
        ↪ color[e.to], e.cost };
        new_e.id = i;
        new_edges.push_back(new_e);
    }
}

answer += res;
li mst_res = findMst(new_edges, curColor,
    ↪ color[root]);
res += mst_res;

can_min.clear();
used.assign(n, false);

function<void(int)> sc_dfs = [&](int v) {
    used[v] = true;
    for (auto ed: zero_to[v]) {
        int u = get<0>(ed);
        if (color[u] == color[v] && !used[u]) {
            assert(get<1>(ed) >= 0);
            min_edges.push_back(get<2>(ed));
            sc_dfs(u);
        }
    }
};

for (int i = 0; i < min_edges.size(); i++) {
    int id = min_edges[i];
    edge& e = edges[id];
    can_min.push_back(e.id);

    sc_dfs(e.to);
}

sc_dfs(root);

min_edges = can_min;

```

```

    return res;
}

```

### 5.3 dominator\_tree.h

```

struct DominatorTree {
    int n;
    int root;
    vector<int> tin, revin;
    vector<int> sdom, idom;
    vector<vector<int>> g, revg;
    vector<int> parent;

    vector<int> dsu;
    vector<int> min_v;
    int cnt = 0;

    int get(int v) {
        ++cnt;
        if (dsu[v] == v) {
            return v;
        }
        int next_v = get(dsu[v]);
        if (sdom[min_v[dsu[v]]] < sdom[min_v[v]]) {
            min_v[v] = min_v[dsu[v]];
        }
        dsu[v] = next_v;
        return next_v;
    }

    void merge(int from, int to) {
        dsu[from] = to;
    }

    DominatorTree(int n, int root): n(n),
    ↪ root(root), dsu(n) {
        tin.resize(n, -1);
        revin.resize(n, -1);
        sdom.resize(n);
        idom.resize(n);
        g.resize(n);
        revg.resize(n);
        dsu.resize(n);
        parent.assign(n, -1);
        min_v.assign(n, -1);
        for (int i = 0; i < n; ++i) {
            dsu[i] = i;
            min_v[i] = i;
            sdom[i] = i;
            idom[i] = i;
        }
    }

    void dfs(int v, vector<vector<int>>& cur_g, int&
    ↪ timer) {
        tin[v] = timer++;
        for (int to: cur_g[v]) {
            if (tin[to] == -1) {
                dfs(to, cur_g, timer);
                parent[tin[to]] = tin[v];
            }
            revg[tin[to]].push_back(tin[v]);
        }
    }

    vector<int> get_tree(vector<vector<int>> cur_g) {
        vector<char> used(n, false);
        int timer = 0;
        dfs(root, cur_g, timer);
        for (int i = 0; i < n; ++i) {
            if (tin[i] == -1) {
                continue;
            }
            revin[tin[i]] = i;
            for (int to: cur_g[i]) {
                g[tin[i]].push_back(tin[to]);
            }
        }

        vector<vector<int>> buckets(n);
        for (int i = n - 1; i >= 0; --i) {
            for (int to: revg[i]) {
                get(to);
                sdom[i] = min(sdom[i], sdom[min_v[to]]);
            }
        }
    }
}

```

```

    }
    if (revin[i] == -1) {
        continue;
    }
    if (i) {
        buckets[sdom[i]].push_back(i);
    }
    for (int w : buckets[i]) {
        get(w);
        int v = min_v[w];
        if (sdom[v] == sdom[w]) {
            idom[w] = sdom[w];
        } else {
            idom[w] = v;
        }
    }
    for (int to : g[i]) {
        if (parent[to] == i) {
            merge(to, i);
        }
    }
}
for (int i = 0; i < n; ++i) {
    if (revin[i] == -1) {
        continue;
    }
    if (idom[i] == sdom[i]) {
        continue;
    } else {
        idom[i] = idom[idom[i]];
    }
}

vector<int> res(n, -1);
for (int i = 0; i < n; ++i) {
    if (revin[i] == -1) {
        continue;
    }
    res[revin[i]] = revin[idom[i]];
}
return res;
}
};

```

## 5.4 edmonds\_matching.h

```

// O(N^3)
int n;
vi e[maxn];
int mt[maxn], p[maxn], base[maxn], b[maxn], blos[maxn];
int q[maxn];
int blca[maxn]; // used for lca

int lca(int u, int v) {
    for (i, n) blca[i] = 0;
    while (true) {
        u = base[u];
        blca[u] = 1;
        if (mt[u] == -1) break;
        u = p[mt[u]];
    }
    while (!blca[base[v]]) {
        v = p[mt[base[v]]];
    }
    return base[v];
}

void mark_path(int v, int b, int ch) {
    while (base[v] != b) {
        blos[base[v]] = blos[base[mt[v]]] = 1;
        p[v] = ch;
        ch = mt[v];
        v = p[mt[v]];
    }
}

int find_path(int root) {
    for (i, n) {
        base[i] = i;
        p[i] = -1;
        b[i] = 0;
    }
    b[root] = 1;
    q[0] = root;

```

```

    int lq = 0, rq = 1;
    while (lq != rq) {
        int v = q[lq++];
        for (int to : e[v]) {
            if (base[v] == base[to] || mt[v] == to) ←
                continue;
            if (to == root || (mt[to] != -1 && ←
                p[mt[to]] != -1)) {
                int curbase = lca(v, to);
                for (i, n) blos[i] = 0;
                mark_path(v, curbase, to);
                mark_path(to, curbase, v);
                for (i, n) if (blos[base[i]]) {
                    base[i] = curbase;
                    if (!b[i]) b[i] = 1, q[rq++] = i;
                }
            } else if (p[to] == -1) {
                p[to] = v;
                if (mt[to] == -1) {
                    return to;
                }
                to = mt[to];
                b[to] = 1;
                q[rq++] = to;
            }
        }
    }
    return -1;
}

int matching() {
    for (i, n) mt[i] = -1;
    int res = 0;
    for (i, n) if (mt[i] == -1) {
        int v = find_path(i);
        if (v != -1) {
            ++res;
            while (v != -1) {
                int pv = p[v], ppv = mt[p[v]];
                mt[v] = pv, mt[ppv] = v;
                v = ppv;
            }
        }
    }
    return res;
}

```

## 5.5 euler\_cycle.h

```

struct Edge {
    int to, id;
};

bool usedEdge[maxn];
vector<Edge> g[maxn];
int ptr[maxn];

vector<int> cycle;
void eulerCycle(int u) {
    while (ptr[u] < sz(g[u]) && ←
        usedEdge[g[u][ptr[u]].id])
        ++ptr[u];
    if (ptr[u] == sz(g[u]))
        return;
    const Edge &e = g[u][ptr[u]];
    usedEdge[e.id] = true;
    eulerCycle(e.to);
    cycle.push_back(e.id);
    eulerCycle(u);
}

```

## 6 maths

### 6.1 berlekamp.h

```

vector<int> massey(vector<int> dp) {
    //dp.erase(dp.begin(), dp.begin() + 1);
    vector<int> C(1, 1);
    int L = 0;
    vector<int> B(1, 1);
    int b = 1;

```

```

for (int n = 0; n < dp.size(); ++n) {
    int d = 0;
    for (int i = 0; i <= L; ++i) {
        d += C[i] * dp[n - i];
        d %= mod;
        if (d < 0) {
            d += mod;
        }
    }
    B.insert(B.begin(), 0);
    if (d == 0) {
        continue;
    }
    auto prevC = C;
    if (C.size() < B.size()) {
        C.resize(B.size(), 0);
    }
    int cur_mult = d * binpow(b, mod - 2) % mod;
    for (int i = 0; i < B.size(); ++i) {
        C[i] -= B[i] * cur_mult;
        C[i] %= mod;
        if (C[i] < 0) {
            C[i] += mod;
        }
    }
    if (2 * L <= n) {
        b = d;
        L = n - L + 1;
        B = prevC;
    }
}
return C;
}

```

## 6.2 crt.h

```

inline int inv(int a, int b) {
    return a == 1 ? 1 : b - 111 * inv(b % a, a) * b
    ↪ / a % b;
}

pair<int, int> euc(int a, int b) {
    // returns {x, y} s.t. ax + by = g
    int g = __gcd(a, b);
    a /= g, b /= g;
    int x = inv(a, b);
    int y = (1 - 111 * a * x) / b;

    return {x, y};
}

// be careful if the whole base is long long
pair<int, int> crt(const vector<int>& mods,
    ↪ vector<int>& rems) {
    int rem = 0, mod = 1;
    for (int i = 0; i < (int)mods.size(); ++i) {
        long long g = __gcd(mods[i], mod);
        if (rem % g != rems[i] % g) {
            return {-1, -1};
        }

        int k = euc(mod, mods[i]).first * 111 *
        ↪ (rems[i] - rem + mods[i]) % mods[i];
        if (k < 0) {
            k += mods[i];
        }
        rem += mod / g * k;
        mod = mod / g * mods[i];
    }
    return {rem, mod};
}

```

## 6.3 gauss\_bitset\_inverse.h

```

const int N = 100;
using Bs = bitset<N>;
using Matrix = vector<Bs>;

Matrix getInverse(Matrix a) {
    assert(!a.empty());
    int n = a.size();

    Matrix b(n);

```

```

for (int i = 0; i < n; ++i) {
    b[i][i] = 1;
}

int row = 0;
for (int col = 0; col < n; ++col) {
    if (!a[row][col]) {
        int i = row + 1;
        while (i < n && !a[i][col]) {
            ++i;
        }
        if (i == n) {
            return {}; // assert(false);
            ↪ throw PoshelNahuiException();
            ↪ etc
        }
        swap(a[i], a[row]);
        swap(b[i], b[row]);
    }

    for (int i = row + 1; i < n; ++i) {
        if (a[i][col]) {
            a[i] ^= a[row];
            b[i] ^= b[row];
        }
    }

    ++row;
}

for (int i = n - 1; i >= 0; --i) {
    for (int j = 0; j < i; ++j) {
        if (a[j][i]) {
            a[j] ^= a[i];
            b[j] ^= b[i];
        }
    }
}

return b;
}

```

## 6.4 gauss\_bitset\_solve\_slu.h

```

const int N = 100;
using Bs = bitset<N>;
using Matrix = vector<Bs>;

Bs solveLinearSystem(Matrix a, Bs b) {
    // solves Av = b
    assert(!a.empty());
    int n = a.size();

    int row = 0;
    vector<int> cols(n);
    for (int col = 0; col < N; ++col) {
        if (row == n) {
            break;
        }
        if (!a[row][col]) {
            int i = row + 1;
            while (i < n && !a[i][col]) {
                ++i;
            }
            if (i == n) {
                continue;
            }
            swap(a[i], a[row]);
            b[i] = b[i] ^ b[row];
            b[row] = b[row] ^ b[i];
            b[i] = b[i] ^ b[row];
        }

        for (int i = row + 1; i < n; ++i) {
            if (a[i][col]) {
                a[i] ^= a[row];
                b[i] = b[i] ^ b[row];
            }
        }

        cols[row] = col;
        ++row;
    }
}

```



```

for (int i = row; i < n; ++i) {
    if (b[i]) {
        return {}; // assert(false); throw
        ↪ PoshelNahuiException(); etc
    }
}

Bs result = {};
while (row) {
    --row;
    for (int i = cols[row] + 1; i < N; ++i) {
        b[row] = b[row] ^ (a[row][i] * result[i]);
    }
    result[cols[row]] = b[row];
}

return result;
}

```

## 6.5 gauss\_double\_inverse.h

```

using Matrix = vector<vector<ld>>;

const ld eps = 1e-6;

Matrix getInverse(Matrix a) {
    assert(!a.empty());
    int n = a.size();
    assert(n == (int)a[0].size());

    Matrix b(n, vector<ld>(n, 0));
    for (int i = 0; i < n; ++i) {
        b[i][i] = 1;
    }

    int row = 0;
    for (int col = 0; col < n; ++col) {
        if (abs(a[row][col]) < eps) {
            int i = row + 1;
            while (i < n && abs(a[i][col]) < eps) {
                ++i;
            }
            if (i == n) {
                return {}; // assert(false);
                ↪ throw PoshelNahuiException();
                ↪ etc
            }
            a[i].swap(a[row]);
            b[i].swap(b[row]);
        }

        for (int i = row + 1; i < n; ++i) {
            ld k = a[i][col] / a[row][col];
            for (int j = col; j < n; ++j) {
                a[i][j] -= k * a[row][j];
            }
            for (int j = 0; j < n; ++j) {
                b[i][j] -= k * b[row][j];
            }
        }

        ++row;
    }

    for (int i = n - 1; i >= 0; --i) {
        for (int j = 0; j < i; ++j) {
            ld k = a[j][i] / a[i][i];
            for (int l = 0; l < n; ++l) {
                a[j][l] -= a[i][l] * k;
                b[j][l] -= b[i][l] * k;
            }
        }
        ld k = a[i][i];
        for (int l = 0; l < n; ++l) {
            b[i][l] /= k;
        }
        a[i][i] /= k;
    }

    return b;
}

```

## 6.6 gauss\_double\_solve\_slu.h

```

using Matrix = vector<vector<ld>>;

const ld eps = 1e-6;

vector<ld> solveLinearSystem(Matrix a, vector<ld> b) {
    // solves Av = b
    assert(!a.empty());
    int n = a.size(), m = a[0].size();
    assert(n == (int)b.size());

    int row = 0;
    vector<int> cols(n);
    for (int col = 0; col < m; ++col) {
        if (row == n) {
            break;
        }
        if (abs(a[row][col]) < eps) {
            int i = row + 1;
            while (i < n && abs(a[i][col]) < eps) {
                ++i;
            }
            if (i == n) {
                continue;
            }
            a[i].swap(a[row]);
            swap(b[i], b[row]);
        }

        for (int i = row + 1; i < n; ++i) {
            ld k = a[i][col] / a[row][col];
            for (int j = col; j < m; ++j) {
                a[i][j] -= k * a[row][j];
            }
            b[i] -= b[row] * k;
        }

        cols[row] = col;
        ++row;
    }

    for (int i = row; i < n; ++i) {
        if (abs(b[i]) < eps) {
            return {}; // assert(false); throw
            ↪ PoshelNahuiException(); etc
        }
    }

    vector<ld> result(m);
    while (row) {
        --row;
        for (int i = cols[row] + 1; i < m; ++i) {
            b[row] -= a[row][i] * result[i];
        }
        result[cols[row]] = b[row] / a[row][cols[row]];
    }

    return result;
}

```

## 6.7 miller\_rabin\_test.h

```

bool millerRabinTest(ll n, ll a) {
    if (gcd(n, a) > 1)
        return false;
    ll x = n - 1;
    int l = 0;
    while (x % 2 == 0) {
        x /= 2;
        ++l;
    }
    ll c = binpow(a, x, n);
    for (int i = 0; i < l; ++i) {
        ll nx = mul(c, c, n);
        if (nx == 1) {
            if (c != 1 && c != n - 1)
                return false;
            else
                return true;
        }
        c = nx;
    }
    return c == 1;
}

```

}

## 7 misc

### 7.1 ch\_trick\_with\_binary\_summation\_struct.cpp

```

const int INF = (int)1e6;

struct Line {
    int k;
    li b;
    bool operator < (const Line& ot) const {
        if (k != ot.k) {
            return k > ot.k;
        }
        return b < ot.b;
    }
    li eval(li x) {
        return k * 1LL * x + b;
    }
};

double get_intersect(Line& q, Line& w) {
    return (q.b - w.b) / 1.0 / (w.k - q.k);
}

struct Hull {
    vector<Line> lines;
    vector<double> borders;
    int Size = 0;
    void append(Line cur) {
        lines.push_back(cur);
    }
    void set_size(int val) {
        Size = val;
    }
    void build() {
        sort(all(lines));
        borders.clear();
        vector<Line> new_lines;
        for (auto& line : lines) {
            if (!new_lines.empty() && new_lines.back().k
                == line.k) {
                continue;
            }
            while (new_lines.size() > 1 &&
                get_intersect(new_lines[new_lines.size() -
                2], new_lines.back()) >
                get_intersect(new_lines.back(), line)) {
                new_lines.pop_back();
                borders.pop_back();
            }
            if (new_lines.empty()) {
                borders.push_back(-INF);
            } else {
                borders.push_back(get_intersect(new_lines.back(),
                line));
            }
            new_lines.push_back(line);
        }
        new_lines.swap(lines);
    }
    int size() {
        return Size;
    }
    li get_min(li x) {
        int id = (int)(lower_bound(all(borders),
            (double)x - borders.begin());
        li res = (li)1e18;
        for (int i = max(id - 1, 0); i < min(id + 2,
            (int)lines.size()); ++i) {
            res = min(res, lines[i].eval(x));
        }
        return res;
    }
};

struct Lupa {
    vector<Hull> hulls;
    int Size = 0;
    void append_line(Line cur) {

```

```

        hulls.push_back(Hull());
        hulls.back().append(cur);
        hulls.back().set_size(1);
        while (hulls.size() >= 2 && hulls.back().size()
            == hulls[hulls.size() - 2].size()) {
            for (auto& item : hulls.back().lines) {
                hulls[hulls.size() - 2].append(item);
            }
            hulls.pop_back();
            hulls.back().set_size(hulls.back().size() * 2);
        }
        hulls.back().build();
        ++Size;
    }
    li get_min(li x) {
        li res = (li)1e18;
        for (auto& vec : hulls) {
            res = min(res, vec.get_min(x));
        }
        return res;
    }
    int size() {
        return Size;
    }
    void merge_with(Lupa& ot) {
        for (auto& vec : ot.hulls) {
            for (auto& item : vec.lines) {
                append_line(item);
            }
            vec.lines.clear();
        }
    }
    void make_swap(Lupa& ot) {
        swap(ot.Size, Size);
        ot.hulls.swap(hulls);
    }
};

```

### 7.2 cht\_stl.cpp

```

const li is_query = -(1LL << 62);

struct Line {
    // mx + b
    li m, b;
    mutable function<const Line *(>> succ;

    bool operator<(const Line &rhs) const {
        if (rhs.b != is_query) return m < rhs.m;
        const Line *s = succ();
        if (!s) return 0;
        li x = rhs.m;
        return b - s->b < (s->m - m) * x;
    }
};

using LI = __int128_t; // or long double; long long
// WARNING: don't try to swap this structure (e.g.
// in lower to greater):
// it will make next iterators inconsistent and SIGSEGV
struct HullDynamic : public multiset<Line> {
    bool bad(iterator y) {
        auto z = next(y);
        if (y == begin()) {
            if (z == end()) return 0;
            return y->m == z->m && y->b <= z->b;
        }
        auto x = prev(y);
        if (z == end()) return y->m == x->m && y->b
            <= x->b;
        return (x->b - y->b) * (LI)(z->m - y->m) >=
            (y->b - z->b) * (LI)(y->m - x->m);
    }
    void insert_line(li m, li b) {
        auto y = insert({m, b});
        y->succ = [=] { return next(y) == end() ? 0
            : &*next(y); };
        if (bad(y)) {
            erase(y);
        }
    }
};

```

```

        return;
    }
    while (next(y) != end() && bad(next(y)))
        ↪ erase(next(y));
    while (y != begin() && bad(prev(y)))
        ↪ erase(prev(y));
}

li getMax(li x) {
    auto l = *lower_bound((Line) {x, is_query});
    return l.m * x + l.b;
}
};

```

### 7.3 tree\_bidirectional\_dp.h

```

/* For any commutative function f({x, y, ..., z}) =
↪ f(x, f(y, f(..., z)))
* like sum, min, max, or, xor, and, etc
* calculates in dp[i][j] f(subtree),
* where subtree is a connectivity component of G \
↪ (i, a[i][j]) with vertex a[i][j]
*/

const int N = 222222;
vector<int> a[N];
vector<int> dp[N];
int par[N];

#define data asdf
int data[N];

inline int f(int x, int y) {
    return x | y;
}

int dfsDown(int v) {
    int res = data[v];
    for (int i = 0; i < (int)a[v].size(); ++i) {
        int to = a[v][i];
        if (to == par[v]) {
            continue;
        }
        par[to] = v;
        res = f(res, dp[v][i] = dfsDown(to));
    }
    return res;
}

void dfsUp(int v, int to_parent = 0) {
    vector<int> pref, suf;
    pref.reserve(a[v].size());
    suf.reserve(a[v].size());
    int j = 0;
    for (int i = 0; i < (int)a[v].size(); ++i) {
        int to = a[v][i];
        if (to == par[v]) {
            dp[v][i] = to_parent;
            continue;
        }
        pref.push_back(j ? f(pref[j - 1], dp[v][i])
        ↪ : dp[v][i]);
        ++j;
    }
    j = 0;
    for (int i = (int)a[v].size() - 1; i >= 0; --i) {
        int to = a[v][i];
        if (to == par[v]) {
            continue;
        }
        suf.push_back(j ? f(dp[v][i], suf[j - 1]) :
        ↪ dp[v][i]);
        ++j;
    }
    reverse(all(suf));

    j = 0;
    to_parent = f(to_parent, data[v]);
    for (int i = 0; i < (int)a[v].size(); ++i) {
        int to = a[v][i];
        if (to == par[v]) {
            continue;
        }
    }
}

```

```

    int new_to_parent = to_parent;
    if (j > 0) {
        new_to_parent = f(pref[j - 1],
        ↪ new_to_parent);
    }
    if (j < (int)suf.size() - 1) {
        new_to_parent = f(new_to_parent, suf[j +
        ↪ 1]);
    }
    dfsUp(to, new_to_parent);
    ++j;
}
}

```

### 7.4 tree\_order\_statistics.cpp

```

#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
#include <bits/stdc++.h>

using namespace std;
using namespace __gnu_pbds;

using orderedSet = tree<
    int,
    null_type,
    less<int>,
    rb_tree_tag,
    tree_order_statistics_node_update
>;

int main() {
    orderedSet X;
    X.insert(1);
    X.insert(2);
    X.insert(4);
    X.insert(8);
    X.insert(16);

    std::cout << *X.find_by_order(1) << std::endl; // 2
    std::cout << *X.find_by_order(2) << std::endl; // 4
    std::cout << *X.find_by_order(4) << std::endl; // 16
    std::cout << std::boolalpha <<
        (end(X) == X.find_by_order(6)) << std::endl;
    ↪ // true

    std::cout << X.order_of_key(-5) << std::endl; // 0
    std::cout << X.order_of_key(1) << std::endl; // 0
    std::cout << X.order_of_key(3) << std::endl; // 2
    std::cout << X.order_of_key(4) << std::endl; // 2
    std::cout << X.order_of_key(400) << std::endl; // 5
}

```

## 8 numeric

### 8.1 integration.cpp

```

template<typename F>
F integrate(F (*f)(F), F a, F b, int nodes) {
    F d = (b - a) / (nodes + 1);
    F ans = 0;
    for (int i = 0; i < nodes + 1; ++i) {
        F L = a, R = a + d;
        ans += d * (f(L) + f(R) + 4 * f(0.5 * (L + R))) / 6;
        a = R;
    }
    return ans;
}

```

### 8.2 simplex.cpp

```

//indexes
//0: constant
//1..N: non-basic variables
//N+1..B+N+1: basic variables
template<typename F>
class CanonicalSolver {
public:
    static F* solve_feasible(int B, int N, int * lhs,
        F ** rhs, F * func, F eps) {
        F * values = new F[B + N + 1];
        memset(values, 0, sizeof(F) * (B + N + 1));
    }
}

```

```

for(int i = 0; i < B; i++)
    values[lhs[i]] = rhs[i][0];
values[0] = 1;
bool * basis = new bool[B + N + 1];
memset(basis, 0, sizeof(bool) * (B + N + 1));
while(1){
    int pos = -1;
    for(int i = 0; i < B; i++)
        basis[lhs[i]] = 1;
    for(int i = 1; i < B + N + 1; i++){
        if(basis[i] || func[i] < eps)
            continue;
        if(pos == -1 || func[i] > func[pos])
            pos = i;
    }
    for(int i = 0; i < B; i++)
        basis[lhs[i]] = 0;
    if(pos == -1)break;
    F bnd = 0;
    bool was = 0;
    int what = 0;
    for(int i = 0; i < B; i++){
        if(rhs[i][pos] > -eps)
            continue;
        F curr = values[lhs[i]];
        curr /= -rhs[i][pos];
        if(!was || bnd > curr){
            was = 1;
            what = i;
            bnd = curr;
        }
    }
    if(!was)
        return nullptr;
    for(int i = 0; i < B; i++)
        values[lhs[i]] += bnd * rhs[i][pos];
    int old = lhs[what];
    lhs[what] = pos;
    values[pos] += bnd;
    F oldval = 1/rhs[what][pos];
    for(int i = 0; i < 1 + B + N; i++){
        rhs[what][i] *= -oldval;
        rhs[what][old] = oldval;
        rhs[what][pos] = 0;
    }
    for(int i = 0; i < B; i++){
        if(i == what)
            continue;
        F coeff = rhs[i][pos];
        rhs[i][pos] = 0;
        for(int j = 0; j < 1 + B + N; j++)
            rhs[i][j] += rhs[what][j] * coeff;
    }
    F coeff = func[pos];
    func[pos] = 0;
    for(int j = 0; j < 1 + B + N; j++)
        func[j] += rhs[what][j] * coeff;
}
delete[] basis;
return values;
}
//0: solution exists
//1: unbounded
//-1: unfeasible
static pair<F*, int> solve(int B, int N, int * lhs,
    F ** rhs, F * func, F eps){
    bool fea = 1;
    for(int i = 0; i < B; i++)
        if(rhs[i][0] < -eps){fea = 0; break;}
    if(fea){
        auto res = solve_feasible(B, N, lhs, rhs,
            func, eps);
        return res == nullptr ? make_pair(res, 1) :
            make_pair(res, 0);
    }
    int pos = 0;
    for(int i = 1; i < B; i++)
        if(rhs[i][0] < rhs[pos][0])
            pos = i;
    int * new_lhs = new int[B];
    memcpy(new_lhs, lhs, B * sizeof(int));
    F ** new_rhs = (F**)malloc(B * sizeof(F*));
    for(int i = 0; i < B; i++){
        new_rhs[i] = (F*)malloc((2 + B + N) *
            sizeof(F));
        memcpy(new_rhs[i], rhs[i], (1 + B + N) *
            sizeof(F));
        new_rhs[i][1 + B + N] = 1;
    }
    F * new_func = new F[2 + N + B];
    memset(new_func, 0, sizeof(F) * (2 + N + B));
    new_rhs[pos][1 + N + B] = 0;
    for(int j = 0; j < 2 + N + B; j++)
        new_rhs[pos][j] = -new_rhs[pos][j];
    new_rhs[pos][lhs[pos]] = 1;
    new_lhs[pos] = 1 + N + B;
    for(int i = 0; i < B; i++){
        if(pos == i)
            continue;
        new_rhs[i][1 + N + B] = 0;
        for(int j = 0; j < 1 + N + B; j++)
            new_rhs[i][j] += new_rhs[pos][j];
    }
    for(int i = 0; i < 1 + N + B; i++)
        new_func[i] = -new_rhs[pos][i];
    auto res_lambda = solve_feasible(B, N + 1,
        new_lhs,
        new_rhs, new_func, eps);
    if(res_lambda == nullptr)
        return make_pair(nullptr, -1);
    F cres = 0;
    for(int i = 0; i < 2 + N + B; i++)
        cres += res_lambda[i] * new_func[i];
    if(abs(cres) > eps)
        return make_pair(nullptr, -1);
    int bpos = -1;
    for(int i = 0; i < B; i++)
        if(new_lhs[i] == 1 + N + B){
            bpos = i;
            break;
        }
    if(bpos == -1){
        memcpy(lhs, new_lhs, B * sizeof(int));
        for(int i = 0; i < B; i++)
            memcpy(rhs[i], new_rhs[i], (1 + B + N) *
                sizeof(F));
        memcpy(new_func, func, (1 + B + N) *
            sizeof(F));
        for(int i = 0; i < B; i++){
            F coeff = func[new_lhs[i]];
            new_func[new_lhs[i]] = 0;
            for(int j = 0; j < 1 + B + N; j++)
                new_func[j] += coeff *
                    new_rhs[i][j];
        }
        memcpy(func, new_func, (1 + B + N) *
            sizeof(F));
        auto res = solve_feasible(B, N, lhs, rhs,
            func, eps);
        return res == nullptr ? make_pair(res, 1) :
            make_pair(res, 0);
    }
    int with_what = -1;
    for(int i = 1; i < 1 + N + B; i++){
        if(abs(new_rhs[bpos][i]) > eps){
            with_what = i;
            break;
        }
    }
    F coeff = -new_rhs[bpos][with_what];
    new_rhs[bpos][with_what] = 0;
    new_rhs[bpos][new_lhs[bpos]] = -1;
    new_lhs[bpos] = with_what;
    for(int j = 0; j < 2 + N + B; j++)
        new_rhs[bpos][j] /= coeff;
    for(int i = 0; i < B; i++){
        if(i == bpos)
            continue;
        F coeff = new_rhs[i][with_what];
        for(int j = 0; j < 2 + N + B; j++)
            new_rhs[i][j] += coeff *
                new_rhs[bpos][j];
    }
    memcpy(lhs, new_lhs, B * sizeof(int));
    for(int i = 0; i < B; i++)
        memcpy(rhs[i], new_rhs[i], (1 + B + N) *
            sizeof(F));
    memcpy(new_func, func, (1 + B + N) * sizeof(F));

```

```

    for(int i = 0; i < B; i++){
        F coeff = func[new_lhs[i]];
        new_func[new_lhs[i]] = 0;
        for(int j = 0; j < 1 + B + N; j++){
            new_func[j] += coeff * new_rhs[i][j];
        }
        memcpy(func, new_func, (1 + B + N) * sizeof(F));
        auto res = solve_feasible(B, N, lhs, rhs,
            func, eps);
        return res == nullptr ? make_pair(res, 1) :
            make_pair(res, 0);
    }
};

```

## 9 strings

### 9.1 aho\_corasick.h

```

const int ALPHABET = 26;

struct state {
    array<int, ALPHABET> transition = {};
    int link = 0;

    bool isTerminal = false;
};

struct automaton {
    vector<state> states = { state() };
    int numStates = 1;

    void addString(const string& s) {
        int cur = 0;
        for (char c: s) {
            c -= 'a';
            int& to = states[cur].transition[c];
            if (to) {
                cur = to;
            }
            else {
                cur = to = states.size();
                states.push_back(state());
            }
        }
        states[cur].isTerminal = true;
    }

    void build() {
        deque<int> q;
        q.push_back(0);

        while (!q.empty()) {
            int v = q.front();
            q.pop_front();
            states[v].isTerminal =
                states[v].isTerminal ||
                states[states[v].link].isTerminal;

            for (int c = 0; c < ALPHABET; ++c) {
                if (int u = states[v].transition[c]) {
                    states[u].link = v ?
                        states[states[v].link].transition[c]
                        : 0;
                    q.push_back(u);
                }
                else {
                    states[v].transition[c] =
                        states[states[v].link].transition[c];
                }
            }
        }
    }
};

```

### 9.2 manacher.h

```

array<vector<int>, 2> manacher(const string& s) {
    int n = s.length();
    array<vector<int>, 2> res;
    for (auto& v : res) {
        v.assign(n, 0);
    }
}

```

```

for (int z = 0, l = 0, r = 0; z < 2; ++z, l = 0,
    r = 0) {
    for (int i = 0; i < n; ++i) {
        if (i < r) {
            res[z][i] = min(r - i + !z, res[z][l
                + r - i + !z]);
        }
        int L = i - res[z][i], R = i + res[z][i]
            - !z;
        while (L - 1 >= 0 && R + 1 < n && s[L -
            1] == s[R + 1]) {
            ++res[z][i];
            --L;
            ++R;
        }
        if (R > r) {
            l = L;
            r = R;
        }
    }
}
return res;
}

```

### 9.3 palindromes\_on\_subsegment.h

```

struct Node {
    int len;
    int link;
    vector<int> trans;
    bool all_equal;
    Node() {
        len = 0;
        link = 0;
        trans.assign(26, -1);
        all_equal = true;
    }
};

struct Eertree {
    vector<Node> nodes;
    vector<int> one_len;
    Eertree() {
        nodes.push_back(Node());
        one_len.assign(26, -1);
    }

    vector<int> feed_string(const string& s) {
        int v = 0;
        int n = s.length();
        vector<int> state(n);
        for (int i = 0; i < s.length(); ++i) {
            int c = s[i] - 'a';
            bool flag = false;
            while (v) {
                if (nodes[v].all_equal && s[i] ==
                    s[i - 1]) {
                    if (nodes[v].trans[c] == -1) {
                        nodes[v].trans[c] =
                            nodes.size();
                        nodes.push_back(Node());
                        nodes.back().len =
                            nodes[v].len + 1;
                        nodes.back().all_equal = true;
                        nodes.back().link = v;
                    }
                    v = nodes[v].trans[c];
                    flag = true;
                    break;
                }
            }
            if (i > nodes[v].len && s[i] == s[i
                - nodes[v].len - 1]) {
                if (nodes[v].trans[c] == -1) {
                    nodes[v].trans[c] =
                        nodes.size();
                    nodes.push_back(Node());
                    nodes.back().len =
                        nodes[v].len + 2;
                    nodes.back().link = -1;
                    nodes.back().all_equal = false;
                    int cur_v = nodes[v].link;
                    while (cur_v) {

```

```

    if (nodes[cur_v].trans[c] != -1) {
        int cand = nodes[cur_v].trans[c];
        if (s[i] == s[i - nodes[cand].len + 1]) {
            nodes.back().link = nodes[cur_v].trans[c];
            break;
        }
    }
    cur_v = nodes[cur_v].link;
}
if (nodes.back().link == -1) {
    if (nodes[cur_v].trans[c] != -1) {
        nodes.back().link = nodes[cur_v].trans[c];
    } else {
        nodes[cur_v].link = 0;
    }
}
v = nodes[v].trans[c];
flag = true;
break;
}
v = nodes[v].link;
}
if (!flag) {
    if (one_len[c] == -1) {
        nodes[v].trans[c] = nodes.size();
        nodes.push_back(Node());
        nodes.back().len = 1;
        one_len[c] = nodes[v].trans[c];
        nodes.back().all_equal = true;
        nodes.back().link = 0;
    } else {
        nodes[v].trans[c] = one_len[c];
    }
    v = nodes[v].trans[c];
}
state[i] = v;
}
return state;
}

void enclose() {
    for (int v = 0; v < nodes.size(); ++v) {
        for (int c = 0; c < 26; ++c) {
            if (nodes[v].trans[c] == -1) {
                int cur_v = nodes[v].link;
                while (true) {
                    if (nodes[cur_v].trans[c] != -1) {
                        nodes[v].trans[c] = nodes[cur_v].trans[c];
                        break;
                    }
                    if (cur_v == 0) {
                        nodes[v].trans[c] = 0;
                        break;
                    }
                    cur_v = nodes[cur_v].link;
                }
            }
        }
    }
}

struct Query {
    int l, r;
    int id;
    bool operator < (const Query& ot) const {
        if (r != ot.r) {
            return r < ot.r;
        }
    }
};

void solve(bool read) {
    string s;
    cin >> s;
    Eertree tree;
    tree.feed_string(s);
    tree.enclose();
    int Q;
    cin >> Q;
    int n = s.length();
    int block_size = max((int)(sqrt(n) * 1.5), 1);
    int blocks = (n - 1) / block_size + 1;
    for (int i = 0; i < Q; ++i) {
        Query cur;
        cin >> cur.l >> cur.r;
        --cur.l;
        cur.id = i;
        q[cur.l / block_size].push_back(cur);
    }
    vector<int> ans(Q);
    vector<int> used(tree.nodes.size(), 0);
    vector<int> left_used(tree.nodes.size(), 0);
    int TIMER = 0;
    int LEFT_TIMER = 0;
    for (int block = 0; block < blocks; ++block) {
        sort(all(q[block]));
        int right_border = min((block + 1) * block_size, n);
        int uk = 0;
        while (uk < q[block].size() && q[block][uk].r < right_border) {
            ++TIMER;
            int res = 0;
            int v = 0;
            for (int pos = q[block][uk].l; pos < q[block][uk].r; ++pos) {
                v = tree.nodes[v].trans[s[pos] - 'a'];
                if (s[pos] != s[pos - tree.nodes[v].len + 1]) {
                    v = tree.nodes[v].link;
                }
                if (tree.nodes[v].len > pos + 1 - q[block][uk].l) {
                    v = tree.nodes[v].link;
                }
                if (used[v] != TIMER) {
                    ++res;
                    used[v] = TIMER;
                }
            }
            ans[q[block][uk].id] = res;
            ++uk;
        }
        int cur_r = right_border;
        int overall_pals = 0;
        int right_state = 0;
        int left_state = 0;
        ++TIMER;
        while (uk < q[block].size()) {
            while (cur_r < q[block][uk].r) {
                right_state = tree.nodes[right_state].trans[s[cur_r] - 'a'];
                if (s[cur_r] != s[cur_r - tree.nodes[right_state].len + 1]) {
                    right_state = tree.nodes[right_state].link;
                }
                if (tree.nodes[right_state].len > cur_r + 1 - right_border) {
                    right_state = tree.nodes[right_state].link;
                }
                if (used[right_state] != TIMER) {
                    ++overall_pals;
                    used[right_state] = TIMER;
                }
            }
        }
    }
}

```



```

    if (tree.nodes[right_state].len ==
        ↪ cur_r + 1 - right_border) {
        left_state = right_state;
    }
    ++cur_r;
}
++LEFT_TIMER;
int cur_l = right_border;
int cur_left_state = left_state;
int cur_res = overall_pals;
while (cur_l > q[block][uk].l) {
    --cur_l;
    cur_left_state =
        ↪ tree.nodes[cur_left_state].trans[s[cur_l]
        ↪ - 'a'];
    if (s[cur_l] != s[cur_l +
        ↪ tree.nodes[cur_left_state].len -
        ↪ 1]) {
        cur_left_state =
            ↪ tree.nodes[cur_left_state].link;
    }
    if (tree.nodes[cur_left_state].len >
        ↪ cur_r - cur_l) {
        cur_left_state =
            ↪ tree.nodes[cur_left_state].link;
    }
    if (used[cur_left_state] != TIMER &&
        ↪ left_used[cur_left_state] !=
        ↪ LEFT_TIMER) {
        ++cur_res;
        left_used[cur_left_state] =
            ↪ LEFT_TIMER;
    }
}
ans[q[block][uk].id] = cur_res;
++uk;
}
}
for (int i = 0; i < Q; ++i) {
    cout << ans[i] << "\n";
}
}

```

## 9.4 prefix\_function.h

```

void prefixFunction(const string& s, vector<int>& p) {
    if (s.length() == 0)
        return;
    p[0] = 0;
    for (size_t i = 1; i < s.length(); ++i) {
        int j = p[i - 1];
        while (j > 0 && s[i] != s[j])
            j = p[j - 1];
        if (s[i] == s[j])
            ++j;
        p[i] = j;
    }
}

const char first = 'a';
const int alphabet = 26;
// вылазит из массива, после того, как совпадет все.
↪ можно добавить aut[n] = aut[p[n - 1]]
// это сэмулирует переход по суф ссылке
vector<vi> pfautomaton(const string& s) {
    vi p(s.length());
    prefixFunction(s, p);
    vector<vi> aut(s.length(), vi(alphabet));
    for (size_t i = 0; i < s.length(); ++i) {
        for (char c = 0; c < alphabet; ++c) {
            if (i > 0 && c != s[i] - first) {
                aut[i][c] = aut[p[i - 1]][c];
            }
            else {
                aut[i][c] = i + (c == s[i] - first);
            }
        }
    }
    return aut;
}

```

## 9.5 suffix\_array.cpp

```

void Build(const string& init, vector<int>&
    ↪ suffArray, vector<int>& lcp) {
    string s = init;
    s.push_back(char(0));
    int n = s.size();
    vector<int> head(max(n, 256));
    vector<int> color(n);
    vector<int> colorSub(n);
    vector<int> suffArraySub(n);
    lcp.resize(n);
    suffArray.resize(n);

    for (int i = 0; i < s.size(); ++i) {
        ++head[s[i]];
    }
    for (int i = 1; i < 256; ++i) {
        head[i] += head[i - 1];
    }
    for (int i = 255; i > 0; --i) {
        head[i] = head[i - 1];
    }
    head[0] = 0;
    for (int i = 0; i < s.size(); ++i) {
        suffArray[head[s[i]]] = i;
        ++head[s[i]];
    }
    int numClasses = 1;
    head[0] = 0;
    for (int i = 1; i < s.size(); ++i) {
        if (s[suffArray[i - 1]] != s[suffArray[i]]) {
            ++numClasses;
            head[numClasses - 1] = i;
        }
        color[suffArray[i]] = numClasses - 1;
    }
    for (int k = 1; k < s.size(); k *= 2) {
        for (int i = 0; i < s.size(); ++i) {
            int first = suffArray[i] - k;
            if (first < 0) {
                first += s.size();
            }
            suffArraySub[head[color[first]]] = first;
            ++head[color[first]];
        }
        suffArray = suffArraySub;

        int second;
        pair<int, int> prevClasses, curClasses;
        curClasses = { -1, 0 };
        numClasses = 0;

        for (int i = 0; i < s.size(); ++i) {
            prevClasses = curClasses;

            second = suffArray[i] + k;
            if (second >= s.size()) {
                second -= s.size();
            }
            curClasses = { color[suffArray[i]],
                ↪ color[second] };

            if (curClasses != prevClasses) {
                ++numClasses;
                head[numClasses - 1] = i;
            }
            colorSub[suffArray[i]] = numClasses - 1;
        }

        color = colorSub;

        if (numClasses == s.size())
            break;
    }
    vector<int> pos;
    int curLcp = 0;
    pos.resize(s.size());
    for (int i = 0; i < s.size(); ++i) {
        pos[suffArray[i]] = i;
    }
    lcp.resize(s.size());
    for (int i = 0; i < s.size(); ++i) {
        if (pos[i] == s.size() - 1) {

```

```

        lcp[pos[i]] = 0;
        curLcp = 0;
        continue;
    }

    while (s[(i + curLcp) % s.size()] ==
        ↪ s[(suffArray[pos[i] + 1] + curLcp) %
        ↪ s.size()]]) {
        ↪ ++curLcp;
    }
    lcp[pos[i]] = curLcp;

    --curLcp;
    if (curLcp < 0)
        curLcp = 0;
}

void BuildSparseTable(const vector<int>& a, vector
    ↪ < vector<int> >& sparseTable) {
    ↪ int logSize = 0;
    while ((1 << logSize) < a.size()) {
        ↪ ++logSize;
    }
    logSize = 19; // <-- THINK HERE!
    sparseTable.assign(a.size(), vector<int>
        ↪ (logSize + 1));

    for (int i = 0; i < a.size(); ++i) {
        ↪ sparseTable[i][0] = a[i];
    }

    for (int k = 1; k <= logSize; ++k) {
        ↪ for (int i = 0; i + (1 << k) <= a.size(); ++i) {
            ↪ sparseTable[i][k] = min(sparseTable[i][k
            ↪ - 1], sparseTable[i + (1 << (k -
            ↪ 1))][k - 1]);
        }
    }
}

int GetMin(int l, int r, const vector< vector<int>
    ↪ >& sparseTable) {
    ↪ assert(l < r);
    int sz = 31 - __builtin_clz(r - l);
    ↪ return min(sparseTable[l][sz], sparseTable[r -
    ↪ (1 << sz)][sz]);
}

void solve(__attribute__((unused)) bool read) {
    string s;
    cin >> s;
    int n = s.length();
    vector<int> suffArray, lcp;
    Build(s, suffArray, lcp);
    suffArray.erase(suffArray.begin());
    lcp.erase(lcp.begin());
    vector<int> pos_in_array(n);
    for (int i = 0; i < suffArray.size(); ++i) {
        ↪ pos_in_array[suffArray[i]] = i;
    }
    vector<vector<int>> sparse;
    BuildSparseTable(lcp, sparse);
}

```

## 9.6 suffix\_automaton\_kostroma.h

```

const int UNDEFINED_VALUE = -1;

class SuffixAutomaton {
public:
    struct State {
        map<char, int> transitions;
        int link;
        int maxlen;
        int firstPos, lastPos;
        int cnt;
        State().link(UNDEFINED_VALUE),
            ↪ firstPos(UNDEFINED_VALUE),
            ↪ lastPos(UNDEFINED_VALUE), maxlen(0),
            ↪ cnt(0) {}
    };
};

```

```

vector<State> states;
int lastState;
SuffixAutomaton(const string& s) {
    states.push_back(State());
    lastState = 0;
    for (int i = 0; i < s.length(); ++i)
        append(s[i]);
    vector<pair<int, int>> p(states.size());
    for (int i = 0; i < p.size(); ++i) {
        ↪ p[i].second = i;
        ↪ p[i].first = states[i].maxLen;
    }
    sort(all(p));
    reverse(all(p));
    for (int i = 0; i < p.size(); ++i) {
        ↪ int curState = p[i].second;
        ↪ if (states[curState].lastPos ==
        ↪ UNDEFINED_VALUE)
            ↪ states[curState].lastPos =
            ↪ states[curState].firstPos;
        ↪ if (states[curState].link !=
        ↪ UNDEFINED_VALUE) {
            ↪ states[states[curState].link].lastPos
            ↪ =
            ↪ max(states[states[curState].link].lastPos,
            ↪ states[curState].lastPos);
            ↪ states[states[curState].link].cnt +=
            ↪ states[curState].cnt;
        }
    }
}

private:
void append(char c) {
    int curState = states.size();
    states.push_back(State());
    states[curState].maxLen =
        ↪ states[lastState].maxLen + 1;
    states[curState].firstPos =
        ↪ states[lastState].maxLen;
    states[curState].cnt = 1;
    int prevState = lastState;
    for (; prevState != UNDEFINED_VALUE;
        ↪ prevState = states[prevState].link) {
        ↪ if (states[prevState].transitions.count(c))
            ↪ break;
        ↪ states[prevState].transitions[c] = curState;
    }

    if (prevState == UNDEFINED_VALUE) {
        ↪ states[curState].link = 0;
    }
    else {
        int nextState =
            ↪ states[prevState].transitions[c];
        ↪ if (states[nextState].maxLen ==
        ↪ states[prevState].maxLen + 1) {
            ↪ states[curState].link = nextState;
        }
        else {
            int cloneState = states.size();
            states.push_back(State());
            states[cloneState].maxLen =
                ↪ states[prevState].maxLen + 1;
            states[cloneState].link =
                ↪ states[nextState].link;
            states[cloneState].firstPos =
                ↪ states[nextState].firstPos;
            states[curState].link =
                ↪ states[nextState].link =
                ↪ cloneState;

            states[cloneState].transitions =
                ↪ states[nextState].transitions;
            for (; prevState != UNDEFINED_VALUE
                ↪ &&
                ↪ states[prevState].transitions[c]
                ↪ == nextState; prevState =
                ↪ states[prevState].link)
                ↪ states[prevState].transitions[c]
                ↪ = cloneState;
        }
    }
}

```

```

    }
    lastState = curState;
}
};

```

## 9.7 suffix\_tree\_from\_automaton.cpp

```

struct SuffixTree {
    vector<vector<pair<int, int>>> g;
    vector<int> is_leaf, max_len;
    vector<int> leaves_before;
    vector<int> cnt_leaves;
    int n;
    SuffixTree(vector<int> s) {
        s.push_back(-1);
        reverse(all(s));
        n = s.size();
        auto automata = SuffixAutomaton(s);
        g.resize(automata.states.size());
        is_leaf.resize(automata.states.size(), 0);
        max_len.assign(g.size(), 0);
        cnt_leaves.assign(g.size(), 0);
        leaves_before.assign(g.size(), 0);
        for (int v = 1; v < automata.states.size(); ++v) {
            int p = automata.states[v].link;
            max_len[v] = automata.states[v].maxLen;
            is_leaf[v] = automata.states[v].firstPos + 1
            ↪ == automata.states[v].maxLen;
            int transition_pos =
            ↪ automata.states[v].lastPos -
            ↪ automata.states[p].maxLen;
            g[p].push_back({s[transition_pos], v});
        }
        for (auto& vec : g) {
            sort(all(vec));
        }
        vector<int> new_leaves;
        for (int i = 0; i < g.size(); ++i) {
            vector<int> to_erase;
            for (int j = 0; j < g[i].size(); ++j) {
                int to = g[i][j].second;
                if (is_leaf[to]) {
                    --max_len[to];
                    if (max_len[to] == max_len[i]) {
                        to_erase.push_back(j);
                        is_leaf[to] = false;
                        if (i > 0) {
                            new_leaves.push_back(i);
                        }
                    }
                }
            }
        }
        vector<pair<int, int>> copy_g;
        int uk = 0;
        for (int j = 0; j < g[i].size(); ++j) {
            if (uk < to_erase.size() && j == to_erase[uk]) {
                ++uk;
                continue;
            }
            copy_g.push_back(g[i][j]);
        }
        copy_g.swap(g[i]);
    }
    for (int v : new_leaves) {
        is_leaf[v] = 1;
    }
};

```

## 9.8 z\_function.h

```

vector<int> zFunction(const string& s) {
    int n = s.length();

    vector<int> z(n);
    int l = 0, r = 0;
    for (int i = 1; i < n; ++i) {
        z[i] = max(min(z[i - l], r - i), 0);

        while (i + z[i] < n && s[i + z[i]] == s[z[i]])
            ++z[i];
    }
}

```

```

        if (i + z[i] > r) {
            l = i;
            r = i + z[i];
        }
    }

    if (n)
        z[0] = n;

    return z;
}

```

## 10 templates

### 10.1 template.cpp

```

//g++ options: -Wall -Wextra -O2 --std=c++17 -DLOCAL
//#pragma GCC optimize('Ofast,unroll-loops')
//#pragma GCC target('avx2,tune=native')
#include <bits/stdc++.h>

using namespace std;

#define all(v) (v).begin(), (v).end()
#define sz(a) ((ll)(a).size())
#define X first
#define Y second

using ll = long long;
using ull = unsigned long long;
using dbl = long double;
mt19937_64
↪ rng(chrono::steady_clock::now().time_since_epoch().count());
ll myRand(ll mod) {
    return (ull)rng() % mod;
}

void solve() {
}

signed main() {
#ifdef LOCAL
    assert(freopen("input.txt", "r", stdin));
    // assert(freopen("output.txt", "w", stdout));
#endif
    ios_base::sync_with_stdio(false);
    cin.tie(nullptr);
    cout << fixed << setprecision(20);

    int T = 1;
    // cin >> T;
    for (int i = 0; i < T; ++i) {
        solve();
    }

#ifdef LOCAL
    cout << endl << endl << "time = " << clock() /
    ↪ (double)CLOCKS_PER_SEC << endl;
#endif
}

```

## 11 treap

### 11.1 treap.cpp

// fuckup: don't forget to push in recursive walk

```

int getrand() {
    /*static std::random_device rd;
    static std::mt19937 generator(rd());
    static std::uniform_int_distribution<int>
    ↪ distribution(0, INT_MAX);
    return distribution(generator);*/
    return rand() ^ (rand() << 15);
}

struct Node {
    Node *left;
    Node *right;
}

```

```

int priority;
int size;
ll value;
ll sum;
ll add;
bool isReversed;

explicit Node(ll value): left(nullptr),
    right(nullptr), value(value) {
    priority = getrand();
    size = 1;
    sum = value;
    isReversed = false;
    add = 0;
}

int getSize(Node *node) {
    return node ? node->size: 0;
}

ll getSum(Node *node) {
    return node ? node->sum: 0;
}

void addToNode(Node *node, ll value) {
    if (node) {
        node->value += value;
        node->sum += value * getSize(node);
        node->add += value;
    }
}

void reverseNode(Node *node) {
    if (node) {
        std::swap(node->left, node->right);
        node->isReversed = !node->isReversed;
    }
}

void push(Node *node) {
    if (!node) return;
    if (node->isReversed) {
        reverseNode(node->left);
        reverseNode(node->right);
    }
    if (node->add) {
        addToNode(node->left, node->add);
        addToNode(node->right, node->add);
    }
    node->isReversed = false;
    node->add = 0;
}

void recalc(Node *node) {
    node->size = 1 + getSize(node->left) +
        getSize(node->right);
    node->sum = node->value + getSum(node->left) +
        getSum(node->right);
}

Node* Merge(Node *left, Node *right) {
    if (!right)
        return left;
    if (!left)
        return right;
    push(left);
    push(right);
    if (left->priority > right->priority) {
        left->right = Merge(left->right, right);
        recalc(left);
        return left;
    } else {
        right->left = Merge(left, right->left);
        recalc(right);
        return right;
    }
}

std::pair<Node*, Node*> Split(Node *node, int k) {
    /*return (T1, T2). |T1| = max(0, min(k, |node|))*/*
    if (!node)
        return {nullptr, nullptr};
    push(node);
    if (getSize(node->left) < k) {
        Node *left, *right;
        std::tie(left, right) = Split(node->right, k -
            1 - getSize(node->left));
        node->right = left;
        recalc(node);
        return {node, right};
    } else {
        Node *left, *right;
        std::tie(left, right) = Split(node->left, k);
        node->left = right;
        recalc(node);
        return {left, node};
    }
}

std::pair<Node*, Node*> SplitByValue(Node *node, int
    value) {
    /*use only if tree is sorted*/
    /*return (T1, T2). For all x in T1 x < value*/
    if (!node)
        return {nullptr, nullptr};
    push(node);
    if (node->value < value) {
        Node *left, *right;
        std::tie(left, right) =
            SplitByValue(node->right, value);
        node->right = left;
        recalc(node);
        return {node, right};
    } else {
        Node *left, *right;
        std::tie(left, right) =
            SplitByValue(node->left, value);
        node->left = right;
        recalc(node);
        return {left, node};
    }
}

void Insert(Node* &node, int pos, ll value) {
    Node *left, *right;
    std::tie(left, right) = Split(node, pos);
    node = Merge(Merge(left, new Node(value)), right);
}

void Remove(Node* &node, int pos) {
    Node *left, *mid, *right;
    std::tie(left, right) = Split(node, pos + 1);
    std::tie(left, mid) = Split(left, pos);
    delete mid;
    node = Merge(left, right);
}

template<typename Function>
void queryOnSegment(Node* &node, int l, int r,
    Function callback) {
    Node *left, *mid, *right;
    std::tie(left, right) = Split(node, r + 1);
    std::tie(left, mid) = Split(left, l);
    callback(mid);
    node = Merge(Merge(left, mid), right);
}

ll getSumOnSegment(Node* &root, int l, int r) {
    ll answer;
    queryOnSegment(root, l, r, [&answer] (Node*
        &node) {answer = getSum(node);});
    return answer;
}

void addToSegment(Node* &root, int l, int r, ll value) {
    queryOnSegment(root, l, r, [value] (Node* &node)
        {addToNode(node, value);});
}

```