

Jira CLI: what the two commands the last report missed do when you use them

Black-box exploratory session against `search-jira-issues` and `attach-jira-issue` — the two `jira::*` recipes added after `docs/jira-cli-exploratory-report.pdf` was written and therefore never exercised by it. Same method, same three lenses (Project Manager, Developer, Tester), run live against the same Jira Cloud site.

TARGET	BRANCH	METHOD
2 <code>jira::*</code> recipes not in the prior report's scope <code>search-jira-issues</code> , <code>attach-jira-issue</code>	<code>claude/jira-commands-test-coverage-1jown7</code>	Black-box: CLI, <code>--list</code> , own errors only
ENVIRONMENT	SESSION DATE	STATUS
Live Jira Cloud (<code>manmik.atlassian.net</code>)	2026-08-27	Report complete

01 Summary

Why this session exists: the original report scoped itself to the 7 recipes that existed when it ran. Two more shipped afterward — `attach-jira-issue` (#15), which closed the original F4 gap ("no attachment-upload path"), and `search-jira-issues` (#17) — and neither has had a live exploratory pass until now.

30	0	2	1	6
scenarios run	critical findings	high-severity	medium-severity	notably well-designed

Headline finding: both commands are built on the diagnosability fixes the original report's F1/F2/R5 findings drove into the `shared/workflows.py/adapters.py` layer, and it shows — malformed keys, nonexistent issues, and even a genuine Jira JQL syntax error all surface specific, actionable messages now, with no re-run of the old "collapses into three words" pattern anywhere in this session. What's new instead is command-shaped: `search-jira-issues --view full` silently returns empty per-issue data when used the way its own `--view` documentation implies, and `--safe` — reused unmodified from the rest of the CLI — happens to match `attach-jira-issue`'s own result field names (`attachments`, `filename`) and deletes them, leaving a redacted attach result that doesn't confirm anything was attached.

02 Session walkthrough

Two throwaway issues (JUSTDEV-9, JUSTDEV-10) were created for this session and deleted at the end. The excerpts below are the two findings worth seeing verbatim; the full scenario list is in §06.

```
$ just search-jira-issues "project = JUSTDEV" --view full --format json
{"isLast": true, "issues": [{"fields": {}, "id": "10042"}, {"fields": {}, "id": "10041"}]}
← --view full asks for the complete per-issue payload; every field, and even "key", is
missing

$ just search-jira-issues "project = JUSTDEV" --view full --fields "summary,status" --format
json
{"isLast": true, "issues": [{"expand": "...", "fields": {"status": {...}, "summary": "..."},
"id": "10042", "key": "JUSTDEV-10", "self": "..."}]}
← the moment --fields is given explicitly, --view full works exactly as advertised
```

```
$ just attach-jira-issue JUSTDEV-10 ./test-attach.txt --yes --safe --format json
{"preview": {"action": "attach file to Jira issue", "details": {"file_path": "...",
"issue_id_or_key": "JUSTDEV-10", "size_bytes": 22}}}
{"issue_id_or_key": "JUSTDEV-10"}
← the attachment id, filename, and size are all gone – nothing here confirms a file was
attached
```

Everything else in both commands' lifecycles — valid search, valid attach, every validated error path, dry-run, the non-TTY refusal — passed cleanly; see §03–§05 for the rest.

03 Functionality

Does it do the job end to end, and is each command's intent clear? PM + Dev lens.

F7

HIGH

DEV

PM

--view full on search-jira-issues silently returns empty per-issue data

Scenarios: S32 (fail), S33 (confirms the workaround)

`read-jira-issue --view full` works with no other flags (confirmed in the original report's S24).

`search-jira-issues --view full` does not: with no `--fields`, every issue comes back as `{"fields": {}, "id": "..."} — not just trimmed, empty, and even key is missing.`

Root cause: `jira_fields_parameter()` returns `None` for a full view with no explicit fields, so the recipe omits the `fields` query parameter entirely — which is exactly right for the single-issue GET `/issue/{key}` endpoint (its default is the complete field set) but wrong for `search/jql`, whose documented default when `fields` is omitted is *no fields at all*. The same helper function serves both endpoints and assumes they share a default; they don't.

Impact: a user reads `--view full` as "give me everything" (it says so for every other command), runs it, and gets back issues that look deleted or permission-stripped — with no error to explain why. The workaround (pass `--fields` explicitly) works perfectly, but nothing tells the user they need it. **Fix:** when `view == "full"` and no explicit fields are given, send an explicit `fields=*all` (or equivalent) for the search request instead of omitting the parameter.

F8

HIGH

PM

TESTER

--safe deletes attach-jira-issue's entire result, not just PII

Scenarios: S52 (attach), S53 (same bug reached via `read-jira-issue --include attachments --safe`)

`filter_safe_output()`'s redaction regex drops any key whose name matches `attachment(?:s)?` or `filename` — written for the nested Jira user/URL objects that carry those names as leaf noise. `attach-jira-issue`'s own result happens to use those exact names as its *top-level* keys (`filename`, `attachments`), so `--safe` deletes the entire payload down to `{"issue_id_or_key": "JUSTDEV-10"}` — no attachment id, no filename, no size, no confirmation anything happened. The same collision reaches `read-jira-issue --include attachments --safe` too: the whole attachment array vanishes, silently turning `--include attachments` into a no-op whenever `--safe` is also set.

Impact: a CI pipeline or redaction-by-policy caller that always passes `--safe` gets a false "nothing to show" on the one command whose entire job is confirming a file landed. **Fix:** scope the redaction regex to leaf/nested keys (inside a user, avatar, or link object) rather than matching a command's own top-level result keys — or give `attach-jira-issue`'s result shape a narrow exemption.

F9

LOW

TESTER

A directory path and a missing path get the identical local error

Scenarios: S42, S43

`attach-jira-issue ISSUE ./a-directory` and `attach-jira-issue ISSUE ./does-not-exist.txt` both fail with 'PATH' does not exist or is not a file. — a small echo of the original report's F1 pattern, but local and low-stakes: both are still clearly the caller's own path being wrong, and no network call happens either way.

04 Robustness

Bad input, edge cases, unexpected sequencing, failure conditions. Dev lens.

R6

GOOD

DEV

The original report's diagnosability fixes generalize to both new commands for free

Scenarios: S27, S31, S44, S45

```
$ just search-jira-issues "project === JUSTDEV"
error: Remote service rejected the request (400). Error in JQL Query: Expecting either
a value, list
or function but got '='. You must surround '=' in quotation marks to use it as a value.
(line 1, character 10)

$ just attach-jira-issue JUSTDEV-99999 ./file.txt --yes
error: Remote service rejected the request (404). Issue does not exist or you do not
have permission to see it.

$ just attach-jira-issue "not a valid key!!" ./file.txt --yes
error: 'not a valid key!!' is not a valid Jira issue ID or key (expected e.g. 'ABC-123'
or a numeric ID).
```

Because both commands were built on top of the fixed workflows.py/adapters.py layer rather than before it, neither one reintroduced the "collapses into three words" pattern or the unvalidated-key round-trip the original session flagged as F1/R5. That's the fix paying for itself on new surface area, not just the surface it was written against.

R7

GOOD

DEV

attach-jira-issue's input checks are thorough and entirely client-side

Scenarios: S42, S43, S48, S49, S50

Missing file, a directory instead of a file, a 0-byte file, a Unicode filename, and a file over Jira's 25 MB attachment limit were all handled correctly — the size check in particular names the exact byte count and the limit before making any network call:

```
$ just attach-jira-issue JUSTDEV-10 ./big.bin --yes
error: '../big.bin' is 27262976 bytes, larger than the 25 MB Jira attachment size
limit.
```

R8

GOOD

DEV

No injection surface in the JQL argument either

Scenario: S39

A JQL string containing shell metacharacters and command substitutions (`$(whoami)`), backticks, `rm -rf /`) was sent to Jira as inert text — it never touched a shell. Jira's own API rejected it with `The token is not authorized for this operation.` (a content-safety response from Atlassian's side, not a CLI error), consistent with the original report's R1 finding and the same "\$-prefixed parameters are exported by just" guarantee.

R9

LOW

DEV

--limit and --expand validation is asymmetric by design, not by gap

Scenarios: S29, S38

`--limit` is eagerly and precisely validated (0, 101, -1, and abc each get their own clear message: "must be between 1 and 100" or "must be an integer"). `--expand` takes any string and silently passes an unknown value straight to Jira, which ignores it with no error — the same "no client-side check, defer to the remote" choice `read-jira-issue --expand` already makes. Consistent, not a defect, but worth naming so it isn't mistaken for an oversight later.

05 Usability

Learnable unaided, discoverable, clear and actionable errors. Tester lens.

U5

EXCELLENT

TESTER

search-jira-issues' default output is the best-designed view on this surface

Scenario: S36

```
$ just search-jira-issues "project = JUSTDEV order by created asc"
- **JUSTDEV-9**: Exploratory test issue for search/attach coverage – To Do, Unassigned
- **JUSTDEV-10**: Second exploratory test issue for search paging – To Do, Unassigned
```

One line per issue — key, summary, status, assignee — with a trailing "_Next page token: ...\" data-bbox="105 308 900 377">

U6

MEDIUM

TESTER

attach-jira-issue's default output reintroduces the old raw-dump problem

Scenario: S51

With no --format given, a successful attach prints the full Jira attachment object — nested author with four avatar sizes, self and content URLs, accountType, timeZone — before the one line that actually answers "did it work" (filename, size). This is the original report's U2 finding (no lean default view), unresolved for the one new command where a one-line confirmation ("JUSTDEV-10: attached test-attach.txt (22 bytes)", in the same spirit as render_search_markdown) would matter most.

U7

GOOD

TESTER

Both commands inherit the CLI's existing discoverability conventions without regressing them

Scenario: S40

just search-jira-issues --help and just attach-jira-issue --help fail exactly the way OPEN_ISSUES.md's U3 resolution says every recipe should (that gap was accepted as won't-fix, with just -list jira as the supported path — both new recipes show up correctly there). Missing-argument errors on both commands print the exact just jira::<recipe> [OPTIONS] ... usage line, matching the original report's U4 finding.

06 Scenario log

Continues the original report's numbering (which ended at S24). 30 scenarios, both new recipes, run against two throwaway issues (JUSTDEV-9, JUSTDEV-10) created and deleted during this session.

ID	SCENARIO	RESULT	NOTE
S25	Valid JQL, default (summary) view	Pass	Full 6-field default, as documented
S26	Empty / whitespace-only JQL	Pass	Clear "JQL query is required." for both
S27	Invalid JQL syntax	Pass	Jira's own field-level error surfaced verbatim (R6)
S28	JQL matching zero issues	Pass	Clean "_No issues found._", no error
S29	--limit boundaries (0, 101, -1, "abc")	Pass	Each gets a distinct, specific message
S30	Pagination via --limit + nextPageToken	Pass	isLast/nextPageToken round-trip correctly
S31	Bogus --next-page-token	Pass	Jira's own "invalid or expired" message passed through
S32	--view full, no --fields	Concern	Empty per-issue fields, no error (F7)
S33	--view full with explicit --fields	Pass	Full payload, confirms the workaround
S34	Invalid --view value	Pass	"must be 'summary' or 'full'"
S35	--fields custom subset	Pass	Exactly the requested fields, per issue
S36	Default markdown, multiple issues	Pass	Best-in-surface concise view (U5)
S37	--safe redaction on search results	Pass	Strips self/URLs/email/whole reporter, consistent with rest of CLI
S38	--expand changelog / unknown value	Pass	Unknown value silently ignored by Jira (R9)
S39	Injection-style JQL	Pass	No shell surface; Jira's own content policy rejected it (R8)
S40	--help / missing positional arg (both commands)	Pass	Matches accepted U3 resolution + U4 usage-line pattern
S41	Attach a valid file, full lifecycle	Pass	Closes original report's F4 gap end to end
S42	Attach a nonexistent local file	Pass	Clear local error, no network call (F9)
S43	Attach a directory instead of a file	Pass	Same message as S42 (F9, low)
S44	Attach to a nonexistent issue	Pass	Specific 404 reason surfaced (R6)
S45	Attach to a malformed issue key	Pass	Caught client-side (R6)
S46	--dry-run makes no real upload	Pass	Verified via before/after read --include attachments
S47	Non-TTY without --yes	Pass	Safe refusal, no hang, names the fix
S48	Zero-byte file	Pass	Uploads with size: 0 confirmed
S49	Unicode / special-character filename	Pass	Round-trips correctly through upload and read-back
S50	Oversized file (>25 MB)	Pass	Caught client-side with exact byte count (R7)

ID	SCENARIO	RESULT	NOTE
S51	Default markdown/text output of a successful attach	Concern	Raw API dump before the useful line (U6)
S52	--safe on attach-jira-issue's own result	Concern	Deletes the entire confirmation payload (F8)
S53	read-jira-issue --include attachments --safe	Concern	Same collision reaches the pre-existing read path (F8)
S54	Invalid --format on both commands	Pass	Eager, clear, exit code 2 as documented by R4

07 Next steps

- **Fix first — F7:** when `search-jira-issues --view full` has no explicit `--fields`, send an explicit "all fields" request to `search/jql` instead of omitting the parameter — the endpoint's own default is not the same as the single-issue read endpoint's, and nothing today accounts for that difference.
- **Fix second — F8:** `scope filter_safe_output()`'s `attachment(?:s)?/filename` match to nested leaf keys, or exempt a command's own top-level result shape, so `--safe` redacts identity/URL noise without deleting the one thing `attach-jira-issue` and `read-jira-issue --include attachments` exist to report.
- **Worth fixing — U6:** give `attach-jira-issue` a purpose-built one-line default renderer, the same way `render_search_markdown` replaced the raw dump for search results.
- **Not a defect — F9, R9:** both are minor consistency notes, not action items; recorded so a future pass doesn't mistake settled, deliberate behavior for an oversight.
- **Out of scope, as before:** `bitbucket`, `confluence`, `jenkins`, `project`, `quality`, `devtools` targets untouched; `jira-integration-smoke` itself (the opt-in automated smoke test) was not modified by this session.

Jira-facing recipes only, tested black-box against a live Jira Cloud site. Two test issues (JUSTDEV-9, JUSTDEV-10) were created and deleted during this session; no other project data was modified. This report continues `docs/jira-cli-exploratory-report.pdf`'s scenario numbering and finding prefixes (F7–F9, R6–R9, U5–U7) rather than restarting them.