

Module 9: Logistic Regression

Rebecca C. Steorts

Agenda

- ▶ 1986 Challenger explosion
- ▶ What happened?
- ▶ Background
- ▶ Logistic regression

The Challenger Case Study

On 28 January 1986, the Space Shuttle Challenger broke apart, 73 seconds into flight. All seven crew members died. The cause of the disaster was the failure of an o-ring on the right solid rocket booster.

O-rings

- ▶ O-rings help seal the joints of different segments of the solid rocket boosters.
- ▶ We learned after this fatal mission that o-rings can fail at extremely low temperature.

Motivations and goals

- ▶ In 1986, the Challenger space shuttle exploded as it took off.
- ▶ The question of interest was what happened and could it have been prevented?
- ▶ We will revisit not just the challenger data, but other missions to understand the relationship between o-ring failure and temperature.
- ▶ To understand this, we need to learn about logistic regression.

Loading the Faraway Package

```
library(faraway)
data("orings")
orings[1,] <- c(53,1)
head(orings)
```

| ## | temp | damage |
|------|------|--------|
| ## 1 | 53 | 1 |
| ## 2 | 57 | 1 |
| ## 3 | 58 | 1 |
| ## 4 | 63 | 1 |
| ## 5 | 66 | 0 |
| ## 6 | 67 | 0 |

Space Shuttle Missions


The 1986 crash of the space shuttle Challenger was linked to failure of o-ring seals in the rocket engines.

Data was collected on the 23 previous shuttle missions, where the following variables were collected:

- ▶ temperature for each mission
- ▶ damage to the number of o-rings (out of a total of six)

Plot

```
plot(damage~temp, data=orings, xlab="temperature (F)",  
     ylab="damage (out of 6)",  
     pch=16, col="red", ylim=c(0,6))
```



Plot


```
library(ggplot2)
geom_boxplot(outlier.colour="black", outlier.shape=14,
             outlier.size=2, notch=FALSE)

## geom_boxplot: outlier.colour = black, outlier.fill = NULL
## stat_boxplot: na.rm = FALSE, orientation = NA
## position_dodge2

damage <- as.factor(orings$damage)
temp <- orings$temp
head(damage)

## [1] 1 1 1 1 0 0
## Levels: 0 1
```

Boxplot of temperature versus o-ring failure



Response and covariate

- ▶ The response is the damage to the o-ring (in each shuttle launch).
- ▶ The covariate is the temperature (F) in each shuttle launch.

Notation and Setup

- ▶ Let p_i be the probability that o-ring i fails.
- ▶ The corresponding **odds of failure** are

$$\frac{p_i}{1 - p_i}.$$

Notation and Setup

- ▶ The probability of failure p_i is between $[0, 1]$
- ▶ The odds of failure is any real number.

Logistic Regression

The response

$$Y_i \mid p_i \sim \text{Bernoulli}(p_i) \quad (1)$$

for $i = 1, \dots, n$.

The logistic regression model writes that the logit of the probability p_i is a linear function of the predictor variable(s) x_i :

$$\text{logit}(p_i) := \log\left(\frac{p_i}{1 - p_i}\right) = \beta_0 + \beta_1 x_i. \quad (2)$$

Interpretation of Co-efficients

- ▶ The regression co-efficients β_0, β_1 are directly related to the log odds $\log(\frac{p_i}{1-p_i})$ and not p_i .
- ▶ For example, the intercept β_0 is the $\log(\frac{p_i}{1-p_i})$ for observation i when the predictor takes a value of 0.
- ▶ The slope β_1 refers to the change in the expected log odds of failure of an o-ring for a decrease in temperature.

Exercise

Assume that $\log(\frac{p_i}{1-p_i}) = \beta_0 + \beta_1 x_i$.

Show that

$$p_i = \frac{e^{\beta_0 + \beta_1 x_i}}{e^{\beta_0 + \beta_1 x_i} + 1}.$$

This shows that logit function guarantees that the probability p_i lives in $[0, 1]$.

Bayesian Logistic Regression

Recall that

$$Y_i \mid p_i \sim \text{Bernoulli}(p_i) \quad (3)$$

for $i = 1, \dots, n$.

$$\text{logit}(p_i) := \log\left(\frac{p_i}{1 - p_i}\right) = \beta_0 + \beta_1 x_i. \quad (4)$$

How can we build minimal Bayesian prior knowledge?

Priors on β_0 and β_1

Conjugate priors do not exist on β_0 and β_1 .

We will consider the following weakly informative priors:

$$\beta_0 \sim \text{Normal}(0, 1000) \quad (5)$$

$$\beta_1 \sim \text{Normal}(0, 1000) \quad (6)$$

$$(7)$$

Posterior sampling

Since we cannot find the posterior in closed form, we will resort to MCMC to approximate inference regarding β_0, β_1 .

We can do this easily using the `logitMCMC` function in the `MCMCpack` R package.

This package implements a random walk Metropolis algorithm.

Posterior sampling

```
library(MCMCpack)
```

```
## Loading required package: coda
```

```
## Loading required package: MASS
```

```
## ##
```

```
## ## Markov Chain Monte Carlo Package (MCMCpack)
```

```
## ## Copyright (C) 2003-2020 Andrew D. Martin, Kevin M. Quinn
```

```
## ##
```

```
## ## Support provided by the U.S. National Science Foundation
```

```
## ## (Grants SES-0350646 and SES-0350613)
```

```
## ##
```

```
failure <- orings$damage
```


```
temperature <- orings$temp
```

```
output <- MCMClogit(failure~temperature,  
                    mcmc=1000, b0=0, B0=0.001)
```


Traceplots

`plot(output)`


Trace of (Intercept)




Density of (Intercept)



Trace of temperature



Density of temperature



Summary

```
summary(output)
```

```
##
## Iterations = 1001:2000
## Thinning interval = 1
## Number of chains = 1
## Sample size per chain = 1000
##
## 1. Empirical mean and standard deviation for each variable,
##    plus standard error of the mean:
##
##              Mean      SD Naive SE Time-series SE
## (Intercept) 19.4239 8.1171 0.256684      0.88555
## temperature -0.2955 0.1191 0.003765      0.01309
##
## 2. Quantiles for each variable:
##
##              2.5%      25%      50%      75%      97.5%
## (Intercept)  5.3608 13.6196 18.7297 24.4156 36.08274
## temperature -0.5441 -0.3734 -0.2853 -0.2108 -0.09241
```

Simulating Posterior Prediction

Given a certain temperature, we can simulate the results of future space shuttle launches using the posterior predictive distribution.

Suppose that on launch day, it's 80 degrees (F).

How would we simulate a predictive probability that a o-ring would fail?

Simulating Posterior Prediction

```
library(boot)
```

```
##
```

```
## Attaching package: 'boot'
```

```
## The following objects are masked from 'package:faraway':
```

```
##
```

```
##      logit, melanoma
```

```
temp <- 80
```

```
fail.prob <- inv.logit(output[,1] + temp*output[,2])
```

```
y.pred <- rbinom(2100, size=1, prob=fail.prob)
```


Simulating Posterior Prediction

```
barplot(table(y.pred))
```

