

# **Teaching a robot to interpret natural language navigation instructions**

Ryan Eloff

Supervisor: Dr. H. Kamper  
Department of Electrical & Electronic Engineering

Maties Machine Learning  
Stellenbosch University

23 February 2018




UNIVERSITEIT•STELLENBOSCH•UNIVERSITY  
jou kennisvennoot \* your knowledge partner


# Natural language for human-robot interaction




(a)



(b)



“Please pick up these three yellow blocks for me.”



“Okay, um, two objects to put away, this red triangle and the screen (*sic*) on a pepper thing.”

(c)

The Gambit platform which learns to identify and pick up objects from a user's speech and gestures.<sup>1</sup>

<sup>1</sup>C. Matuszek, L. Bo, L. Zettlemoyer, et al., “Learning from unscripted deictic gesture and language for human-robot interactions,” in *Proceedings of the Twenty-Eighth AAAI Conference on Artificial Intelligence*, 2014.

# Natural language for human-robot interaction



A robotic wheelchair that learns about the environment from a narrated tour.<sup>2</sup>

---

<sup>2</sup>M. R. Walter, S. Hemachandra, B. Homberg, et al., "A framework for learning semantic maps from grounded natural language descriptions," *The International Journal of Robotics Research*, 2014.

# Natural language for human-robot interaction

- ▶ Still face challenges in building robots that can understand our written natural language instructions.


# Natural language for human-robot interaction

- ▶ Still face challenges in building robots that can understand our written natural language instructions.
- ▶ Most existing systems are only available in most commonly used languages: English, German, Spanish ...


# Natural language for human-robot interaction

- ▶ Still face challenges in building robots that can understand our written natural language instructions.
- ▶ Most existing systems are only available in most commonly used languages: English, German, Spanish ...
- ▶ These technologies are not available for **low-resource languages**.
- ▶ This is a problem in South Africa!

# Natural language instructions for route direction




# Natural language instructions for route direction



- ▶ “Walk forward once”
- ▶ “Move to the sofa”
- ▶ “Go down till the chair”
- ▶ “Go forward one segment to the intersection with a bare concrete floor”

# Natural language instructions for route direction



- ▶ “Walk forward once”
- ▶ “Move to the sofa”
- ▶ “Go down till the chair”
- ▶ “Go forward one segment to the intersection with a bare concrete floor”

Can we build a **language independent** system for interpreting **written natural language** navigation instructions that is also **less dependent on data**?

# Evaluation, virtual environments, & web application

Select a map:  
Jelly

View Instruction Data   User Customized Model   SAIL Data Model

Enter an instruction:

Move forward and turn right!

Execute!

## Example instruction data

- ▶ Example 1: “Walk two steps forward”


## Example instruction data

- ▶ Example 2: “Move forward and turn right”

## Example instruction data

- ▶ Example 3: “Move to the easel”

# Unseen instruction problem



- ▶ Unseen: "Walk three steps to the easel"

# General model

# General model


## Observations

Instruction  $x^{(i)}$


World State  $w^{(i)}$

Action  
Sequence  $a^{(i)}$


# General model




# General model




# General model



# General model




# General model



# Proposed models

k-Nearest neighbours (kNN) models:




Proposed distance metrics:

- ▶ Levenshtein distance
- ▶ Euclidean distance

# Proposed models


k-Nearest neighbours (kNN) models:



Proposed distance metrics:

- ▶ Levenshtein distance
- ▶ Euclidean distance

Basic one-vs-rest (OVR) logistic regression model:




# Results: Overall model performance

- Overall performance of the proposed models and that of previous work:

Model	$F_1$	Accuracy
kNN with Levenshtein distance	77.10	55.25
kNN with Euclidean distance	75.44	51.65
Basic logistic regression	<b>78.18</b>	<b>57.32</b>
Stepwise logistic regression	72.58	44.36
Chen and Mooney (2011)	68.37	54.40
Chen (2012)	69.43	57.28
Mei et al. (2016)	-	<b>69.98</b>



# Results: Performance on small datasets

- Average strict accuracy of the proposed models when trained on different sample sizes  $n$ :



# Results: Performance on an Afrikaans corpus

- Proposed models evaluated on an **Afrikaans translation** of the benchmark English corpus\*:



\* English corpus translated to Afrikaans using Google's state-of-the-art Neural Machine Translation system.

# Contributions

- ▶ Simple machine learning models used for the novel purpose of **learning from limited datasets**, which is competitive with complex systems of previous work.

# Contributions

- ▶ Simple machine learning models used for the novel purpose of **learning from limited datasets**, which is competitive with complex systems of previous work.
- ▶ Web application has data collection capabilities which is ideal for future research on human-robot interaction.

# Contributions

- ▶ Simple machine learning models used for the novel purpose of **learning from limited datasets**, which is competitive with complex systems of previous work.
- ▶ Web application has data collection capabilities which is ideal for future research on human-robot interaction.
- ▶ These models are the first steps and foundation for future research on more complex models for limited data. (and **speech!!**)

# Contributions

- ▶ Simple machine learning models used for the novel purpose of **learning from limited datasets**, which is competitive with complex systems of previous work.
- ▶ Web application has data collection capabilities which is ideal for future research on human-robot interaction.
- ▶ These models are the first steps and foundation for future research on more complex models for limited data. (and **speech!!**)
- ▶ First Afrikaans system for Robotic instruction following. The system may also be trained in **any language**, so it is ideal for low-resource languages.

# My current work

- ▶ One-shot learning of small multimodal datasets consisting of images combined with speech captions.
- ▶ One-shot learning example:<sup>3</sup>

This is a "dax".



- ▶ Goal: Develop systems that learn and think like people.


---

<sup>3</sup>R. Feinman and B. M. Lake, "Learning inductive biases with simple neural networks," *arXiv:1802.02745*, 2018.

# My current work

- ▶ One-shot learning of small multimodal datasets consisting of images combined with speech captions.
- ▶ One-shot learning example:<sup>3</sup>

This is a "dax".



Which of these is a "dax"?

(1)



(2)



(3)



- ▶ Goal: Develop systems that learn and think like people.


---

<sup>3</sup>R. Feinman and B. M. Lake, "Learning inductive biases with simple neural networks," arXiv:1802.02745, 2018.

# My current work

- ▶ One-shot learning of small multimodal datasets consisting of images combined with speech captions.
- ▶ One-shot learning example:<sup>3</sup>

This is a "dax".



Which of these is a "dax"?

(1)



(2)



(3)



- ▶ Goal: Develop systems that learn and think like people.

---

<sup>3</sup>R. Feinman and B. M. Lake, "Learning inductive biases with simple neural networks," arXiv:1802.02745, 2018.

**Some other slides ...**

# Word embeddings with latent semantic analysis


Example instructions:

- ▶  $d_1$  : *Move forward two steps*
- ▶  $d_2$  : *Travel forward*
- ▶  $d_3$  : *Travel two steps*
- ▶  $d_4$  : *Turn left*
- ▶  $d_5$  : *Turn right and move to the chair*

# Word embeddings with latent semantic analysis


Example instructions:

- ▶  $d_1$  : Move forward two steps
- ▶  $d_2$  : Travel forward
- ▶  $d_3$  : Travel two steps
- ▶  $d_4$  : Turn left
- ▶  $d_5$  : Turn right and move to the chair




# Stepwise logistic regression

Stepwise one-vs-rest (OVR) logistic regression model:



# Stepwise logistic regression

Stepwise one-vs-rest (OVR) logistic regression model:



# Stepwise logistic regression

Stepwise one-vs-rest (OVR) logistic regression model:

