```
--------------------------------------------------------------------------------

  K-Meter
  =======
  Implementation of a K-System meter according to Bob Katz' specifications

  Copyright (c) 2010-2012 Martin Zuther (http://www.mzuther.de/)

  This program is free software: you can redistribute it and/or modify
  it under the terms of the GNU General Public License as published by
  the Free Software Foundation, either version 3 of the License, or
  (at your option) any later version.

  This program is distributed in the hope that it will be useful,
  but WITHOUT ANY WARRANTY; without even the implied warranty of
  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
  GNU General Public License for more details.

  You should have received a copy of the GNU General Public License
  along with this program.  If not, see <http://www.gnu.org/licenses/>.

  Thank you for using free software!

--------------------------------------------------------------------------------


FLAC-compressed wave file (48 kHz, 24 bit)
==========================================
Please verify the correctness of K-System meter values over time by
making use of your eyes and the expanded metering mode.

00:00 - 00:03  silence
00:03 - 01:03  uncorrelated band-limited pink noise (20 Hz to 20000 Hz,
               -23.01 dB FS RMS)
01:03 - 01:06  silence


Validation settings
===================
File:     pink_noise.flac
Host SR:  48 000 Hz
Channel:  All
Display:  [x] Average meter level
          [ ] Peak meter level
          [ ] Maximum peak level
          [ ] Stereo meter value
          [ ] Phase correlation


RMS correction of K-System meter
================================
RMS = A / sqrt(2)
RMS / A  = sqrt(2) = +3.01 dB


Pink noise (20 Hz to 20000 Hz, -23.01 dB FS RMS)
================================================
K-20 :=   0.00 dB  (crest factor: 20 dB)
K-14 :=  -6.00 dB  (crest factor: 14 dB)
K-12 :=  -8.00 dB  (crest factor: 12 dB)
Norm := -20.00 dB  (crest factor:  0 dB)
```