Outcomes in H and the definitions using them

15 references, 7 outcomes

condition c (one outcome per $V(\mathrm{dep}(c))$)	used by SR	RA	RR	ER	rerun after `item` load	rerun after sales append
`KeyUnique(store_sales.`K`)`	●		●	●	—	●
`KeyUnique(store_returns.`K_r`)`		●	●		—	—
`KeyUnique(item.i_item_sk)`				●	● ✕	—
`KeyUnique(date_dim.d_date_sk)`	●	●	●	●	—	—
`Unmatched(store_sales → item)`				●	●	●
`Unmatched(store_sales → date_dim)`	●		●	●	—	●
`Unmatched(store_returns → date_dim)`		●			—	—
checks, each once for all agents (whole-definition recheck)					**2** (5)	**3** (12)

Repair: a filter on `item` that restores one row per key

6

`KeyUnique(item.i_item_sk)` at ⟨9662, 1001, 1⟩: 1001 rows, 1000 keys; ratio < 1.5, so search

column (distinct values)	value	rows	rows/keys under it	
`i_is_current` (2)	`'Y'`	1000	1000/1000	✓ **the only pass**
	`'N'`	1		— pruned: rows ≠ keys
`i_category` (5)	each value	200–201		— pruned: rows ≠ keys

`i_current_price` has 50 values: not a candidate (limit 20)

exactly one filter passes: kept as `grain:item`; join, metric rev 1 after regression