



parc[®]
A Xerox Company

MESSAGES DOCUMENT

Marc Mosko (marc.mosko@parc.com)

ICNRG (Prague, CZ) July 20, 2015

MAIN UPDATES

- Changed to RG document
- Vendor Specific Information
- PayloadID and PayloadIDMethod
- Fixed reference
- Next set of work items

RG DOCUMENT

- Name change
 - Was: draft-mosko-icnrg-ccnxmessages-01.txt
 - Now: draft-irtf-icnrg-ccnxmessages-00.txt

VENDOR SPECIFIC INFORMATION

- Updated the type for Vendor Specific Information to 0x0FFF.

PAYLOADID (1)

- The PayloadID identifies the Payload of an Interest as a Name Segment.
- Allows multiplexing different payloads.
- Previously, the PayloadID was just an ID and the PayloadIDMethod identified how the PayloadID was generated.
- New spec removes PayloadIDMethod and adopts the RFC 6920 format (Naming Things with Hashes) for all PayloadIDs.
- Adds new types to RFC 6920 types using the reserved types for Nonce and Application Specific method.

PAYLOADID (2)

- Clarified that even if PayloadID is a hash, it is not a security context, must still use a Validation section for an actual signature.

FIXED REFERENCE

- Incorrect reference to RFC 3820 replaced by RFC 5280 (X509).

NEXT SET OF WORK ITEMS

- As per Semantics edits