

# **Text Embedding. Text Retrieval & Ranking. Retrieval-Augmented Generation.**

Alekseev Ilya, AIMasters, Fall 2024.


# Text Embedding

## Outline

- Text Embedding & Sequence-level Tasks
- BERT Embedding
- SBERT
- Contrastive Learning: Loss, Positives, Negatives

# Text Embedding

*Embedding must be useful as **feature representation** and for **vector search**.*



[Припев: Big Baby Tape]

Свет мой, зеркало, скажи, покажи мне, кто тут G

Кто был на районе, поставлял барыгам кирпичи?

Передайте мне ключи, передайте мне ключи

Mirror, mirror on the wall, крадусь на них — я вор в ночи

$(0, 1, 3.14, -5.6)$

?

$(0, 1, 3.14, -5.6)$

miro


# Sequence-level Tasks

- **Natural Language Inference (NLI)**: contradiction, entailment, and neutral (pair classification)
- **Bitext Mining**: mine closest translation pairs from parallel corpus (knn)
- **Semantic Textual Similarity (STS)**: estimate the similarity of two texts (pair regression)
- **Retrieval**: find relevant documents for query text (knn)
- **Paraphrase detection** (pair classification)
- Classification, clustering, reranking, summarization


# BERT Embedding

Feed to BERT and pool last hidden states:

- CLS
- Average
- Attention



# BERT is not trained to produce good embeddings!




# We need **sentence-level** task to encourage model to aggregate info effectively

Reimers & Gurevych, "Sentence-BERT: Sentence Embeddings using Siamese BERT-Networks", EMNLP 2019 (citations: 12866)

Sequence-level task: *train BERT on NLI data.*

# SBERT






## **SBERT: pros and cons**

- + sequence-level task
- + bottleneck trick
- supervised data
- only features but not a vector search

# Contrastive Learning

$$\mathcal{L} = -\log \frac{\exp(\cos(x, y))}{\sum_{z \in Z} \exp(\cos(x, z))}$$



## How to Mine Positives

- supervised datasets (NLI, STS, summarization, retrieval)
- scrapped data (QA forums, Reddit threads, web articles, news)
- augmentations (synonyms, paraphrasing, dropout, token shuffling)

## How to Mine Negatives




- in-batch negative sampling
- queue
- memory bank
- momentum contrast (MoCo)

# In-batch Negative Sampling

```
# joint embedding
x_emb = encoder(x_txt) # [B, d]
y_emb = encoder(y_txt) # [B, d]

# pairwise cosine similarities
x_emb = F.normalize(x_emb, dim=1)
y_emb = F.normalize(y_emb, dim=1)
similarities = x_emb @ y_emb.T # [B, B]

# symmetric loss
labels = torch.arange(len(x_emb))
loss_r = F.cross_entropy(similarities, labels, reduction='mean')
loss_c = F.cross_entropy(similarities.T, labels, reduction='mean')
loss = (loss_c + loss_r) / 2
```



# SOTA Embedding Models

<https://huggingface.co/spaces/mteb/leaderboard>

# Text Embedding: Summary

- Text Embedding & Sequence-level Tasks
- BERT Embedding
- SBERT
- Contrastive Learning: Loss, Positives, Negatives



# Text Retrieval & Ranking


## Outline

- Symmetric vs Asymmetric Search
- Bi-encoder vs Cross-encoder
- Sparse Text Embedding: BM25


# Retrieval Types

- **symmetric** search (clustering, knn, bitext mining)
  - query  $\sim$  document
  - `q="The last time the survey was conducted, in 1995, those numbers matched."`
  - `d="In 1978, the paper's numbers weren't believed to be true."`
- **asymmetric** search (web search, QA)
  - query  $\not\sim$  document
  - `q="What is Python"`
  - `d="Python is an interpreted, high-level and general-purpose programming language."`


# Search Engine



# Bi-encoder



# Cross-encoder



# Sparse Text Embedding

Вектор  $e(d)$  размера  $|V|$ :

- BoW:

$$[e(d)]_i = \text{tf}(w_i, d)$$

- TF-IDF

$$[e(d)]_i = \text{tf}(w_i, d) \cdot \text{idf}(w_i)$$

- BM25

$$[e(d)]_i = \widetilde{\text{tf}}(w_i, d) \cdot \widetilde{\text{idf}}(w_i)$$

# TF-IDF

- term frequency  $\text{tf}(w, d)$  есть число вхождений токена  $w_i$  в документ  $d$
- document frequency  $\text{df}(w)$  есть число документов, в которых встречается  $w$
- inverse document frequency есть мера редкости токена:

$$\text{idf}(w) = 1 + \log \frac{1 + |D|}{1 + \text{df}(w)}$$

- вместе дает число токенов с учётом редкости каждого токена:

$$[e(d)]_i = \text{tf}(w_i, d) \cdot \text{idf}(w_i)$$

## BM25

- пусть  $\ell(d)$  это отношение длины  $d$  к средней длине документов в датасете
- term frequency с поправкой на длину документа:

$$\widetilde{\text{tf}}(w, d) = \frac{3 \cdot \text{tf}(w)}{3(0.25 + 0.75 \cdot \ell(d)) + \text{tf}(w)}$$

- inverse document frequency

$$\widetilde{\text{idf}}(w_i) = \log \frac{|D| - \text{df}(w) + 0.5}{\text{df}(w) + 0.5}$$

- вместе это дает число токенов с учетом редкости, длины текста, числа повторений этого токена

$$[e(d)]_i = \widetilde{\text{tf}}(w_i, d) \cdot \widetilde{\text{idf}}(w_i)$$



# Text Retrieval & Ranking: Summary

- Symmetric vs Asymmetric Search
- Search Engine Pipeline
- Bi-encoder vs Cross-encoder
- Sparse Text Embedding: BM25

# Retrieval Augmented Generation

## Outline


- Introduction. Naive RAG
- Evaluation
- Improve RAG. Prompting Techniques
- Improve RAG. Retriever and LLM Joint Training

# Introduction. Naive RAG

# Language Models are Few-Shot Learners

GPT-3 [Brown et al., 2020]

...tasks which require using the information stored in the model's parameters to answer general knowledge questions.




# QA via Prompt Completion

Problems of simple generation:


- hallucinations, missing references
- hard to update

Solution: **retrieval-augmented generation (RAG)**



# Naive RAG


- retrieve documents relevant to query (user's input)
- insert top-k documents into prompt
- feed as prompt



# Knowledge Stores

- web pages
- PDF, word, markdown (closed-book)
- wikipedia dump
- search engines

# Implementation: LangChain






## Implementation: LangChain

- choose SOTA LLM (Chatbot Arena)
- choose SOTA embedder (MTEB)

See also: [LlamaIndex](#).




# Evaluation

- Knowledge-intensive tasks
- RAG-specific benchmarks

# RAGAs [Es et al., 2023]

Automated evaluation with LLM as assessor.



## RAGAs [Es et al., 2023]

	<b>Faith.</b>	<b>Ans. Rel.</b>	<b>Cont. Rel.</b>
RAGAs	<b>0.95</b>	<b>0.78</b>	<b>0.70</b>
GPT Score	0.72	0.52	0.63
GPT Ranking	0.54	0.40	0.52

Table 1: Agreement with human annotators in pairwise comparisons of faithfulness, answer relevance and context relevance, using the WikEval dataset (accuracy).

## Improve Your RAG

- choose SOTA embedder and LLM according to public leaderboards
- prompting techniques
- train retriever and generator jointly

# Prompting Techniques

- query summarization / paraphrasing
- decompose into multiple questions (Chain-of-Thought)
- reranking chunks

# Prompting Techniques: Chain-of-Thought

## Standard Prompting

### Model Input

Q: Roger has 5 tennis balls. He buys 2 more cans of tennis balls. Each can has 3 tennis balls. How many tennis balls does he have now?

A: The answer is 11.

Q: The cafeteria had 23 apples. If they used 20 to make lunch and bought 6 more, how many apples do they have?

### Model Output

A: The answer is 27. ❌

## Chain-of-Thought Prompting

### Model Input

Q: Roger has 5 tennis balls. He buys 2 more cans of tennis balls. Each can has 3 tennis balls. How many tennis balls does he have now?

A: Roger started with 5 balls. 2 cans of 3 tennis balls each is 6 tennis balls.  $5 + 6 = 11$ . The answer is 11.


Q: The cafeteria had 23 apples. If they used 20 to make lunch and bought 6 more, how many apples do they have?

### Model Output

A: The cafeteria had 23 apples originally. They used 20 to make lunch. So they had  $23 - 20 = 3$ . They bought 6 more apples, so they have  $3 + 6 = 9$ . The answer is 9. ✅

# Prompting Techniques: Rerank Chunks

Lost in the middle [Liu et al., 2023]





# Train Retriever and Generator Jointly

- RAG [Piktus et al., 2020], BART + DPR
- Hindsight [Paranjape et al., 2022], BART + Colbert
- Atlas [Izacard et al., 2022], T5 + Contriever
- Replug [Shi et al., 2023], GPT-3 + Contriever
- RA-DIT [Lin et al, 2023], Llama 2 + DRAGON

Meta AI almost everywhere!

# RAG: Summary

- Introduction. Naive RAG
- Evaluation
- Improve RAG. Prompting Techniques
- Improve RAG. Retriever and LLM Joint Training