


1

Neural Learning Methods

- ▶ An obvious source of biological inspiration for learning research: **the brain**
- ▶ The work of McCulloch and Pitts on the **perceptron** (1943) started as research into how we could precisely model the **neuron** and the **network of connections** that allow animals (like us) to learn
- ▶ These networks are used as **classifiers**: given an input, they label that input with a classification, or a distribution over possible classifications

2


The Basic Neuron Model



- ▶ Neuron gets input from a set of other neurons, or from the problem input, and computes function g
- ▶ Output a_j is either passed along to another set of neurons, or is used as final output for learning problem itself

3

Input Bias Weights




- ▶ Each input a_i to neuron j is given a weight $w_{i,j}$
- ▶ Each neuron is treated as having a fixed dummy input, $a_0 = 1$
- ▶ The input function is then the weighted linear sum:

$$in_j = \sum_{i=0}^n w_{i,j} a_i = w_{0,j} a_0 + w_{1,j} a_1 + w_{2,j} a_2 + \cdots + w_{n,j} a_n$$

$$= w_{0,j} + w_{1,j} a_1 + w_{2,j} a_2 + \cdots + w_{n,j} a_n$$

4

We've Seen This Before!



- ▶ The weighted linear sum of inputs, with dummy, $a_0 = 1$, is just a form of the cross-product that our classifiers have been using all along
- ▶ Remember that the “neuron” here is just another way of looking at the perceptron idea we already discussed

$$in_j = \sum_{i=0}^n w_{i,j} a_i = w_{0,j} + w_{1,j} a_1 + w_{2,j} a_2 + \dots + w_{n,j} a_n$$


$$= \mathbf{w}_j \cdot \mathbf{a}$$

Machine Learning (COMP 135)

5

5

Neuron Output Functions




- ▶ While the **inputs** to any neuron are treated in a linear fashion, the **output** function g **need not** be linear
- ▶ The power of neural nets comes from fact that we can combine large numbers of neurons together to compute any function (linear or not) that we choose

Machine Learning (COMP 135)

6

6

The Perceptron Threshold Function



- ▶ One possible function is the **binary threshold**, which is suitable for “firm” classification problems, and causes the neuron to activate based on a simple binary function:


$$g(in_j) = \begin{cases} 1 & \text{if } in_j \geq 0 \\ 0 & \text{else} \end{cases}$$

Machine Learning (COMP 135)

7

7

The Sigmoid Activation Function



- ▶ A function that has been more often used in neural networks is the **logistic** (also known as the Sigmoid)
- ▶ This gives us a “soft” value, which we can often interpret as the **probability** of belonging to some output class

$$g(in_j) = \frac{1}{1 + e^{-in_j}}$$

Machine Learning (COMP 135)

8

8

Power of Perceptron Networks

- ▶ A **single-layer** network combines a *linear* function of input weights with the *non-linear* output function
 - ▶ If we threshold output, we have a boolean (1/0) function
 - ▶ This is sufficient to compute numerous linear functions

x_1 OR x_2		
x_1	x_2	y
0	0	0
0	1	1
1	0	1
1	1	1

x_1 AND x_2		
x_1	x_2	y
0	0	0
0	1	0
1	0	0
1	1	1

Machine Learning (COMP 135)


9

9

Power of Perceptron Networks

- ▶ A single-layer network with inputs for variables (x_1, x_2), and bias term ($x_0 == 1$), can compute the OR of its inputs
 - ▶ **Threshold:** ($y == 1$) if weighted sum ($S \geq 0$); else ($y == 0$)

x_1 OR x_2		
x_1	x_2	y
0	0	0
0	1	1
1	0	1
1	1	1



- ▶ What weights can we apply to the three inputs to produce OR?
 - ▶ One answer: $-0.5 + x_1 + x_2$


Machine Learning (COMP 135)

10

10

Power of Perceptron Networks

x_1 AND x_2		
x_1	x_2	y
0	0	0
0	1	0
1	0	0
1	1	1



- ▶ What about the AND function instead?
 - ▶ One answer: $-1.5 + x_1 + x_2$

Machine Learning (COMP 135)


11

11

Linear Separation with Perceptron Networks

- ▶ We can think of binary functions as dividing (x_1, x_2) plane
- ▶ The ability to express such a function is *analogous* to the ability to **linearly separate** data in such regions

x_1 OR x_2		
x_1	x_2	y
0	0	0
0	1	1
1	0	1
1	1	1




Machine Learning (COMP 135)

12

12

Linear Separation with Perceptron Networks

- ▶ We can think of binary functions as dividing (x_1, x_2) plane
- ▶ The ability to express such a function is *analogous* to the ability to **linearly separate** data in such regions




Machine Learning (COMP 135) 13

13

Functions with Non-Linear Boundaries

- ▶ There are some functions that cannot be expressed using a single layer of linear weighted inputs, and a non-linear output
- ▶ Again, this is analogous to the *inability* to linearly separate data in some cases




Machine Learning (COMP 135) 14

14

MLP's for Non-Linear Boundaries


- ▶ Neural networks gain expressive power because they can have *more than one layer*
- ▶ A **multi-layer perceptron** has one or more **hidden layers** between input and output
- ▶ Each hidden node applies a non-linear **activation function**, producing output that it sends along to the next layer
 - ▶ In such cases, much more complex functions are possible, corresponding to non-linear decision boundaries (as in current homework assignment)



Machine Learning (COMP 135) 15

15

Review: Properties of the Sigmoid Function



- ▶ The Sigmoid takes its name from the shape of its plot
- ▶ It always has a value in range:
 $0 \leq x \leq 1$
- ▶ The function is everywhere differentiable, and has a **derivative** that is easy to calculate, which turns out to be useful for learning:

$$g'(in_j) = g(in_j)(1 - g(in_j))$$

Machine Learning (COMP 135) 16

16


Do We Always Use the Logistic Sigmoid?

- ▶ While historically popular, the logistic function is **not** always used in modern neural network research
 - ▶ There are many other functions that can be, and are, used
 - ▶ Some models even use combinations of different functions on different layers of the network
 - ▶ Often, the logistic is used at the final layer only, where it is sometimes called a **softmax** (probability) function
 - ▶ In our presentation, we will assume the logistic, but the overall details of the key algorithm do not change if we use something else
- ▶ In general, we want a function that is
 1. **Non-linear**: allowing for more complex outputs.
 2. **Differentiable**: standard **back-propagation** algorithms for learning in the networks use gradient-based approaches, and require access to the derivative of the function

Machine Learning (COMP 135) 17

17

Other Popular Activation Functions




- ▶ The **rectifier** (or “ramp”) function is popular for many modern applications
 - ▶ A network using the rectifier is known as a **rectifier linear unit** (ReLU)
- ▶ The **Softplus** function is a smooth approximation to the rectifier

Machine Learning (COMP 135) 18

18

Other Popular Activation Functions



- ▶ The ReLU function is **partially** differentiable:

$$\frac{\delta \text{ReLU}}{\delta x}(x) = \begin{cases} 0 & \text{if input } x < 0 \\ 1 & \text{if input } x > 0 \\ \text{undef} & \text{if input } x = 0 \end{cases}$$

- ▶ For many purposes, the undefined value of the derivative is simply set **arbitrarily** (say to 0.5)

- ▶ Alternatively, if using Softplus approximation, we have a well-defined derivative everywhere:

$$\frac{\delta \text{Softplus}}{\delta x}(x) = \frac{1}{1 + e^{-x}}$$

The derivative of Softplus is the Sigmoid Logistic!

Machine Learning (COMP 135) 19

19

Activation Functions Everywhere!

- | | | |
|----------------------|--|---|
| ▶ Logistic | $f(x) = \frac{1}{1 + e^{-x}}$ | $\frac{\delta f}{\delta x}(x) = f(x)(1 - f(x))$ |
| ▶ ReLU | $f(x) = \max(0, x)$ | $\frac{\delta f}{\delta x}(x) = \{0, \text{undef}, 1\}$ |
| ▶ Softplus | $f(x) = \ln(1 + e^x)$ | $\frac{\delta f}{\delta x}(x) = \frac{1}{1 + e^{-x}}$ |
| ▶ Hyperbolic Tangent | $f(x) = \frac{1 - e^{-2x}}{1 + e^{-2x}}$ | $\frac{\delta f}{\delta x}(x) = 1 - f(x)^2$ |
| ▶ Gaussian | $f(x) = e^{-\frac{x^2}{2}}$ | $\frac{\delta f}{\delta x}(x) = -x f(x)$ |

Machine Learning (COMP 135) 20


20

Choosing Activation Functions

► Functions have different pros and cons:


1. Sigmoid: historically popular, less so today

- Susceptible to **saturation**: very large weights, tiny gradients
- Not zero-centered, which is sometimes inconvenient
- More popular as an *output probability* function (generally in a **softmax** manner, with values are normalized to sum to 1)



2. Hyperbolic tangent

- Can saturate like the sigmoid, but is zero-centered



3. ReLU/Softplus: most popular function in modern uses

- ReLU is susceptible to “dying” neurons (these do not contribute to output in any real way)
- Sensitive to learning rate
- Softplus sometimes preferred, due to its smoothness

