

CSE 221: Algorithms

Sorting lower bounds and Linear time sorting

Mumit Khan

Computer Science and Engineering
BRAC University

References

- 1 T. H. Cormen, C. E. Leiserson, R. L. Rivest, and C. Stein, *Introduction to Algorithms, Second Edition*. The MIT Press, September 2001.
- 2 Erik Demaine and Charles Leiserson, *6.046J Introduction to Algorithms*. MIT OpenCourseWare, Fall 2005. Available from: ocw.mit.edu/OcwWeb/Electrical-Engineering-and-Computer-Science/6-046JFall-2005/CourseHome/index.htm

Last modified: October 27, 2009



This work is licensed under the *Creative Commons Attribution-Noncommercial-Share Alike 3.0 Unported License*.

Contents

- 1 Sorting lower bounds
 - What's the best we can do?
 - Lower bound

- 2 Sorting in linear time
 - Counting sort
 - Radix sort
 - Conclusion

Contents

- 1 Sorting lower bounds
 - What's the best we can do?
 - Lower bound
- 2 Sorting in linear time
 - Counting sort
 - Radix sort
 - Conclusion

What's the best we can do?

- Bubble, selection, insertion, quicksort ... $O(n^2)$
- Heapsort, mergesort ... $O(n \lg n)$

What's the best we can do?

- Bubble, selection, insertion, quicksort ... $O(n^2)$
- Heapsort, mergesort ... $O(n \lg n)$

What's the best we can do?

- Bubble, selection, insertion, quicksort ... $O(n^2)$
- Heapsort, mergesort ... $O(n \lg n)$

What's the best we can do?

- Bubble, selection, insertion, quicksort ... $O(n^2)$
- Heapsort, mergesort ... $O(n \lg n)$

Question

Can a sorting algorithm do better than $O(n \lg n)$ in the worst-case?

What's the best we can do?


- Bubble, selection, insertion, quicksort ... $O(n^2)$
- Heapsort, mergesort ... $O(n \lg n)$

Question

Can a sorting algorithm do better than $O(n \lg n)$ in the worst-case?
We can use a **decision tree** to answer this question.


Decision tree for comparison based sorting

Sequence $A = \langle 9, 4, 6 \rangle$




Decision tree for comparison based sorting

Sequence $A = \langle 9, 4, 6 \rangle$




Decision tree for comparison based sorting

Sequence $A = \langle 9, 4, 6 \rangle$



Decision tree for comparison based sorting

Sequence $A = \langle 9, 4, 6 \rangle$




Decision tree for comparison based sorting

Sequence $A = \langle 9, 4, 6 \rangle$

\Rightarrow

Sequence $B = \langle 4, 6, 9 \rangle$



Lower bound on comparison based sorting

Question

What is the best that we can do with comparison-based sorting?

- $n!$ possible permutations, one of which is the sorted sequence.
- Minimum number of comparisons is the path from root of the decision tree to one of the $n!$ leaves.
- Height of a binary tree with $n!$ leaves is $\lceil \lg n! \rceil$. (Note: by Stirling's approximation $n! \geq (n/e)^n$, where e is Euler's constant.)

$$\begin{aligned} h &= \lceil \lg n! \rceil \geq \lceil \lg((n/e)^n) \rceil = \lceil n \lg n - n \lg e \rceil \\ &= \Omega(n \lg n) \end{aligned}$$

Lower bound on comparison based sorting

Question

What is the best that we can do with comparison-based sorting?

- $n!$ possible permutations, one of which is the sorted sequence.
- Minimum number of comparisons is the path from root of the decision tree to one of the $n!$ leaves.
- Height of a binary tree with $n!$ leaves is $\lceil \lg n! \rceil$. (Note: by Stirling's approximation $n! \geq (n/e)^n$, where e is Euler's constant.)

$$\begin{aligned} h &= \lceil \lg n! \rceil \geq \lceil \lg((n/e)^n) \rceil = \lceil n \lg n - n \lg e \rceil \\ &= \Omega(n \lg n) \end{aligned}$$

Lower bound on comparison based sorting

Question

What is the best that we can do with comparison-based sorting?

- $n!$ possible permutations, one of which is the sorted sequence.
- Minimum number of comparisons is the path from root of the decision tree to one of the $n!$ leaves.
- Height of a binary tree with $n!$ leaves is $\lceil \lg n! \rceil$. (Note: by Stirling's approximation $n! \geq (n/e)^n$, where e is Euler's constant.)

$$\begin{aligned} h &= \lceil \lg n! \rceil \geq \lceil \lg((n/e)^n) \rceil = \lceil n \lg n - n \lg e \rceil \\ &= \Omega(n \lg n) \end{aligned}$$

Lower bound on comparison based sorting

Question

What is the best that we can do with comparison-based sorting?

- $n!$ possible permutations, one of which is the sorted sequence.
- Minimum number of comparisons is the path from root of the decision tree to one of the $n!$ leaves.
- Height of a binary tree with $n!$ leaves is $\lceil \lg n! \rceil$. (Note: by Stirling's approximation $n! \geq (n/e)^n$, where e is Euler's constant.)

$$\begin{aligned} h &= \lceil \lg n! \rceil \geq \lceil \lg((n/e)^n) \rceil = \lceil n \lg n - n \lg e \rceil \\ &= \Omega(n \lg n) \end{aligned}$$

Lower bound on comparison based sorting

Question

What is the best that we can do with comparison-based sorting?

- $n!$ possible permutations, one of which is the sorted sequence.
- Minimum number of comparisons is the path from root of the decision tree to one of the $n!$ leaves.
- Height of a binary tree with $n!$ leaves is $\lceil \lg n! \rceil$. (Note: by Stirling's approximation $n! \geq (n/e)^n$, where e is Euler's constant.)

$$\begin{aligned} h &= \lceil \lg n! \rceil \geq \lceil \lg((n/e)^n) \rceil = \lceil n \lg n - n \lg e \rceil \\ &= \Omega(n \lg n) \end{aligned}$$

Lower bound on comparison based sorting

Question

What is the best that we can do with comparison-based sorting?

- $n!$ possible permutations, one of which is the sorted sequence.
- Minimum number of comparisons is the path from root of the decision tree to one of the $n!$ leaves.
- Height of a binary tree with $n!$ leaves is $\lceil \lg n! \rceil$. (Note: by Stirling's approximation $n! \geq (n/e)^n$, where e is Euler's constant.)

$$\begin{aligned} h &= \lceil \lg n! \rceil \geq \lceil \lg((n/e)^n) \rceil = \lceil n \lg n - n \lg e \rceil \\ &= \Omega(n \lg n) \end{aligned}$$

Lower bound on comparison based sorting

Question

What is the best that we can do with comparison-based sorting?

- $n!$ possible permutations, one of which is the sorted sequence.
- Minimum number of comparisons is the path from root of the decision tree to one of the $n!$ leaves.
- Height of a binary tree with $n!$ leaves is $\lceil \lg n! \rceil$. (Note: by Stirling's approximation $n! \geq (n/e)^n$, where e is Euler's constant.)

$$\begin{aligned} h &= \lceil \lg n! \rceil \geq \lceil \lg((n/e)^n) \rceil = \lceil n \lg n - n \lg e \rceil \\ &= \Omega(n \lg n) \end{aligned}$$

Lower bound on comparison based sorting

Question

What is the best that we can do with comparison-based sorting?

- $n!$ possible permutations, one of which is the sorted sequence.
- Minimum number of comparisons is the path from root of the decision tree to one of the $n!$ leaves.
- Height of a binary tree with $n!$ leaves is $\lceil \lg n! \rceil$. (Note: by Stirling's approximation $n! \geq (n/e)^n$, where e is Euler's constant.)

$$\begin{aligned} h &= \lceil \lg n! \rceil \geq \lceil \lg((n/e)^n) \rceil = \lceil n \lg n - n \lg e \rceil \\ &= \Omega(n \lg n) \end{aligned}$$

Theorem

The worst-case asymptotic time complexity for any *comparison-based* sorting algorithm is $\Omega(n \lg n)$.

Contents

- 1 Sorting lower bounds
 - What's the best we can do?
 - Lower bound
- 2 Sorting in linear time
 - Counting sort
 - Radix sort
 - Conclusion

Sorting in linear time: Counting sort

Counting sort: No comparisons between elements.

- **Input:** $A[1..n]$, where $A[j] \in \{1, 2, \dots, k\}$.
- **Output:** $B[1..n]$, sorted.
- **Auxiliary storage:** $C[1..k]$.

Sorting in linear time: Counting sort

Counting sort: No comparisons between elements.

- **Input:** $A[1..n]$, where $A[j] \in \{1, 2, \dots, k\}$.
- **Output:** $B[1..n]$, sorted.
- **Auxiliary storage:** $C[1..k]$.

Counting sort algorithm

```
1  for  $i \leftarrow 1$  to  $k$ 
2      do  $C[i] \leftarrow 0$ 
3  for  $j \leftarrow 1$  to  $n$ 
4      do  $C[A[j]] \leftarrow C[A[j]] + 1$             $\triangleright C[i] = |\{key = i\}|$ 
5  for  $i \leftarrow 2$  to  $k$ 
6      do  $C[i] \leftarrow C[i] + C[i - 1]$           $\triangleright C[i] = |\{key \leq i\}|$ 
7  for  $j \leftarrow n$  downto 1
8      do  $B[C[A[j]]] \leftarrow A[j]$ 
9       $C[A[j]] \leftarrow C[A[j]] - 1$ 
```


Counting sort example

	1	2	3	4	5
<i>A</i> :	4	1	3	4	3

	1	2	3	4
<i>C</i> :				

<i>B</i> :					
------------	--	--	--	--	--

Counting sort example: loop 1

	1	2	3	4	5
<i>A</i> :	4	1	3	4	3

	1	2	3	4
<i>C</i> :	0	0	0	0

<i>B</i> :					
------------	--	--	--	--	--

```
for  $i \leftarrow 1$  to  $k$ 
  do  $C[i] \leftarrow 0$ 
```

Counting sort example: loop 2

	1	2	3	4	5
A:	4	1	3	4	3

	1	2	3	4
C:	0	0	0	1

B:					
----	--	--	--	--	--

for $j \leftarrow 1$ to n

do $C[A[j]] \leftarrow C[A[j]] + 1$

$\triangleright C[i] = |\{key = i\}|$

Counting sort example: loop 2

	1	2	3	4	5
A:	4	1	3	4	3

	1	2	3	4
C:	1	0	0	1

B:					
----	--	--	--	--	--

for $j \leftarrow 1$ to n

do $C[A[j]] \leftarrow C[A[j]] + 1$

$\triangleright C[i] = |\{key = i\}|$

Counting sort example: loop 2

	1	2	3	4	5
A:	4	1	3	4	3

	1	2	3	4
C:	1	0	1	1

B:					
----	--	--	--	--	--

for $j \leftarrow 1$ to n

do $C[A[j]] \leftarrow C[A[j]] + 1$

$\triangleright C[i] = |\{key = i\}|$

Counting sort example: loop 2

	1	2	3	4	5
<i>A</i> :	4	1	3	4	3

	1	2	3	4
<i>C</i> :	1	0	1	2

<i>B</i> :					
------------	--	--	--	--	--

for $j \leftarrow 1$ to n

do $C[A[j]] \leftarrow C[A[j]] + 1$

$\triangleright C[i] = |\{key = i\}|$

Counting sort example: loop 2

	1	2	3	4	5
A:	4	1	3	4	3

	1	2	3	4
C:	1	0	2	2

B:					
----	--	--	--	--	--

for $j \leftarrow 1$ to n

do $C[A[j]] \leftarrow C[A[j]] + 1$

$\triangleright C[i] = |\{key = i\}|$

Counting sort example: loop 3

	1	2	3	4	5
A:	4	1	3	4	3

	1	2	3	4
C:	1	0	2	2

B:					
-----------	--	--	--	--	--

C':	1	1	2	2
------------	---	---	---	---

for $i \leftarrow 2$ **to** k

do $C[i] \leftarrow C[i] + C[i - 1]$

$\triangleright C[i] = |\{key \leq i\}|$

Counting sort example: loop 3

	1	2	3	4	5
A:	4	1	3	4	3

	1	2	3	4
C:	1	0	2	2

B:					
-----------	--	--	--	--	--

C':	1	1	3	2
------------	---	---	---	---

for $i \leftarrow 2$ **to** k

do $C[i] \leftarrow C[i] + C[i - 1]$

$\triangleright C[i] = |\{key \leq i\}|$

Counting sort example: loop 3

	1	2	3	4	5
<i>A</i> :	4	1	3	4	3

	1	2	3	4
<i>C</i> :	1	0	2	2

<i>B</i> :					
------------	--	--	--	--	--



<i>C'</i> :	1	1	3	5
-------------	---	---	---	---

for $i \leftarrow 2$ **to** k

do $C[i] \leftarrow C[i] + C[i - 1]$



$\triangleright C[i] = |\{key \leq i\}|$

Counting sort example: loop 4





```
for  $j \leftarrow n$  downto 1  
  do  $B[C[A[j]]] \leftarrow A[j]$   
      $C[A[j]] \leftarrow C[A[j]] - 1$ 
```

Counting sort example: loop 4





```
for  $j \leftarrow n$  downto 1  
  do  $B[C[A[j]]] \leftarrow A[j]$   
      $C[A[j]] \leftarrow C[A[j]] - 1$ 
```

Counting sort example: loop 4




```
for  $j \leftarrow n$  downto 1  
  do  $B[C[A[j]]] \leftarrow A[j]$   
      $C[A[j]] \leftarrow C[A[j]] - 1$ 
```

Counting sort example: loop 4



```
for  $j \leftarrow n$  downto 1  
  do  $B[C[A[j]]] \leftarrow A[j]$   
      $C[A[j]] \leftarrow C[A[j]] - 1$ 
```

Counting sort example: loop 4




```
for  $j \leftarrow n$  downto 1  
  do  $B[C[A[j]]] \leftarrow A[j]$   
      $C[A[j]] \leftarrow C[A[j]] - 1$ 
```

Sort stability

Counting sort is stable, ie., it preserves the relative order of “equal” elements in the input.


Sort stability

Counting sort is stable, ie., it preserves the relative order of “equal” elements in the input.



Sort stability

Counting sort is stable, ie., it preserves the relative order of “equal” elements in the input.




Questions

- Would it still be stable if we had used **for $j \leftarrow 1$ to n** instead of **for $j \leftarrow n$ downto 1**?

Sort stability

Counting sort is stable, ie., it preserves the relative order of “equal” elements in the input.



Questions

- Would it still be stable if we had used **for $j \leftarrow 1$ to n** instead of **for $j \leftarrow n$ downto 1**?
- What other sort algorithms that you've seen so far are stable?

Counting sort complexity

```
for  $i \leftarrow 1$  to  $k$ 
    do  $C[i] \leftarrow 0$ 
for  $j \leftarrow 1$  to  $n$ 
    do  $C[A[j]] \leftarrow C[A[j]] + 1$ 
for  $i \leftarrow 2$  to  $k$ 
    do  $C[i] \leftarrow C[i] + C[i - 1]$ 
for  $j \leftarrow n$  downto  $1$ 
    do  $B[C[A[j]]] \leftarrow A[j]$ 
        $C[A[j]] \leftarrow C[A[j]] - 1$ 
```

Counting sort complexity

$\Theta(k)$ { **for** $i \leftarrow 1$ **to** k
 do $C[i] \leftarrow 0$
 for $j \leftarrow 1$ **to** n
 do $C[A[j]] \leftarrow C[A[j]] + 1$
 for $i \leftarrow 2$ **to** k
 do $C[i] \leftarrow C[i] + C[i - 1]$
 for $j \leftarrow n$ **downto** 1
 do $B[C[A[j]]] \leftarrow A[j]$
 $C[A[j]] \leftarrow C[A[j]] - 1$

Counting sort complexity

$\Theta(k)$ { **for** $i \leftarrow 1$ **to** k
 do $C[i] \leftarrow 0$

$\Theta(n)$ { **for** $j \leftarrow 1$ **to** n
 do $C[A[j]] \leftarrow C[A[j]] + 1$

for $i \leftarrow 2$ **to** k
 do $C[i] \leftarrow C[i] + C[i - 1]$

for $j \leftarrow n$ **downto** 1
 do $B[C[A[j]]] \leftarrow A[j]$
 $C[A[j]] \leftarrow C[A[j]] - 1$

Counting sort complexity

$\Theta(k)$ { **for** $i \leftarrow 1$ **to** k
 do $C[i] \leftarrow 0$

$\Theta(n)$ { **for** $j \leftarrow 1$ **to** n
 do $C[A[j]] \leftarrow C[A[j]] + 1$

$\Theta(k)$ { **for** $i \leftarrow 2$ **to** k
 do $C[i] \leftarrow C[i] + C[i - 1]$

for $j \leftarrow n$ **downto** 1
 do $B[C[A[j]]] \leftarrow A[j]$
 $C[A[j]] \leftarrow C[A[j]] - 1$

Counting sort complexity

$\Theta(k)$	{	for $i \leftarrow 1$ to k
		do $C[i] \leftarrow 0$
$\Theta(n)$	{	for $j \leftarrow 1$ to n
		do $C[A[j]] \leftarrow C[A[j]] + 1$
$\Theta(k)$	{	for $i \leftarrow 2$ to k
		do $C[i] \leftarrow C[i] + C[i - 1]$
$\Theta(n)$	{	for $j \leftarrow n$ downto 1
		do $B[C[A[j]]] \leftarrow A[j]$ $C[A[j]] \leftarrow C[A[j]] - 1$

Counting sort complexity

$\Theta(k)$	{	for $i \leftarrow 1$ to k
		do $C[i] \leftarrow 0$
$\Theta(n)$	{	for $j \leftarrow 1$ to n
		do $C[A[j]] \leftarrow C[A[j]] + 1$
$\Theta(k)$	{	for $i \leftarrow 2$ to k
		do $C[i] \leftarrow C[i] + C[i - 1]$
$\Theta(n)$	{	for $j \leftarrow n$ downto 1
		do $B[C[A[j]]] \leftarrow A[j]$ $C[A[j]] \leftarrow C[A[j]] - 1$

$\Theta(n + k)$

Running time of Counting sort

The worst-case running time of Counting sort is $O(n + k)$.

Running time of Counting sort

The worst-case running time of Counting sort is $O(n + k)$.

Observations

- If $k = O(n)$, then the worst case running time is $\Theta(n)$.

Running time of Counting sort

The worst-case running time of Counting sort is $O(n + k)$.

Observations

- If $k = O(n)$, then the worst case running time is $\Theta(n)$.
- But didn't we just prove that sorting takes $\Omega(n \lg n)$ time?

Running time of Counting sort

The worst-case running time of Counting sort is $O(n + k)$.

Observations

- If $k = O(n)$, then the worst case running time is $\Theta(n)$.
- But didn't we just prove that sorting takes $\Omega(n \lg n)$ time?
- So what's wrong with this picture?

Running time of Counting sort

The worst-case running time of Counting sort is $O(n + k)$.

Observations

- If $k = O(n)$, then the worst case running time is $\Theta(n)$.
- But didn't we just prove that sorting takes $\Omega(n \lg n)$ time?
- So what's wrong with this picture?

And the answer is ...

- The $\Omega(n \lg n)$ is for **comparison** sorting.

Running time of Counting sort

The worst-case running time of Counting sort is $O(n + k)$.

Observations

- If $k = O(n)$, then the worst case running time is $\Theta(n)$.
- But didn't we just prove that sorting takes $\Omega(n \lg n)$ time?
- So what's wrong with this picture?

And the answer is ...

- The $\Omega(n \lg n)$ is for **comparison** sorting.
- Counting sort is **not** a **comparison** sort.

Running time of Counting sort

The worst-case running time of Counting sort is $O(n + k)$.

Observations

- If $k = O(n)$, then the worst case running time is $\Theta(n)$.
- But didn't we just prove that sorting takes $\Omega(n \lg n)$ time?
- So what's wrong with this picture?

And the answer is ...

- The $\Omega(n \lg n)$ is for **comparison** sorting.
- Counting sort is **not** a **comparison** sort.
- In fact, counting sort does not use a single **comparison**.

Radix sort

3	2	9		3	2	9
4	5	7		3	5	5
6	5	7		4	3	6
8	3	9	⇒	4	5	7
4	3	6		6	5	7
7	2	0		7	2	0
3	5	5		8	3	9

Radix sort basics

- Digit by digit sort.
- Can be either *most-significant* digit first, or *least-significant* digit first.
- A good way is to stably sort *least-significant* digit first.


Radix sort in action

3	2	9
4	5	7
6	5	7
8	3	9
4	3	6
7	2	0
3	5	5


Radix sort in action

3	2	9
4	5	7
6	5	7
8	3	9
4	3	6
7	2	0
3	5	5


Radix sort in action




Radix sort in action



Radix sort in action



Radix sort in action



Analysis: For numbers in the range $[0..n^d - 1]$, radix sort runs in $\Theta(dn)$ time.

Conclusion

- Linear-time sorting algorithms beat the $\Omega(n \lg n)$ lower bound of comparison-based sorts by *not* doing any element comparison.

Conclusion

- Linear-time sorting algorithms beat the $\Omega(n \lg n)$ lower bound of comparison-based sorts by *not* doing any element comparison.
- Counting sort is a $\Theta(n)$ time algorithm if $k = O(n)$, and it is stable.

Conclusion

- Linear-time sorting algorithms beat the $\Omega(n \lg n)$ lower bound of comparison-based sorts by *not* doing any element comparison.
- Counting sort is a $\Theta(n)$ time algorithm if $k = O(n)$, and it is stable.
- Radix sort is a $\Theta(dn)$ algorithm for numbers in $[0 \dots 2^d - 1]$ range.

Conclusion

- Linear-time sorting algorithms beat the $\Omega(n \lg n)$ lower bound of comparison-based sorts by *not* doing any element comparison.
- Counting sort is a $\Theta(n)$ time algorithm if $k = O(n)$, and it is stable.
- Radix sort is a $\Theta(dn)$ algorithm for numbers in $[0 \dots 2^d - 1]$ range.
- Radix sort is an excellent algorithm is trivial to implement, and works well for large inputs.

Conclusion

- Linear-time sorting algorithms beat the $\Omega(n \lg n)$ lower bound of comparison-based sorts by *not* doing any element comparison.
- Counting sort is a $\Theta(n)$ time algorithm if $k = O(n)$, and it is stable.
- Radix sort is a $\Theta(dn)$ algorithm for numbers in $[0 \dots 2^d - 1]$ range.
- Radix sort is an excellent algorithm is trivial to implement, and works well for large inputs.
- Radix sort often uses counting sort as the stable auxiliary sorting routine.

Conclusion

- Linear-time sorting algorithms beat the $\Omega(n \lg n)$ lower bound of comparison-based sorts by *not* doing any element comparison.
- Counting sort is a $\Theta(n)$ time algorithm if $k = O(n)$, and it is stable.
- Radix sort is a $\Theta(dn)$ algorithm for numbers in $[0 \dots 2^d - 1]$ range.
- Radix sort is an excellent algorithm is trivial to implement, and works well for large inputs.
- Radix sort often uses counting sort as the stable auxiliary sorting routine.

Questions to ask (and remember)

Conclusion

- Linear-time sorting algorithms beat the $\Omega(n \lg n)$ lower bound of comparison-based sorts by *not* doing any element comparison.
- Counting sort is a $\Theta(n)$ time algorithm if $k = O(n)$, and it is stable.
- Radix sort is a $\Theta(dn)$ algorithm for numbers in $[0 \dots 2^d - 1]$ range.
- Radix sort is an excellent algorithm is trivial to implement, and works well for large inputs.
- Radix sort often uses counting sort as the stable auxiliary sorting routine.

Questions to ask (and remember)

- What is the lower bound of comparison-based sorting algorithms?

Conclusion

- Linear-time sorting algorithms beat the $\Omega(n \lg n)$ lower bound of comparison-based sorts by *not* doing any element comparison.
- Counting sort is a $\Theta(n)$ time algorithm if $k = O(n)$, and it is stable.
- Radix sort is a $\Theta(dn)$ algorithm for numbers in $[0 \dots 2^d - 1]$ range.
- Radix sort is an excellent algorithm is trivial to implement, and works well for large inputs.
- Radix sort often uses counting sort as the stable auxiliary sorting routine.

Questions to ask (and remember)

- What is the lower bound of comparison-based sorting algorithms?
- Are there sorting algorithms that beat this lower bound?

Conclusion

- Linear-time sorting algorithms beat the $\Omega(n \lg n)$ lower bound of comparison-based sorts by *not* doing any element comparison.
- Counting sort is a $\Theta(n)$ time algorithm if $k = O(n)$, and it is stable.
- Radix sort is a $\Theta(dn)$ algorithm for numbers in $[0 \dots 2^d - 1]$ range.
- Radix sort is an excellent algorithm is trivial to implement, and works well for large inputs.
- Radix sort often uses counting sort as the stable auxiliary sorting routine.

Questions to ask (and remember)

- What is the lower bound of comparison-based sorting algorithms?
- Are there sorting algorithms that beat this lower bound?
- How can you beat a proven lower bound?

Conclusion

- Linear-time sorting algorithms beat the $\Omega(n \lg n)$ lower bound of comparison-based sorts by *not* doing any element comparison.
- Counting sort is a $\Theta(n)$ time algorithm if $k = O(n)$, and it is stable.
- Radix sort is a $\Theta(dn)$ algorithm for numbers in $[0 \dots 2^d - 1]$ range.
- Radix sort is an excellent algorithm is trivial to implement, and works well for large inputs.
- Radix sort often uses counting sort as the stable auxiliary sorting routine.

Questions to ask (and remember)

- What is the lower bound of comparison-based sorting algorithms?
- Are there sorting algorithms that beat this lower bound?
- How can you beat a proven lower bound?
- Why do we recommend sorting *least-significant* digits first in radix sort?