Grammars and ambiguity

CS164 3:30-5:00 TT 10 Evans

Prof. Bodik CS 164 Lecture 8

Recall: derivations and parse trees

A $\textit{derivation}\$ is a sequence of productions

$$S \rightarrow ... \rightarrow ...$$


A derivation can be drawn as a parse tree

- Start symbol is the tree's root
- For a production $X \to Y_1 \dots Y_n$ add children $\ Y_1, \dots, \ Y_n$ to node X

You need parse trees to build ASTs

Prof. Bodik CS 164 Lecture 8

Derivation Example (Cont.)



Prof. Bodik CS 164 Lecture 8

Derivation in Detail (2)



Prof. Bodik CS 164 Lecture 8

Overview

- derivations and parse trees
 - different derivations produce may produce same parse tree
- ambiguous grammars
 - what they are
 - and how to fix them

Prof. Bodik CS 164 Lecture 8

Derivation Example

• Grammar

$$E \rightarrow E+E \mid E*E \mid (E) \mid id$$

String

$$id * id + id$$

Prof. Bodik CS 164 Lecture 8

Derivation in Detail (1)


Е

4

E


Prof. Bodik CS 164 Lecture 8


Derivation in Detail (3)



Prof. Bodik CS 164 Lecture 8

Derivation in Detail (4) $E \\ \rightarrow E+E \\ \rightarrow E*E+E \\ \rightarrow id*E+E$ Prof. Bodik CS 164 Lecture 8





Derivation in Detail (5) E $\rightarrow E+E$ $\rightarrow E*E+E$ $\rightarrow id*E+E$ $\rightarrow id*id+E id id$ Prof. Bodik CS 164 Lecture 8

Notes on Derivations

- · A parse tree has
 - Terminals at the leaves
 - Non-terminals at the interior nodes
- An in-order traversal of the leaves is the original input
- The parse tree shows the association of operations, the input string does not

Prof. Bodik CS 164 Lecture 8

12


14

Right-most Derivation in Detail (1)

E


Prof. Bodik CS 164 Lecture 8

Right-most Derivation in Detail (3)




Prof. Bodik CS 164 Lecture 8

Right-most Derivation in Detail (4)




Prof. Bodik CS 164 Lecture 8

Right-most Derivation in Detail (5)



Right-most Derivation in Detail (6)



Derivations and Parse Trees

- Note that right-most and left-most derivations have the same parse tree
- The difference is only in the order in which branches are added

Prof. Bodik CS 164 Lecture 8

20

ambiguity

Ambiguity

• Grammar

$$E \rightarrow E + E \mid E * E \mid (E) \mid int$$


Strings

Prof. Bodik CS 164 Lecture 8

22

Ambiguity. Example


This string has two parse trees



23

Ambiguity. Example

This string has two parse trees



* has higher precedence than +

Prof. Bodik CS 164 Lecture 8

24

Ambiguity (Cont.)

- A grammar is ambiguous if it has more than one parse tree for some string
 - Equivalently, there is more than one right-most or left-most derivation for some string
- · Ambiguity is bad
 - Leaves meaning of some programs ill-defined
- Ambiguity is <u>common</u> in programming languages
 - Arithmetic expressions
 - IF-THEN-ELSE

Prof. Bodik CS 164 Lecture 8

25

27

Dealing with Ambiguity

- · There are several ways to handle ambiguity
- Most direct method is to rewrite the grammar unambiguously

$$E \rightarrow E + T \mid T$$

 $T \rightarrow T^* \text{ int } | \text{ int } | (E)$


- Enforces precedence of * over +
- Enforces left-associativity of + and *

Prof. Bodik CS 164 Lecture 8

26

Ambiguity. Example

The int * int + int has ony one parse tree now



Prof. Bodik CS 164 Lecture 8

Ambiguity: The Dangling Else

• Consider the grammar

$$S \rightarrow \text{if E then S}$$

| if E then S else S
| OTHER

· This grammar is also ambiguous

28


Prof. Bodik CS 164 Lecture 8

The Dangling Else: Example

· The expression

if E_1 then if E_2 then S_3 else S_4 has two parse trees





· Typically we want the second form

Prof. Bodik CS 164 Lecture 8

The Dangling Else: A Fix

- · else matches the closest unmatched then
- We can describe this in the grammar (distinguish between matched and unmatched "then")

```
S \rightarrow MIF /* all then are matched */ | UIF /* some then are unmatched */ MIF \rightarrow if E then MIF else MIF | OTHER UIF \rightarrow if E then S | if E then MIF else UIF
```

· Describes the same set of strings

Prof. Bodik CS 164 Lecture 8


30

The Dangling Else: Example Revisited

The expression if E₁ then if E₂ then S₃ else S₄



 A valid parse tree (for a UIF)



 Not valid because the then expression is not a MIF

Prof. Bodik CS 164 Lecture 8

Ambiguity

- · No general techniques for handling ambiguity
- Impossible to convert automatically an ambiguous grammar to an unambiguous one
- Used with care, ambiguity can simplify the grammar
 - Sometimes allows more natural definitions
 - We need disambiguation mechanisms

3

Precedence and Associativity Declarations

- · Instead of rewriting the grammar
 - Use the more natural (ambiguous) grammar
 - Along with disambiguating declarations
- LR (bottom-up) parsers allow <u>precedence and</u> <u>associativity declarations</u> to disambiguate grammars
- Examples ...


Prof. Bodik CS 164 Lecture 8

33

Precedence Declarations

- Consider the grammar $E \rightarrow E + E \mid E * E \mid$ int
 - And the string int + int * int





Precedence declarations: %left + %left *


Prof. Bodik CS 164 Lecture 8

35

Associativity Declarations

- Consider the grammar
- · Ambiguous: two parse trees of int + int + int





 $E \rightarrow E + E \mid int$

• Left-associativity declaration: %left +

Prof. Bodik CS 164 Lecture 8

34