

IPA attribute	IPA value	How to conver it	LDAP attribute	LDAP value
<i>cn</i>	ipa_rule	copy*	<i>cn</i>	ipa_rule
<i>userCategory</i>	all	upper letters	<i>sudoUser</i>	ALL
<i>memberUser</i>	uid= admin ,cn=users,cn=accounts,\$DC	extract value of uid		admin
	cn= ipausers ,cn=groups,cn=accounts,\$DC	extract value of cn		%ipausers
<i>externalUser</i>	xpaulc03	copy*		xpaulc03
<i>hostCategory</i>	all	upper letters	<i>sudoHost</i>	ALL
<i>memberHost</i>	fqdn= client1.example.cz ,cn=computers,cn=accounts,\$DC	extract value of fqdn		client1.example.cz
	cn= clients ,cn=hostgroups,cn=accounts,\$DC	extract value of cn		+clients
<i>externalHost</i>	xpaulc03.ad-domain.cz	copy*		xpaulc03.ad-domain.cz
<i>cmdCategory</i>	all	upper letters	<i>sudoCommand</i>	ALL
<i>memberAllowCmd</i>	ipaUniqueID=976b...4dc10b,cn=sudocmds,cn=sudo,\$DC	copy sudoCmd from deref(6f545188-...o,\$DC)		/bin/fdisk
	cn=disc,cn=sudocmdgroups,cn=sudo,\$DC	entry contain DNs of ipa commands		
<i>memberDenyCmd</i>	ipaUniqueID=6f545188-...-c10b,cn=sudocmds,cn=sudo,\$DC	copy sudoCmd from deref(6f545188-...o,\$DC)		/sbin/blkid
			<i>sudoRunAs (deprecated)</i>	
<i>ipaSudoRunAsUserCategory</i>	all	upper letters	<i>sudoRunAsUser</i>	ALL
<i>ipaSudoRunAs</i>	uid= admin ,cn=users,cn=accounts,\$DC	extract value of uid		admin
	cn= ipausers ,cn=groups,cn=accounts,\$DC	extract value of cn		%ipausers
<i>ipaSudoRunAsExtUser</i>	xpaulc03	copy*		xpaulc03
<i>ipaSudoRunAsGroupCategory</i>	all	upper letters	<i>sudoRunAsGroup</i>	ALL
<i>ipaSudoRunAsGroup**</i>	cn= gid_not_matched ,cn=groups,cn=accounts,\$DC	extract value of cn		gid_not_matched
<i>ipaSudoRunAsExtGroup**</i>	managers	copy*		managers
<i>ipaSudoOpt</i>	!authenticate	copy*	<i>sudoOption</i>	!authenticate
<i>sudoNotBefore</i>		copy*	<i>sudoNotBefore</i>	
<i>sudoNotAfter</i>		copy*	<i>sudoNotAfter</i>	
<i>ipaSudoOrder</i>		copy*	<i>sudoOrder</i>	

cn=sudorules,cn=sudo,\$DC	example		
<i>ipaUniqueID</i>	976b3972-a2b5-11e3-86b0-0800274dc10b		
<i>sudoCmd</i>	/bin/fdisk	copy*	<i>sudoCommand</i>
<i>memberOf</i>	cn=disc,cn=sudocmdgroups,cn=sudo,\$DC		

cn=sudocmdgroups,cn=sudo,\$DC	example		
<i>ipaUniqueID</i>	976b3972-a2b5-11e3-86b0-0800274dc10b		
<i>cn</i>	Disc Operations		
<i>description</i>	Disc Operations		
<i>member</i>	ipaUniqueID=fdcaf84-...-080027eec4b0,cn=sudocmds,cn=sudo,\$DC		

* use attrs map for it

** the group has to be POSIX (but this is IPA problem)