Záznam sudo pravidla v IPA SUDO schématu

dn: ipaUniqueID=e6917a9c,cn=sudorules,cn=sudo,\$DC

cn: test13

ipaEnabledFlag: TRUE

memberUser: uid=xsruba03,cn=users,cn=accounts,\$DC

memberHost: fqdn=client1.example.cz ,cn=computers,cn=accounts,\$DC

memberAllowCmd: cn=disc,cn=sudocmdgroups,cn=sudo,\$DC

Compat Plugin

dn: cn=disc,cn=**sudocmdgroups**cn=sudo,\$DC

cn: disc

member: ipaUniqueID=fdfcaf84,cn=sudocmds,cn=sudo,\$DC

member: ipaUniqueID=c484ca28,cn=sudocmds,cn=sudo, \$DC

dn: cn=test13,ou=sudoers,\$DC

cn: test13

sudoUser. xsruba03

sudoHost client1.example.cz sudoCommand: /sbin/fdisk sudoCommand: /sbin/blkid dn: ipaUniqueID=c484ca28,cn=sudocmdscn=sudo,\$DC

sudoCmd /sbin/fdisk

memberOf: cn=disc,cn=sudocmdgroups,cn=sudo,\$DC

dn: ipaUniqueID=fdfcaf84,cn=sudocmdscn=sudo,\$DC

sudoCmd /sbin/blkid

memberOf: cn=disc,cn=sudocmdgroups,cn=sudo,\$DC