
Fundamentals of Computer Programming

CS-110

***Course Instructor: Dr.
Momina Moetesum***




Basic I/O, Variables, Constants, Escape Sequences

Week 2-A

```
51 template <typename T, typename I>
52 void TestIntegral(const T values[], int num_values) {
53     for (int i = 0; i < num_values; ++i) {
54         T t0 = values[i];
55         I i0 = absl::bit_cast<I>(t0);
56         T t1 = absl::bit_cast<T>(i0);
57         I i1 = absl::bit_cast<I>(t1);
58         ASSERT_EQ(0, memcmp(&t0, &t1, sizeof(T)));
59         ASSERT_EQ(i0, i1);
60     }
61 }
62
63 TEST(BitCast, Bool) {
64     static const bool bool_list[] = { false, true };
65     TestMarshall<bool>(bool_list, ABSL_ARRAYSIZE(bool_list));
66 }
67
68 TEST(BitCast, Int32) {
69     static const int32_t int_list[] =
70         { 0, 1, 100, 2147483647, -1, -100, -2147483647, -2147483647-1 };
71     TestMarshall<int32_t>(int_list, ABSL_ARRAYSIZE(int_list));
72 }
73
74 TEST(BitCast, Int64) {
75     static const int64_t int64_list[] =
76         { 0, 1, 1LL << 40, -1, -(1LL<<40) };
77     TestMarshall<int64_t>(int64_list, ABSL_ARRAYSIZE(int64_list));
```

C++ Tokens



There are 95 keywords reserved in C++. Some of the main Keywords are:

break	try	catch	char	class	const	continue
default	delete	auto	else	friend	for	float
long	new	operator	private	protected	public	return
short	sizeof	static	this	typedef	enum	throw
mutable	struct	case	register	switch	and	or
namespace	static_cast	goto	not	xor	bool	do
double	int	unsigned	void	virtual	union	while

Keywords

Keywords in C++ are the tokens that are the reserved words in programming languages that have their specific meaning and functionalities within a program.

Safeguarding:
using namespace std; OR
std::keyword

Identifiers

In C++, entities like variables, functions, classes, or structs must be given unique names within the program so that they can be uniquely identified.

The unique names given to these entities are known as “identifiers”

Valid Identifiers	Invalid Identifiers
<code>_name</code>	<code>#name</code> (Cannot start with special character except ‘_’)
<code>Number89</code>	<code>2num</code> (Cannot start with a digit)
<code>first_name</code>	<code>first name</code> (Cannot include space)
<code>_last_name_</code>	<code>string</code> (Cannot be same as a keyword)

Rules for Identifiers



An identifier can only have alphabets, numbers, and the underscore _.



An identifier cannot begin with a number.



It is a preferred practice to begin an identifier with a lowercase character. For example, **name** is preferable to **Name**.



An identifier cannot be a keyword. For example, `int` is a keyword that is used to denote integers.



An identifier can start with an underscore. However, it's not considered a good practice.

Special symbols are the token characters having specific meanings within the syntax of the programming language.


- **Semicolon (;):** It is used to terminate the statement.
- **Square brackets []:** They are used to store array elements.
- **Curly Braces {}:** They are used to define blocks of code.
- **Scope resolution (::):** Scope resolution operator is used to access members of namespaces, classes, etc.
- **Dot (.):** Dot operator also called member access operator used to access class and struct members.
- **Assignment operator '=':** This operator is used to assign values to variables.
- **Double-quote ("):** It is used to enclose string literals.
- **Single-quote ('):** It is used to enclose character literals.

Variables

```
int age = 14;    // age is 14
age = 17;        // age is 17
```


- Variables in C++ is a name given to a memory location. It is the basic unit of storage in a program.
- The value stored in a variable can be changed during program execution.
- A variable is only a name given to a memory location, all the operations done on the variable effects that memory location.
- In C++, all the variables must be declared before use.

Variable Declaration & initialization in one line



Variables


- Variable Declaration
- Variable Initialization
- Variable Definition



```
1  /* C++ program to show difference between
2  definition and declaration of a variable */
3  #include <iostream>
4  using namespace std;
5  int main()
6  {
7      int a; // this is declaration of variable a
8      a = 10; // this is initialisation of a
9      int b = 20; // this is definition = declaration + initialisation
10     char a123 = 'a'; // declaration and definition of variable 'a123'
11     // This is also both declaration and definition
12     // as 'c' is allocated memory and assigned some garbage value.
13     float c;
14     int _c, _d45, e; // multiple declarations and definitions
15     int num1=34, num2=55, num3=68; // multiple definitions
16     // Let us print a variable
17     cout << a123 << endl;
18     return 0;
19 }
20
```


Literals

- Literals represent fixed values that cannot be modified.
- Literals contain memory but they do not have references as variables.



Data Types

C++ supports a wide variety of data types and the programmer can select the data type appropriate to the needs of the application. Data types specify the size and types of values to be stored.



`int` - stores integers (whole numbers), without decimals, such as 123 or -123

`double` - stores floating point numbers, with decimals, such as 19.99 or -19.99

`char` - stores single characters, such as 'a' or 'B'. Char values are surrounded by single quotes

`string` - stores text, such as "Hello World". String values are surrounded by double quotes

`bool` - stores values with two states: true or false

Data Types and Memory Allocation

Data Type	Size (In Bytes)	Range
short int	2	-32,768 to 32,767
unsigned short int	2	0 to 65,535
unsigned int	4	0 to 4,294,967,295
int	4	-2,147,483,648 to 2,147,483,647
long int	4	-2,147,483,648 to 2,147,483,647
unsigned long int	4	0 to 4,294,967,295
long long int	8	$-(2^{63})$ to $(2^{63})-1$
unsigned long long int	8	0 to 18,446,744,073,709,551,615
signed char	1	-128 to 127
unsigned char	1	0 to 255
float	4	
double	8	
long double	12	
wchar_t	2 to 4	1 wide character

Address	Content	Name	Type
90000000	00	sum	int (4 bytes)
90000001	00		
90000002	00		
90000003	FF	age	short (2 bytes)
90000004	FF		
90000005	FF		
90000006	1F	average	double (8 bytes)
90000007	FF		
90000008	FF		
90000009	FF		
9000000A	FF		
9000000B	FF		
9000000C	FF		
9000000D	FF		

C and C++ language provide the **sizeof()** operator to check the size of the data types

Constants

- Constants are variables whose values cannot be modified once they are declared in the program.
- In C and C++ language, the **const** keyword is used to define the constants.

```
1 // C++ program to illustrate constant variable definition
2 #include <stdio.h>
3 int main()
4 {
5     // defining integer constant using const keyword
6     const int int_const = 25;
7     // defining character constant using const keyword
8     const char char_const = 'A';
9     // defining float constant using const keyword
10    const float float_const = 15.66;
11    cout<<"Printing value of Integer Constant="<<int_const;
12    cout<<"Printing value of Integer Constant="<<char_const;
13    cout<<"Printing value of Integer Constant="<<float_const;
14    return 0;
15 }
```

How to Declare Constants

const int var;



const int var;
var=5



Const int var = 5;



Basic User Input/Output

- **#include <iostream>** is a header file library that lets us work with input and output objects
- **cout** is pronounced "see-out". Used for output, and uses the **insertion** operator (<<)
- **cin** is pronounced "see-in". Used for input, and uses the **extraction** operator (>>)

```
int x, y;
int sum;
cout << "Type a number: ";
cin >> x;
cout << "Type another number: ";
cin >> y;
sum = x + y;
cout << "Sum is: " << sum;
```

Escape Sequences

- Sometimes, it is necessary to use characters that cannot be typed or has special meaning in C++ programming. For example, newline (enter), tab, question mark, etc.
- In order to use these characters, escape sequences are used.
- Try the following:
- <https://ciphertrick.com/c-beginners-introduction-to-escape-sequences/>
- <https://programmingdigest.com/escape-sequence-in-c-with-examples/>

Escape Sequence	Meaning
<code>\n</code>	New Line
<code>\t</code>	Horizontal Tab
<code>\b</code>	BackSpace
<code>\r</code>	Carriage Return
<code>\a</code>	Audible bell
<code>\'</code>	Printing single quotation
<code>\"</code>	printing double quotation
<code>\?</code>	Question Mark Sequence
<code>\\</code>	Back Slash
<code>\f</code>	Form Feed
<code>\v</code>	Vertical Tab
<code>\0</code>	Null Value
<code>\nnn</code>	Print octal value
<code>\xhh</code>	Print Hexadecimal value



Acknowledgment

- Content of these slides are taken from:
 - <https://www.geeksforgeeks.org/>
 - <https://www.tutorialspoint.com/>
 - <https://www.programiz.com/>