π SOD-M: Building Service-Oriented Applications in the Presence of Non-Functional Requirements

Khalid Belhajjame¹, Valeria de Castro², Umberto Souza da Costa³, Javier A. Espinosa-Oviedo⁴, Martin A. Musicante^{3,*}, Plácido A. Souza Neto⁵, Genoveva Vargas-Solar⁶, José-Luis Zechinelli-Martini⁴

Abstract Specifying non-functional requirements (NFRs) is a complex task, being usually dealt with on the later phases of the software process. The late inclusion of NFRs in the development may compromise the quality of the deployed application. This paper presents π SOD-M, a method and associated tools that (i) allows the early specification of non-functional requirements in a principled way: users are abstracted away from low level details; (ii) embraces the MDA philosophy, generating models (code) whenever possible. The proposed solution has been utilized in the context of an industrial and real case study.

Keywords MDA, Non-Functional Requirements, Service-based software process

1 Introduction

In Service-Oriented Computing [?], preexisting services are combined to build an application business logic. The selection of services is usually guided by the $functional^7$ requirements of the application being devel-

- *.Corresponding author.
- ¹.Université de Paris Dauphine Paris, France. kbelhajj@googlemail.com.
- ². Universidad Rey Juan Carlos Móstoles, Spain. valeria.decastro@urjc.es.
- ³.Universidade Federal do Rio Grande do Norte Natal, Brazil. {umberto,mam}@dimap.ufrn.br.
- 4 . Universidad de las Américas-Puebla, LAFMIA – Cholula, Mexico. javiera.espinosa@gmail.com, joseluis.zechinelli@udlap.mx.
- ⁵.Instituto Federal de Educação, Ciência e Tecnologia do Rio Grande do Norte Natal, Brazil. placido.neto@ifrn.edu.br.
 - $^6. {\rm CNRS}, \, {\rm LIG\text{-}LAFMIA}, \, {\rm Saint \,\, Martin \,\, d'Hères}, \, {\rm France.} \, \, {\it genoveva.vargas@imag.fr.}$
- ⁷.Functional properties of a computer system are characterized by the effect produced by the system when given a defined input.