

CONFIDENTIAL — PRODUCT

QynRun Guide (Enterprise Automation)

Qyenx vOPS HUB — v1.0.0 · Document v1.0

Document Version	1.0
Software Version	v1.0.0
Applies To	Qyenx vOPS HUB v1.0.0
Classification	Confidential — Product
Owner	QynRun Engineering
Status	Released
Last Updated	2026-06-30
Document Type	Module guide

REVISION HISTORY

Version	Date	Notes
1.0	2026-06-30	Initial QynRun guide (Sprint 23): automation workflows, runbooks, executions, approvals, learning, and AI-assisted runbook drafting on the shared Automation Platform.

Table of Contents

- 1. What QynRun is
- 2. Library (registry-driven)
- 3. Workflows
- 4. Runbooks (incl. AI-assisted drafting)
- 5. Executions, approvals, rollback
- 6. Automation Learning
- 7. API (workspace-scoped, UUID-only)
- 8. Safety summary

25 — QynRun Guide (Enterprise Automation)

Audience: Operators and SREs using QynRun. **Scope:** QynRun — the operator surface over the shared **Automation Platform** (see guide 24) and the **third production AI adapter** on the Quenyx AI Platform.

1. What QynRun is

QynRun lets you **author, run, approve, and learn from automation** — safely. It consumes the shared Automation Platform, so its execution, approval, rollback, audit, and learning are platform capabilities, not QynRun-specific code.

UI: `/app/workspaces/:id/qynrun/automation` with tabs: **Overview, Library, Workflows, Runbooks, Executions, Approvals, Learning**, plus the contextual ✨ **Automation Copilot**.

2. Library (registry-driven)

The **Library** tab shows the live **execution adapters** (with `operational` / `planned` state) and the **action catalog** discovered from the registry. Destructive actions are clearly marked *Requires approval*. Nothing here is hardcoded in the UI — it reflects whatever is registered.

3. Workflows

A workflow is a data-only definition: **trigger** → **conditions** → **actions** → **approval** → **execution** → **verification** → **notification** → **audit**, with trigger types `manual` | `scheduled` | `event` | `api`. Running a workflow dispatches its actions through the shared Execution Engine (dry-run by default; live runs require approval per action).

4. Runbooks (incl. AI-assisted drafting)

Runbooks are named, ordered step sets. **Draft Runbook** asks Quenyx AI to draft an **editable** runbook for a problem ("High CPU", "Disk Full", "Apache Down", "Database Latency", "Service Failure", "VPN Failure"). The draft is diagnostic-first, flags destructive steps as requiring approval, and is **never auto-executed** — you review, edit, and save it.

5. Executions, approvals, rollback

- **Executions** lists every run with status (`dry_run` , `succeeded` , `failed` , `skipped` , `rolled_back` , ...) and mode.
- **Approvals** lists live actions awaiting a decision; approving runs them, rejecting cancels them. Requires `administerAi`.
- **Rollback** is available on a succeeded, rollback-capable execution.

6. Automation Learning

The **Learning** tab shows aggregated, auditable outcomes per action (success rate, average duration). These feed AI recommendations — **no self-training**, everything inspectable.

7. API (workspace-scoped, UUID-only)

Base: `/api/qynrun`. Reads/dry-run require `accessAi`; approvals, live runs, rollback, deletes require `administerAi`.

Method	Endpoint	Purpose
GET	<code>/automation/adapters</code>	Registered execution adapters + <code>live_execution_enabled</code> .
GET	<code>/automation/actions</code>	Action catalog.
GET/POST	<code>/automation/workflows</code>	List / create workflows.
GET/PUT/DELETE	<code>/automation/workflows/{uuid}</code>	Read / update / delete.
POST	<code>/automation/workflows/{uuid}/run</code>	Run (<code>mode=dry_run</code>
GET/POST	<code>/automation/runbooks</code>	List / create runbooks.
GET/PUT/DELETE	<code>/automation/runbooks/{uuid}</code>	Read / update / delete.
POST	<code>/automation/runbooks/{uuid}/run</code>	Run.
GET/POST	<code>/automation/executions</code>	History / ad-hoc dispatch.
GET	<code>/automation/executions/{uuid}</code>	Execution detail + steps.
POST	<code>/automation/executions/{uuid}/rollback</code>	Rollback.
POST	<code>/automation/executions/{uuid}/feedback</code>	Operator feedback (learning).
GET	<code>/automation/approvals</code>	Pending approvals.
POST	<code>/automation/approvals/{uuid}/decide</code>	Approve / reject.
GET	<code>/automation/learning</code>	Aggregated outcomes.
GET	<code>/intelligence/overview</code>	Automation dashboard.
POST	<code>/intelligence/copilot</code>	Automation Copilot (reuses Quenyx AI conversations).
POST	<code>/intelligence/runbooks/suggest</code>	AI-assisted editable runbook draft.
POST	<code>/intelligence/executions/{uuid}/explain</code>	Explain an execution.

8. Safety summary

Dry-run by default · approval gate for live · HTTP allowlist · per-runner enable flags · rollback · workspace isolation · RBAC · UUID-only · full audit · EN/AR UI. See guide 24 for the platform-level detail.