

# INSTRUCTION LEVEL PARALLELISM

Mahdi Nazm Bojnordi


Assistant Professor

School of Computing

University of Utah


# Performance vs. Pipeline Depth

- Impact of stall cycles on performance
  - ▣ Independent instructions
  - ▣ Dependent instructions




# Performance vs. Pipeline Depth

- Impact of stall cycles on performance
  - ▣ Independent instructions
  - ▣ Dependent instructions



# Performance vs. Pipeline Depth


- Impact of stall cycles on performance
  - ▣ Independent instructions
  - ▣ Dependent instructions



# Instruction Level Parallelism

- Potential overlap among instructions
  - ▣ A property of the program dataflow

Code 1



```
graph TD; I1[ADD R1, R2, R3] --> I2[SUB R4, R1, R5]; I2 --> I3[XOR R6, R4, R7]; I3 --> I4[AND R8, R6, R9];
```

ADD R1, R2, R3  
SUB R4, R1, R5  
XOR R6, R4, R7  
AND R8, R6, R9

**ILP = 1**  
**Fully serial**

Code 2

ADD R1, R2, R3  
SUB R4, R6, R5  
XOR R8, R2, R7  
AND R9, R6, R0

**ILP = 4**  
**Fully parallel**

# Instruction Level Parallelism

- Potential overlap among instructions
  - ▣ A property of the program dataflow
  - ▣ Influenced by compiler

$X \leftarrow A + B + C + D$

Code 1:

ADD R5, R1, R2

ADD R5, R5, R3

ADD R5, R5, R4

# Instruction Level Parallelism

- Potential overlap among instructions
  - ▣ A property of the program dataflow
  - ▣ Influenced by compiler

$$X \leftarrow A + B + C + D$$

Code 1:

```
ADD R5, R1, R2
ADD R5, R5, R3
ADD R5, R5, R4
```

**Average ILP =  $3/3 = 1$**   
**Five registers**

Code 2:

```
ADD R6, R1, R2
ADD R7, R3, R4
ADD R5, R6, R7
```

**Average ILP =  $3/2 = 1.5$**   
**Seven registers**

# Instruction Level Parallelism

- Potential overlap among instructions
  - ▣ A property of the program dataflow
  - ▣ Influenced by compiler
- An upper limit for attainable IPC for a given code
  - ▣ IPC represents exploited ILP

```
ADD R5, R1, R2
ADD R5, R5, R3
ADD R5, R5, R4
```

**Average ILP =  $3/3 = 1$**   
**Five registers**

```
ADD R6, R1, R2
ADD R7, R3, R4
ADD R5, R6, R7
```

**Average ILP =  $3/2 = 1.5$**   
**Seven registers**



# Instruction Level Parallelism

- Potential overlap among instructions
  - ▣ A property of the program dataflow
  - ▣ Influenced by compiler
- An upper limit for attainable IPC for a given code
  - ▣ IPC represents exploited ILP
- Can be exploited by HW-/SW-intensive techniques
  - ▣ Dynamic scheduling in hardware
  - ▣ Static scheduling in software (compiler)