PIPELINING: HAZARDS

Mahdi Nazm Bojnordi

Assistant Professor

School of Computing

University of Utah

Pipelining Technique

- Improving throughput at the expense of latency
  - Delay: $D = T + n\delta$
  - Throughput: $IPS = n/(T + n\delta)$



Pipelining Technique

- Improving throughput at the expense of latency
  - Delay: $D = T + n\delta$
  - Throughput: $IPS = n/(T + n\delta)$



Five Stage MIPS Pipeline

Instruction Fetch

- Read an instruction from memory (I-Cache)
  - Use the program counter (PC) to index into the I-Memory
  - Compute NPC by incrementing current PC
    - What about branches?
- Update pipeline registers
  - Write the instruction into the pipeline registers

Instruction Fetch



NPC = PC + 4

Why increment by 4?

Instruction Fetch



Instruction Decode

- Generate control signals for the opcode bits
- Read source operands from the register file (RF)
  - Use the specifiers for indexing RF
    - How many read ports are required?
- Update pipeline registers
  - Send the operand and immediate values to next stage
  - Pass control signals and NPC to next stage

Instruction Decode



Execute Stage

- Perform ALU operation
  - Compute the result of ALU
    - Operation type: control signals
    - First operand: contents of a register
    - Second operand: either a register or the immediate value
  - Compute branch target
    - Target = NPC + immediate
- Update pipeline registers
  - Control signals, branch target, ALU results, and destination

Execute Stage



Memory Access

- Access data memory
  - Load/store address: ALU outcome
  - Control signals determine read or write access
- Update pipeline registers
  - ALU results from execute
  - Loaded data from D-Memory
  - Destination register

Memory Access



Register Write Back

- Update register file
  - Control signals determine if a register write is needed
  - Only one write port is required
    - Write the ALU result to the destination register, or
    - Write the loaded data into the register file

Five Stage Pipeline

- Ideal pipeline: IPC=1
  - Do we have enough resources to keep the pipeline stages busy all the time?



Pipeline Hazards

Pipeline Hazards

- Structural hazards: multiple instructions compete for the same resource
- Data hazards: a dependent instruction cannot proceed because it needs a value that hasn't been produced
- Control hazards: the next instruction cannot be fetched because the outcome of an earlier branch is unknown

Structural Hazards

- 1. Unified memory for instruction and data

R1← Mem[R2]

R3← Mem[R20]

R6← R4-R5

R7← R1+R0



Structural Hazards

- 1. Unified memory for instruction and data

R1← Mem[R2]

R3← Mem[R20]

R6← R4-R5

R7← R1+R0



Separate inst. and data memories.

Structural Hazards

- 1. Unified memory for instruction and data
- 2. Register file with shared read/write access ports



Structural Hazards

- 1. Unified memory for instruction and data
- 2. Register file with shared read/write access ports



Register access in half cycles.

Data Hazards

- True dependence: read-after-write (RAW)
  - Consumer has to wait for producer

Loading data from memory.

R1← Mem[R2]

R3← R1+R0

R4← R1-R3



Data Hazards

- True dependence: read-after-write (RAW)
  - Consumer has to wait for producer

Loaded data will be available two cycles later.



Data Hazards

- True dependence: read-after-write (RAW)
  - Consumer has to wait for producer

Inserting two bubbles.



R1← Mem[R2]

Nothing

Nothing

R3← R1+R0

R4← R1-R3

Data Hazards

- True dependence: read-after-write (RAW)
  - Consumer has to wait for producer

Inserting single bubble + RF bypassing.

R1← Mem[R2]

Nothing

R3← R1+R0

R4← R1-R3



Load delay slot.
SW vs. HW management?

Data Hazards

- True dependence: read-after-write (RAW)
  - Consumer has to wait for producer

Using the result of an ALU instruction.



Data Hazards

- True dependence: read-after-write (RAW)
  - Consumer has to wait for producer



Using the result of an ALU instruction.



Forwarding ALU result.

Data Hazards

- True dependence: read-after-write (RAW)
- Anti dependence: write-after-read (WAR)
  - Write must wait for earlier read



Data Hazards

- True dependence: read-after-write (RAW)
- Anti dependence: write-after-read (WAR)
  - Write must wait for earlier read



No WAR hazards in 5-stage pipeline!

Data Hazards

- True dependence: read-after-write (RAW)
- Anti dependence: write-after-read (WAR)
- Output dependence: write-after-write (WAW)
  - Old writes must not overwrite the younger write



Data Hazards

- True dependence: read-after-write (RAW)
- Anti dependence: write-after-read (WAR)
- Output dependence: write-after-write (WAW)
  - Old writes must not overwrite the younger write



No WAW hazards in 5-stage pipeline!

Data Hazards

- Forwarding with additional hardware



Data Hazards

- How to detect and resolve data hazards
  - Show all of the data hazards in the code below

R1← Mem[R2]

R2← R1+R0

R1← R1-R2

Mem[R3] ← R2

Data Hazards

- How to detect and resolve data hazards
  - Show all of the data hazards in the code below