Transformer MLP Transplants Depend on the Receiving State

Muhammed Nehan
Ajman University
202410365@ajmanuni.ac.ae

Abstract

Activation patching and steering move internal updates between forward passes and often treat a moved update as if it carried a portable effect. Ordinary transplants cannot test this, because the update and the state that receives it change together. We isolate the receiver with a crossed-receiver design: a natural transformer MLP displacement $\Delta u = u_j - u_i$ is computed once, frozen, and physically added to many natural receiver states of Qwen3-8B and Mistral-7B; its exact next-token distributional effect is measured as a KL divergence. The same displacement is mild in some receivers and disruptive in others; across 31 receivers its effect typically spans more than three orders of magnitude. An established receiver-local Fisher score ranks these full-dose effects consistently, with median within-displacement Spearman correlation 0.858–0.928 across all six model–bucket replications; the corresponding unweighted response reaches at most 0.568. The association remains after removing generic displacement strength and receiver fragility, with residual correlation 0.50–0.68. The receiver also changes the direction of the effect: footprints of one displacement diverge across receivers, yet receiver-specific low-rank maps fitted on other displacements predict held-out footprints better than a global map. The effect of an internal update depends on where it is written, in both size and direction.[1]

1 Introduction

Activation patching, path patching, and causal tracing move hidden activations between forward passes to localize the components that drive a behavior [Vig et al., 2020, Geiger et al., 2021, Goldowsky-Dill et al., 2023, Zhang and Nanda, 2024]; activation addition and function vectors move them to control behavior [Turner et al., 2023, Todd et al., 2024]. Both uses read a moved activation as carrying an effect. That reading is only as portable as the downstream network allows, because the remaining layers process the moved activation together with the state that receives it.

Transformer MLPs make the question concrete. At layer ℓ, a host context i and a donor context j produce MLP outputs u_i and u_j. Replacing u_i by u_j is exactly adding the natural displacement $\Delta u_{ij} = u_j - u_i$ to the host's residual stream (Figure 1a). In an ordinary transplant, every host receives a different displacement, so the update and its destination change together. Ordinary transplants can show that host-side quantities are associated with transplant effects (Appendix D.1), but not whether the receiving state changes what a fixed update does.

In this paper, we isolate the receiver. In the crossed-receiver design (Figure 1b, Algorithm 1), a natural displacement is computed once, frozen, and physically added, with unchanged direction and norm, to many other natural receiver states. Because the update is identical across receivers, any variation of its exact effect is caused by the receiving state and its interaction with the update. We

[1] Code and reproducibility: github.com/mnehan67/neurips-2026

40th Conference on Neural Information Processing Systems (NeurIPS 2026). Workshop: MusIML 2026.




Figure 1: **The crossed-receiver design holds the update fixed and changes only its destination.** (a) Replacing the host MLP output u_i by the donor output u_j adds the natural displacement $\Delta u_{ij} = u_j - u_i$ to the host. (b) In the crossed-receiver test, one natural displacement Δu_d is computed once, frozen, and added unchanged to many natural receiver states $r_1, \ldots, r_R$. For each receiver we measure the exact effect $K_{d,k}$ and the receiver-local score $Q_{\text{recv}}(r_k, \Delta u_d)$, and we rank receivers within the fixed displacement (Algorithm 1).

explain this variation in two steps. For its *size*, we use the receiver-local Fisher score, the standard second-order pullback of output KL through the downstream network [Martens, 2020, Park et al., 2026, Wang and Zhao, 2026], as a diagnostic; we do not claim a new geometry. For its *direction*, we trace the causal footprint of the displacement through every downstream layer and test whether receiver-specific structure in it generalizes to displacements never used for fitting.

What the design adds beyond nonlinearity. A nonlinear network is state dependent in general, so receiver dependence alone is not our claim. We ask how large and how structured it is for natural MLP updates at full dose, with three tests that do not follow from nonlinearity: the primary statistic ranks receivers while the physical update is held fixed; a residual analysis removes generic update strength and receiver fragility before asking whether the Fisher score tracks the pair-specific remainder; and a held-out map test asks whether the receiver-dependent change of direction transfers to unseen displacements, which tests for reusable receiver-specific structure beyond generic state dependence.

Our contributions are as follows (related work is discussed in Appendix A):

- **Crossed-receiver design.** We hold a natural MLP displacement physically fixed and vary only its receiver (Algorithm 1). In Qwen3-8B and Mistral-7B, across three disjoint data buckets and four depths, the exact full-dose effect of a fixed displacement varies strongly and systematically with the receiver (Section 5.2).
- **Receiver-side explanation of effect size.** The established receiver-local Fisher score ranks receivers with median within-displacement $\rho = 0.858$–0.928, ahead of matched-magnitude, attribution-patching, relative-norm, receiver-norm, and alignment baselines (Table 2), and retains a residual association of 0.50–0.68 with pair-specific variation (Table 3).
- **Receiver-conditioned transformation of direction.** The same displacement acquires different downstream causal directions in different receivers, and receiver-specific rank-16 maps predict a reproducible component of this transformation for held-out displacements in both model families (Figure 3).

2 Problem Setup

Fix a frozen decoder-only transformer, an MLP layer ℓ, and contexts of 64 tokens. All interventions act on the MLP output at the final token, and no model parameter is changed.

Natural displacements. Let F_ℓ be the MLP at layer ℓ and let m_c be its input at the final token of context c. A host i and a donor j produce

$$u_i = F_\ell(m_i), \qquad u_j = F_\ell(m_j), \qquad \Delta u_{ij} = u_j - u_i. \tag{1}$$

It is *natural*: both endpoints are MLP outputs the model actually produces.

Algorithm 1 Crossed-receiver test for one natural displacement

Require: frozen model; layer ℓ; host i; donor j; receivers $k_1, \ldots, k_R$ (natural contexts)
$\Delta u_d \leftarrow F_\ell(m_j) - F_\ell(m_i)$ ▷ natural displacement, computed once
freeze Δu_d ▷ identical direction and norm for every receiver
for $k \in \{k_1, \ldots, k_R\}$ **do**
  run receiver k natively; record r_k and p_k
  run receiver k with $r_k \leftarrow r_k + \Delta u_d$; record $p_{k,+\Delta u_d}$
  $K_{d,k} \leftarrow D_{\mathrm{KL}}(p_k \,\|\, p_{k,+\Delta u_d})$ ▷ exact full-dose effect
  record predictors at $(r_k, \Delta u_d)$: Q_{recv}, q_{p2}, attribution, norm, and alignment scores
  record causal footprints $c^{(m)}_{d,k} = h_m(k; +\Delta u_d) - h_m(k)$ ▷ control panel only
end for
$\rho_d \leftarrow \mathrm{Spearman}_{k \neq i}\big(\text{predictor}_{d,k},\, K_{d,k}\big)$ ▷ update fixed inside ρ_d
return ρ_d; the primary statistic is $\mathrm{median}_d\, \rho_d$ over displacements

Receivers and the exact effect. For any context k, let r_k be the residual state immediately after the layer-ℓ MLP at the final token, and let p_k be the native next-token distribution. Writing a displacement Δu into receiver k replaces r_k by $r_k + \Delta u$ (equivalently, the MLP output u_k by $u_k + \Delta u$) and leaves the rest of the forward pass unchanged. With $p_{k,+\Delta u}$ the resulting next-token distribution, the exact next-token distributional effect (for short, the exact effect) is

$$K_k(\Delta u) = D_{\mathrm{KL}}\big(p_k \,\big\|\, p_{k,+\Delta u}\big)\,. \tag{2}$$

The forward KL from the native distribution, over the full vocabulary, measures how far the physically applied intervention moves the model from its unpatched behavior. An ordinary transplant is the special case $K_{i \leftarrow j} = K_i(\Delta u_{ij})$; a self-patch recovers the native output to numerical precision.

Goal. Our goal is to determine whether, for a fixed natural displacement Δu_d, the effect $K_k(\Delta u_d)$ depends on the receiver k, how strongly it does so, and whether receiver-side quantities explain both the size and the direction of the dependence.

3 The Crossed-Receiver Design

We first present the protocol and its statistics; the receiver-side quantities it records are defined in Section 4.

3.1 Protocol

Each crossed experiment samples natural displacements $\Delta u_d = u_{j_d} - u_{i_d}$ from host–donor pairs and crosses each with a set of natural receivers, never rescaling or re-orienting it (Algorithm 1). The original host is kept as an anchor row; the primary statistic uses only alternative receivers $k \neq i_d$.

3.2 Three correlations, one primary statistic

The protocol yields displacement-by-receiver matrices of exact effects $K_{d,k}$ and predictor values $X_{d,k}$. We summarize their association in three ways that answer three different questions (formal definitions in Appendix B.4).

1. **Pooled correlation** $\rho_{\mathrm{pool}} = \mathrm{Spearman}(X_{d,k}, K_{d,k})$ over all rows. It is descriptive and mixes update, receiver, and pair-specific variation.
2. **Within-displacement correlation (primary)** $\mathrm{median}_d\ \rho_d$, where ρ_d correlates $X_{d,k}$ and $K_{d,k}$ across the receivers of one fixed displacement. It asks whether X ranks receivers correctly *while the physical update is held fixed*.
3. **Residual-rank correlation.** Rank-transform X and K, remove additive displacement and receiver main effects from each by alternating demeaning, and correlate the residuals. It asks whether X still captures pair-specific structure *after generic displacement strength and receiver fragility are removed*. It was introduced after inspecting the crossed data and is reported as post hoc.

These are not competing estimates of one quantity. In the six crossed matrices, receiver identity alone explains 0.70–0.80 of the rank variance of exact KL, displacement identity 0.04–0.12, and 0.18–0.25 remains as non-additive residual variation (Table 4). A high within-displacement correlation thus largely means that a predictor identifies generically fragile receivers; the residual correlation asks whether it also tracks the smaller non-additive part. Values near 0.9 for the first question and 0.5–0.68 for the second are therefore consistent. With one effect per cell, we do not interpret the remainder as a separately identified interaction. Every Fisher–KL correlation in the paper is one of these types on a specific panel; Table 5 lists them side by side.

What the design identifies. Within a displacement the intervention vector is physically identical across receivers, so differences in $K_{d,k}$ are caused by the receiving state and its interaction with the update, for the given model and layer. The design does not identify which mechanism (attention, normalization, or MLP gating) produces the dependence, nor whether an MLP update represents a semantic function; our endpoints are next-token behavior and causal-effect geometry.

4 Receiver-Side Measurements

4.1 Receiver-local sensitivity

Let G_ℓ map the post-MLP residual state at layer ℓ to the final logits, with the rest of the context held fixed. A small movement of receiver r along Δu changes the logits by $\Delta z = JG_\ell(r)\,\Delta u$. With p the receiver's native next-token distribution and $C_p = \mathrm{diag}(p) - pp^\top$, the receiver-local score is

$$Q_{\mathrm{recv}}(r, \Delta u) = \tfrac{1}{2}\left(JG_\ell(r)\Delta u\right)^\top C_p \left(JG_\ell(r)\Delta u\right). \tag{3}$$

This is the standard second-order pullback of output KL, $D_{\mathrm{KL}}(p_r \,\|\, p_{r+\epsilon\Delta u}) = \epsilon^2\, Q_{\mathrm{recv}}(r, \Delta u) + O(\epsilon^3)$ [Martens, 2020, Park et al., 2026, Wang and Zhao, 2026] (Appendix B.1); we use it as a diagnostic rather than claim a new geometry. The empirical question is whether this local quantity, evaluated at each receiver, ranks the *full-dose* effect ($\epsilon = 1$) of a fixed natural displacement.

Remark 1 (Standard variance reading). $(JG_\ell\Delta u)^\top C_p\,(JG_\ell\Delta u) = \mathrm{Var}_{y\sim p}\big[(JG_\ell\Delta u)_y\big]$, so Q_{recv} is half the variance of the logit change under the receiver's own next-token distribution. A uniform logit shift costs nothing, and changes on tokens the receiver considers unlikely cost little. The matched baseline $q_{p2} = \frac{1}{2}\|JG_\ell(r)\Delta u\|_2^2$ uses the same response without this weighting, isolating the contribution of the receiver's output distribution.

The crossed experiments estimate $JG_\ell(r)\Delta u$ by centered finite differences ($\epsilon = 0.075$) on FP16 model evaluations. An exact FP32 downstream-suffix JVP audit on 16 control-panel cases per model shows negligible truncation error (median cosine 1.0000; $\rho = 1.000$ between FP32 finite-difference and exact Fisher scores), whereas FP16 scores for the same cases agree less closely ($\rho = 0.785$, 0.544; Appendix D.12). We therefore use the FP16 score as a ranking diagnostic: the primary crossed result is an empirical association between this computed score and the independently measured full-dose KL, and it does not require the score to be a numerically exact FP32 Fisher quadratic. The directional results (Sections 5.5 and 5.6) do not use the score.

Alternative predictors. We compare Q_{recv} with q_{p2}; with first-order attribution of the native top-token log-probability (AtP-top) and of the native top1–top2 logit margin (AtP-margin), in the spirit of attribution patching [Kramár et al., 2024]; with the relative displacement norm $\|\Delta u\|/\|r\|$; with the receiver norm $\|r\|$; and with the alignment $|\cos(\Delta u, r)|$. We also run a physical control in which every natural displacement is rescaled to a common norm before being applied (Appendix C.5).

Remark 2 (Why KL is not attributed directly). With p_α the distribution after adding $\alpha\Delta u$, $\frac{d}{d\alpha} D_{\mathrm{KL}}(p \,\|\, p_\alpha)\big|_{\alpha=0} = 0$ (Appendix B.3), so first-order attribution of KL is identically zero and AtP uses the non-stationary targets above, in absolute value.

4.2 Following the causal effect downstream

KL measures how much the final distribution changes, but not the direction of the hidden-state effect. For displacement d with original host i and receiver k, the causal footprint at downstream layer m is

$$c_{d,k}^{(m)} = h_m(k; +\Delta u_d) - h_m(k), \tag{4}$$

Table 1: **Experimental panels.** All panels use frozen weights, 64-token C4 validation contexts, and final-token MLP interventions. "Rows" counts interventions per depth, per bucket, or per Pythia run (256 hosts); a depth count of 1 means the primary depth (layer 2 for Pythia). Crossed receiver counts include the original host as an anchor row; the within-displacement statistic uses the 15 or 31 alternative receivers.

Panel	Design	Rows	Depths	Used for
Ordinary	all directed pairs, 64 contexts	4032	4	residual; wrong-state; dose; horizon
Large ordinary	Mistral, 256 contexts	65,280	1	scale; permutation test
Crossed B1	512 $\Delta u \times 16$ receivers	8192	4	primary statistic; depth
Crossed B2, B3	512 $\Delta u \times 32$ receivers	16,384	1	replication
Control	96 $\Delta u \times 8$ receivers	768	1	baselines; footprints; maps
Pythia-70M ($\times 6$)	ordinary, 5-NN donors	256	1	independent pretraining

the difference between patched and native final-token hidden states, with $c^{(m)}_{d,i}$ defined analogously at the original host. Both footprints equal Δu_d at the intervention site. We summarize how they separate with the directional fidelity $F^{(m)}_{d,k} = \cos(c^{(m)}_{d,i}, c^{(m)}_{d,k})$, the gain $A^{(m)}_{d,k} = \langle c^{(m)}_{d,i}, c^{(m)}_{d,k} \rangle / \|c^{(m)}_{d,i}\|^2_2$, and the rewrite residual $E^{(m)}_{d,k} = c^{(m)}_{d,k} - A^{(m)}_{d,k} c^{(m)}_{d,i}$. Together they distinguish an effect that is preserved but attenuated or amplified ($F \approx 1$, $A \neq 1$) from one whose direction is rewritten (small F, large E).

Held-out receiver maps. To test whether the receiver-dependent transformation has reusable structure, we fit at each downstream layer a low-rank map $T^{(m)}_k$ predicting $c^{(m)}_{d,k}$ from $c^{(m)}_{d,i}$. Displacements are split once, before analysis, into 75% training and 25% held out; a rank-16 PCA basis is fit on training displacements only, and ridge maps are fit in that subspace. We compare five predictors of the held-out footprint: the *identity* ($c_k \approx c_i$), a *gain-only* scalar per receiver, one *global map* shared by all receivers, the *receiver-specific map*, and a *wrong-receiver map* taken from another receiver by a fixed cyclic permutation. If receiver identity carried no reusable structure beyond a shared transformation, receiver-specific maps should not systematically outperform a global map on held-out displacements; under a pure change of scale, gain only would suffice. We score cosine and normalized RMSE on held-out displacements, with the held-out displacements as independent units after averaging receivers (Appendix B.5).

5 Experiments

We apply the design to two 7–8B models, then test the size explanation against baselines and pair-specific structure, and finally the direction of the effect and its generalization.

5.1 Setup

Models. We use Qwen3-8B [Yang et al., 2025] (36 layers) and Mistral-7B-v0.3 [Jiang et al., 2023] (32 layers) with frozen FP16 weights. The four probed depths are Qwen layers 7, 14, 21, 26 and Mistral layers 6, 12, 19, 23; the primary depths, at about 40% of each network, are Qwen layer 14 and Mistral layer 12. Six independently pretrained Pythia-70M runs [Biderman et al., 2023, van der Wal et al., 2025] provide a separate ordinary-transplant replication (Section 5.7).

Data. Contexts are deterministic samples from the C4 validation split [Raffel et al., 2020], selected by a SHA-256 hash rule before model-specific tokenization. Each context has 64 tokens, and every intervention and measurement uses the final token. The three crossed buckets B1–B3 are assigned by distinct hash residues and are therefore disjoint.

Panels. Table 1 lists the panels. The crossed buckets carry the primary result. The control panel is a separate deterministic 96×8 panel, sampled with a different seed and selection rule; it stores layerwise hidden-state differences for the baselines, footprints, and held-out maps, and its 96 displacements are split once into 72 training and 24 held-out. The primary statistic and baselines are those of Sections 3.2 and 4.1.




Figure 2: **Receiver-local sensitivity ranks the effects of a fixed displacement across receivers.** Bucket B2, primary depth: 512 frozen natural displacements, each applied to 31 alternative receivers (15,872 interventions per model); both axes $\log_{10}$. Headers give the primary statistic. Other buckets and depths: Tables 3 and 6.

Table 2: **Alternative predictors of receiver ordering.** Median within-displacement Spearman correlation (↑) with exact full-dose KL on the 96×8 control panel; bold marks the best per model. With 8 receivers per displacement, medians are coarser and lower than in the 32-receiver buckets (Table 5); pooled and residual versions are in Table 8.

Model	Fisher Q_{recv}	AtP-top	AtP-margin	q_{p2}	$\|\Delta u\|/\|r\|$	$\|r\|$	$\|\cos(\Delta u, r)\|$
Qwen3-8B	**0.738**	0.500	0.429	0.226	0.071	−0.071	−0.012
Mistral-7B	**0.905**	0.750	0.179	0.060	0.000	0.000	0.048

Implementation details. We use Hugging Face Transformers and shard the large models with Accelerate across two NVIDIA T4 GPUs (16 GB each). No model is trained or fine-tuned. Seeds, context identifiers, and the split are fixed before analysis. Protocols, compute, and frozen outputs are in Appendix C and at https://anonymous.4open.science/r/newinml-7402/.

5.2 The same displacement has different effects in different receivers

A fixed natural displacement does not have one effect. With 31 alternative receivers (buckets B2 and B3), the largest and smallest exact effects of the same displacement differ by a median factor of $10^{4.4}$–$10^{4.8}$ in Qwen3-8B and $10^{3.3}$–$10^{3.6}$ in Mistral-7B, and by at least a factor of 100 for 99.0–100% of displacements (Appendix D.5).

This variation is ordered. The receiver-local score ranks receivers with median within-displacement correlation $0.871/0.872/0.858$ in Qwen3-8B buckets B1/B2/B3 and $0.911/0.928/0.928$ in Mistral-7B (Figure 2), and the correlation is positive for 99.4–99.8% of Qwen displacements and every sampled Mistral displacement. The unweighted response q_{p2}, computed from the same finite differences, reaches only 0.340–0.355 in Qwen and 0.510–0.568 in Mistral, so weighting by the receiver's own next-token distribution (Remark 1) accounts for much of the ranking.

5.3 Scale, attribution, and alignment baselines do not explain the ordering

On the control panel (Table 2), the Fisher score is the strongest predictor in both models. Attribution of the native top-token log-probability is the closest competitor (0.500 in Qwen3-8B, 0.750 in Mistral-7B); the relative displacement norm, receiver norm, and displacement–state alignment are near zero. A physical control gives the sharpest scale check: rescaling every natural displacement to a common norm before applying it leaves the receiver ordering of exact KL unchanged (median within-displacement $\rho = 1.000$ between original and equal-norm orderings in both models). Since a

Table 3: **Within-displacement and pair-specific association in the six crossed replications.** "Within" is the primary statistic. "Residual" is the post-hoc rank correlation after removing additive displacement and receiver effects (Section 3.2). "Non-additive" is the share of rank-KL variance not explained by the additive displacement-plus-receiver model (Table 4). Higher is better for all correlation columns.

		Within-displacement ρ		Residual ρ		
Model	Bucket	Fisher Q_{recv}	q_{p2}	Fisher Q_{recv}	q_{p2}	Non-additive
Qwen3-8B	B1	0.871	0.355	0.504	0.284	0.211
Qwen3-8B	B2	0.872	0.340	0.504	0.292	0.221
Qwen3-8B	B3	0.858	0.352	0.520	0.317	0.246
Mistral-7B	B1	0.911	0.529	0.664	0.411	0.196
Mistral-7B	B2	0.928	0.510	0.675	0.442	0.185
Mistral-7B	B3	0.928	0.568	0.658	0.414	0.180

displacement's scale factor is shared by all its receivers, displacement norm does not produce the receiver ordering.

5.4 Pair-specific structure remains after removing generic fragility

A high within-displacement correlation could reflect generic receiver fragility alone. Table 3 separates the two: 18–25% of the rank variance of exact KL is non-additive in every crossed matrix, and after removing additive displacement and receiver effects the Fisher score's residual correlation is 0.504–0.520 in Qwen3-8B and 0.658–0.675 in Mistral-7B, above q_{p2} in all six replications (0.284–0.442). The score therefore tracks pair-specific variation, not only fragility; the analysis is post hoc and descriptive.

5.5 The receiver changes the direction of the causal effect

The scalar results leave open whether receivers merely amplify or attenuate a fixed update. On the control panel, the footprints of one displacement at the original host and at a receiver start identical and then separate quickly: median directional fidelity falls from 1 to 0.030 at Qwen3-8B's final layer and 0.037 at Mistral-7B's, and the median gain decays with it (Figure 4). The receiver's final footprint is nearly orthogonal to the host's, so the receiver rewrites the direction of the effect rather than rescaling a shared one.

5.6 A receiver-specific transformation generalizes to held-out displacements

Figure 3 shows that part of this rewriting is systematic. At the final layer, receiver-specific maps reach mean held-out cosine 0.316 in Qwen3-8B and 0.241 in Mistral-7B, against 0.086 and 0.109 for the global map and -0.023 and 0.028 for wrong-receiver maps. Bootstrapping the 24 held-out displacements, the advantage over the global map is $+0.230$ (95% CI $[0.205, 0.256]$) in Qwen3-8B and $+0.132$ ($[0.108, 0.155]$) in Mistral-7B, and over wrong-receiver maps $+0.340$ ($[0.281, 0.400]$) and $+0.213$ ($[0.180, 0.244]$): the predictive structure belongs to the specific receiver. Exact vector reconstruction improves much less (normalized RMSE 0.945 versus 1.005 for the global map in Qwen3-8B, 0.986 versus 0.999 in Mistral-7B; Table 9). The transformation thus contains a reproducible receiver-specific *component*, while substantial update-specific variation remains.

5.7 Robustness

Depth and scale. In the B1 depth sweep, the median within-displacement correlation ranges from 0.857 to 0.954 across the four Qwen depths and from 0.854 to 0.957 across the four Mistral depths (Table 6). A 65,280-pair Mistral matrix of ordinary transplants gives Fisher–KL correlation 0.911 and host–donor residual correlation 0.660 (q_{p2}: 0.415), with joint context-label permutation $p = 0.0005$, the smallest value attainable with 2000 permutations (Appendix D.1).




Figure 3: **A receiver-specific transformation predicts the footprints of unseen displacements.** Mean cosine between predicted and actual held-out footprints $c_{d,k}^{(m)}$ at every downstream layer m, on the 96×8 control panel. Maps are fit on 72 natural displacements and evaluated on 24 held-out displacements. Bands: ± 1 standard error across the 24 held-out displacements, after averaging the eight receivers within each. Identity and gain only coincide (a scalar gain does not change direction) and decay with depth; receiver-specific rank-16 maps keep signal through the final layer, global maps are weaker, and wrong-receiver maps fall to about zero.

Dose and horizon. On a random 256-pair subset of the ordinary matrices, the score stays informative up to the full transplant (Fisher–KL correlation 0.831 in Qwen3-8B and 0.907 in Mistral-7B at dose $\lambda = 1$; Figure 5). On a random 128-pair subset run on the true continuation, receiver-local sensitivity remains associated with KL summed over the next h teacher-forced positions, although the association weakens with the horizon ($0.857 \rightarrow 0.565$ in Qwen3-8B and $0.930 \rightarrow 0.812$ in Mistral-7B from $h = 1$ to 32; Appendix D.10). Teacher forcing does not establish persistence under unconstrained autoregressive generation.

Independent pretraining. On six independently pretrained Pythia-70M runs, all six partial Spearman correlations between $\log(1 + Q_{\mathrm{recv}})$ and transplant KL, controlling for update and state distance, nonlinear residual, and tangent alignment, are positive (median 0.800, 95% bootstrap interval $[0.742, 0.827]$; Appendix D.11). This uses ordinary transplants, not the crossed design: it shows that the local-geometry association replicates across independently pretrained small models, while the crossed-receiver evidence comes from the two large models.

6 Conclusion

A natural MLP displacement does not carry one context-free behavioral effect. Holding the update physically fixed while changing only its receiver produces large, systematic differences in exact next-token behavior, which an established receiver-local Fisher score ranks beyond generic receiver fragility and beyond scale, attribution, and alignment baselines. The receiver also rewrites the downstream direction of the effect, and receiver-specific maps recover a reproducible component of that transformation for unseen displacements. Analyses that move internal updates across contexts should treat the receiving state as part of the intervention.

Limitations. We study final-token MLP outputs and next-token behavior; other components and longer horizons are not covered. The large-scale evidence comes from one Qwen3-8B and one Mistral-7B checkpoint, and independent-pretraining replication exists only for Pythia-70M under ordinary transplants. The residual analysis is post hoc and descriptive. The receiver maps are linear and rank-16 and measure causal-effect geometry, not preservation of a semantic function. The crossed experiments use FP16 finite-difference Fisher scores; the FP32 suffix audit closes truncation error on the tested directions but does not make these scores numerically exact (Appendix D.12). Teacher-forced checks do not establish behavior under free generation. The study is diagnostic and proposes no steering method; preserving an intervention's intended causal effect across receiver states is a natural direction for future work (Appendix E).

References

Stella Biderman, Hailey Schoelkopf, Quentin Gregory Anthony, Herbie Bradley, Kyle O'Brien, Eric Hallahan, Mohammad Aflah Khan, Shivanshu Purohit, Usvsn Sai Prashanth, Edward Raff, Aviya Skowron, Lintang Sutawika, and Oskar Van Der Wal. Pythia: A suite for analyzing large language models across training and scaling. In Andreas Krause, Emma Brunskill, Kyunghyun Cho, Barbara Engelhardt, Sivan Sabato, and Jonathan Scarlett, editors, *Proceedings of the 40th International Conference on Machine Learning*, volume 202 of *Proceedings of Machine Learning Research*, pages 2397–2430. PMLR, 23–29 Jul 2023.

Arthur Conmy, Augustine Mavor-Parker, Aengus Lynch, Stefan Heimersheim, and Adrià Garriga-Alonso. Towards automated circuit discovery for mechanistic interpretability. In *Advances in Neural Information Processing Systems*, volume 36, pages 16318–16352, 2023. doi: 10.52202/075280-0719. URL https://papers.neurips.cc/paper_files/paper/2023/hash/34e1dbe95d34d7ebaf99b9bcaeb5b2be-Abstract-Conference.html.

Weilong Dong, Xinwei Wu, Renren Jin, Shaoyang Xu, and Deyi Xiong. CONTRANS: Weak-to-strong alignment engineering via concept transplantation. In *Proceedings of the 31st International Conference on Computational Linguistics*, pages 4130–4148, Abu Dhabi, UAE, 2025. Association for Computational Linguistics. URL https://aclanthology.org/2025.coling-main.279/.

Gabriel Garcia. No free swap: Protocol-dependent layer redundancy in transformers. *arXiv preprint arXiv:2605.16234*, 2026.

Atticus Geiger, Hanson Lu, Thomas Icard, and Christopher Potts. Causal abstractions of neural networks. In *Advances in Neural Information Processing Systems*, volume 34, pages 9574–9586. Curran Associates, Inc., 2021.

Atticus Geiger, Duligur Ibeling, Amir Zur, Maheep Chaudhary, Sonakshi Chauhan, Jing Huang, Aryaman Arora, Zhengxuan Wu, Noah Goodman, Christopher Potts, and Thomas Icard. Causal abstraction: A theoretical foundation for mechanistic interpretability. *Journal of Machine Learning Research*, 26(83):1–64, 2025. URL https://jmlr.org/papers/v26/23-0058.html.

Mor Geva, Roei Schuster, Jonathan Berant, and Omer Levy. Transformer feed-forward layers are key-value memories. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 5484–5495, Online and Punta Cana, Dominican Republic, November 2021. Association for Computational Linguistics. doi: 10.18653/v1/2021.emnlp-main.446.

Mor Geva, Avi Caciularu, Kevin Wang, and Yoav Goldberg. Transformer feed-forward layers build predictions by promoting concepts in the vocabulary space. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 30–45, Abu Dhabi, United Arab Emirates, December 2022. Association for Computational Linguistics. doi: 10.18653/v1/2022.emnlp-main.3.

Asma Ghandeharioun, Avi Caciularu, Adam Pearce, Lucas Dixon, and Mor Geva. Patchscopes: A unifying framework for inspecting hidden representations of language models. In *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *Proceedings of Machine Learning Research*, pages 15466–15490. PMLR, 2024. URL https://proceedings.mlr.press/v235/ghandeharioun24a.html.

Nicholas Goldowsky-Dill, Chris MacLeod, Lucas Sato, and Aryaman Arora. Localizing model behavior with path patching. *arXiv preprint arXiv:2304.05969*, 2023. URL https://arxiv.org/abs/2304.05969.

Satchel Grant, Simon Jerome Han, Alexa R. Tartaglini, and Christopher Potts. Addressing divergent representations from causal interventions on neural networks. In *The Fourteenth International Conference on Learning Representations*, 2026. URL https://openreview.net/forum?id=cZrTMqYVL6.

Albert Q. Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, et al. Mistral 7B. *arXiv preprint arXiv:2310.06825*, 2023.

János Kramár, Tom Lieberum, Rohin Shah, and Neel Nanda. AtP*: An efficient and scalable method for localizing LLM behaviour to components. *arXiv preprint arXiv:2403.00745*, 2024. URL https://arxiv.org/abs/2403.00745.

Jiaqian Li, Yanshu Li, and Kuan-Hao Huang. Steering vector fields for context-aware inference-time control in large language models. *arXiv preprint arXiv:2602.01654*, 2026.

Kenneth Li, Oam Patel, Fernanda Viégas, Hanspeter Pfister, and Martin Wattenberg. Inference-time intervention: Eliciting truthful answers from a language model. In *Advances in Neural Information Processing Systems*, volume 36, 2023. doi: 10.52202/075280-1797.

SiYuan Ma, Yiqin Luo, Zhangji, Canran Xiao, Albert Gao, Wei-Hsing Huang, Wei Wang, Qiwei Wu, Xinran Li, Jinfeng Wei, and Qixin Zhang. Hidden APIs in language models: Discovering reusable causal interfaces from forked futures. *arXiv preprint arXiv:2607.27617*, 2026. URL https://arxiv.org/abs/2607.27617.

James Martens. New insights and perspectives on the natural gradient method. *Journal of Machine Learning Research*, 21(146):1–76, 2020.

Kevin Meng, David Bau, Alex Andonian, and Yonatan Belinkov. Locating and editing factual associations in GPT. In *Advances in Neural Information Processing Systems*, volume 35, pages 17359–17372. Curran Associates, Inc., 2022. doi: 10.52202/068431-1262.

David N. Olivieri and Antonio F. Pérez Rodríguez. Transformer field theory: A response-theoretic approach to mechanistic interpretability. *arXiv preprint arXiv:2605.25225*, 2026.

Gustaw Opiełka, Hannes Rosenbusch, and Claire E. Stevenson. Causality $\neq$ invariance: Function and concept vectors in LLMs. In *The Fourteenth International Conference on Learning Representations*, 2026. URL https://proceedings.iclr.cc/paper_files/paper/2026/hash/86b3697c4eb7792c951831636bfdacd5-Abstract-Conference.html.

Koyena Pal, Jiuding Sun, Andrew Yuan, Byron C. Wallace, and David Bau. Future lens: Anticipating subsequent tokens from a single hidden state. In *Proceedings of the 27th Conference on Computational Natural Language Learning (CoNLL)*, pages 548–560, Singapore, December 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.conll-1.37. URL https://aclanthology.org/2023.conll-1.37/.

Kiho Park, Todd Nief, Yo Joong Choe, and Victor Veitch. The information geometry of softmax: Probing and steering. In *Proceedings of the 43rd International Conference on Machine Learning*, 2026. URL https://arxiv.org/abs/2602.15293.

Philip Quirke. Necessary, decodable and reversible, yet not transferable: A stress test for attention-head role claims. *arXiv preprint arXiv:2606.08292*, 2026.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J. Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. *Journal of Machine Learning Research*, 21(140):1–67, 2020.

Nina Rimsky, Nick Gabrieli, Julian Schulz, Meg Tong, Evan Hubinger, and Alexander Turner. Steering Llama 2 via contrastive activation addition. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 15504–15522, Bangkok, Thailand, August 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.acl-long.828.

Shashwat Singh, Shauli Ravfogel, Jonathan Herzig, Roee Aharoni, Ryan Cotterell, and Ponnurangam Kumaraguru. Representation surgery: Theory and practice of affine steering. In *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *Proceedings of Machine Learning Research*, pages 45663–45680. PMLR, 2024. URL https://proceedings.mlr.press/v235/singh24d.html.

Julian Skifstad, Xinyue Annie Yang, and Glen Chou. Local linearity of LLMs enables activation steering via model-based linear optimal control. In *Proceedings of the 43rd International Conference on Machine Learning*, 2026. URL https://arxiv.org/abs/2604.19018.

Eric Todd, Millicent L. Li, Arnab Sen Sharma, Aaron Mueller, Byron C. Wallace, and David Bau. Function vectors in large language models. In *The Twelfth International Conference on Learning Representations*, 2024.

Alexander Matt Turner, Lisa Thiergart, Gavin Leech, David Udell, Juan J. Vazquez, Ulisse Mini, and Monte MacDiarmid. Steering language models with activation engineering. *arXiv preprint arXiv:2308.10248*, 2023. URL https://arxiv.org/abs/2308.10248.

Sankaran Vaidyanathan, David Arbour, Aaron Mueller, Scott Niekum, and David Jensen. The curse of multiple mediators: Hidden interaction effects in activation patching. *arXiv preprint arXiv:2606.27510*, 2026.

Oskar van der Wal, Pietro Lesci, Max Müller-Eberstein, Naomi Saphra, Hailey Schoelkopf, Willem Zuidema, and Stella Biderman. PolyPythias: Stability and outliers across fifty language model pre-training runs. In *The Thirteenth International Conference on Learning Representations*, 2025.

Jesse Vig, Sebastian Gehrmann, Yonatan Belinkov, Sharon Qian, Daniel Nevo, Yaron Singer, and Stuart M. Shieber. Investigating gender bias in language models using causal mediation analysis. In *Advances in Neural Information Processing Systems*, volume 33, pages 12388–12401. Curran Associates, Inc., 2020. URL https://proceedings.neurips.cc/paper/2020/hash/92650b2e92217715fe312e6fa7b90d82-Abstract.html.

Sihan Wang and Jiayi Zhao. FishBack: Pullback fisher geometry for optimal activation steering in transformers. *arXiv preprint arXiv:2605.17231*, 2026. URL https://arxiv.org/abs/2605.17231.

Zijian Wang, Britney Whyte, and Chang Xu. Locating and extracting relational concepts in large language models. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 4818–4832, Bangkok, Thailand, August 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.findings-acl.287. URL https://aclanthology.org/2024.findings-acl.287/.

Zhengxuan Wu, Atticus Geiger, Thomas Icard, Christopher Potts, and Noah Goodman. Interpretability at scale: Identifying causal mechanisms in Alpaca. In *Advances in Neural Information Processing Systems*, volume 36, 2023. doi: 10.52202/075280-3418. URL https://papers.nips.cc/paper_files/paper/2023/hash/f6a8b109d4d4fd64c75e94aaf85d9697-Abstract-Conference.html.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, et al. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*, 2025.

Fred Zhang and Neel Nanda. Towards best practices of activation patching in language models: Metrics and methods. In *The Twelfth International Conference on Learning Representations*, 2024.

Andy Zou, Long Phan, Sarah Chen, James Campbell, Phillip Guo, Richard Ren, Alexander Pan, Xuwang Yin, Mantas Mazeika, Ann-Kathrin Dombrowski, Shashwat Goel, Nathaniel Li, Michael J. Byun, Zifan Wang, Alex Mallen, Steven Basart, Sanmi Koyejo, Dawn Song, Matt Fredrikson, J. Zico Kolter, and Dan Hendrycks. Representation engineering: A top-down approach to AI transparency. *arXiv preprint arXiv:2310.01405*, 2023. URL https://arxiv.org/abs/2310.01405.

A Related Work

Activation transplantation and causal interventions. Activation patching, interchange interventions, causal tracing, path patching, and circuit discovery intervene on hidden states to identify the components that causally drive a behavior [Vig et al., 2020, Geiger et al., 2021, 2025, Goldowsky-Dill et al., 2023, Conmy et al., 2023, Wu et al., 2023, Zhang and Nanda, 2024]. AtP* approximates exhaustive patching with gradients [Kramár et al., 2024]. Patchscopes, Future Lens, function vectors, relational-concept extraction, and concept transplantation move information or behavior across contexts [Ghandeharioun et al., 2024, Pal et al., 2023, Todd et al., 2024, Wang et al., 2024, Dong et al., 2025]. Transfer is not automatic: the outcome of activation swaps depends on the protocol, several mediators can interact, causal vectors need not be invariant across formats, intervened representations can diverge from the model's natural distribution, and role claims about components can fail to transfer [Garcia, 2026, Vaidyanathan et al., 2026, Opiełka et al., 2026, Grant et al., 2026, Quirke, 2026]. Our design differs from these lines of work by holding an example-specific natural MLP displacement exactly fixed while changing only the natural state that receives it, so that the receiver's causal contribution is isolated.

MLP updates as units of computation. Feed-forward layers have been described as key–value memories and as promoting concepts in vocabulary space, and editing their weights is a standard way to change stored associations [Geva et al., 2021, 2022, Meng et al., 2022]. These views treat an MLP output as carrying content. We do not assign content to an MLP update; we measure how its causal effect depends on where it is written.

State-dependent steering and local geometry. Activation steering modifies hidden representations to change behavior [Turner et al., 2023, Rimsky et al., 2024, Li et al., 2023, Zou et al., 2023, Singh et al., 2024]. Recent work makes state dependence explicit through context-conditioned steering fields, local linear control, and response-theoretic sensitivity [Li et al., 2026, Skifstad et al., 2026, Olivieri and Pérez Rodríguez, 2026]. The softmax output has a natural Fisher geometry tied to behavioral change [Martens, 2020, Park et al., 2026], and FishBack pulls this geometry back to intermediate transformer states through the downstream Jacobian in order to steer [Wang and Zhao, 2026]. We do not propose a new geometry or a steering method. We use the established local metric as a diagnostic for whether the same natural update has different full-dose effects at different receivers.

Reusable internal computation. Hidden APIs asks whether hidden interfaces support reusable causal computations across forked futures [Ma et al., 2026]. Function vectors and related representation-transfer studies test whether particular behaviors remain portable across prompts or formats [Todd et al., 2024, Opiełka et al., 2026, Quirke, 2026]. Our transformation analysis does not assign a semantic function to an MLP update. It defines the computation operationally by its measured causal footprint and asks whether receiver-specific structure in that footprint generalizes to unseen natural displacements.

B Mathematical Details

The identities in this appendix are standard. We state them to make the diagnostic and the baselines precise, not as new results.

B.1 Local KL identity

Let $A(z) = \log \sum_y e^{z_y}$, so that $\nabla A(z) = p = \mathrm{softmax}(z)$ and $\nabla^2 A(z) = C_p = \mathrm{diag}(p) - pp^\top$. For logits z and a logit change Δ,

$$D_{\mathrm{KL}}\big(\mathrm{softmax}(z) \,\big\|\, \mathrm{softmax}(z+\Delta)\big) = A(z+\Delta) - A(z) - \langle p, \Delta\rangle = \tfrac{1}{2}\,\Delta^\top C_p\,\Delta + O(\|\Delta\|^3). \quad (5)$$

Adding $\epsilon\Delta u$ to the receiver state gives $\Delta(\epsilon) = G_\ell(r + \epsilon\Delta u) - G_\ell(r) = \epsilon\, JG_\ell(r)\Delta u + O(\epsilon^2)$. Because the first-order term of (5) vanishes, the $O(\epsilon^2)$ part of Δ enters the divergence only at order ϵ^3, and

$$D_{\mathrm{KL}}(p_r \,\|\, p_{r+\epsilon\Delta u}) = \epsilon^2\, Q_{\mathrm{recv}}(r, \Delta u) + O(\epsilon^3), \quad (6)$$

with Q_{recv} as in (3). This is the classical second-order expansion of KL in a curved exponential family [Martens, 2020] pulled back through the downstream map [Park et al., 2026, Wang and Zhao, 2026]. The experiments evaluate the score at $\epsilon = 1$, where this expansion is not guaranteed to be accurate; whether it still ranks receivers is an empirical question.

B.2 Variance form and the matched baseline

For any $v \in \mathbb{R}^V$, $v^\top C_p v = \sum_y p_y v_y^2 - \big(\sum_y p_y v_y\big)^2 = \mathrm{Var}_{y\sim p}[v_y]$, which gives Remark 1. In particular $C_p \mathbf{1} = 0$, so a uniform logit shift has zero score. Both Q_{recv} and the matched baseline

$$q_{p2}(r, \Delta u) = \tfrac{1}{2} \| J G_\ell(r) \Delta u \|_2^2 \tag{7}$$

use the same finite-difference estimate of $JG_\ell(r)\Delta u$; they differ only in the weighting by the receiver's next-token distribution.

B.3 First-order attribution of KL is zero

Let z_α be the logits after adding $\alpha \Delta u$, with $z_0 = z$. Differentiating (5) with $\Delta = z_\alpha - z$ gives $\frac{d}{d\alpha} D_{\mathrm{KL}}(p \,\|\, p_\alpha) = \langle p_\alpha - p, \dot{z}_\alpha \rangle$, which is zero at $\alpha = 0$. A first-order attribution score for KL is therefore identically zero at the native point. The AtP baselines instead use two non-stationary targets: the directional derivative of the native top-token log-probability and the directional derivative of the native top1–top2 logit margin. We take absolute values because the question is how strongly a receiver reacts along the intervention direction.

B.4 The three correlation estimands

Let $\mathcal{K}_d$ be the receivers of displacement d, including the original host i_d as an anchor, and let $X_{d,k}$ be a predictor.

1. **Pooled:** $\rho_{\mathrm{pool}} = \mathrm{Spearman}\big(\{X_{d,k}\}, \{K_{d,k}\}\big)$ over all rows, anchors included.
2. **Within-displacement (primary):** $\rho_d = \mathrm{Spearman}_{k \in \mathcal{K}_d \setminus \{i_d\}}(X_{d,k}, K_{d,k})$, reported as $\mathrm{median}_d\, \rho_d$ together with the fraction of displacements with $\rho_d > 0$. Displacements with fewer than four alternative receivers would be skipped; none are in the reported panels.
3. **Residual-rank (crossed matrices):** rank-transform X and K over all rows and standardize them, then remove displacement and receiver means by alternating demeaning until convergence. The statistic is the Pearson correlation of the two residual vectors.

For the ordinary host–donor matrices (Appendix D.1), the pair-specific statistic is computed in the same spirit, but on the original scale: $\log(1 + \cdot)$-transformed values are two-way demeaned by host and donor, and the residuals are compared by Spearman correlation. We report each statistic with the method used to compute it in the frozen artifact; the two procedures are not numerically interchangeable.

B.5 Causal footprints and held-out receiver maps

For downstream layer m, the footprints $c_{d,i}^{(m)}$ and $c_{d,k}^{(m)}$ are differences between patched and native final-token hidden states (Equation (4)). Fidelity, gain, and the rewrite residual are defined in Section 4.2. For prediction, the 96 control-panel displacements are split once into 72 training and 24 held-out displacements, and the split is fixed before analysis. At each layer, a rank-16 PCA basis is fit to training footprints only, and ridge maps (regularization strength 1.0) are fit in this subspace. The baselines are the identity; a scalar gain per receiver; one global map using all receivers; the receiver-specific map; and a wrong-receiver map obtained by a fixed cyclic permutation of receiver identities. We report cosine prediction and normalized RMSE on held-out displacements. For uncertainty, receiver rows are averaged within each held-out displacement, so the 24 held-out displacements are the independent units for both the standard-error bands in Figure 3 and the bootstrap intervals in Section 5.6.

C Experimental and Reproducibility Details

C.1 Models, data, and intervention sites

We use Qwen3-8B and Mistral-7B-v0.3 with frozen weights. Contexts are sampled deterministically from the C4 validation split with SHA-256 thinning before model-specific tokenization. Each context contains 64 tokens, and all interventions and measurements use the final token. The four depth probes are Qwen layers 7, 14, 21, 26 and Mistral layers 6, 12, 19, 23, at relative depths of about 0.20, 0.40, 0.60, and 0.74. The primary depths are Qwen layer 14 and Mistral layer 12. Exact checkpoint revisions are recorded in the artifact.

C.2 Ordinary transplant protocol

The ordinary protocol uses 64 contexts and evaluates every directed non-self donor–host pair, which gives $64 \times 63 = 4032$ interventions at each tested depth. It supports host–donor residualization, the wrong-state diagnostic, and comparison with earlier activation-transplant settings. It does not isolate receiver causality by itself, because the displacement changes with the host. At the primary depth, two random subsets of this matrix are reused: 256 pairs for the dose curve (Figure 5) and 128 pairs for the teacher-forced check (Appendix D.10). A larger ordinary matrix covers all $256 \times 255 = 65{,}280$ directed pairs of the 256 contexts of bucket B1 in Mistral-7B at layer 12.

C.3 Crossed-receiver protocol

The crossed-receiver test uses three disjoint 256-context buckets, assigned by distinct SHA-256 residues modulo 11. Each stage samples 512 natural displacements from host–donor pairs within the bucket. In bucket B1, each displacement is crossed with 16 receivers (the original host as an anchor plus 15 alternatives), giving 8192 interventions per stage. B1 is repeated at all four depths in both models. Buckets B2 and B3 use 32 receivers (the anchor plus 31 alternatives) at the primary depth, giving 16,384 interventions each. In total, the twelve crossed stages contain 131,072 physical interventions. The anchor rows enter the pooled and residual statistics and the variance decomposition, but not the within-displacement statistic.

C.4 Control panel

The control panel is a separate deterministic 96×8 panel per model at the primary depth: 96 natural displacements, built from disjoint host and donor contexts, each crossed with the same eight receivers. Its contexts are selected by a different hash rule from the crossed buckets, and we do not assume that it is statistically independent of them. The panel stores layerwise final-token hidden-state differences, which the scalar-only crossed buckets do not. It is used for the alternative predictors, the equal-norm control, the causal footprints, and the held-out maps.

C.5 Alternative predictors and the equal-norm control

For every row of the control panel, we record Q_{recv}, q_{p2}, the two AtP scores (Appendix B.3), the receiver norm $\|r\|$, the relative displacement norm $\|\Delta u\|/\|r\|$, and $|\cos(\Delta u, r)|$. The AtP gradients are exact automatic-differentiation gradients of the respective targets with respect to the receiver state, with one backward pass through the suffix per receiver. For the physical equal-norm control, each natural displacement is rescaled to the median displacement norm of the panel before it is applied to its receivers, and exact KL is recomputed. Because a displacement's scale factor is shared by all of its receivers, the control asks whether the nonlinear receiver ordering changes once between-displacement magnitude differences are removed.

C.6 Implementation and compute

The large-model experiments use Hugging Face Transformers with FP16 weights, sharded with Accelerate across two NVIDIA T4 GPUs (16 GB each), with gradients disabled except for the AtP baselines, 64-token contexts, and pair batches of four. The twelve crossed-receiver stages and the 65,280-pair Mistral matrix have instrumented stage runtimes totalling 631.3 minutes (437.8 minutes crossed, 193.4 minutes large matrix). The eight ordinary 64-context depth targets total 134.9 minutes,

as recorded in the artifact. The wall-clock time of the two control-panel runs was not instrumented, so we do not report it. The Pythia runs use FP32 and exact JVPs (Appendix D.11). The numerical audit of Appendix D.12.2 produces the natural states with the FP16 model on the same two T4 GPUs and then evaluates the downstream suffix in FP32, with TF32 disabled, split across both GPUs; its runtime was not recorded. Random seeds, context identifiers, and train/held-out splits are fixed before analysis. Frozen outputs, analysis scripts, and figure-generation code are available at https://anonymous.4open.science/r/newinml-7402/. All data figures in this paper are regenerated from these frozen outputs. Row-level outputs allow every crossed-receiver statistic and the Mistral control-panel intervals to be recomputed on CPU. For the Qwen3-8B control panel, the artifact stores the bootstrap and standard-error summaries but not per-displacement map scores.

D Additional Results

D.1 Ordinary transplants and the wrong-state diagnostic

At the primary depth, the ordinary-transplant Fisher–KL Spearman correlation over all 4032 pairs is 0.867 in Qwen3-8B and 0.911 in Mistral-7B. Removing additive host and donor effects leaves 0.563 and 0.677, with two-way bootstrap intervals $[0.484, 0.637]$ and $[0.607, 0.750]$. The wrong-state diagnostic keeps each transplant outcome fixed but evaluates the score of its displacement at unrelated states. On a random 256-pair subset, the correlation between the transplant KL and the score at the correct host is 0.875 in Qwen3-8B and 0.919 in Mistral-7B. When the score is evaluated at eight unrelated states per pair, it drops to -0.015 and 0.028 (2048 rows). The diagnostic shows that the score must be computed at the state that receives the update. It does not show that the receiving state causes the variation, because the displacement still changes with the host; the crossed design in the main text tests that directly.

For the larger Mistral matrix of 65,280 ordinary transplants, the raw Fisher–KL correlation is 0.911, the host–donor residual correlation is 0.660, and the corresponding q_{p2} residual correlation is 0.415. A joint context-label permutation test, which applies the same permutation to both matrix axes, gives $p = 0.0005$, the smallest value attainable with 2000 permutations.

D.2 Rank-KL variance decomposition

To compare the correlation summaries of Section 3.2, we fit descriptive fixed-effect models to the rank-transformed exact KL in each crossed matrix (Table 4). Receiver identity alone explains most of the rank variance, which is why the within-displacement correlation can be high even though it is not purely pair-specific. Adding displacement identity increases the in-sample additive R^2 further, but 18–25% remains. This remainder is the variation targeted by the residual-rank correlation. Because there is one observed outcome per displacement–receiver cell, we call it non-additive residual variation, not a separately identified interaction.

Table 4: **Descriptive decomposition of rank-transformed exact KL in the six crossed matrices.** "Receiver" and "Displacement" are one-factor fixed-effect R^2 values; "Additive" uses both factors; "Non-additive" is $1 - R^2$ of the additive model. N includes the anchor rows.

Model	Bucket	N	Receiver R^2	Displacement R^2	Additive R^2	Non-additive
Qwen3-8B	B1	8192	0.707	0.123	0.789	0.211
Qwen3-8B	B2	16384	0.733	0.063	0.779	0.221
Qwen3-8B	B3	16384	0.704	0.071	0.754	0.246
Mistral-7B	B1	8192	0.773	0.076	0.804	0.196
Mistral-7B	B2	16384	0.795	0.041	0.815	0.185
Mistral-7B	B3	16384	0.798	0.044	0.820	0.180

D.3 Reconciling the Fisher–KL correlations reported in this paper

The paper reports several Fisher–KL correlations. They differ because they use different estimands, designs, samples, and numbers of receivers per displacement, not because of inconsistent reruns. Table 5 lists them side by side. Three patterns explain the differences. First, within-displacement

medians over 8 receivers (control panel) are coarser and lower than those over 15 or 31 receivers (crossed buckets). Second, residual statistics remove the dominant receiver main effect and are therefore lower than within-displacement or pooled ones (Table 4). Third, random subsets of the ordinary matrix (256 dose pairs, 256 wrong-state pairs, 128 teacher-forced pairs) differ from the full 4032-pair value by ordinary sampling variation; at full dose, the dose-subset KL is the same quantity as the ordinary transplant KL.

Table 5: **Every Fisher–KL correlation in the paper, with its design, sample, and estimand.** Ranges are over buckets or depths. All values come from the frozen artifact.

Design and sample	Receivers per Δu	Estimand	Qwen3-8B	Mistral-7B
Crossed B1–B3, primary depth	15 / 31 alternatives	within (primary)	0.858–0.872	0.911–0.928
Crossed B1–B3, primary depth	anchor + 15 / 31	pooled	0.855–0.871	0.921–0.932
Crossed B1–B3, primary depth	anchor + 15 / 31	residual-rank	0.504–0.520	0.658–0.675
Crossed B1, four depths	15 alternatives	within	0.857–0.954	0.854–0.957
Control panel (96×8)	8	within	0.738	0.905
Control panel (96×8)	8	pooled	0.722	0.876
Control panel (96×8)	8	residual-rank	0.456	0.612
Ordinary, all 4032 pairs	—	pooled	0.867	0.911
Ordinary, all 4032 pairs	—	host–donor resid.	0.563	0.677
Ordinary, 256 wrong-state pairs	—	pooled, correct state	0.875	0.919
Ordinary, 256 dose pairs, $\lambda = 1$	—	pooled	0.831	0.907
Ordinary, 128 pairs, $h = 1$	—	pooled	0.857	0.930
Large ordinary, 65,280 pairs	—	pooled / resid.	—	0.911 / 0.660

D.4 Depth sweep

Table 6 gives the B1 crossed-receiver result at every probed depth. The receiver-local score ranks receivers at all four depths in both models, and the within-displacement correlation is positive for at least 99.4% of displacements at every depth.

Table 6: **Crossed-receiver result across depth (bucket B1; 512 displacements, 15 alternative receivers each).** Median within-displacement Spearman correlation between Q_{recv} and exact KL, and the fraction of displacements with a positive correlation.

Model	Layer	Relative depth	Median within $\rho \uparrow$	Positive fraction
Qwen3-8B	7	0.20	0.857	1.000
Qwen3-8B	14	0.40	0.871	0.994
Qwen3-8B	21	0.60	0.936	1.000
Qwen3-8B	26	0.74	0.954	1.000
Mistral-7B	6	0.19	0.854	1.000
Mistral-7B	12	0.39	0.911	1.000
Mistral-7B	19	0.61	0.929	0.994
Mistral-7B	23	0.74	0.957	1.000

D.5 Spread of the effect of a fixed displacement

For each crossed displacement, we compute $\log_{10}(\max_k K_{d,k} / \min_k K_{d,k})$ over its alternative receivers (Table 7). The spread grows with the number of receivers, as any range statistic does, so we compare buckets with the same receiver count.

Table 7: **How much the exact effect of one frozen displacement varies across its receivers.** Median over 512 displacements of $\log_{10}$ of the ratio between the largest and smallest exact KL among the alternative receivers, and the fraction of displacements whose ratio is at least 100.

Model	Bucket	Alternative receivers	Median $\log_{10}$ max/min	Fraction with ratio ≥ 100
Qwen3-8B	B1	15	3.46	0.916
Qwen3-8B	B2	31	4.77	0.994
Qwen3-8B	B3	31	4.36	0.990
Mistral-7B	B1	15	2.90	0.865
Mistral-7B	B2	31	3.31	0.994
Mistral-7B	B3	31	3.65	1.000

D.6 Full alternative-predictor panel

The compact main-text Table 2 reports the primary within-displacement statistic. Table 8 adds the pooled correlation, the fraction of displacements with a positive within-displacement correlation, and the residual-rank correlation. The residual is undefined for the receiver norm, because a predictor that depends only on the receiver is removed entirely by the receiver main effect.

Table 8: **Alternative predictors on the** 96×8 **control panel** (768 rows per model). The magnitudes differ across columns because the estimands differ (Section 3.2).

Model	Predictor	Pooled ρ	Within median ρ	Positive fraction	Residual ρ
Qwen3-8B	Fisher Q_{recv}	0.722	0.738	0.979	0.456
Qwen3-8B	AtP-top	0.512	0.500	0.906	0.283
Qwen3-8B	AtP-margin	0.434	0.429	0.875	0.222
Qwen3-8B	q_{p2}	0.261	0.226	0.708	0.237
Qwen3-8B	$\|\Delta u\|/\|r\|$	0.350	0.071	0.615	0.108
Qwen3-8B	$\|r\|$	-0.081	-0.071	0.354	—
Qwen3-8B	$\|\cos(\Delta u, r)\|$	-0.056	-0.012	0.479	0.047
Mistral-7B	Fisher Q_{recv}	0.876	0.905	1.000	0.612
Mistral-7B	AtP-top	0.736	0.750	1.000	0.413
Mistral-7B	AtP-margin	0.156	0.179	0.656	0.407
Mistral-7B	q_{p2}	0.089	0.060	0.552	0.197
Mistral-7B	$\|\Delta u\|/\|r\|$	0.118	0.000	0.458	-0.036
Mistral-7B	$\|r\|$	-0.006	0.000	0.479	—
Mistral-7B	$\|\cos(\Delta u, r)\|$	0.030	0.048	0.531	0.003

D.7 Layerwise causal footprints

Figure 4 shows how the footprints of one displacement at the original host and at a receiver separate across downstream layers. Fidelity and gain both start at one at the intervention site and decay toward zero by the final layer. The receiver's footprint is therefore neither a rescaled copy of the host's nor simply attenuated along the host's direction; most of it lies in a different direction.




Figure 4: **The downstream direction of a fixed displacement diverges across receivers.** Median over the 768 displacement–receiver pairs of the 96×8 control panel of the directional fidelity $F^{(m)}$ (left) and the gain $A^{(m)}$ (right) between the original host's and the receiver's causal footprints, by number of layers after the intervention. At the final layer, median fidelity is 0.030 in Qwen3-8B and 0.037 in Mistral-7B.

D.8 Receiver-specific transformation at the final layer

Table 9 reports the final-layer held-out prediction scores underlying Figure 3. The receiver-specific map improves directional prediction much more than exact vector reconstruction. This supports a modest interpretation: receiver identity contributes a reproducible directional component to the downstream transformation, while substantial update-specific variation remains unexplained.

Table 9: **Held-out final-layer prediction** (Qwen3-8B layer 35, Mistral-7B layer 31; 24 held-out displacements $\times$ 8 receivers). Cosine is averaged over receiver–displacement pairs; lower normalized RMSE is better. Bold marks the best predictor per model.

Model	Predictor	Mean cosine ↑	Mean NRMSE ↓
Qwen3-8B	Identity	0.029	1.823
Qwen3-8B	Gain only	0.021	1.000
Qwen3-8B	Global map	0.086	1.005
Qwen3-8B	Receiver-specific map	**0.316**	**0.945**
Qwen3-8B	Wrong-receiver map	−0.023	1.122
Mistral-7B	Identity	0.037	1.859
Mistral-7B	Gain only	0.037	1.000
Mistral-7B	Global map	0.109	0.999
Mistral-7B	Receiver-specific map	**0.241**	**0.986**
Mistral-7B	Wrong-receiver map	0.028	1.080

D.9 Intervention dose

On a random 256-pair subset of the ordinary matrix at the primary depth, we apply $u_i + \lambda \Delta u_{ij}$ for $\lambda \in \{0.10, 0.25, 0.50, 0.75, 1.00\}$ and correlate Q_{recv} with the exact KL at each dose (Figure 5). The correlation is highest at small doses, where the local expansion of Appendix B.1 is most accurate, and it remains high at the full transplant.




Figure 5: **The local score remains informative as the intervention reaches full dose.** Spearman correlation between Q_{recv} and exact KL at dose λ on 256 ordinary transplant pairs per model at the primary depth. Values at $\lambda = 0.10, 0.25, 0.50, 0.75, 1.00$: $0.955, 0.970, 0.944, 0.892, 0.831$ in Qwen3-8B and $0.981, 0.986, 0.968, 0.940, 0.907$ in Mistral-7B.

D.10 Teacher-forced persistence check

The main experiments measure the next-token distribution. To check whether the association extends beyond the immediate next token, we take a random 128-pair subset of the ordinary matrix at the primary depth and run each patched forward pass on the true C4 continuation. The MLP output is replaced at the final context token only, and later positions see the change only through the model's own computation. We sum the per-position KL over the next $h \in \{1, 4, 8, 16, 32\}$ positions and correlate Q_{recv} with this cumulative disturbance (Table 10 and Figure 6); $h = 1$ is the ordinary next-token KL. Receiver-local sensitivity remains associated with cumulative disturbance beyond the immediate next token, although the association weakens with the horizon, especially in Qwen3-8B. Teacher forcing fixes the continuation, so this check does not establish persistence under unconstrained autoregressive generation.

Table 10: **Teacher-forced persistence.** Spearman correlation between Q_{recv} and KL summed over the next h teacher-forced positions (128 ordinary transplant pairs per model, primary depth).

Model	$h = 1$	$h = 4$	$h = 8$	$h = 16$	$h = 32$
Qwen3-8B	0.857	0.771	0.704	0.614	0.565
Mistral-7B	0.930	0.896	0.839	0.819	0.812




Figure 6: **Association with cumulative disturbance under teacher forcing.** The values of Table 10 plotted against the horizon h (log scale). The association persists beyond the next token and weakens with h.

D.11 Independent-pretraining replication (Pythia-70M, ordinary transplants)

This replication uses ordinary transplants, not the crossed-receiver design. It tests whether the association between local geometry and transplant KL replicates across independently pretrained models. We use the final checkpoints (step 143,000) of Pythia-70M and five further pretraining seeds [Biderman et al., 2023, van der Wal et al., 2025], with MLP layer 2 and FP32 arithmetic. For each run, 256 hosts are drawn from a held-out pool of C4 contexts (corpus B). Each host receives one donor chosen deterministically from its five nearest non-self neighbours among the MLP-input states, after a 32-dimensional PCA. The downstream Fisher score Q_{recv} is computed with exact automatic-differentiation JVPs. The reported statistic is a rank-residualized partial Spearman correlation between $\log(1 + Q_{\mathrm{recv}})$ and transplant KL. Both variables are rank-transformed, and the ranks of four controls are regressed out by least squares: the log update distance $\log(1 + \|\Delta u\|)$, the log state distance $\log(1 + \|\Delta m\|)$ between donor and host MLP inputs, the normalized nonlinear residual $\|\Delta u - J_{F_\ell}(m_i)\Delta m\|/\|\Delta u\|$, and the tangent alignment $\cos(J_{F_\ell}(m_i)\Delta m, \Delta u)$, where J_{F_ℓ} is the exact MLP Jacobian at the host. Table 11 reports the six runs. All six are positive, which shows that the local-geometry association under ordinary transplants is not specific to one pretraining run.

Table 11: **Partial Spearman correlation between $\log(1 + Q_{\mathrm{recv}})$ and transplant KL on six independently pretrained Pythia-70M runs** (ordinary transplants, layer 2, 256 hosts per run, controls as described in Appendix D.11). The interval is a bootstrap over the six runs.

Run	Hosts	Partial ρ
base	256	0.775
seed1	256	0.824
seed2	256	0.723
seed3	256	0.828
seed4	256	0.762
seed5	256	0.825
Median	—	0.800
95% bootstrap interval	—	[0.742, 0.827]

D.12 Numerical audit of the finite-difference score

The crossed experiments estimate the directional response $JG_\ell(r)\Delta u$ by centered finite differences at $\epsilon = 0.075$ on FP16 model evaluations. We audit this estimate on one frozen 16-pair panel per model: the first 16 control-panel displacements (Appendix C.4), each applied to receiver 0. The 16-pair audit varies displacement direction at a fixed receiver and therefore isolates numerical closure of the

local directional derivative; it does not reproduce the primary within-displacement receiver-ranking statistic, which rests on the physical full-dose crossed experiments. We ask two separate questions.

D.12.1 End-to-end FP16 step-size stability

On FP16 model evaluations, we compare the response at ϵ with the response at half step $\epsilon/2 = 0.0375$ and with centered-difference Richardson extrapolation. The median cosine between the responses at ϵ and $\epsilon/2$ is 0.989 for Qwen3-8B and 0.940 for Mistral-7B, and between the ϵ response and the Richardson estimate 0.981 and 0.899. The median relative difference of the Fisher score from the Richardson estimate is 0.333 and 0.472. These end-to-end comparisons combine finite-difference step effects, FP16 finite-precision effects, and the corresponding changes in native logits and probabilities, so they should not be read as truncation error alone. In the ordinary-matrix step-size sweep, rank stability between step sizes is above 0.95 for every comparison involving the chosen $\epsilon = 0.075$; the minimum over all compared pairs of step sizes is 0.949 in Qwen3-8B (for $\epsilon = 0.04$ versus 0.05) and 0.961 in Mistral-7B.

D.12.2 Exact FP32 downstream-suffix closure

To separate truncation error from finite precision, we recompute the same 16 cases with an exact FP32 downstream-suffix JVP from the same cached natural receiver states. The natural states up to and including layer ℓ (the host and donor MLP outputs and the receiver's layer-ℓ output) are produced in FP16, as in the main experiments. The downstream suffix, from layer $\ell + 1$ through the final norm and the language-model head, is then evaluated in FP32 with TF32 disabled. On this suffix, we compute the exact JVP by automatic differentiation and the centered finite differences at ϵ and $\epsilon/2$, with their Richardson combination. The upstream computation is not repeated in FP32, so this is not a full-model FP32 JVP. The host, donor, and receiver context identifiers match the frozen control panel for all 16 cases in both models.

Table 12: **Numerical audit on 16 frozen cases per model** (control-panel displacements 0–15 at receiver 0; Qwen3-8B layer 14, Mistral-7B layer 12). The upper block compares FP32 finite differences with exact FP32 suffix JVPs. The lower block compares the FP16 finite-difference scores for these same 16 control-panel cases, computed with the same estimator used in the crossed experiments, with the exact FP32 suffix-JVP scores. "Relative Q error" is $|Q - Q_{\mathrm{JVP32}}|/Q_{\mathrm{JVP32}}$.

Comparison	Statistic	Qwen3-8B	Mistral-7B
FD32 ($\epsilon = 0.075$) vs. JVP32	median directional cosine	1.0000	1.0000
	Spearman $\rho(Q_{\mathrm{FD32}}, Q_{\mathrm{JVP32}})$	1.000	1.000
	median relative Q error	0.21%	0.20%
	maximum relative Q error	0.82%	0.37%
FD32 ($\epsilon/2$) vs. JVP32	median relative Q error	0.12%	0.07%
FD32 Richardson vs. JVP32	median relative Q error	0.18%	0.13%
FP16 FD ($\epsilon = 0.075$) vs. JVP32	Spearman $\rho(Q_{\mathrm{FP16}}, Q_{\mathrm{JVP32}})$	0.785	0.544
	median relative Q difference	21.6%	26.7%

Table 12 reports the result. In FP32, the centered finite difference at $\epsilon = 0.075$ reproduces the exact JVP almost perfectly: every directional cosine is at least 0.99998, the Fisher scores are identically ranked, and the median relative score error is about 0.2% in both models, with the half step and Richardson combination equally close. The step $\epsilon = 0.075$ itself therefore introduces negligible centered-difference truncation error on this panel. The FP16 finite-difference scores for the same 16 cases agree less closely with the exact FP32 scores (Spearman 0.785 and 0.544; median relative difference 21.6% and 26.7%), and Richardson extrapolation of the FP16 differences moves further from them (Spearman 0.697 and 0.474), consistent with amplification of finite-precision noise. On this audit panel, this pattern is consistent with finite-precision effects dominating the observed discrepancy in Appendix D.12.1 rather than centered-difference truncation error. Accordingly, we treat the large-scale FP16 Fisher values as ranking diagnostics rather than as numerically exact FP32 quadratic forms; the audit closes truncation error on the tested directions but does not make the FP16 scores exact. The causal-footprint and held-out receiver-map results in Sections 5.5 and 5.6 do not depend on the finite-difference Fisher estimator.

E Scope and Interpretation

The crossed design supports a causal statement about the receiving state, because the intervention vector is physically held fixed within each displacement. It does not establish that an MLP update represents a context-independent semantic function, and we make no such claim. Likewise, the low-rank maps should not be read as complete or deterministic receiver operators. Their held-out cosines are meaningful but far from one, and their normalized RMSE gains are modest. The result is better read as evidence that a reproducible receiver-specific component coexists with substantial update-specific variation.

The next-token endpoint is deliberately narrow. It gives a precise, full-vocabulary behavioral measure and makes exact physical controls possible, but it does not characterize free-running generation. The paper is diagnostic and proposes no steering or editing method. Natural extensions include longer-horizon behavior, other component types such as attention outputs, mechanistic decomposition of the receiver dependence, and intervention methods that aim to preserve a known causal effect across receiver states.

NeurIPS Paper Checklist

1. **Claims**

   Question: Do the main claims made in the abstract and introduction accurately reflect the paper's contributions and scope?

   Answer: [Yes].

   Justification: The abstract and Section 1 state the central empirical claim, that the exact effect of a fixed natural MLP displacement depends on the receiving state, and separate it from the receiver-side explanations. The Fisher score is presented as an established diagnostic rather than a new geometry (Section 4.1). The three correlation estimands are defined in Section 3.2 and reconciled in Table 5, the alternative baselines are in Tables 2 and 8, and the held-out receiver-map result is stated as a reproducible receiver-specific component rather than a complete model (Section 5.6).

   Guidelines:

   - The answer [N/A] means that the abstract and introduction do not include the claims made in the paper.
   - The abstract and/or introduction should clearly state the claims made, including the contributions made in the paper and important assumptions and limitations. A [No] or [N/A] answer to this question will not be perceived well by the reviewers.
   - The claims made should match theoretical and experimental results, and reflect how much the results can be expected to generalize to other settings.
   - It is fine to include aspirational goals as motivation as long as it is clear that these goals are not attained by the paper.

2. **Limitations**

   Question: Does the paper discuss the limitations of the work performed by the authors?

   Answer: [Yes].

   Justification: The Limitations paragraph of Section 6 states that the study is restricted to final-token MLP outputs and next-token behavior, to one Qwen3-8B and one Mistral-7B checkpoint at large scale, and to an ordinary-transplant independent-pretraining replication on Pythia-70M. It also states that the residual analysis is post hoc, that the receiver maps are linear rank-16 approximations of causal-effect geometry rather than models of semantic function, that teacher-forced checks do not establish free-generation behavior, and that the study proposes no steering method. It further states that the crossed experiments use FP16 finite-difference Fisher scores. The 16-pair exact FP32 downstream-suffix JVP audit (Appendix D.12.2) closes finite-difference truncation error on the tested directions but shows that the FP16 scores are not numerically exact, so they are used as ranking diagnostics. The audit varies displacements at one receiver and is not a replication of the crossed ranking statistic.

   Guidelines:

   - The answer [N/A] means that the paper has no limitation while the answer [No] means that the paper has limitations, but those are not discussed in the paper.
   - The authors are encouraged to create a separate "Limitations" section in their paper.
   - The paper should point out any strong assumptions and how robust the results are to violations of these assumptions (e.g., independence assumptions, noiseless settings, model well-specification, asymptotic approximations only holding locally). The authors should reflect on how these assumptions might be violated in practice and what the implications would be.
   - The authors should reflect on the scope of the claims made, e.g., if the approach was only tested on a few datasets or with a few runs. In general, empirical results often depend on implicit assumptions, which should be articulated.
   - The authors should reflect on the factors that influence the performance of the approach. For example, a facial recognition algorithm may perform poorly when image resolution is low or images are taken in low lighting. Or a speech-to-text system might not be used reliably to provide closed captions for online lectures because it fails to handle technical jargon.

- The authors should discuss the computational efficiency of the proposed algorithms and how they scale with dataset size.
- If applicable, the authors should discuss possible limitations of their approach to address problems of privacy and fairness.
- While the authors might fear that complete honesty about limitations might be used by reviewers as grounds for rejection, a worse outcome might be that reviewers discover limitations that aren't acknowledged in the paper. The authors should use their best judgment and recognize that individual actions in favor of transparency play an important role in developing norms that preserve the integrity of the community. Reviewers will be specifically instructed to not penalize honesty concerning limitations.

3. **Theory assumptions and proofs**

   Question: For each theoretical result, does the paper provide the full set of assumptions and a complete (and correct) proof?

   Answer: [N/A].

   Justification: The paper claims no new theoretical result. It uses the classical second-order expansion of KL and two standard identities, which are stated as such with short derivations in Appendix B.

   Guidelines:

   - The answer [N/A] means that the paper does not include theoretical results.
   - All the theorems, formulas, and proofs in the paper should be numbered and cross-referenced.
   - All assumptions should be clearly stated or referenced in the statement of any theorems.
   - The proofs can either appear in the main paper or the supplemental material, but if they appear in the supplemental material, the authors are encouraged to provide a short proof sketch to provide intuition.
   - Inversely, any informal proof provided in the core of the paper should be complemented by formal proofs provided in appendix or supplemental material.
   - Theorems and Lemmas that the proof relies upon should be properly referenced.

4. **Experimental result reproducibility**

   Question: Does the paper fully disclose all the information needed to reproduce the main experimental results of the paper to the extent that it affects the main claims and/or conclusions of the paper (regardless of whether the code and data are provided or not)?

   Answer: [Yes].

   Justification: Sections 2 to 4 and 5.1 and Appendices B and C specify the intervention, the exact effect, the crossed-receiver protocol (Algorithm 1), the three correlation estimands and their computation, the deterministic C4 sampling, the model layers, all panel sizes (Table 1), the alternative predictors, the equal-norm control, the 72/24 held-out split, the PCA rank, the ridge maps, the bootstrap unit, the Pythia protocol and controls, the teacher-forced protocol, the step-size audit, and the exact FP32 downstream-suffix JVP audit. The frozen artifact at `https://anonymous.4open.science/r/newinml-7402/` contains the reported outputs and analysis code.

   Guidelines:

   - The answer [N/A] means that the paper does not include experiments.
   - If the paper includes experiments, a [No] answer to this question will not be perceived well by the reviewers: Making the paper reproducible is important, regardless of whether the code and data are provided or not.
   - If the contribution is a dataset and/or model, the authors should describe the steps taken to make their results reproducible or verifiable.
   - Depending on the contribution, reproducibility can be accomplished in various ways. For example, if the contribution is a novel architecture, describing the architecture fully might suffice, or if the contribution is a specific model and empirical evaluation, it may be necessary to either make it possible for others to replicate the model with the same dataset, or provide access to the model. In general. releasing code and data is often

one good way to accomplish this, but reproducibility can also be provided via detailed instructions for how to replicate the results, access to a hosted model (e.g., in the case of a large language model), releasing of a model checkpoint, or other means that are appropriate to the research performed.

- While NeurIPS does not require releasing code, the conference does require all submissions to provide some reasonable avenue for reproducibility, which may depend on the nature of the contribution. For example
  (a) If the contribution is primarily a new algorithm, the paper should make it clear how to reproduce that algorithm.
  (b) If the contribution is primarily a new model architecture, the paper should describe the architecture clearly and fully.
  (c) If the contribution is a new model (e.g., a large language model), then there should either be a way to access this model for reproducing the results or a way to reproduce the model (e.g., with an open-source dataset or instructions for how to construct the dataset).
  (d) We recognize that reproducibility may be tricky in some cases, in which case authors are welcome to describe the particular way they provide for reproducibility. In the case of closed-source models, it may be that access to the model is limited in some way (e.g., to registered users), but it should be possible for other researchers to have some path to reproducing or verifying the results.

5. **Open access to data and code**

   Question: Does the paper provide open access to the data and code, with sufficient instructions to faithfully reproduce the main experimental results, as described in supplemental material?

   Answer: [Yes].

   Justification: The paper gives the artifact URL `https://anonymous.4open.science/r/newinml-7402/`. The artifact contains analysis code, frozen protocols, row-level crossed-receiver outputs, ordinary-matrix, control-panel, and Pythia results, figure-generation scripts, checksums, the T4×2 notebooks, and the notebook and outputs of the exact FP32 downstream-suffix JVP audit. For the Qwen3-8B control panel, it stores bootstrap and standard-error summaries but not per-displacement map scores (Appendix C.6). It does not redistribute pretrained model weights or full raw C4 documents.

   Guidelines:

   - The answer [N/A] means that paper does not include experiments requiring code.
   - Please see the NeurIPS code and data submission guidelines (`https://neurips.cc/public/guides/CodeSubmissionPolicy`) for more details.
   - While we encourage the release of code and data, we understand that this might not be possible, so [No] is an acceptable answer. Papers cannot be rejected simply for not including code, unless this is central to the contribution (e.g., for a new open-source benchmark).
   - The instructions should contain the exact command and environment needed to run to reproduce the results. See the NeurIPS code and data submission guidelines (`https://neurips.cc/public/guides/CodeSubmissionPolicy`) for more details.
   - The authors should provide instructions on data access and preparation, including how to access the raw data, preprocessed data, intermediate data, and generated data, etc.
   - The authors should provide scripts to reproduce all experimental results for the new proposed method and baselines. If only a subset of experiments are reproducible, they should state which ones are omitted from the script and why.
   - At submission time, to preserve anonymity, the authors should release anonymized versions (if applicable).
   - Providing as much information as possible in supplemental material (appended to the paper) is recommended, but including URLs to data and code is permitted.

6. **Experimental setting/details**

   Question: Does the paper specify all the training and test details (e.g., data splits, hyperparameters, how they were chosen, type of optimizer) necessary to understand the results?

Answer: [Yes].

Justification: Section 5.1, Table 1, and Appendix C report the released checkpoints, the C4 validation sampling rule, 64-token contexts, intervention layers, ordinary and crossed sample sizes, the finite-difference step, the 96×8 control panel, the 72/24 displacement split, the rank-16 PCA representation, the ridge maps, and the T4$\times$2 execution details. No model is trained or fine-tuned.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- The experimental setting should be presented in the core of the paper to a level of detail that is necessary to appreciate the results and make sense of them.
- The full details can be provided either with the code, in appendix, or as supplemental material.

7. **Experiment statistical significance**

Question: Does the paper report error bars suitably and correctly defined or other appropriate information about the statistical significance of the experiments?

Answer: [Yes].

Justification: The paper treats fixed displacements rather than individual receiver rows as the primary unit, reports the fraction of displacements with a positive correlation, and replicates the crossed test in three disjoint buckets and four depths. It also reports two-way bootstrap intervals for the ordinary host–donor matrices, a 2000-permutation test for the larger Mistral matrix (Appendix D.1), bootstrap intervals over the 24 held-out displacements for the final-layer receiver-map advantages (Section 5.6), ± 1 standard-error bands across the 24 held-out displacements in Figure 3, and a bootstrap interval over the six Pythia runs (Table 11). Captions state the aggregation unit.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- The authors should answer [Yes] if the results are accompanied by error bars, confidence intervals, or statistical significance tests, at least for the experiments that support the main claims of the paper.
- The factors of variability that the error bars are capturing should be clearly stated (for example, train/test split, initialization, random drawing of some parameter, or overall run with given experimental conditions).
- The method for calculating the error bars should be explained (closed form formula, call to a library function, bootstrap, etc.)
- The assumptions made should be given (e.g., Normally distributed errors).
- It should be clear whether the error bar is the standard deviation or the standard error of the mean.
- It is OK to report 1-sigma error bars, but one should state it. The authors should preferably report a 2-sigma error bar than state that they have a 96% CI, if the hypothesis of Normality of errors is not verified.
- For asymmetric distributions, the authors should be careful not to show in tables or figures symmetric error bars that would yield results that are out of range (e.g., negative error rates).
- If error bars are reported in tables or plots, the authors should explain in the text how they were calculated and reference the corresponding figures or tables in the text.

8. **Experiments compute resources**

Question: For each experiment, does the paper provide sufficient information on the computer resources (type of compute workers, memory, time of execution) needed to reproduce the experiments?

Answer: [Yes].

Justification: The physical crossed-receiver study was run in a Kaggle session with two NVIDIA Tesla T4 GPUs (16 GB VRAM each). Models were loaded in FP16 with Accelerate sharding (`device_map="balanced"`, 12,000 MiB memory cap per GPU), gradients disabled, 64-token contexts, and pair batch 4. The preserved run contains 12

crossed-receiver stages—four bucket-1 depths for each model plus bucket-2 and bucket-3 primary-depth replications—for 131,072 physical crossed-receiver interventions in total, together with a 65,280-pair Mistral full-core stage. Instrumented successful-stage runtimes in `ALL_STAGE_SUMMARIES.csv` sum to 631.3 minutes (10.52 hours wall-clock): 437.8 minutes for the crossed-receiver stages and 193.4 minutes for the Mistral full-core stage. Because both T4s shard each large model, this corresponds to roughly 21 T4 GPU-hours if both devices are counted for the full measured interval. The observed end-to-end successful notebook run was approximately 10–12 hours, including model loading, native-state caching, and ordinary notebook/session overhead. The eight ordinary 64-context depth targets ran on the same hardware class and total 134.9 minutes of recorded target runtime; the two 96×8 control-panel runs used the same hardware class, but their wall-clock time was not instrumented, so we do not report it. These figures exclude exploratory development and failed engineering attempts, which used additional compute. The saved row-level artifact can be reanalyzed on CPU without rerunning the GPU experiments (Appendix C.6). The exact FP32 downstream-suffix JVP audit (Appendix D.12.2; 16 pairs per model) also ran on Kaggle with two NVIDIA T4 GPUs (16 GB each): natural states were produced with the FP16 model, and the downstream suffix was evaluated in FP32 with TF32 disabled, split across both GPUs. Its runtime was not recorded, so we do not report it.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- The paper should indicate the type of compute workers CPU or GPU, internal cluster, or cloud provider, including relevant memory and storage.
- The paper should provide the amount of compute required for each of the individual experimental runs as well as estimate the total compute.
- The paper should disclose whether the full research project required more compute than the experiments reported in the paper (e.g., preliminary or failed experiments that didn't make it into the paper).

9. **Code of ethics**

   Question: Does the research conducted in the paper conform, in every respect, with the NeurIPS Code of Ethics `https://neurips.cc/public/EthicsGuidelines`?

   Answer: [Yes].

   Justification: The work analyzes publicly released language-model checkpoints and the C4 validation corpus, involves no human-subject experiment or private user data, and reports causal intervention results without deploying a system that acts on people.

   Guidelines:

   - The answer [N/A] means that the authors have not reviewed the NeurIPS Code of Ethics.
   - If the authors answer [No], they should explain the special circumstances that require a deviation from the Code of Ethics.
   - The authors should make sure to preserve anonymity (e.g., if there is a special consideration due to laws or regulations in their jurisdiction).

10. **Broader impacts**

    Question: Does the paper discuss both potential positive societal impacts and negative societal impacts of the work performed?

    Answer: [N/A].

    Justification: This is a diagnostic mechanistic-interpretability study of internal update transplant effects, with no deployed system, new generative capability, or direct application whose societal effects are evaluated. We therefore do not claim a specific positive or negative societal impact.

    Guidelines:

    - The answer [N/A] means that there is no societal impact of the work performed.
    - If the authors answer [N/A] or [No], they should explain why their work has no societal impact or why the paper does not address societal impact.

- Examples of negative societal impacts include potential malicious or unintended uses (e.g., disinformation, generating fake profiles, surveillance), fairness considerations (e.g., deployment of technologies that could make decisions that unfairly impact specific groups), privacy considerations, and security considerations.
- The conference expects that many papers will be foundational research and not tied to particular applications, let alone deployments. However, if there is a direct path to any negative applications, the authors should point it out. For example, it is legitimate to point out that an improvement in the quality of generative models could be used to generate Deepfakes for disinformation. On the other hand, it is not needed to point out that a generic algorithm for optimizing neural networks could enable people to train models that generate Deepfakes faster.
- The authors should consider possible harms that could arise when the technology is being used as intended and functioning correctly, harms that could arise when the technology is being used as intended but gives incorrect results, and harms following from (intentional or unintentional) misuse of the technology.
- If there are negative societal impacts, the authors could also discuss possible mitigation strategies (e.g., gated release of models, providing defenses in addition to attacks, mechanisms for monitoring misuse, mechanisms to monitor how a system learns from feedback over time, improving the efficiency and accessibility of ML).

11. **Safeguards**

    Question: Does the paper describe safeguards that have been put in place for responsible release of data or models that have a high risk for misuse (e.g., pre-trained language models, image generators, or scraped datasets)?

    Answer: [N/A].

    Justification: The work does not release a new pretrained model, generator, or scraped dataset. The new artifact consists of analysis code, frozen protocols, and derived experimental outputs.

    Guidelines:

    - The answer [N/A] means that the paper poses no such risks.
    - Released models that have a high risk for misuse or dual-use should be released with necessary safeguards to allow for controlled use of the model, for example by requiring that users adhere to usage guidelines or restrictions to access the model or implementing safety filters.
    - Datasets that have been scraped from the Internet could pose safety risks. The authors should describe how they avoided releasing unsafe images.
    - We recognize that providing effective safeguards is challenging, and many papers do not require this, but we encourage authors to take this into account and make a best faith effort.

12. **Licenses for existing assets**

    Question: Are the creators or original owners of assets (e.g., code, data, models), used in the paper, properly credited and are the license and terms of use explicitly mentioned and properly respected?

    Answer: [Yes].

    Justification: The main-paper checkpoints are Pythia, Qwen3, and Mistral, used under their published open-weight terms; the artifact records exact checkpoint revisions and licenses. It also preserves clearly labeled scope audits on GPT-2, OPT-125M, and Qwen2.5, which are not part of the claims of this paper. C4 is used under its published dataset terms and Common Crawl provenance. The artifact redistributes neither model weights nor full raw C4 documents; it retains hashes and derived numerical outputs.

    Guidelines:

    - The answer [N/A] means that the paper does not use existing assets.
    - The authors should cite the original paper that produced the code package or dataset.
    - The authors should state which version of the asset is used and, if possible, include a URL.

- The name of the license (e.g., CC-BY 4.0) should be included for each asset.
- For scraped data from a particular source (e.g., website), the copyright and terms of service of that source should be provided.
- If assets are released, the license, copyright information, and terms of use in the package should be provided. For popular datasets, `paperswithcode.com/datasets` has curated licenses for some datasets. Their licensing guide can help determine the license of a dataset.
- For existing datasets that are re-packaged, both the original license and the license of the derived asset (if it has changed) should be provided.
- If this information is not available online, the authors are encouraged to reach out to the asset's creators.

13. **New assets**

    Question: Are new assets introduced in the paper well documented and is the documentation provided alongside the assets?

    Answer: [Yes].

    Justification: The released research artifact is organized around frozen intervention protocols, row-level crossed-receiver results, transformation-map outputs, target summaries, audit scripts, figure-generation code, checksums, and reproduction documentation. It does not redistribute model weights or full raw C4 documents.

    Guidelines:

    - The answer [N/A] means that the paper does not release new assets.
    - Researchers should communicate the details of the dataset/code/model as part of their submissions via structured templates. This includes details about training, license, limitations, etc.
    - The paper should discuss whether and how consent was obtained from people whose asset is used.
    - At submission time, remember to anonymize your assets (if applicable). You can either create an anonymized URL or include an anonymized zip file.

14. **Crowdsourcing and research with human subjects**

    Question: For crowdsourcing experiments and research with human subjects, does the paper include the full text of instructions given to participants and screenshots, if applicable, as well as details about compensation (if any)?

    Answer: [N/A].

    Justification: The study contains no crowdsourcing experiment and no research with human subjects.

    Guidelines:

    - The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.
    - Including this information in the supplemental material is fine, but if the main contribution of the paper involves human subjects, then as much detail as possible should be included in the main paper.
    - According to the NeurIPS Code of Ethics, workers involved in data collection, curation, or other labor should be paid at least the minimum wage in the country of the data collector.

15. **Institutional review board (IRB) approvals or equivalent for research with human subjects**

    Question: Does the paper describe potential risks incurred by study participants, whether such risks were disclosed to the subjects, and whether Institutional Review Board (IRB) approvals (or an equivalent approval/review based on the requirements of your country or institution) were obtained?

    Answer: [N/A].

Justification: The study contains no crowdsourcing or human-subject research, so IRB or equivalent approval is not applicable.

Guidelines:

- The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.
- Depending on the country in which research is conducted, IRB approval (or equivalent) may be required for any human subjects research. If you obtained IRB approval, you should clearly state this in the paper.
- We recognize that the procedures for this may vary significantly between institutions and locations, and we expect authors to adhere to the NeurIPS Code of Ethics and the guidelines for their institution.
- For initial submissions, do not include any information that would break anonymity (if applicable), such as the institution conducting the review.

16. **Declaration of LLM usage**

Question: Does the paper describe the usage of LLMs if it is an important, original, or non-standard component of the core methods in this research? Note that if the LLM is used only for writing, editing, or formatting purposes and does *not* impact the core methodology, scientific rigor, or originality of the research, declaration is not required.

Answer: [Yes].

Justification: General-purpose LLM tools were used during research development for conceptual clarification, experiment-code drafting and debugging, and manuscript editing. They were not used to generate experimental labels, judge model outputs, or replace the reported statistical evaluation; the author executed the experiments, inspected the outputs, and verified the numerical claims.

Guidelines:

- The answer [N/A] means that the core method development in this research does not involve LLMs as any important, original, or non-standard components.
- Please refer to our LLM policy in the NeurIPS handbook for what should or should not be described.