

Timings of common tasks using the **data.table** package in R

Matthew Dowle

Revised: April 20, 2011

(A later revision may be available on the [homepage](#))

* WORK IN PROGRESS *

This document contains a series of tests, followed by a summary table of various timings and comparisons. Please go straight to the summary table first [<here>](#) in which each row has a link back to the test.

This document is reproducible. Simply run the .Rnw file yourself in your environment to confirm the results. Also see `?vignette`, which says that `edit(vignette("datatable-timings"))` will extract the code from this document so you can easily work with it.

The .Rnw included in the package has $N=10,000,000$. This is a small number so that 'R CMD build' completes in a reasonable time (about 5 minutes). We don't want the nightly builds on R-Forge and CRAN to slow down just to run long timing comparisons. We have increased this to $N=100,000,000$ ourselves, and included the output on the [datatable homepage](#) ([<link>](#)).

Contents

1	Timing tests	1
1.1	Extraction	1
1.2	Grouping	2
1.3	Test 3	3
1.4	Test 4	3
1.5	Test 5	3
2	Summary table	3

1 Timing tests

1.1 Extraction

This is a repeat of the test in section 1 of the Introduction vignette. The syntax is explained there. This demonstrates the large difference in speed between vector scans and binary search. Therefore, please avoid using `==` in the `i` expression.

```
> n = ceiling(1e7/26^2) # 10 million rows
> DF = data.frame(x=rep(LETTERS,each=26*n),
+               y=rep(letters,each=n),
+               v=rnorm(n*26^2))
> DT = data.table(DF,key="x,y")
> tables()
```

```
      NAME      NROW MB COLS KEY
[1,] DT    10,000,068 153 x,y,v x,y
Total: 153MB
```

```
> tt=system.time(ans1 <- DF[DF$x=="R" & DF$y=="h",]); tt
```

```

      user  system elapsed
13.009    1.112   14.344

> head(ans1)

      x y      v
6642058 R h -1.2462605
6642059 R h -1.1141423
6642060 R h -0.9684770
6642061 R h -0.5520323
6642062 R h  0.4695192
6642063 R h -1.2885875

> dim(ans1)

[1] 14793      3

> ss=system.time(ans2 <- DT[J("R","h")]); ss

      user  system elapsed
 0.024    0.004    0.028

> head(ans2)

      x y      v
[1,] R h -1.2462605
[2,] R h -1.1141423
[3,] R h -0.9684770
[4,] R h -0.5520323
[5,] R h  0.4695192
[6,] R h -1.2885875

> dim(ans2)

[1] 14793      3

> identical(ans1$v,ans2$v)

[1] TRUE

```

1.2 Grouping

This is a repeat of the test in section 2 of the Introduction vignette. The syntax is explained there.

```

> ttt=system.time(ans1 <- tapply(DF$v,DF$x,sum)); ttt

      user  system elapsed
19.705    1.128   22.370

> head(ans1)

      A      B      C      D      E
164.686217 191.565085 -516.658979  3.905833 -953.843727
      F
225.685019

> sss=system.time(ans2 <- DT[,sum(v),by=x]); sss

      user  system elapsed
 0.452    0.172    0.626

```

```
> head(ans2)

      x      V1
[1,] A 164.686217
[2,] B 191.565085
[3,] C -516.658979
[4,] D   3.905833
[5,] E -953.843727
[6,] F 225.685019

> identical(as.vector(ans1), ans2$V1)

[1] TRUE
```

1.3 Test 3

1.4 Test 4

1.5 Test 5

2 Summary table

```
> ans

      base data.table times faster
==      14.344      0.028      512
tapply 22.370      0.626      35

> toLatex(sessionInfo())

• R version 2.12.1 (2010-12-16), i686-pc-linux-gnu

• Locale: LC_CTYPE=en_GB.utf8, LC_NUMERIC=C, LC_TIME=en_GB.utf8,
  LC_COLLATE=en_GB.utf8, LC_MONETARY=C, LC_MESSAGES=en_GB.utf8,
  LC_PAPER=en_GB.utf8, LC_NAME=C, LC_ADDRESS=C, LC_TELEPHONE=C,
  LC_MEASUREMENT=en_GB.utf8, LC_IDENTIFICATION=C

• Base packages: base, datasets, graphics, grDevices, methods, stats, utils

• Loaded via a namespace (and not attached): tools~2.12.1
```