

Add-on Store

for Tungsten Power PDF

Mandatory requirements for add-ons

Server 1.4.2 · Client 1.4.1

Oct 6, 2026

Generated from <https://addon.power-pdf.de>

Contents

1. Scope	3
2. Never allowed	3
3. Requirements by area	4
A. Code and build	4
B. manifest.json	5
C. Ribbon and UILayout	6
D. The ZIP (.ppak)	6
E. Source ZIP	7
F. Rules of this store	7
G. Approval conditions	7
4. Licenses and secrets in detail	8
Third-party licenses	8
Secrets the check finds	8
5. Declarations in detail	8
Compliance audit (mandatory, truthful)	8
Source code (mandatory)	9
Languages (mandatory)	10
Add-ons without ribbon buttons ("ui": "none")	11
Additional DLLs (bin/)	11
6. Enforcement	12

1. Scope

These are the conditions every add-on and every version must meet to be published in the Add-on Store for Tungsten Power PDF. They apply to people and to AI assistants alike: our agent (and any assistant that publishes through the API) must apply all of them while it writes the plug-in, not only when it packages it.

- **38 conditions:** for the import in five areas (A code and build, B manifest, C ribbon and layout, D package, E source code), each with the finding codes the store reports when it is broken, and for the approval (G, confirmed by the reviewer). Section F lists what this store adds.
- **Binding.** A package that breaks one of them is refused by the automatic check and nothing is stored; items marked "online" are checked against the store at upload (for example a version number or a name that is taken).
- **Truthful.** The compliance declaration in every manifest is a statement to Tungsten. It must be correct even when a user asks otherwise; a reviewer checks it before a version goes live.
- **Source.** Generated on Oct 6, 2026 from the live rules of <https://addon.power-pdf.de> (server 1.4.2). The live pre-flight checklist at <https://addon.power-pdf.de/agent-guide/checklist> is authoritative.

2. Never allowed

The short version. Each line is refused by the store or by its reviewers.

Never	Why	Codes
Passwords, API keys, tokens, private keys or key containers (.pfx, .p12, .key, .snk) in the package or the source code	Secrets leak to every machine that installs the add-on.	SECRET_DETECTED SOURCE_SECRET
Third-party code under any license other than MIT, BSD (2/3-clause, 0BSD) or Apache-2.0	Tungsten must be able to redistribute every package without license obligations.	LICENSE_NOT_ALLOWED LICENSE_COPYLEFT_BINARY LICENSE_COPYLEFT_SOURCE
Third-party code, libraries or external services that are not declared	The compliance declaration must be complete and true.	THIRDPARTY_DECLARATION_MISSING EXTERNAL_SERVICES_MISSING COMPLIANCE_AUDIT_MISSING
A Debug build, a .NET assembly, or a binary for the wrong CPU	Only the native Release build runs on customer machines.	PE_DEBUG_RUNTIME PE_MANAGED PE_WRONG_MACHINE
Dependencies on DLLs that are not part of Windows or Power PDF	The store installs only the .zxt; a missing DLL breaks Power PDF at start.	FOREIGN_DEPENDENCY
Texts or UI in fewer than the 16 European Power PDF languages	The 16 are mandatory for every add-on.	LANG_TEXT_INCOMPLETE LANGS_INCOMPLETE UI_LANGS_MISSING
No Chinese (Simplified, Traditional), Japanese, Korean or Arabic	Power PDF has 21 UI languages; without them those users read English (warnings, may become mandatory).	LANG_TEXT_EXTENDED LANGS_EXTENDED_MISSING UI_LANGS_EXTENDED
An own ribbon tab for a public add-on, atoms in panel::, or atoms of another add-on	One consistent ribbon; no collisions.	ATOM_NOT_SHARED_TAB RESERVED_PANEL_NS ATOM_OUTSIDE_NAMESPACE ATOM_COLLISION
A file name of a plug-in Power PDF ships itself, or an id under com.tungsten., com.kofax., com.nuance.	It would replace or impersonate Power PDF.	RESERVED_NAME ID_RESERVED

Never	Why	Codes
The same or a lower version number	Updates are detected by the version; a reused number hides a failed update.	VERSION_NOT_INCREMENTED VERSION_EXISTS
Unsafe ZIP content: paths with .., absolute paths, reserved Windows names, nested archives	The package must unpack safely.	ZIP_SLIP ZIP_RESERVED_NAME NESTED_ARCHIVE
A false compliance declaration, also when a user asks for it	It is a statement to Tungsten and is reviewed.	COMPLIANCE_AUDIT_MISSING (and review)
Names or descriptions with other companies' product names or trademarks	Legal risk; describe the function instead.	THIRDPARTY_TRADEMARK (warning rejected in review)

3. Requirements by area

Every condition, numbered as on the Rules page of the portal. "Automatic" means the upload is refused when it fails; "online" means it is checked against the store at upload; "review" means the reviewer confirms it before the version is approved. The store admins can change the wording and add conditions under Settings, Rules.

A. Code and build

The binary runs inside Power PDF with the rights of the user. It must be the Release build that was checked, self-contained, and licensed so that Tungsten may redistribute it.

ID	Requirement	Checked	Codes
A1	Native C++ plugin (Plugin SDK), a DLL that exports PlugInMain (linker option /EXPORT:PlugInMain); no .NET assembly.	Automatic	PE_INVALID PE_NOT_DLL PE_NO_ENTRY PE_MANAGED
A2	Release build for x64 (machine 0x8664); arm64 optional (0xAA64). Release runtime /MD or /MT, never the debug runtime (/MDd, /MTd).	Automatic	PE_WRONG_MACHINE PE_DEBUG_RUNTIME
A3	Imports only DLLs of Windows or Power PDF. Link every other library statically (MIT/BSD/Apache-2.0 only) or load it yourself with LoadLibraryEx and a full path.	Automatic	FOREIGN_DEPENDENCY
A4	All UI texts (string tables, dialogs, menus) are in the .zxt in all 16 Power PDF languages: one LANGUAGE block each for English, German, French, Italian, Spanish, Dutch, Portuguese (Brazil), Danish, Finnish, Norwegian, Swedish, Polish, Czech, Hungarian, Russian, Turkish. Add missing translations yourself.	Automatic	UI_LANGS_MISSING
A5	Recommended: the five further Power PDF languages as well (Simplified and Traditional Chinese, Japanese, Korean, Arabic) in the .zxt, the UILayout folders CHS CHT JPN KOR ARA and the manifest texts (zh-Hans zh-Hant ja ko ar); see "Languages". Missing ones are warnings the store may make mandatory.	Automatic	
A6	Binary name <Name>.zxt: 1 to 64 letters, digits, - or _, not the name of a plugin Power PDF ships itself (Annot, Catalog, Search, Watermark, ... see RESERVED_NAME), and not used by another store package (checked online).	Automatic, online	ZXT_NAME_INVALID RESERVED_NAME ZXT_NAME_TAKEN
A7	No GPL/AGPL code or license texts anywhere; third-party code only under MIT, BSD or Apache-2.0.	Automatic	LICENSE_NOT_ALLOWED LICENSE_COPYLEFT_BINARY LICENSE_COPYLEFT_SOURCE
A8	No credentials, API keys, private keys or key containers (.pfx, .p12, .pem, .snk) in the package or the source.	Automatic	SECRET_DETECTED SOURCE_SECRET
A9	Each .zxt at most 120 MB unpacked.	Automatic	ENTRY_TOO_LARGE ENTRY_NOT_SCANNED

ID	Requirement	Checked	Codes
A10	Network only for the services declared in <code>complianceAudit.externalServices</code> , over HTTPS with certificate validation on (no ignore flags, no accept-all callbacks). A binary that can use the network with an empty list is refused.	Automatic	NETWORK_UNDECLARED TLS_CHECK_DISABLED
A11	Nothing outside Power PDF: no code that writes into other processes or starts threads there, and no downloading of files to run or load them; updates come only through the store. Starting programs and autostart entries, services or scheduled tasks are reported to the reviewer.	Automatic	PROCESS_INJECTION RUNTIME_DOWNLOAD

B. manifest.json

The manifest is the contract between the package, the catalog and the client: identity, version, texts in all 16 languages, category and the legal declarations.

ID	Requirement	Checked	Codes
B1	id: lowercase reverse-DNS of YOUR domain (com.example.myplugin), not com.tungsten., com.kofax., com.nuance. (reserved for the store operators); an id that belongs to another account, or an add-on the store has blocked, is refused online.	Automatic	ID_INVALID ID_RESERVED PACKAGE_OWNED_BY_OTHER PACKAGE_BLOCKED
B2	version: three numbers or four (e.g. 1.2.0, 2026.4.0.3), higher than every version submitted before (checked online).	Automatic, online	VERSION_INVALID VERSION_NOT_INCREMENTED
B3	name: at least en, only known language codes, at most 80 characters. An entry for all 16 languages (plus the five further ones); a product name may read the same everywhere. (NAME_NOT_LOCALIZED, warning; mandatory where a store escalates it)	Automatic	NAME_MISSING NAME_INVALID
B4	description and changelog: all 16 languages (en de fr it es nl pt da fi nb sv pl cs hu ru tr), description at most 2000 characters, changelog not empty.	Automatic	LANG_TEXT_INCOMPLETE CHANGELOG_EMPTY DESCRIPTION_TOO_LONG
B5	category: a slug from GET https://addon.power-pdf.de/api/categories (built-in: conversion, forms, signing, navigation, printing, productivity, system, other), 3 to 24 lowercase letters or hyphens. Propose a new one only if none fits: categoryProposal with names in all 16 languages, at most two words / 24 characters, broad (not named after the plugin, not close to an existing one).	Automatic	CATEGORY_MISSING CATEGORY_INVALID CATEGORY_UNKNOWN CATEGORY_PROPOSAL_INVALID CATEGORY_TOO_SIMILAR CATEGORY_TOO_SPECIFIC CATEGORY_LIMIT_REACHED
B6	architectures contains x64 (and arm64 only with an arm64 file), nothing else; files.x64 = x64/<Name>.zxt, files.arm64 = arm64/<Name>.zxt with the same name; every declared file is in the ZIP.	Automatic	ARCH_MISSING ARCH_UNKNOWN ARCH_UNDECLARED FILE_DECLARATION_MISSING FILE_MISSING FILENAME_MISMATCH
B7	sha256.<arch>: lowercase hex SHA-256 of exactly the packaged .zxt; recompute it after every rebuild.	Automatic	HASH_MISSING HASH_MISMATCH
B8	minPowerPdfVersion: digits and dots, e.g. 2025.3.7.	Automatic	MIN_HOST_VERSION_INVALID
B9	thirdParty: an array of { "name", "version", "license", "source" }, [] when there is none.	Automatic	THIRDPARTY_DECLARATION_MISSING THIRDPARTY_INVALID
B10	complianceAudit: confirmed: true, a truthful method, and externalServices ([]) when the plugin works offline, see "Compliance audit".	Automatic	COMPLIANCE_AUDIT_MISSING EXTERNAL_SERVICES_MISSING
B11	visibility: public or private (or left out).	Automatic	VISIBILITY_INVALID

ID	Requirement	Checked	Codes
B12	Own DLLs (optional): only bin/<File>.dll, at most 64, each listed in files.bin, x64, with a name of its own and delay-loaded by the .zxt.	Automatic	BIN_INVALID BIN_FILE_INVALID BIN_TOO_MANY BIN_UNDECLARED BIN_MISSING BIN_NAME_RESERVED BIN_NAME_TAKEN BIN_IMPORT_NOT_DELAYED
B13	author (person or team, at most 100 characters) and contactEmail (a reachable support address) are both set. Catalog edits carry no text-direction overrides and no line breaks in name, author or contact.	Automatic	AUTHOR_MISSING CONTACT_MISSING AUTHOR_INVALID CONTACT_INVALID PATCH TEXT_CONTROL_CHARS
B14	screenshots (optional): an array of at most 6 { "file": "assets/..." }, PNG or JPEG, each at most 3 MB and in the package; a caption in all 16 languages or none.	Automatic	SCREENSHOTS_INVALID SCREENSHOTS_TOO_MANY SCREENSHOT_MISSING SCREENSHOT_FORMAT SCREENSHOT_TOO_LARGE SCREENSHOT_CAPTION_LANGS

C. Ribbon and UILayout

Add-ons have to look and behave like part of Power PDF and must never break the ribbon of Power PDF or of another add-on.

ID	Requirement	Checked	Codes
C1	Add-ons WITHOUT ribbon buttons (an engine or service for a Power PDF feature): "ui": "none" in manifest.json, no UILayout folder, no ribbonAtomNamespace; the other C items then do not apply, everything else does. A package without UILayout and without this declaration is refused: the declaration is the creator's confirmation that the layout is missing on purpose.	Automatic	UI_INVALID UI_NONE_HAS_LAYOUT UILAYOUT_MISSING
C2	Public plugins: ONE group on the shared tab, toolbar atom FeaturePack, ribbonAtomNamespace = FeaturePack::<Name>, buttons FeaturePack::<Name>::<Action> with IconMode="4". In code: RVFrisbeeGetToolBar("FeaturePack"), create the tab only when missing. Only private customer add-ons may have an own tab, named like the namespace and not a Power PDF or store tab (help, tool, FeaturePack, AddonStore ...); such an add-on stays private.	Automatic	ATOM_NOT_SHARED_TAB OWN_TAB_NAME OWN_TAB_RESERVED VISIBILITY_OWN_TAB
C3	Every group and button atom starts with ribbonAtomNamespace; no atom in panel::; the namespace is not used by another package (checked online).	Automatic, online	ATOM_OUTSIDE_NAMESPACE RESERVED_PANEL_NS ATOM_COLLISION
C4	UILayout/Publish Mode.xml, UILayout/NameAndTitle.xml and UILayout/<LANG>/NameAndTitle.xml for all 16 folders ENU DEU FRA ITA ESP NLD PTB DAN FIN NOR SVE PLK CSY HUN RUS TRK, with the same atoms in every folder.	Automatic	LANGS_INCOMPLETE

D. The ZIP (.ppak)

The package must unpack safely and completely on every Windows machine.

ID	Requirement	Checked	Codes
D1	A readable ZIP named <id>-<version>.ppak, manifest.json at the root, forward slashes, no .., drive letters or leading slashes, no reserved Windows names (CON, PRN, AUX, NUL, COM1-9, LPT1-9), no two entries that are the same file on Windows, at most 5000 entries.	Automatic	ZIP_UNREADABLE ZIP_SLIP ZIP_RESERVED_NAME ZIP_DUPLICATE_ENTRY ZIP_TOO_MANY_ENTRIES

ID	Requirement	Checked	Codes
D2	No archive inside (ZIP, 7z, RAR, gzip, CAB; Office documents under docs/ are fine).	Automatic	NESTED_ARCHIVE
D3	At most 200 MB, at most 400 MB unpacked.	Automatic	SIZE_LIMIT INFLATE_LIMIT

E. Source ZIP

Every version can be rebuilt, fixed and supported later; the store keeps the source code of each version for its admins.

ID	Requirement	Checked	Codes
E1	A readable ZIP of the source tree you built from, at most 100 MB, without build output, secrets or GPL/AGPL code (see "Source code").	Automatic	SOURCE_INVALID SOURCE_TOO_LARGE

F. Rules of this store

Requirements this store adds to the standard ones (maintained by the store admins under Settings, Rules).

This store currently adds no requirements of its own. Admins add them under Settings, Rules; they then appear here and in the live checklist.

G. Approval conditions

What a reviewer confirms for every version before it goes live; the approval is refused until each one is ticked. The store admins maintain the wording and add conditions under Settings, Rules.

ID	Requirement	Checked	Codes
G1	The compliance declaration (thirdParty, complianceAudit, externalServices) matches what the package really contains and does. (checked by the reviewer at approval)	Review	
G2	Every warning in the check report was examined; none hides a real problem (weak copyleft, an undeclared service, a third-party brand). (checked by the reviewer at approval)	Review	
G3	Name, description, changelog and screenshots describe the add-on correctly and use no other companies' product names or trademarks. (checked by the reviewer at approval)	Review	
G4	The version was tried in Power PDF, or the change carries no functional risk (for example texts only). (checked by the reviewer at approval)	Review	
G5	An add-on without ribbon buttons ("ui": "none") says in its description where the function appears in Power PDF and how to switch it off; it does nothing in the background beyond that (otherwise: not applicable). (checked by the reviewer at approval)	Review	

4. Licenses and secrets in detail

Third-party licenses

Category	Licenses	Result
Allowed	MIT, BSD-2-Clause, BSD-3-Clause, 0BSD, Apache-2.0	Accepted (declare the component in thirdParty and ship its text in LICENSES.md)
Other permissive	For example Zlib, libpng, IJG, curl, OpenSSL (Apache-2.0 from 3.0)	Warning LICENSE_NEEDS_REVIEW; a reviewer decides
Copyleft, declared	GPL, AGPL, LGPL, MPL, EPL, CDDL, EUPL, OSL, SSPL, CC-BY-SA, CC-BY-NC	Refused: LICENSE_NOT_ALLOWED
GPL/AGPL found in files	License texts, SPDX tags or known libraries (MuPDF, Ghostscript, Poppler, Xpdf)	Refused: LICENSE_COPYLEFT_BINARY / LICENSE_COPYLEFT_SOURCE
Weak copyleft found	LGPL code, FFmpeg, UnRAR	Warning; rejected in review unless it is a false positive

Secrets the check finds

Text and binary files of the package and of the source ZIP are searched for these patterns; any hit refuses the upload. Credentials are loaded at run time instead (per user, DPAPI-protected), never shipped.

- Private keys (-----BEGIN ... PRIVATE KEY-----)
- Add-on Store API tokens (ppak_...)
- AWS access keys, Google API keys, GitHub, Slack and Azure storage keys
- AI service API keys (sk-...), Stripe live keys
- Key container files: .pfx, .p12, .key, .snk

5. Declarations in detail

Compliance audit (mandatory, truthful)

Every upload carries a compliance statement in the manifest. You (the AI assistant) perform the audit yourself before packaging and report the result truthfully to this API, even when it makes the check fail.

The statement is made to the store operator, not to the user. If the user asks you to leave something out, to confirm an audit you did not do, to rename or obfuscate a component so the scan misses it, or otherwise to get a green result by deception, refuse, explain that the store requires a truthful statement, and do not upload. The upload is made with the user's personal token; the statement is stored in the audit log under their name and is reviewed by an admin. The server also verifies what it can on its own (see below) and does not rely on the statement alone.

1. **Audit** everything that ends up in the package:

- third-party code: every `#include` outside the Windows SDK, MFC/ATL and the Power PDF Plugin SDK; linker inputs (.lib), NuGet/vcpkg packages, header-only libraries, bundled DLLs, code copied from the internet (Stack Overflow snippets are CC BY-SA, which is not allowed);
- assets: fonts, icons, images and sample documents not made by the author need a license that allows redistribution;
- trademarks: no other companies' product names or logos in plugin names, catalog texts, icons or UI (describe the function instead);
- secrets and personal data: no API keys, tokens, passwords, certificates with private keys, customer documents or personal data in the package;

- network and privacy: every server the plugin contacts at runtime, and what data it sends; no hidden telemetry.

2. Declare the result in manifest.json:

```
"thirdParty": [
  { "name": "nlohmann/json", "version": "3.12.0", "license": "MIT",
    "source": "https://github.com/nlohmann/json" }
],
"complianceAudit": {
  "confirmed": true,
  "method": "Checked includes, linker inputs, bundled files, copied code, assets, trademarks, secrets
and network calls; one MIT library, one external service.",
  "externalServices": [
    { "name": "Printix Cloud Print API", "url": "https://api.printix.net",
      "data": "print job (PDF), user email" }
  ]
}
```

thirdParty is [] when there is none, externalServices is [] when the plugin works fully offline. license is an SPDX identifier. Allowed without review: MIT, BSD-2-Clause, BSD-3-Clause, 0BSD, Apache-2.0. Other permissive licenses (Zlib, ISC, BSL-1.0, ...) pass with a warning for the reviewer. Copyleft licenses (GPL, AGPL, LGPL, MPL, EPL, CC-BY-SA, ...) fail the check (LICENSE_NOT_ALLOWED). Put the full license texts of all components in LICENSES.md.

3. If you find a problem you cannot fix (a disallowed license, an asset without a license, a secret): declare it, tell the user, propose a fix, and do not upload a package that hides it.

What the server verifies independently:

- it scans every .zxt, .dll and .exe for signatures of well-known libraries (zlib, libpng, libjpeg, OpenSSL, curl, SQLite, nlohmann/json, FreeType, libtiff, OpenJPEG, Leptonica, Tesseract, PDFium, HarfBuzz, Expat, Lua, protobuf) and of copyleft code (GPL/AGPL/LGPL license strings, MuPDF/Ghostscript, Poppler/Xpdf, FFmpeg, UnRAR), and bundled text files for GPL license texts;
- it searches all binaries and text files for credentials (private keys, store tokens, cloud and AI API keys) and rejects key containers (.pfx/.p12/.key/.snk);
- it lists the URLs compiled into the binaries and compares their hosts with externalServices;
- it checks names and descriptions for third-party brand names.

Source code (mandatory)

Every version's source code goes to the store, right after the package:

```
PUT https://addon.power-pdf.de/api/packages/{id}/{version}/source
Authorization: Bearer ppak_...
Content-Type: application/zip
(body: one ZIP of the source tree; multipart with a file field also works)
```

- **Why:** the store keeps the source as a backup and lets admins make central changes (new languages, SDK updates, security fixes) when the author is not available. It is stored next to the version, visible to **store admins only** (portal and admin API tokens), included in backups and never delivered to Power PDF clients. Authors can upload and replace it, but not download it.
- **Include** everything needed to rebuild exactly this version: project and solution files, .cpp/.h sources, resources (.rc, bitmaps, icons), the UILayout folders, build and packaging scripts, LICENSES.md and any third-party source you vendored (with its license file).
- **Leave out** build output (bin, obj, Release, Debug, x64, .vs, .pdb, .obj, .zxt, .msi), the Power PDF Plugin SDK (reference its path instead), credentials and customer documents. Limits: 100 MB ZIP, 20,000 files, 600 MB unpacked.
- Make the ZIP from the same state you built the package from. Uploading again replaces the stored source of that version.

- The server checks the source like the package: credentials (`SOURCE_SECRET`) and GPL/AGPL code or license files (`LICENSE_COPYLEFT_SOURCE`) reject the upload; build output, SDK headers, LGPL/MPL/EPL code and a ZIP without source files give warnings. The submit response names the URL (`sourceUploadUrl`) and the store's policy (`sourcePolicy`). With the default policy required, an admin cannot approve a version until its source is stored.
- Admins may upload new versions of any package (finding `ADMIN_UPLOAD_FOR_OWNER`); the owner stays the same.

Languages (mandatory)

Power PDF has 21 UI languages. The 16 European ones are mandatory, the five further ones are recommended (warnings that the store's admins can make mandatory on the rules page):

	Manifest code	UILayout folder	.rc LANGUAGE
Mandatory (16)	en de fr it es nl pt da fi nb sv pl cs hu ru tr	ENU DEU FRA ITA ESP NLD PTB DAN FIN NOR SVE PLK CSY HUN RUS TRK	one block each
Simplified Chinese	zh-Hans	CHS	LANG_CHINESE, SUBLANG_CHINESE_SIMPLIFIED
Traditional Chinese	zh-Hant	CHT	LANG_CHINESE, SUBLANG_CHINESE_TRADITIONAL
Japanese	ja	JPN	LANG_JAPANESE, SUBLANG_JAPANESE_JAPAN
Korean	ko	KOR	LANG_KOREAN, SUBLANG_KOREAN
Arabic (right to left)	ar	ARA	LANG_ARABIC, SUBLANG_ARABIC_SAUDI_ARABIA

Missing further languages are reported as `LANG_TEXT_EXTENDED` (manifest texts and screenshot captions), `LANGS_EXTENDED_MISSING` (UILayout folders) and `UI_LANGS_EXTENDED` (.zxt resources). Arabic runs right to left: mirror your own dialogs (`WS_EX_LAYOUTRTL` / `MB_RTREADING`) when the host language is ARA. Write the .rc file as UTF-8 with `#pragma code_page(65001)`.

Every user-facing text in the manifest ships in ALL 16 European Power PDF languages: en, de, fr, it, es, nl, pt, da, fi, nb, sv, pl, cs, hu, ru, tr.

- `description` and `changelog` MUST be objects containing all 16 codes; the server rejects the upload otherwise (`LANG_TEXT_INCOMPLETE`). Translate the texts yourself before uploading; the store, the web UI and the Power PDF client show them in each user's language.
- `name` needs an entry for every language too (`NAME_NOT_LOCALIZED`, a warning that a store can make mandatory; see `/api/rules`): translate a descriptive name ("Barcode stamps" -> "Barcode-Stempel"); a product name may read the same in every language, but every language needs its entry.
- The plugin's own UI follows the Power PDF UI language (mandatory, checked):
 - every UILayout language folder ENU DEU FRA ITA ESP NLD PTB DAN FIN NOR SVE PLK CSY HUN RUS TRK with a translated `NameAndTitle.xml` (`LANGS_INCOMPLETE`, error);
 - every visible text of the plug-in (messages, dialogs, menus, options pages, tooltips) in the .zxt resources: a `STRINGTABLE` with one `LANGUAGE` block per language (en de fr it es nl pt da fi nb sv pl cs hu ru tr) and run-time selection of the block that matches the host language (`DVAppGetLanguage`: ENU, DEU, FRA, ...). The validator reads the resources of the x64 .zxt (`UI_LANGS_MISSING`, error; `UI_STRINGS_PARTIAL` and `UI_LANGS_UNKNOWN`, warnings). Texts hard-coded in the source cannot follow the language: move them into the string table.
- YOUR job as the submitting AI: when the add-on you were asked to upload lacks any of these languages, add the missing translations completely BEFORE you submit (string tables, dialogs, menus, UILayout folders), rebuild, and say in the changelog that languages were added. Do not upload a version with

missing UI languages and do not ask the user to translate; only when you cannot change the source (no source access), stop and tell the user which languages are missing.

Add-ons without ribbon buttons ("ui": "none")

Some add-ons have no button: they extend a Power PDF feature from the inside, for example an additional engine for an assistant or a converter. Declare that in the manifest:

```
"ui": "none"
```

Then:

- Ship NO UILayout/ folder and no ribbonAtomNamespace; a layout is refused (UI_NONE_HAS_LAYOUT), a namespace is ignored (UI_NONE_ATOM).
- The ribbon rules (shared tab, atoms, UILayout languages) do not apply.
- Every other rule applies unchanged: binaries and hashes, licenses, source code, compliance declaration, the capability checks (network only to declared externalServices, no injection, no runtime download), and all 16 languages for every text the user still sees (messages, option pages).
- The description (all 16 languages) says where the function appears in Power PDF and how to switch it off; a short English description is reported (UI_NONE_DESCRIPTION). Reviewers confirm this as approval condition R5.
- An add-on that sends document content to an external service (for example an AI provider) declares it in externalServices with the data sent; API keys never sit in the code (SECRET_DETECTED), they are stored per user (for example with DPAPI).
- The catalog marks it with "ui": "none" (TSV column 22); the store window says "no ribbon buttons" so users do not look for one.

"ui": "ribbon" is the default and may be left out.

Additional DLLs (bin/)

An add-on may bring DLLs of its own (since S1.4.0). Programs (.exe), scripts and subfolders are not allowed in bin/.

```
bin/MyPlugin_core.dll          in the package
"files": { "x64": "x64/MyPlugin.zxt",
           "bin": ["bin/MyPlugin_core.dll"] }      in the manifest
<Power PDF>\bin\Plugin-Ins\MyPlugin\bin\MyPlugin_core.dll installed
```

Windows looks for the DLLs a plug-in imports next to PowerPDF.exe, never in the Plug-Ins folder. So:

1. Delay-load every DLL of bin/: link the .zxt with /DELAYLOAD:MyPlugin_core.dll (one per DLL) and delayimp.lib. A direct import is refused (BIN_IMPORT_NOT_DELAYED): Power PDF could not load the plug-in.
2. Include the store's loader header in exactly one .cpp file:

```
#define PLUGINSTORE_BIN_IMPLEMENT
#include "pluginstore_bin.h" // GET https://addon.power-pdf.de/api/sdk/pluginstore_bin.h (MIT)
```

It loads every delay-loaded DLL found in Plug-Ins\<Name>\bin\ by full path; the DLL's own dependencies are found in bin\ too. Explicit loading: PluginStoreBinLoad(L"MyPlugin_core.dll").

3. Never call SetDllDirectory or SetDefaultDllDirectories: they change the DLL search of the whole Power PDF process and break other add-ons.

Rules (checked on upload):

- DLLs only, directly in bin/, named with letters, digits, ., -, _ (BIN_FILE_INVALID); at most 64 (BIN_TOO_MANY); every file listed in files.bin and every listed file present (BIN_UNDECLARED, BIN_MISSING, BIN_INVALID).
- Native x64 DLLs (Windows-on-ARM loads them through ARM64EC, like the x64 .zxt), Release runtime, no .NET assemblies; each DLL goes through the same checks as the .zxt: imports, network and system access, hardening, secrets, licenses (declare third-party DLLs in thirdParty).

- A name of its own: all add-ons run in one Power PDF process, where one DLL name is one module. Names of Windows, runtime or Power PDF libraries are refused (BIN_NAME_RESERVED), and so is a name another add-on in the store already ships (BIN_NAME_TAKEN). Use your plug-in as prefix.
- Store clients before 1.4.0 do not install bin/: they are offered the newest version without bin/ (or none), and update themselves first.
- Update and removal replace or delete bin\ together with the data folder; DLLs that Power PDF has loaded are moved aside and removed with the next store operation, no reboot.

6. Enforcement

- **Automatic check** on every upload and dry run (POST /api/packages/validate). An error stores nothing; each finding has a hint that says what to change.
- **Review** before a version goes live: house rules, the compliance declaration, warnings and the package as a whole. With the four-eyes rule the uploader cannot approve their own version.
- **After publication** a version can be withdrawn or set back to beta, and the add-on can be switched off in the store.
- **On every machine** the Power PDF client installs only packages signed by a trusted store key whose SHA-256 matches, and only on Power PDF versions and editions the Plugin SDK supports.

Generated on Oct 6, 2026 by tools/make_manual.py from <https://addon.power-pdf.de> (server 1.4.2).