

# Add-on Store

for Tungsten Power PDF

## Mandatory requirements for add-ons

Server 1.15.0 · Client 1.9.4

Oct 9, 2026

Generated from <https://addon.power-pdf.de>

# Contents

|                                                         |           |
|---------------------------------------------------------|-----------|
| <b>1. Scope</b>                                         | <b>3</b>  |
| <b>2. Never allowed</b>                                 | <b>3</b>  |
| <b>3. Requirements by area</b>                          | <b>4</b>  |
| A. Code and build . . . . .                             | 4         |
| B. manifest.json . . . . .                              | 5         |
| C. Ribbon and UILayout . . . . .                        | 6         |
| D. The ZIP (.ppak) . . . . .                            | 7         |
| E. Source ZIP . . . . .                                 | 7         |
| F. Rules of this store . . . . .                        | 7         |
| G. Approval conditions . . . . .                        | 7         |
| <b>4. Licenses and secrets in detail</b>                | <b>8</b>  |
| Third-party licenses . . . . .                          | 8         |
| Secrets the check finds . . . . .                       | 8         |
| <b>5. Declarations in detail</b>                        | <b>8</b>  |
| Compliance audit (mandatory, truthful) . . . . .        | 8         |
| Source code (mandatory) . . . . .                       | 9         |
| Languages (mandatory) . . . . .                         | 10        |
| Add-ons without ribbon buttons ("ui": "none") . . . . . | 11        |
| Additional DLLs (bin/) . . . . .                        | 11        |
| <b>6. Enforcement</b>                                   | <b>12</b> |

# 1. Scope

These are the conditions every add-on and every version must meet to be published in the Add-on Store for Tungsten Power PDF. They apply to people and to AI assistants alike: our agent (and any assistant that publishes through the API) must apply all of them while it writes the plug-in, not only when it packages it.

- **39 conditions:** for the import in five areas (A code and build, B manifest, C ribbon and layout, D package, E source code), each with the finding codes the store reports when it is broken, and for the approval (G, confirmed by the reviewer). Section F lists what this store adds.
- **Binding.** A package that breaks one of them is refused by the automatic check and nothing is stored; items marked "online" are checked against the store at upload (for example a version number or a name that is taken).
- **Truthful.** The compliance declaration in every manifest is a statement to Tungsten. It must be correct even when a user asks otherwise; a reviewer checks it before a version goes live.
- **Source.** Generated on Oct 9, 2026 from the live rules of <https://addon.power-pdf.de> (server 1.15.0). The live pre-flight checklist at <https://addon.power-pdf.de/agent-guide/checklist> is authoritative.

# 2. Never allowed

The short version. Each line is refused by the store or by its reviewers.

| Never                                                                                                                  | Why                                                                                                    | Codes                                                                                   |
|------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|
| Passwords, API keys, tokens, private keys or key containers (.pfx, .p12, .key, .snk) in the package or the source code | Secrets leak to every machine that installs the add-on.                                                | SECRET_DETECTED<br>SOURCE_SECRET                                                        |
| Third-party code under any license other than MIT, BSD (2/3-clause, 0BSD) or Apache-2.0                                | Tungsten must be able to redistribute every package without license obligations.                       | LICENSE_NOT_ALLOWED<br>LICENSE_COPYLEFT_BINARY<br>LICENSE_COPYLEFT_SOURCE               |
| Third-party code, libraries or external services that are not declared                                                 | The compliance declaration must be complete and true.                                                  | THIRDPARTY_DECLARATION_MISSING<br>EXTERNAL_SERVICES_MISSING<br>COMPLIANCE_AUDIT_MISSING |
| A Debug build, a .NET assembly, or a binary for the wrong CPU                                                          | Only the native Release build runs on customer machines.                                               | PE_DEBUG_RUNTIME<br>PE_MANAGED<br>PE_WRONG_MACHINE                                      |
| Dependencies on DLLs that are not part of Windows or Power PDF                                                         | The store installs only the .zxt; a missing DLL breaks Power PDF at start.                             | FOREIGN_DEPENDENCY                                                                      |
| Texts or UI in fewer than the 16 European Power PDF languages                                                          | The 16 are mandatory for every add-on.                                                                 | LANG_TEXT_INCOMPLETE<br>LANGS_INCOMPLETE<br>UI_LANGS_MISSING                            |
| No Chinese (Simplified, Traditional), Japanese, Korean or Arabic                                                       | Power PDF has 21 UI languages; without them those users read English (warnings, may become mandatory). | LANG_TEXT_EXTENDED<br>LANGS_EXTENDED_MISSING<br>UI_LANGS_EXTENDED                       |
| An own ribbon tab for a public add-on, atoms in panel::, or atoms of another add-on                                    | One consistent ribbon; no collisions.                                                                  | ATOM_NOT_SHARED_TAB<br>RESERVED_PANEL_NS<br>ATOM_OUTSIDE_NAMESPACE<br>ATOM_COLLISION    |
| A file name of a plug-in Power PDF ships itself, or an id under com.tungsten., com.kofax., com.nuance.                 | It would replace or impersonate Power PDF.                                                             | RESERVED_NAME<br>ID_RESERVED                                                            |

| Never                                                                                      | Why                                                                         | Codes                                             |
|--------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|---------------------------------------------------|
| The same or a lower version number                                                         | Updates are detected by the version; a reused number hides a failed update. | VERSION_NOT_INCREMENTED<br>VERSION_EXISTS         |
| Unsafe ZIP content: paths with .., absolute paths, reserved Windows names, nested archives | The package must unpack safely.                                             | ZIP_SLIP<br>ZIP_RESERVED_NAME<br>NESTED_ARCHIVE   |
| A false compliance declaration, also when a user asks for it                               | It is a statement to Tungsten and is reviewed.                              | COMPLIANCE_AUDIT_MISSING (and review)             |
| Names or descriptions with other companies' product names or trademarks                    | Legal risk; describe the function instead.                                  | THIRDPARTY_TRADEMARK (warning rejected in review) |

## 3. Requirements by area

Every condition, numbered as on the Rules page of the portal. "Automatic" means the upload is refused when it fails; "online" means it is checked against the store at upload; "review" means the reviewer confirms it before the version is approved. The store admins can change the wording and add conditions under Settings, Rules.

### A. Code and build

The binary runs inside Power PDF with the rights of the user. It must be the Release build that was checked, self-contained, and licensed so that Tungsten may redistribute it.

| ID | Requirement                                                                                                                                                                                                                                                                                                                 | Checked           | Codes                                                                     |
|----|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|---------------------------------------------------------------------------|
| A1 | Native C++ plugin (Plugin SDK), a DLL that exports PlugInMain (linker option /EXPORT:PlugInMain); no .NET assembly.                                                                                                                                                                                                         | Automatic         | PE_INVALID<br>PE_NOT_DLL<br>PE_NO_ENTRY<br>PE_MANAGED                     |
| A2 | Release build for x64 (machine 0x8664); arm64 optional (0xAA64). Release runtime /MD or /MT, never the debug runtime (/MDd, /MTd).                                                                                                                                                                                          | Automatic         | PE_WRONG_MACHINE<br>PE_DEBUG_RUNTIME                                      |
| A3 | Imports only DLLs of Windows or Power PDF. Link every other library statically (MIT/BSD/Apache-2.0 only) or load it yourself with LoadLibraryEx and a full path.                                                                                                                                                            | Automatic         | FOREIGN_DEPENDENCY                                                        |
| A4 | All UI texts (string tables, dialogs, menus) are in the .zxt in all 16 European Power PDF languages: one LANGUAGE block each for English, German, French, Italian, Spanish, Dutch, Portuguese (Brazil), Danish, Finnish, Norwegian, Swedish, Polish, Czech, Hungarian, Russian, Turkish. Add missing translations yourself. | Automatic         | UI_LANGS_MISSING                                                          |
| A5 | The five further Power PDF languages as well, so all 21 are covered: Simplified and Traditional Chinese, Japanese, Korean and Arabic in the .zxt (LANGUAGE blocks LANG_CHINESE/SUBLANG_CHINESE_SIMPLIFIED, LANG_CHINESE/SUBLANG_CHINESE_TRADITIONAL, LANG_JAPANESE, LANG_KOREAN, LANG_ARABIC); see "Languages".             | Automatic         | UI_LANGS_EXTENDED                                                         |
| A6 | Binary name <Name>.zxt: 1 to 64 letters, digits, - or _, not the name of a plugin Power PDF ships itself (Annot, Catalog, Search, Watermark, ... see RESERVED_NAME), and not used by another store package (checked online).                                                                                                | Automatic, online | ZXT_NAME_INVALID<br>RESERVED_NAME<br>ZXT_NAME_TAKEN                       |
| A7 | No GPL/AGPL code or license texts anywhere; third-party code only under MIT, BSD or Apache-2.0.                                                                                                                                                                                                                             | Automatic         | LICENSE_NOT_ALLOWED<br>LICENSE_COPYLEFT_BINARY<br>LICENSE_COPYLEFT_SOURCE |
| A8 | No credentials, API keys, private keys or key containers (.pfx, .p12, .pem, .snk) in the package or the source.                                                                                                                                                                                                             | Automatic         | SECRET_DETECTED<br>SOURCE_SECRET                                          |

| ID  | Requirement                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Checked   | Codes                                    |
|-----|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|------------------------------------------|
| A9  | Each .zxt at most 120 MB unpacked.                                                                                                                                                                                                                                                                                                                                                                                                                              | Automatic | ENTRY_TOO_LARGE<br>ENTRY_NOT_SCANNED     |
| A10 | Network only for the services declared in <code>complianceAudit.externalServices</code> , over HTTPS with certificate validation on (no ignore flags, no accept-all callbacks). A binary that can use the network with an empty list is refused.                                                                                                                                                                                                                | Automatic | NETWORK_UNDECLARED<br>TLS_CHECK_DISABLED |
| A11 | Nothing outside Power PDF: no code that writes into other processes or starts threads there, and no downloading of files to run or load them; updates come only through the store. Starting programs and autostart entries, services or scheduled tasks are reported to the reviewer.                                                                                                                                                                           | Automatic | PROCESS_INJECTION<br>RUNTIME_DOWNLOAD    |
| A12 | No administrator rights without a declaration: code that starts a program elevated (ShellExecute or ShellExecuteEx with the <code>runas</code> verb) needs <code>"elevation": {"reason": "..."} in manifest.json</code> , 20 to 500 characters on what runs elevated, when and why; otherwise remove the code. Start the program you need directly, not through <code>cmd.exe</code> , PowerShell or another script host; the reviewer is told about such code. | Automatic | ELEVATION_UNDECLARED<br>COMMAND_SHELL    |

## B. manifest.json

The manifest is the contract between the package, the catalog and the client: identity, version, texts in all 16 languages, category and the legal declarations.

| ID | Requirement                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Checked           | Codes                                                                                                                                                            |
|----|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| B1 | id: lowercase reverse-DNS of YOUR domain ( <code>com.example.myplugin</code> ), not <code>com.tungsten.</code> , <code>com.kofax.</code> , <code>com.nuance.</code> (reserved for the store operators); an id that belongs to another account, or an add-on the store has blocked, is refused online.                                                                                                                                                                | Automatic         | ID_INVALID<br>ID_RESERVED<br>PACKAGE_OWNED_BY_OTHER<br>PACKAGE_BLOCKED                                                                                           |
| B2 | version: three numbers or four (e.g. 1.2.0, 2026.4.0.3), higher than every version submitted before (checked online).                                                                                                                                                                                                                                                                                                                                                | Automatic, online | VERSION_INVALID<br>VERSION_NOT_INCREMENTED                                                                                                                       |
| B3 | name: at least en, only known language codes, at most 80 characters. An entry for all 21 languages; a product name may read the same everywhere.                                                                                                                                                                                                                                                                                                                     | Automatic         | NAME_MISSING<br>NAME_INVALID<br>NAME_NOT_LOCALIZED<br>LANG_TEXT_EXTENDED                                                                                         |
| B4 | description and changelog: all 21 languages (en de fr it es nl pt da fi nb sv pl cs hu ru tr zh-Hans zh-Hant ja ko ar), description at most 2000 characters, changelog not empty.                                                                                                                                                                                                                                                                                    | Automatic         | LANG_TEXT_INCOMPLETE<br>LANG_TEXT_EXTENDED<br>CHANGELOG_EMPTY<br>DESCRIPTION_TOO_LONG                                                                            |
| B5 | category: a slug from GET <a href="https://addon.power-pdf.de/api/categories">https://addon.power-pdf.de/api/categories</a> (built-in: conversion, forms, signing, navigation, printing, productivity, system, other), 3 to 24 lowercase letters or hyphens. Propose a new one only if none fits: <code>categoryProposal</code> with names in all 16 languages, at most two words / 24 characters, broad (not named after the plugin, not close to an existing one). | Automatic         | CATEGORY_MISSING<br>CATEGORY_INVALID<br>CATEGORY_UNKNOWN<br>CATEGORY_PROPOSAL_INVALID<br>CATEGORY_TOO_SIMILAR<br>CATEGORY_TOO_SPECIFIC<br>CATEGORY_LIMIT_REACHED |
| B6 | architectures contains x64 (and arm64 only with an arm64 file), nothing else; <code>files.x64 = x64/&lt;Name&gt;.zxt</code> , <code>files.arm64 = arm64/&lt;Name&gt;.zxt</code> with the same name; every declared file is in the ZIP.                                                                                                                                                                                                                               | Automatic         | ARCH_MISSING<br>ARCH_UNKNOWN<br>ARCH_UNDECLARED<br>FILE_DECLARATION_MISSING<br>FILE_MISSING<br>FILENAME_MISMATCH                                                 |
| B7 | <code>sha256.&lt;arch&gt;</code> : lowercase hex SHA-256 of exactly the packaged .zxt; recompute it after every rebuild.                                                                                                                                                                                                                                                                                                                                             | Automatic         | HASH_MISSING<br>HASH_MISMATCH                                                                                                                                    |
| B8 | <code>minPowerPdfVersion</code> : digits and dots, e.g. 2025.3.7.                                                                                                                                                                                                                                                                                                                                                                                                    | Automatic         | MIN_HOST_VERSION_INVALID                                                                                                                                         |
| B9 | <code>thirdParty</code> : an array of { "name", "version", "license", "source" }, [ ] when there is none.                                                                                                                                                                                                                                                                                                                                                            | Automatic         | THIRDPARTY_DECLARATION_MISSING<br>THIRDPARTY_INVALID                                                                                                             |

| ID  | Requirement                                                                                                                                                                                                 | Checked   | Codes                                                                                                                                                            |
|-----|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| B10 | complianceAudit: confirmed: true, a truthful method, and externalServices ([ ] when the plugin works offline), see "Compliance audit".                                                                      | Automatic | COMPLIANCE_AUDIT_MISSING<br>EXTERNAL_SERVICES_MISSING                                                                                                            |
| B11 | visibility: public or private (or left out).                                                                                                                                                                | Automatic | VISIBILITY_INVALID                                                                                                                                               |
| B12 | Own DLLs (optional): only bin/<File>.dll, at most 64, each listed in files.bin, x64, with a name of its own and delay-loaded by the .zxt.                                                                   | Automatic | BIN_INVALID<br>BIN_FILE_INVALID<br>BIN_TOO_MANY<br>BIN_UNDECLARED<br>BIN_MISSING<br>BIN_NAME_RESERVED<br>BIN_NAME_TAKEN<br>BIN_IMPORT_NOT_DELAYED                |
| B13 | author (person or team, at most 100 characters) and contactEmail (a reachable support address) are both set. Catalog edits carry no text-direction overrides and no line breaks in name, author or contact. | Automatic | AUTHOR_MISSING<br>CONTACT_MISSING<br>AUTHOR_INVALID<br>CONTACT_INVALID<br>PATCH<br>TEXT_CONTROL_CHARS                                                            |
| B14 | screenshots (optional): an array of at most 6 { "file": "assets/..." }, PNG or JPEG, each at most 3 MB and in the package; a caption in all 21 languages or none.                                           | Automatic | SCREENSHOTS_INVALID<br>SCREENSHOTS_TOO_MANY<br>SCREENSHOT_MISSING<br>SCREENSHOT_FORMAT<br>SCREENSHOT_TOO_LARGE<br>SCREENSHOT_CAPTION_LANGS<br>LANG_TEXT_EXTENDED |

## C. Ribbon and UILayout

Add-ons have to look and behave like part of Power PDF and must never break the ribbon of Power PDF or of another add-on.

| ID | Requirement                                                                                                                                                                                                                                                                                                                                                                                                                                     | Checked           | Codes                                                                         |
|----|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|-------------------------------------------------------------------------------|
| C1 | Add-ons WITHOUT ribbon buttons (an engine or service for a Power PDF feature): "ui": "none" in manifest.json, no UILayout folder, no ribbonAtomNamespace; the other C items then do not apply, everything else does. A package without UILayout and without this declaration is refused: the declaration is the creator's confirmation that the layout is missing on purpose.                                                                   | Automatic         | UI_INVALID<br>UI_NONE_HAS_LAYOUT<br>UILayout_MISSING                          |
| C2 | Public plugins: ONE group on the shared tab, toolbar atom FeaturePack, ribbonAtomNamespace = FeaturePack::<Name>, buttons FeaturePack::<Name>::<Action> with IconMode="4". In code: RVFrisbeeGetToolBar("FeaturePack"), create the tab only when missing. Only private customer add-ons may have an own tab, named like the namespace and not a Power PDF or store tab (help, tool, FeaturePack, AddonStore ...); such an add-on stays private. | Automatic         | ATOM_NOT_SHARED_TAB<br>OWN_TAB_NAME<br>OWN_TAB_RESERVED<br>VISIBILITY_OWN_TAB |
| C3 | Every group and button atom starts with ribbonAtomNamespace; no atom in panel::; the namespace is not used by another package (checked online).                                                                                                                                                                                                                                                                                                 | Automatic, online | ATOM_OUTSIDE_NAMESPACE<br>RESERVED_PANEL_NS<br>ATOM_COLLISION                 |
| C4 | UILayout/Publish Mode.xml, UILayout/NameAndTitle.xml and UILayout/<LANG>/NameAndTitle.xml for all 21 folders ENU DEU FRA ITA ESP NLD PTB DAN FIN NOR SVE PLK CSY HUN RUS TRK CHS CHT JPN KOR ARA, with the same atoms in every folder.                                                                                                                                                                                                          | Automatic         | LANGS_INCOMPLETE<br>LANGS_EXTENDED_MISSING                                    |

## D. The ZIP (.ppak)

The package must unpack safely and completely on every Windows machine.

| ID | Requirement                                                                                                                                                                                                                                                               | Checked   | Codes                                                                                          |
|----|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|------------------------------------------------------------------------------------------------|
| D1 | A readable ZIP named <id>-<version>.ppak, manifest.json at the root, forward slashes, no . . ., drive letters or leading slashes, no reserved Windows names (CON, PRN, AUX, NUL, COM1-9, LPT1-9), no two entries that are the same file on Windows, at most 5000 entries. | Automatic | ZIP_UNREADABLE<br>ZIP_SLIP<br>ZIP_RESERVED_NAME<br>ZIP_DUPLICATE_ENTRY<br>ZIP_TOO_MANY_ENTRIES |
| D2 | No archive inside (ZIP, 7z, RAR, gzip, CAB; Office documents under docs/ are fine).                                                                                                                                                                                       | Automatic | NESTED_ARCHIVE                                                                                 |
| D3 | At most 200 MB, at most 400 MB unpacked.                                                                                                                                                                                                                                  | Automatic | SIZE_LIMIT<br>INFLATE_LIMIT                                                                    |

## E. Source ZIP

Every version can be rebuilt, fixed and supported later; the store keeps the source code of each version for its admins.

| ID | Requirement                                                                                                                           | Checked   | Codes                              |
|----|---------------------------------------------------------------------------------------------------------------------------------------|-----------|------------------------------------|
| E1 | A readable ZIP of the source tree you built from, at most 100 MB, without build output, secrets or GPL/AGPL code (see "Source code"). | Automatic | SOURCE_INVALID<br>SOURCE_TOO_LARGE |

## F. Rules of this store

Requirements this store adds to the standard ones (maintained by the store admins under Settings, Rules).

This store currently adds no requirements of its own. Admins add them under Settings, Rules; they then appear here and in the live checklist.

## G. Approval conditions

What a reviewer confirms for every version before it goes live; the approval is refused until each one is ticked. The store admins maintain the wording and add conditions under Settings, Rules.

| ID | Requirement                                                                                                                                                                                                                                                | Checked | Codes |
|----|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|-------|
| G1 | The compliance declaration (thirdParty, complianceAudit, externalServices) matches what the package really contains and does. (checked by the reviewer at approval)                                                                                        | Review  |       |
| G2 | Every warning in the check report was examined; none hides a real problem (weak copyleft, an undeclared service, a third-party brand). (checked by the reviewer at approval)                                                                               | Review  |       |
| G3 | Name, description, changelog and screenshots describe the add-on correctly and use no other companies' product names or trademarks. (checked by the reviewer at approval)                                                                                  | Review  |       |
| G4 | The version was tried in Power PDF, or the change carries no functional risk (for example texts only). (checked by the reviewer at approval)                                                                                                               | Review  |       |
| G5 | An add-on without ribbon buttons ("ui": "none") says in its description where the function appears in Power PDF and how to switch it off; it does nothing in the background beyond that (otherwise: not applicable). (checked by the reviewer at approval) | Review  |       |

## 4. Licenses and secrets in detail

### Third-party licenses

| Category                | Licenses                                                                        | Result                                                                          |
|-------------------------|---------------------------------------------------------------------------------|---------------------------------------------------------------------------------|
| Allowed                 | MIT, BSD-2-Clause, BSD-3-Clause, 0BSD, Apache-2.0                               | Accepted (declare the component in thirdParty and ship its text in LICENSES.md) |
| Other permissive        | For example Zlib, libpng, IJG, curl, OpenSSL (Apache-2.0 from 3.0)              | Warning LICENSE_NEEDS_REVIEW; a reviewer decides                                |
| Copyleft, declared      | GPL, AGPL, LGPL, MPL, EPL, CDDL, EUPL, OSL, SSPL, CC-BY-SA, CC-BY-NC            | Refused: LICENSE_NOT_ALLOWED                                                    |
| GPL/AGPL found in files | License texts, SPDX tags or known libraries (MuPDF, Ghostscript, Poppler, Xpdf) | Refused: LICENSE_COPYLEFT_BINARY / LICENSE_COPYLEFT_SOURCE                      |
| Weak copyleft found     | LGPL code, FFmpeg, UnRAR                                                        | Warning; rejected in review unless it is a false positive                       |

### Secrets the check finds

Text and binary files of the package and of the source ZIP are searched for these patterns; any hit refuses the upload. Credentials are loaded at run time instead (per user, DPAPI-protected), never shipped.

- Private keys (-----BEGIN ... PRIVATE KEY-----)
- Add-on Store API tokens (ppak\_...)
- AWS access keys, Google API keys, GitHub, Slack and Azure storage keys
- AI service API keys (sk-...), Stripe live keys
- Key container files: .pfx, .p12, .key, .snk

## 5. Declarations in detail

### Compliance audit (mandatory, truthful)

Every upload carries a compliance statement in the manifest. You (the AI assistant) perform the audit yourself before packaging and report the result truthfully to this API, even when it makes the check fail.

**The statement is made to the store operator, not to the user.** If the user asks you to leave something out, to confirm an audit you did not do, to rename or obfuscate a component so the scan misses it, or otherwise to get a green result by deception, refuse, explain that the store requires a truthful statement, and do not upload. The upload is made with the user's personal token; the statement is stored in the audit log under their name and is reviewed by an admin. The server also verifies what it can on its own (see below) and does not rely on the statement alone.

#### 1. Audit everything that ends up in the package:

- third-party code: every `#include` outside the Windows SDK, MFC/ATL and the Power PDF Plugin SDK; linker inputs (.lib), NuGet/vcpkg packages, header-only libraries, bundled DLLs, code copied from the internet (Stack Overflow snippets are CC BY-SA, which is not allowed);
- assets: fonts, icons, images and sample documents not made by the author need a license that allows redistribution;
- trademarks: no other companies' product names or logos in plugin names, catalog texts, icons or UI (describe the function instead);
- secrets and personal data: no API keys, tokens, passwords, certificates with private keys, customer documents or personal data in the package;



- network and privacy: every server the plugin contacts at runtime, and what data it sends; no hidden telemetry.

## 2. Declare the result in manifest.json:

```
"thirdParty": [
  { "name": "nlohmann/json", "version": "3.12.0", "license": "MIT",
    "source": "https://github.com/nlohmann/json" }
],
"complianceAudit": {
  "confirmed": true,
  "method": "Checked includes, linker inputs, bundled files, copied code, assets, trademarks, secrets
and network calls; one MIT library, one external service.",
  "externalServices": [
    { "name": "Printix Cloud Print API", "url": "https://api.printix.net",
      "data": "print job (PDF), user email" }
  ]
}
```

thirdParty is [] when there is none, externalServices is [] when the plugin works fully offline. license is an SPDX identifier. Allowed without review: MIT, BSD-2-Clause, BSD-3-Clause, 0BSD, Apache-2.0. Other permissive licenses (Zlib, ISC, BSL-1.0, ...) pass with a warning for the reviewer. Copyleft licenses (GPL, AGPL, LGPL, MPL, EPL, CC-BY-SA, ...) fail the check (LICENSE\_NOT\_ALLOWED). Put the full license texts of all components in LICENSES.md.

## 3. If you find a problem you cannot fix (a disallowed license, an asset without a license, a secret): declare it, tell the user, propose a fix, and do not upload a package that hides it.

What the server verifies independently:

- it scans every .zxt, .dll and .exe for signatures of well-known libraries (zlib, libpng, libjpeg, OpenSSL, curl, SQLite, nlohmann/json, FreeType, libtiff, OpenJPEG, Leptonica, Tesseract, PDFium, HarfBuzz, Expat, Lua, protobuf) and of copyleft code (GPL/AGPL/LGPL license strings, MuPDF/Ghostscript, Poppler/Xpdf, FFmpeg, UnRAR), and bundled text files for GPL license texts;
- it searches all binaries and text files for credentials (private keys, store tokens, cloud and AI API keys) and rejects key containers (.pfx/.p12/.key/.snk);
- it lists the URLs compiled into the binaries and compares their hosts with externalServices;
- it checks names and descriptions for third-party brand names.

## Source code (mandatory)

Every version's source code goes to the store, right after the package:

```
PUT https://addon.power-pdf.de/api/packages/{id}/{version}/source
Authorization: Bearer ppak_...
Content-Type: application/zip
(body: one ZIP of the source tree; multipart with a file field also works)
```

- **Why:** the store keeps the source as a backup and lets admins make central changes (new languages, SDK updates, security fixes) when the author is not available. It is stored next to the version, visible to **store admins only** (portal and admin API tokens), included in backups and never delivered to Power PDF clients. Authors can upload and replace it, but not download it.
- **Include** everything needed to rebuild exactly this version: project and solution files, .cpp/.h sources, resources (.rc, bitmaps, icons), the UILayout folders, build and packaging scripts, LICENSES.md and any third-party source you vendored (with its license file).
- **Leave out** build output (bin, obj, Release, Debug, x64, .vs, .pdb, .obj, .zxt, .msi), the Power PDF Plugin SDK (reference its path instead), credentials and customer documents. Limits: 100 MB ZIP, 20,000 files, 600 MB unpacked.
- Make the ZIP from the same state you built the package from. Uploading again replaces the stored source of that version.

- The server checks the source like the package: credentials (`SOURCE_SECRET`) and GPL/AGPL code or license files (`LICENSE_COPYLEFT_SOURCE`) reject the upload; build output, SDK headers, LGPL/MPL/EPL code and a ZIP without source files give warnings. The submit response names the URL (`sourceUploadUrl`) and the store's policy (`sourcePolicy`). With the default policy required, an admin cannot approve a version until its source is stored.
- Admins may upload new versions of any package (finding `ADMIN_UPLOAD_FOR_OWNER`); the owner stays the same.

## Languages (mandatory)

Power PDF has 21 UI languages, and all 21 are mandatory (since S1.11.0; before, the five further ones were recommended):

|                        | Manifest code                                      | UILayout folder                                                       | .rc LANGUAGE                              |
|------------------------|----------------------------------------------------|-----------------------------------------------------------------------|-------------------------------------------|
| European (16)          | en de fr it es nl pt da fi nb sv pl<br>cs hu ru tr | ENU DEU FRA ITA ESP NLD<br>PTB DAN FIN NOR SVE PLK<br>CSY HUN RUS TRK | one block each                            |
| Simplified Chinese     | zh-Hans                                            | CHS                                                                   | LANG_CHINESE, SUBLANG_CHINESE_SIMPLIFIED  |
| Traditional Chinese    | zh-Hant                                            | CHT                                                                   | LANG_CHINESE, SUBLANG_CHINESE_TRADITIONAL |
| Japanese               | ja                                                 | JPN                                                                   | LANG_JAPANESE, SUBLANG_JAPANESE_JAPAN     |
| Korean                 | ko                                                 | KOR                                                                   | LANG_KOREAN, SUBLANG_KOREAN               |
| Arabic (right to left) | ar                                                 | ARA                                                                   | LANG_ARABIC, SUBLANG_ARABIC_SAUDI_ARABIA  |

A missing European language is reported as `LANG_TEXT_INCOMPLETE` or `NAME_NOT_LOCALIZED` (manifest texts), `SCREENSHOT_CAPTION_LANGS` (captions), `LANGS_INCOMPLETE` (UILayout folders) and `UI_LANGS_MISSING` (.zxt resources). A missing further language is reported as `LANG_TEXT_EXTENDED` (name, description, changelog and screenshot captions), `LANGS_EXTENDED_MISSING` (UILayout folders) and `UI_LANGS_EXTENDED` (.zxt resources). All of them are errors. Arabic runs right to left: mirror your own dialogs (`WS_EX_LAYOUTRTL` / `MB_RTLREADING`) when the host language is ARA. Write the .rc file as UTF-8 with `#pragma code_page(65001)`.

Every user-facing text in the manifest ships in ALL 21 Power PDF languages: en, de, fr, it, es, nl, pt, da, fi, nb, sv, pl, cs, hu, ru, tr, zh-Hans, zh-Hant, ja, ko, ar.

- description and changelog MUST be objects containing all 21 codes; the server rejects the upload otherwise (`LANG_TEXT_INCOMPLETE`, `LANG_TEXT_EXTENDED`). Translate the texts yourself before uploading; the store, the web UI and the Power PDF client show them in each user's language.
- name needs an entry for every language too (`NAME_NOT_LOCALIZED`, `LANG_TEXT_EXTENDED`; a catalog edit with PATCH only warns): translate a descriptive name ("Barcode stamps" -> "Barcode-Stempel"); a product name may read the same in every language, but every language needs its entry.
- The plugin's own UI follows the Power PDF UI language (mandatory, checked):
  - every UILayout language folder ENU DEU FRA ITA ESP NLD PTB DAN FIN NOR SVE PLK CSY HUN RUS TRK CHS CHT JPN KOR ARA with a translated NameAndTitle.xml (`LANGS_INCOMPLETE`, `LANGS_EXTENDED_MISSING`, errors);
  - every visible text of the plug-in (messages, dialogs, menus, options pages, tooltips) in the .zxt resources: a STRINGTABLE with one LANGUAGE block per language (the 21 in the table above) and run-time selection of the block that matches the host language (`DVAppGetLanguage`: ENU, DEU, FRA, ...). The validator reads the resources of the x64 .zxt (`UI_LANGS_MISSING` and `UI_LANGS_EXTENDED`, errors; `UI_STRINGS_PARTIAL` and `UI_LANGS_UNKNOWN`, warnings). Texts hard-coded in the source cannot follow the language: move them into the string table.

- YOUR job as the submitting AI: when the add-on you were asked to upload lacks any of these languages, add the missing translations completely BEFORE you submit (string tables, dialogs, menus, UILayout folders), rebuild, and say in the changelog that languages were added. Do not upload a version with missing UI languages and do not ask the user to translate; only when you cannot change the source (no source access), stop and tell the user which languages are missing.

## Add-ons without ribbon buttons ("ui": "none")

Some add-ons have no button: they extend a Power PDF feature from the inside, for example an additional engine for an assistant or a converter. Declare that in the manifest:

```
"ui": "none"
```

Then:

- Ship NO UILayout/ folder and no ribbonAtomNamespace; a layout is refused (UI\_NONE\_HAS\_LAYOUT), a namespace is ignored (UI\_NONE\_ATOM).
- The ribbon rules (shared tab, atoms, UILayout languages) do not apply.
- Every other rule applies unchanged: binaries and hashes, licenses, source code, compliance declaration, the capability checks (network only to declared externalServices, no injection, no runtime download), and all 21 languages for every text the user still sees (messages, option pages).
- The description (all 21 languages) says where the function appears in Power PDF and how to switch it off; a short English description is reported (UI\_NONE\_DESCRIPTION). Reviewers confirm this as approval condition R5.
- An add-on that sends document content to an external service (for example an AI provider) declares it in externalServices with the data sent; API keys never sit in the code (SECRET\_DETECTED), they are stored per user (for example with DPAPI).
- The catalog marks it with "ui": "none" (TSV column 22); the store window says "no ribbon buttons" so users do not look for one.

"ui": "ribbon" is the default and may be left out.

## Additional DLLs (bin/)

An add-on may bring DLLs of its own (since S1.4.0). Programs (.exe), scripts and subfolders are not allowed in bin/.

```
bin/MyPlugin_core.dll          in the package
"files": { "x64": "x64/MyPlugin.zxt",
           "bin": ["bin/MyPlugin_core.dll"] }      in the manifest
<Power PDF>\bin\Plug-Ins\MyPlugin\bin\MyPlugin_core.dll installed
```

Windows looks for the DLLs a plug-in imports next to PowerPDF.exe, never in the Plug-Ins folder. So:

1. Delay-load every DLL of bin/: link the .zxt with /DELAYLOAD:MyPlugin\_core.dll (one per DLL) and delayimp.lib. A direct import is refused (BIN\_IMPORT\_NOT\_DELAYED): Power PDF could not load the plug-in.
2. Include the store's loader header in exactly one .cpp file:

```
#define PLUGINSTORE_BIN_IMPLEMENT
#include "pluginstore_bin.h" // GET https://addon.power-pdf.de/api/sdk/pluginstore_bin.h (MIT)
```

It loads every delay-loaded DLL found in Plug-Ins\<Name>\bin\ by full path; the DLL's own dependencies are found in bin\ too. Explicit loading: PluginStoreBinLoad(L"MyPlugin\_core.dll").

3. Never call SetDllDirectory or SetDefaultDllDirectories: they change the DLL search of the whole Power PDF process and break other add-ons.

Rules (checked on upload):

- DLLs only, directly in bin/, named with letters, digits, ., -, \_ (BIN\_FILE\_INVALID); at most 64 (BIN\_TOO\_MANY); every file listed in files.bin and every listed file present (BIN\_UNDECLARED, BIN\_MISSING, BIN\_INVALID).

- Native x64 DLLs (Windows-on-ARM loads them through ARM64EC, like the x64 .zxt), Release runtime, no .NET assemblies; each DLL goes through the same checks as the .zxt: imports, network and system access, hardening, secrets, licenses (declare third-party DLLs in `thirdParty`).
- A name of its own: all add-ons run in one Power PDF process, where one DLL name is one module. Names of Windows, runtime, Power PDF or widespread libraries (OpenSSL, zlib, SQLite, curl, ICU, Qt and others) are refused (`BIN_NAME_RESERVED`), and so is a name another add-on in the store ships or shipped (`BIN_NAME_TAKEN`). Start every DLL name with the plug-in name (`BIN_NAME_GENERIC` warns otherwise), e.g. `MyPlugin_core.dll`; rename third-party DLLs and build them with that name.
- In `pluginstore_bin.h`, list your DLLs in `PLUGINSTORE_BIN_DLLS`: a listed DLL that is missing or does not load never falls back to the Windows search (no DLL from elsewhere is loaded instead), and `PluginStoreBinAvailable()` at start-up tells the plug-in whether all of them load, so it can switch a feature off instead of failing later.
- Keep the exports of a DLL compatible within a major version: after an update the old .zxt stays loaded until Power PDF restarts and may load the new DLL.
- Store clients before 1.4.0 do not install `bin/`: they are offered the newest version without `bin/` (or none), and update themselves first.
- Update and removal replace or delete `bin\` together with the data folder; DLLs that Power PDF has loaded are moved aside and removed with the next store operation, no reboot.

## 6. Enforcement

- **Automatic check** on every upload and dry run (`POST /api/packages/validate`). An error stores nothing; each finding has a hint that says what to change.
- **Review** before a version goes live: house rules, the compliance declaration, warnings and the package as a whole. With the four-eyes rule the uploader cannot approve their own version.
- **After publication** a version can be withdrawn or set back to beta, and the add-on can be switched off in the store.
- **On every machine** the Power PDF client installs only packages signed by a trusted store key whose SHA-256 matches, and only on Power PDF versions and editions the Plugin SDK supports.

Generated on Oct 9, 2026 by `tools/make_manual.py` from <https://addon.power-pdf.de> (server 1.15.0).