

表 (17)

名称	类型	架构
Attendance		CREATE TABLE Attendance (id INTEGER PRIMARY KEY AUTOINCREMENT, brand_code TEXT NOT NULL DEFAULT 'century_field', payroll_month TEXT, nick_name TEXT, location TEXT, days_worked INTEGER DEFAULT 0, hours REAL DEFAULT 0, ot_hours REAL DEFAULT 0, expenses REAL DEFAULT 0, adjustment REAL DEFAULT 0, attendance_bonus REAL DEFAULT 0, basic_pay_override REAL, allowance_override REAL, UNIQUE (brand_code, payroll_month, nick_name, location), FOREIGN KEY (brand_code) REFERENCES Brands (brand_code))
id	INTEGER	"id" INTEGER
brand_code	TEXT	"brand_code" TEXT NOT NULL DEFAULT 'century_field'
payroll_month	TEXT	"payroll_month" TEXT
nick_name	TEXT	"nick_name" TEXT
location	TEXT	"location" TEXT
days_worked	INTEGER	"days_worked" INTEGER DEFAULT 0
hours	REAL	"hours" REAL DEFAULT 0
ot_hours	REAL	"ot_hours" REAL DEFAULT 0
expenses	REAL	"expenses" REAL DEFAULT 0
adjustment	REAL	"adjustment" REAL DEFAULT 0
attendance_bonus	REAL	"attendance_bonus" REAL DEFAULT 0
basic_pay_override	REAL	"basic_pay_override" REAL
allowance_override	REAL	"allowance_override" REAL
AuditLog		CREATE TABLE AuditLog (id INTEGER PRIMARY KEY AUTOINCREMENT, timestamp TEXT NOT NULL, user TEXT, action TEXT NOT NULL, table_name TEXT, record_id TEXT, old_value TEXT, new_value TEXT, ip TEXT)
id	INTEGER	"id" INTEGER
timestamp	TEXT	"timestamp" TEXT NOT NULL
user	TEXT	"user" TEXT
action	TEXT	"action" TEXT NOT NULL
table_name	TEXT	"table_name" TEXT
record_id	TEXT	"record_id" TEXT
old_value	TEXT	"old_value" TEXT
new_value	TEXT	"new_value" TEXT
ip	TEXT	"ip" TEXT
AutoBackupSettings		CREATE TABLE AutoBackupSettings (id INTEGER PRIMARY KEY CHECK (id = 1), enabled INTEGER NOT NULL DEFAULT 0, backup_time TEXT NOT NULL DEFAULT '02:00', last_run_date TEXT, updated_at TEXT DEFAULT CURRENT_TIMESTAMP)
id	INTEGER	"id" INTEGER CHECK ("id" = 1)
enabled	INTEGER	"enabled" INTEGER NOT NULL DEFAULT 0
backup_time	TEXT	"backup_time" TEXT NOT NULL DEFAULT '02:00'
last_run_date	TEXT	"last_run_date" TEXT
updated_at	TEXT	"updated_at" TEXT DEFAULT CURRENT_TIMESTAMP
BrandMonthInputSource		CREATE TABLE BrandMonthInputSource (brand_code TEXT NOT NULL, payroll_month TEXT NOT NULL, input_source TEXT NOT NULL CHECK (input_source IN ('excel',

名称	类型	架构
		'web')), updated_at TEXT DEFAULT CURRENT_TIMESTAMP, PRIMARY KEY (brand_code, payroll_month), FOREIGN KEY (brand_code) REFERENCES Brands(brand_code))
brand_code	TEXT	"brand_code" TEXT NOT NULL
payroll_month	TEXT	"payroll_month" TEXT NOT NULL
input_source	TEXT	"input_source" TEXT NOT NULL CHECK("input_source" IN ('excel', 'web'))
updated_at	TEXT	"updated_at" TEXT DEFAULT CURRENT_TIMESTAMP
Brands		CREATE TABLE Brands (brand_code TEXT PRIMARY KEY, brand_name TEXT NOT NULL, is_active INTEGER NOT NULL DEFAULT 1, created_at TEXT DEFAULT CURRENT_TIMESTAMP, updated_at TEXT DEFAULT CURRENT_TIMESTAMP)
brand_code	TEXT	"brand_code" TEXT
brand_name	TEXT	"brand_name" TEXT NOT NULL
is_active	INTEGER	"is_active" INTEGER NOT NULL DEFAULT 1
created_at	TEXT	"created_at" TEXT DEFAULT CURRENT_TIMESTAMP
updated_at	TEXT	"updated_at" TEXT DEFAULT CURRENT_TIMESTAMP
DailyAttendance		CREATE TABLE DailyAttendance (id INTEGER PRIMARY KEY AUTOINCREMENT, payroll_month TEXT, work_date TEXT, nick_name TEXT, location TEXT, in_time TEXT, out_time TEXT, normal_hours REAL DEFAULT 0, actual_hours REAL DEFAULT 0, ot_hours REAL DEFAULT 0, brand_code TEXT NOT NULL DEFAULT 'century_field', roster_in TEXT, roster_out TEXT)
id	INTEGER	"id" INTEGER
payroll_month	TEXT	"payroll_month" TEXT
work_date	TEXT	"work_date" TEXT
nick_name	TEXT	"nick_name" TEXT
location	TEXT	"location" TEXT
in_time	TEXT	"in_time" TEXT
out_time	TEXT	"out_time" TEXT
normal_hours	REAL	"normal_hours" REAL DEFAULT 0
actual_hours	REAL	"actual_hours" REAL DEFAULT 0
ot_hours	REAL	"ot_hours" REAL DEFAULT 0
brand_code	TEXT	"brand_code" TEXT NOT NULL DEFAULT 'century_field'
roster_in	TEXT	"roster_in" TEXT
roster_out	TEXT	"roster_out" TEXT
Employees		CREATE TABLE Employees (id INTEGER PRIMARY KEY AUTOINCREMENT, brand_code TEXT NOT NULL DEFAULT 'century_field', nick_name TEXT NOT NULL, hourly_rate REAL DEFAULT 0, allowance REAL DEFAULT 0, commission_rate REAL DEFAULT 0.03, require_mpf INTEGER DEFAULT 0, mpf_start_month TEXT, full_name TEXT, salary_type TEXT DEFAULT 'hourly', monthly_salary REAL DEFAULT 0.0, UNIQUE (brand_code, nick_name), FOREIGN KEY (brand_code) REFERENCES Brands(brand_code))
id	INTEGER	"id" INTEGER
brand_code	TEXT	"brand_code" TEXT NOT NULL DEFAULT 'century_field'
nick_name	TEXT	"nick_name" TEXT NOT NULL
hourly_rate	REAL	"hourly_rate" REAL DEFAULT 0

名称	类型	架构
allowance	REAL	"allowance" REAL DEFAULT 0
commission_rate	REAL	"commission_rate" REAL DEFAULT 0.03
require_mpf	INTEGER	"require_mpf" INTEGER DEFAULT 0
mpf_start_month	TEXT	"mpf_start_month" TEXT
full_name	TEXT	"full_name" TEXT
salary_type	TEXT	"salary_type" TEXT DEFAULT 'hourly'
monthly_salary	REAL	"monthly_salary" REAL DEFAULT 0.0
Locations		CREATE TABLE Locations (id INTEGER PRIMARY KEY AUTOINCREMENT, brand_code TEXT NOT NULL DEFAULT 'century_field', name TEXT NOT NULL, display_name TEXT, region TEXT, UNIQUE (brand_code, name), FOREIGN KEY (brand_code) REFERENCES Brands (brand_code))
id	INTEGER	"id" INTEGER
brand_code	TEXT	"brand_code" TEXT NOT NULL DEFAULT 'century_field'
name	TEXT	"name" TEXT NOT NULL
display_name	TEXT	"display_name" TEXT
region	TEXT	"region" TEXT
LoginAttempts		CREATE TABLE LoginAttempts (username TEXT NOT NULL, ip TEXT NOT NULL, failed_count INTEGER NOT NULL DEFAULT 0, locked_until TEXT, updated_at TEXT DEFAULT CURRENT_TIMESTAMP, PRIMARY KEY (username, ip))
username	TEXT	"username" TEXT NOT NULL
ip	TEXT	"ip" TEXT NOT NULL
failed_count	INTEGER	"failed_count" INTEGER NOT NULL DEFAULT 0
locked_until	TEXT	"locked_until" TEXT
updated_at	TEXT	"updated_at" TEXT DEFAULT CURRENT_TIMESTAMP
MonthInputSource		CREATE TABLE MonthInputSource (payroll_month TEXT PRIMARY KEY, input_source TEXT NOT NULL CHECK (input_source IN ('excel', 'web')), updated_at TEXT DEFAULT CURRENT_TIMESTAMP)
payroll_month	TEXT	"payroll_month" TEXT
input_source	TEXT	"input_source" TEXT NOT NULL CHECK("input_source" IN ('excel', 'web'))
updated_at	TEXT	"updated_at" TEXT DEFAULT CURRENT_TIMESTAMP
MonthlyRates		CREATE TABLE MonthlyRates (id INTEGER PRIMARY KEY AUTOINCREMENT, brand_code TEXT NOT NULL DEFAULT 'century_field', payroll_month TEXT NOT NULL, nick_name TEXT NOT NULL, hourly_rate REAL, allowance REAL, commission_rate REAL, monthly_salary REAL, remarks TEXT, UNIQUE (brand_code, payroll_month, nick_name), FOREIGN KEY (brand_code) REFERENCES Brands (brand_code))
id	INTEGER	"id" INTEGER
brand_code	TEXT	"brand_code" TEXT NOT NULL DEFAULT 'century_field'
payroll_month	TEXT	"payroll_month" TEXT NOT NULL
nick_name	TEXT	"nick_name" TEXT NOT NULL
hourly_rate	REAL	"hourly_rate" REAL
allowance	REAL	"allowance" REAL
commission_rate	REAL	"commission_rate" REAL
monthly_salary	REAL	"monthly_salary" REAL
remarks	TEXT	"remarks" TEXT

名称	类型	架构
Products		CREATE TABLE Products (id INTEGER PRIMARY KEY AUTOINCREMENT, brand_code TEXT NOT NULL DEFAULT 'century_field', model TEXT NOT NULL, product_line TEXT, commission_rate REAL DEFAULT 0.03, product_category TEXT, UNIQUE (brand_code, model), FOREIGN KEY (brand_code) REFERENCES Brands (brand_code))
id	INTEGER	"id" INTEGER
brand_code	TEXT	"brand_code" TEXT NOT NULL DEFAULT 'century_field'
model	TEXT	"model" TEXT NOT NULL
product_line	TEXT	"product_line" TEXT
commission_rate	REAL	"commission_rate" REAL DEFAULT 0.03
product_category	TEXT	"product_category" TEXT
Sales		CREATE TABLE Sales (id INTEGER PRIMARY KEY AUTOINCREMENT, payroll_month TEXT, date TEXT, promoter_name TEXT, location TEXT, model TEXT, quantity INTEGER, price REAL, brand_code TEXT NOT NULL DEFAULT 'century_field')
id	INTEGER	"id" INTEGER
payroll_month	TEXT	"payroll_month" TEXT
date	TEXT	"date" TEXT
promoter_name	TEXT	"promoter_name" TEXT
location	TEXT	"location" TEXT
model	TEXT	"model" TEXT
quantity	INTEGER	"quantity" INTEGER
price	REAL	"price" REAL
brand_code	TEXT	"brand_code" TEXT NOT NULL DEFAULT 'century_field'
SpecialCommissions		CREATE TABLE SpecialCommissions (id INTEGER PRIMARY KEY AUTOINCREMENT, brand_code TEXT NOT NULL DEFAULT 'century_field', model TEXT NOT NULL, start_month TEXT NOT NULL, end_month TEXT NOT NULL, rate REAL NOT NULL, FOREIGN KEY (brand_code) REFERENCES Brands (brand_code))
id	INTEGER	"id" INTEGER
brand_code	TEXT	"brand_code" TEXT NOT NULL DEFAULT 'century_field'
model	TEXT	"model" TEXT NOT NULL
start_month	TEXT	"start_month" TEXT NOT NULL
end_month	TEXT	"end_month" TEXT NOT NULL
rate	REAL	"rate" REAL NOT NULL
UserBrandPermissions		CREATE TABLE UserBrandPermissions (id INTEGER PRIMARY KEY AUTOINCREMENT, username TEXT NOT NULL, brand_code TEXT NOT NULL, created_at TEXT DEFAULT CURRENT_TIMESTAMP, UNIQUE (username, brand_code), FOREIGN KEY (username) REFERENCES Users (username), FOREIGN KEY (brand_code) REFERENCES Brands (brand_code))
id	INTEGER	"id" INTEGER
username	TEXT	"username" TEXT NOT NULL
brand_code	TEXT	"brand_code" TEXT NOT NULL
created_at	TEXT	"created_at" TEXT DEFAULT CURRENT_TIMESTAMP
Users		CREATE TABLE Users (id INTEGER PRIMARY KEY AUTOINCREMENT, username TEXT NOT NULL UNIQUE,

名称	类型	架构
		password_hash TEXT NOT NULL, is_admin INTEGER NOT NULL DEFAULT 0, is_active INTEGER NOT NULL DEFAULT 1, created_at TEXT DEFAULT CURRENT_TIMESTAMP, updated_at TEXT DEFAULT CURRENT_TIMESTAMP)
id	INTEGER	"id" INTEGER
username	TEXT	"username" TEXT NOT NULL UNIQUE
password_hash	TEXT	"password_hash" TEXT NOT NULL
is_admin	INTEGER	"is_admin" INTEGER NOT NULL DEFAULT 0
is_active	INTEGER	"is_active" INTEGER NOT NULL DEFAULT 1
created_at	TEXT	"created_at" TEXT DEFAULT CURRENT_TIMESTAMP
updated_at	TEXT	"updated_at" TEXT DEFAULT CURRENT_TIMESTAMP
sqlite_sequence		CREATE TABLE sqlite_sequence(name,seq)
name		"name"
seq		"seq"

索引 (0)

名称	类型	架构
----	----	----

视图 (0)

名称	类型	架构
----	----	----

触发器 (3)

名称	类型	架构
update_attendance_after_delete		CREATE TRIGGER update_attendance_after_delete AFTER DELETE ON DailyAttendance FOR EACH ROW BEGIN UPDATE Attendance SET days_worked = (SELECT COUNT(*) FROM DailyAttendance WHERE brand_code = OLD.brand_code AND payroll_month = OLD.payroll_month AND nick_name = OLD.nick_name AND location = OLD.location), hours = COALESCE((SELECT SUM(actual_hours - ot_hours) FROM DailyAttendance WHERE brand_code = OLD.brand_code AND payroll_month = OLD.payroll_month AND nick_name = OLD.nick_name AND location = OLD.location), 0), ot_hours = COALESCE((SELECT SUM(ot_hours) FROM DailyAttendance WHERE brand_code = OLD.brand_code AND payroll_month = OLD.payroll_month AND nick_name = OLD.nick_name AND location = OLD.location), 0) WHERE brand_code = OLD.brand_code AND payroll_month = OLD.payroll_month AND nick_name = OLD.nick_name AND location = OLD.location; END
update_attendance_after_insert		CREATE TRIGGER update_attendance_after_insert AFTER INSERT ON DailyAttendance FOR EACH ROW BEGIN INSERT OR IGNORE INTO Attendance (brand_code, payroll_month, nick_name, location, days_worked, hours, ot_hours, expenses, adjustment, attendance_bonus) VALUES (NEW.brand_code, NEW.payroll_month, NEW.nick_name, NEW.location, 0, 0, 0, 0, 0, 0); UPDATE Attendance SET days_worked = (SELECT COUNT(*) FROM DailyAttendance WHERE brand_code = NEW.brand_code AND payroll_month = NEW.payroll_month AND nick_name = NEW.nick_name AND location = NEW.location), hours = COALESCE((SELECT SUM(actual_hours - ot_hours) FROM DailyAttendance

名称	类型	架构
		WHERE brand_code = NEW.brand_code AND payroll_month = NEW.payroll_month AND nick_name = NEW.nick_name AND location = NEW.location), 0), ot_hours = COALESCE((SELECT SUM(ot_hours) FROM DailyAttendance WHERE brand_code = NEW.brand_code AND payroll_month = NEW.payroll_month AND nick_name = NEW.nick_name AND location = NEW.location), 0) WHERE brand_code = NEW.brand_code AND payroll_month = NEW.payroll_month AND nick_name = NEW.nick_name AND location = NEW.location; END
update_attendance_after_update		CREATE TRIGGER update_attendance_after_update AFTER UPDATE ON DailyAttendance FOR EACH ROW BEGIN UPDATE Attendance SET days_worked = (SELECT COUNT(*) FROM DailyAttendance WHERE brand_code = NEW.brand_code AND payroll_month = NEW.payroll_month AND nick_name = NEW.nick_name AND location = NEW.location), hours = COALESCE((SELECT SUM(actual_hours - ot_hours) FROM DailyAttendance WHERE brand_code = NEW.brand_code AND payroll_month = NEW.payroll_month AND nick_name = NEW.nick_name AND location = NEW.location), 0), ot_hours = COALESCE((SELECT SUM(ot_hours) FROM DailyAttendance WHERE brand_code = NEW.brand_code AND payroll_month = NEW.payroll_month AND nick_name = NEW.nick_name AND location = NEW.location), 0) WHERE brand_code = NEW.brand_code AND payroll_month = NEW.payroll_month AND nick_name = NEW.nick_name AND location = NEW.location; END