



Bookmarks

► [How To?](#)

► [Week 1](#)

▼ [Week 2](#)

[Computational Complexity. Linear Data Structures](#)

[2nd Week Problems](#)

[due Nov 14, 2016 22:00 CET](#)

[2nd Week Problems: Training](#)

[2nd Week: Editorials](#)

► [Week 3](#)

► [Week 4](#)

► [Week 5](#)

Week 2 > 2nd Week Problems > Stack

Stack

🔖 Bookmark this page

Stack

2.0/2.0 points (graded)

Input file:	stack.in
Output file:	stack.out
Time limit:	2 seconds
Memory limit:	256 megabytes

Implement a stack which supports push and pop operations. For every pop operation, output its result.

Input

The first line of the input file contains a single integer number N ($1 \leq N \leq 10^6$) – the number of commands. N lines follow, each line contains exactly one command. There are the following commands:

- $+ x$: push x to the stack. Every x will be an integer such that $|x| \leq 10^9$. The symbol $+$ and the number will be separated by exactly one white space.
- $-$: pop an element from the stack. It is guaranteed that this operation will never be executed on an empty stack. There will be at least one such operation.

Output

Output the integers popped from the stack, one per line, in the order they were popped.

Example

stack.in	stack.out
6	10
+ 1	1234
+ 10	
-	

+ 2	
+ 1234	
-	
Download	Download

[Choose Files](#) No file chosen

Accepted

[Submit](#)

You have used 2 of 200 attempts

Discussion

Topic: 04: 2nd Week Problems / Stack

[Show Discussion](#)

© All Rights Reserved



© 2016 edX Inc. All rights reserved except where noted. EdX, Open edX and the edX and Open EdX logos are registered trademarks or trademarks of edX Inc.

POWERED BY
OPENedX®

