



Bookmarks

▶ [How To?](#)▶ [Week 1](#)▶ [Week 2](#)▼ [Week 3](#)

[Sorting And Search Algorithms](#)

3rd Week

Problems

due Nov 20, 2016 22:00
CET

3rd Week

Problems: Training

▶ [Week 4](#)▶ [Week 5](#)

Week 3 > 3rd Week Problems > Anti-Quicksort

Anti-Quicksort

[Bookmark this page](#)

Anti-Quicksort

2.0/2.0 points (graded)

Input file:	antiqs.in
Output file:	antiqs.out
Time limit:	2 seconds
Memory limit:	256 megabytes

For sorting integer sequences, the Quicksort algorithm is widely used. Below we give a program which sorts an array a using this algorithm.

```
var a : array [1..N] of integer;
```

```
procedure QSort(left, right : integer);
```

```
var i, j, key, buf : integer;
```

```
begin
```

```
  key := a[(left + right) div 2];
```

```
  i := left;
```

```
  j := right;
```

```
  repeat
```

```
    while a[i] < key do
```

```
      inc(i);
```

```
    while key < a[j] do
```

```
      dec(j);
```

```
    if i <= j then begin
```

```
      buf := a[i];
```

```
      a[i] := a[j];
```

```
      a[j] := buf;
```

```
      inc(i);
```

```
      dec(j);
```

```
    end;
```

```
  until i > j;
```

```
  if left < j then QSort(left, j);
```

```
  if i < right then QSort(i, right);
```

```
end;
```

```
begin
...
QSort(1, N);
end.
```

Although Quicksort is very fast on average, there exist integer sequences, which take quite a long time to be sorted using this algorithm. We will measure the running time of the algorithm by the number of comparisons where array elements participate (that is, the total number of comparisons in the first and the second while loop).

Your task is to generate a test, which forces the given Quicksort implementation to perform the maximum number of these comparisons.

Input

The first line of the input file contains a single integer number n ($1 \leq n \leq 10^6$).

Output

Output a permutation of numbers from 1 to n , which forces the given Quicksort implementation to perform the maximum number of these comparisons (among all permutations of numbers from 1 to n). If there are several such permutations, print any of them.

Example

antiqs.in	antiqs.out
3	1 3 2
Download	Download

[Choose Files](#) No file chosen

Accepted

[Submit](#) You have used 4 of 200 attempts

Discussion

Topic: 06: 3rd Week Problems / Anti-Quicksort

[Show Discussion](#)



© 2016 edX Inc. All rights reserved except where noted. EdX, Open edX and the edX and Open EdX logos are registered trademarks or trademarks of edX Inc.

