

Resumen de tests realizados (extraídos de Doc vivo.pdf)

Este informe lista los comandos de verificación y suites de pruebas que aparecen ejecutadas en el documento, junto con un breve resumen y capturas de las páginas donde se registran.

Índice de tests

#	Fecha	Test	Páginas
1	12/10/2025	Ping de conectividad	4
2	19/10/2025	Verificación MD5 de fuentes	15
3	21/10/2025	Verificación MD5 de fuentes	16
4	6/11/2025	Sanity checks de toolchain	24, 25, 26
5	30/12/2025	Glibc-2.42: suite de tests (make check)	97, 98
6	1/01/2026	Zlib-1.3.1: suite de tests (make check)	105
7	1/01/2026	Xz-5.8.1: suite de tests (make check)	111
8	1/01/2026	Lz4-1.10: suite de tests (make check)	114
9	1/01/2026	Zstd-1.5.7: suite de tests (make check)	117
10	2/01/2025	File-5.46: suite de tests (make check)	119
11	2/01/2025	M4-1.4.20: suite de tests (make check)	125
12	2/01/2025	Flex-2.6.4: suite de tests (make check)	131
13	2/01/2025	DejaGNU-1.6.3: suite de tests (make check)	143
14	5/01/2026	Binutils-2.45: suite de tests (make check)	148
15	5/01/2026	GMP: suite de tests (make check)	152
16	5/01/2026	MPFR: suite de tests (make check)	155
17	5/01/2026	MPC-1.3.1: suite de tests (make check)	159
18	5/01/2026	Attr-2.5.2: suite de tests (make check)	162
19	5/01/2026	Acl-2.3.2: suite de tests (make check)	165
20	5/01/2026	Libxcrypt-4.4.38: suite de tests (make check)	170
21	6/01/2026	GCC-15.2.0: suite de tests (make check)	177, 178, 180, 181
22	6/01/2026	Sed-4.9: suite de tests (make check)	186
23	6/01/2026	Psmisc-23.7: suite de tests (make check)	190
24	7/01/2026	Gettext-0.26: suite de tests (make check)	193
25	7/01/2026	Bison-3.8.2: suite de tests (make check)	196
26	7/01/2026	Grep-3.12: suite de tests (make check)	199
27	7/01/2026	Bash-5.3: suite de tests (make tests)	203
28	7/01/2026	Libtool-2.5.4: suite de tests (make check)	207
29	7/01/2026	GDBM-1.26: suite de tests (make check)	210, 212
30	8/01/2026	GDBM-1.26: suite de tests (make check)	215, 218
31	8/01/2026	Less-679: suite de tests (make check)	221
32	8/01/2026	Intltool-0.51.0: suite de tests (make check)	229

#	Fecha	Test	Páginas
33	8/01/2026	Autoconf-2.72: suite de tests (make check)	232
34	8/01/2026	Automake-1.18.1: suite de tests (make check)	234
35	9/01/2026	Libelf: suite de tests (make check)	241, 243
36	9/01/2026	Coreutils-9.7: suite de tests (make check)	259
37	9/01/2026	Diffutils-3.12: suite de tests (make check)	262
38	9/01/2026	Gawk-5.3.2: suite de tests (make check)	265
39	10/01/2026	Findutils-4.10.0: suite de tests (make check)	269
40	10/01/2026	Groff-1.23.0: suite de tests (make check)	271
41	10/01/2026	Gzip-1.14: suite de tests (make check)	275
42	10/01/2026	Make-4.4.1: suite de tests (make check)	285
43	10/01/2026	Patch-2.8: suite de tests (make check)	288
44	10/01/2026	Tar-1.35: suite de tests (make check)	290
45	10/01/2026	Texinfo-7.2: suite de tests (make check)	293
46	11/01/2026	Man-DB-2.13.1: suite de tests (make check)	309
47	11/01/2026	Procps-ng-4.0.5: suite de tests (make check)	312
48	11/01/2026	Util-linux-2.41.1: suite de tests (make check)	314
49	11/01/2026	E2fsprogs-1.47.3: suite de tests (make check)	317
50	14/01/2026	OpenSSH: tests y validaciones de servicio	351, 353

Detalle por test

1. Ping de conectividad

Fecha: 12/10/2025 Páginas: 4

Resumen: Validar conectividad de red (ICMP) hacia un host público.

Comandos (tal como aparecen):

```
Ping -c 3 8.8.8.8
```

Captura de la página 4 del documento fuente.

Comandos utilizados:

Prueba de conexión

Ping -c 3 8.8.8.8

```
terence@hutchkjLFS ~$ ping -c 3 8.8.8.8
PING 8.8.8.8 (8.8.8.8): 56(84) bytes of data:
64 bytes from 8.8.8.8: icmp_seq=1 ttl=255 time=30.6 ms
64 bytes from 8.8.8.8: icmp_seq=2 ttl=255 time=31.0 ms
64 bytes from 8.8.8.8: icmp_seq=3 ttl=255 time=26.3 ms

--- 8.8.8.8 ping statistics ---
3 packets transmitted, 3 received, 0% packet loss, time 200ms
rtt min/avg/max/mdev = 26.312/29.563/31.018/2.351 ms
terence@hutchkjLFS ~$
```

Actualizar e instalar lo básico del host (inspirado por la IA)

`sudo dnf -y update`: Actualiza todo el sistema base (parches de seguridad/bugs). Evita compilar LFS encima de librerías viejas.

`sudo dnf -y groupinstall "Development Tools"`: Instala de un saque compilador, make, etc. (toolchain del host). LFS exige que el **host** tenga estas herramientas.

`sudo dnf -y install bison gawk m4 texinfo xz gzip bzip2 tar sed findutils diffutils \ patch perl python3 wget curl rsync file which util-linux make gcc gcc-c++ binutils`: Completa utilidades específicas que LFS pide (por ejemplo `patch`, `makeinfo`/`texinfo`, `gawk`, `bison`, compresores, `tar`, `sed`, `diff`...).

Repos y Verificación (inspirado por la IA)

- `dnf-plugins-core`, `dnf config-manager --set-enabled crb`, `dnf makecache`
Aseguran que los repos con paquetes “de desarrollo” (como `texinfo`) estén accesibles.

- `patch --version`, `makeinfo --version`
Chequeos rápidos de que esas herramientas realmente quedaron instaladas y operativas.

Detectar y preparar el disco nuevo

- `lsblk -o NAME,SIZE,TYPE,MOUNTPOINT`
Lista discos/particiones para **identificar** el nuevo disco (normalmente `sdb`).
- `sudo fdisk /dev/sdb → dentro: o n p l Enter Enter w`
Abre el particionador en `sdb` y:
 - `o`: crea **tabla MBR** simple.
 - `n p 1 ...`: crea **partición primaria 1** usando todo el disco.
 - `w`: **graba** los cambios.
- `sudo mkfs.ext4 -v /dev/sdb1`
Formatea la partición recién creada con **ext4** (sistema de archivos).

Montar la partición donde vivirá LFS

- `export LFS=/mnt/lfs`
Define la variable **\$LFS** apuntando al punto de montaje estándar.
- `sudo mkdir -pv $LFS`
Crea el directorio **/mnt/lfs** (con `-p` por si faltan padres, `-v` muestra lo que hace).
- `sudo mount -v -t ext4 /dev/sdb1 $LFS`
Monta la partición LFS en **/mnt/lfs**.

2. Verificación MD5 de fuentes

Fecha: 19/10/2025 **Páginas:** 15

Resumen: Validar integridad de tarballs descargados contra checksums del libro. Se registran problemas: archivos faltantes o checksums que no coinciden, y errores de permisos al intentar guardar logs fuera del directorio de trabajo; además se menciona un mirror inaccesible.

Comandos (tal como aparecen):

```
md5sum -c md5sums
```

Captura de la página 15 del documento fuente.

Los comandos utilizados fueron:

```
cd $LFS/sources
```

```
wget https://www.linuxfromscratch.org/lfs/view/12.4-systemd/wget-list-systemd\
```

<https://www.linuxfromscratch.org/lfs/view/12.4-systemd/md5sums>

```
lfs@src:/lfs/sources$ wget https://www.linuxfromscratch.org/lfs/view/12.4-systemd/wget-list-systemd \
https://www.linuxfromscratch.org/lfs/view/12.4-systemd/md5sums
--2025-10-19 23:35:51-- https://www.linuxfromscratch.org/lfs/view/12.4-systemd/wget-list-systemd
Resolving www.linuxfromscratch.org (www.linuxfromscratch.org)... 208.118.60.65
Connecting to www.linuxfromscratch.org (www.linuxfromscratch.org):80... connected.
HTTP request sent, awaiting response... 200 OK
Length: 5769 (5.6K)
Saving to: 'wget-list-systemd'

wget-list-systemd 100%[=====] 5.63K --.-KB/s in 0.001s

2025-10-19 23:35:52 (4.12 MB/s) - 'wget-list-systemd' saved (5769/5769)

--2025-10-19 23:35:52-- https://www.linuxfromscratch.org/lfs/view/12.4-systemd/md5sums
Resolving existing connection to www.linuxfromscratch.org:443.
HTTP request sent, awaiting response... 200 OK
Length: 4922 (4.8K)
Saving to: 'md5sums'

md5sums 100%[=====] 4.81K --.-KB/s in 0s

2025-10-19 23:35:53 (255 MB/s) - 'md5sums' saved (4922/4922)

FINISHED --2025-10-19 23:35:53--
Total wall clock time: 1.9s
Downloaded: 2 Files, 10K in 0.001s (7.53 MB/s)
```

```
wget -c -i wget-list-systemd --directory-prefix=$LFS/sources
```

```
sed -i 's/\r$//' md5sums
```

```
md5sum -c md5sums
```

Problemas encontrados:

Solución aplicada (sugerido por la IA)

- **Descargas incompletas/corruptas**
 - Al correr `md5sum -c md5sums` salían muchos **“FAILED open or read / No such file or directory”** y uno que otro **“computed checksum did NOT match”**.
 - Causa: algunos tarballs no se descargaron o quedaron cortados.
- **Ruta de salida sin permisos**
 - Intentamos guardar logs/archivos en .. (el padre de `$LFS/sources`, o sea `/mnt/lfs`), que es de **root**.
 - Síntoma: **“Permission denied”** y **“No such file or directory”** para `../md5-check.log`, `../need-redownload.txt`, etc.
- **Mirror caído/bloqueado (<ftp.gnu.org>)**
 - Al re-descargar ciertos paquetes de GNU: **“Connection refused”** contra <ftp.gnu.org>.
 - Causa: mirror inaccesible en ese momento / rechazos a 443
- **(Latente) Riesgo de mezclar listas de otra versión**
 - Diferencia entre `.../view/12.4-systemd/...` (foto fija) y `.../downloads/stable-systemd/...` (alias a la última). Si se mezclan, los MD5 no coinciden

3. Verificación MD5 de fuentes

Fecha: 21/10/2025 **Páginas:** 16

Resumen: Validar integridad de tarballs descargados contra checksums del libro. Se ejecuta nuevamente la verificación guardando logs con tee; se arma un listado de paquetes faltantes y se re-descargan; verificación final con grep reporta 'Todo OK' si no hay discrepancias. Verificación final reporta 'Todo OK'.

Comandos (tal como aparecen):

```
md5sum -c md5sums | tee md5-check.log  
md5sum -c md5sums | tee md5-check-final.log
```

Captura de la página 16 del documento fuente.

Solución aplicada (sugerido por la IA)

- **Trabajar SIEMPRE dentro de `$LFS/sources` (como usuario `lfs`)**
 - Guardar ahí logs y listas para evitar permisos de `/mnt/lfs:`
 - `cd $LFS/sources`
 - `sed -i 's/\r$//' md5sums`
 - `md5sum -c md5sums | tee md5-check.log`
- **Fijar versión del libro (12.4 systemd) y usar su par correcto**
 - Descargamos `wget-list-systemd` y `md5sums` desde:
 - <https://www.linuxfromscratch.org/lfs/view/12.4-systemd/wget-list-systemd>
 - <https://www.linuxfromscratch.org/lfs/view/12.4-systemd/md5sums>
 - Así evitamos cambios de “stable” que rompan checksums.
- **Re-descargar SOLO los faltantes/corruptos**
 - Generamos lista:
 - `awk -F: '/: FAILED|No such file|NOT FOUND/ {print $1}' md5-check.log | sort -u > need.txt`
 - Para cada uno: borrar y bajar de nuevo desde la URL oficial que sale en `wget-list-systemd`:
 - ```
while read -r f; do
 rm -f "$f"
 url=$(grep -F "$f" wget-list-systemd | head -n1)
 [-z "$url"] && url=$(grep -F "$f" wget-list-systemd | head -n1)
 wget -c "$url"
done < need.txt
```
- **Cambiar de mirror cuando `ftp.gnu.org` falla**
  - Sustituimos el host por `ftpmirror.gnu.org` (o seguimos redirecciones a mirrors HTTPS):
  - `url="{url//ftp.gnu.org/ftpmirror.gnu.org}"`
  - `wget --tries=6 --timeout=25 --retry-connrefused "$url"`
  - Para casos puntuales (`sed`, `tar`, `texinfo`, `readline`) los bajamos directo desde `ftpmirror.gnu.org`.
- **Verificación final**
  - Repetimos:
  - `md5sum -c md5sums | tee md5-check-final.log`
  - `grep -v ': OK' md5-check-final.log || echo "Todo OK ✅"`



## 4. Sanity checks de toolchain

Fecha: 6/11/2025 Páginas: 24, 25, 26

**Resumen:** Verificar rutas de enlazado y que el ejecutable use el enlazador/libc esperados. Se revisan crt\*.o, rutas de include, SEARCH paths del linker y referencias a libc.so.6 mediante dummy.log.

**Comandos (tal como aparecen):**

```
verbose &> dummy.log readelf -l a.out | grep ': /lib'
1. grep -E -o "$LFS/lib.*/S?crt[1in].*succeeded" dummy.log
2. grep -B3 "^ $LFS/usr/include" dummy.log
1. grep 'SEARCH.*/usr/lib' dummy.log | sed 's|; |\n|g'
1. grep "/lib.*/libc.so.6 " dummy.log
2. grep found dummy.log
1. rm -v a.out dummy.log
$LFS_TGT-gcc -x c dummy.c -o a.out -v -Wl,--verbose &> dummy.log
readelf -l a.out | grep ': /lib'
```

Captura de la página 24 del documento fuente.



- ix. Nos aseguramos de que estemos configurados para usar los archivos de inicio correctos y verificamos que el compilador esté buscando los archivos de encabezado correctos:
  - 1. `grep -E -o "SLFS/lib.*S?crt[lin].*succeeded" dummy.log`
  - 2. `grep -B3 "^ SLFS/usr/include" dummy.log`
- x. Verificamos que el nuevo enlazador se esté utilizando con las rutas de búsqueda correctas:
  - 1. `grep 'SEARCH.*usr/lib' dummy.log | sed 's|;|\\n|g'`
- xi. Nos aseguramos de que estamos usando la libc correcta y que GCC esté utilizando el enlazador dinámico correcto:
  - 1. `grep "/lib.*libc.so.6 " dummy.log`
  - 2. `grep found dummy.log`
- xii. Limpiamos los test files:
  - 1. `rm -v a.out dummy.log`

[illegible]

Problemas encontrados:

1. Variables de entorno perdidas:

**Síntoma:** -bash: export: `=/mnt/lfs': no es un identificador válido, echo "\$LFS" vacío, command -v "\$LFS TGT-gcc" no mostraba nada.

**Causa:** Cambiaste de usuario/shell (root ↔ lfs) y se perdió el entorno; además hubo un pegado con un = inicial.

**Arreglo (sugerido por la IA):**

- Como **root**: `echo 'export LFS=/mnt/lfs' >> /root/.bashrc ; source /root/.bashrc`
- Como **lfs**: `source ~/.bash_profile` (donde ya están `LFS`, `LFS_TGT`, `PATH`, etc.).

## 5. Glibc-2.42: suite de tests (make check)

Fecha: 30/12/2025   Páginas: 97, 98

**Resumen:** Ejecutar la batería de pruebas del paquete para validar build/instalación. Se re-ejecutan tests individuales ajustando TIMEOUTFACTOR. Se buscan time-outs en salidas de tests. Se listan FAILs desde archivos \*.sum. El documento menciona 6 FAIL(s) iniciales. Se observan fallos por /bin/sh inexistente; se sugiere corregir enlaces/symlinks. Se observan fallos por /bin/cat inexistente; se sugiere convertir /bin y /sbin en symlinks.

**Comandos (tal como aparecen):**

```
make check
grep "Timed out" $(find -name *.out)
grep '^FAIL:' $(find -name *.sum) | sort -u
TIMEOUTFACTOR=30 make -j1 test t=nptl/tst-mutex10
TIMEOUTFACTOR=30 make -j1 test t=nptl/tst-thread-affinity-sched
TIMEOUTFACTOR=30 make -j1 test t=stdlib/test-bz22786
TIMEOUTFACTOR=30 make -j1 test t=stdlib/test-cxa_atexit-race2
TIMEOUTFACTOR=30 make -j1 test t=stdlib/test-bz22786
TIMEOUTFACTOR=30 make -j1 test t=nptl/tst-mutex10
TIMEOUTFACTOR=30 make -j1 test t=nptl/tst-thread-affinity-sched
TIMEOUTFACTOR=30 make -j1 test t=stdio-common/test-popen
```

Captura de la página 97 del documento fuente.

make check

```
(lfs chroot) root:/sources/glibc-2.42/build# make check_
```

[illegible]

- i) Identificamos los time-outs con el siguiente comando sugerido por el libro

```
grep "Timed out" $(find -name *.out)
```

```
(lfs chroot) root:/sources/glibc-2.42/build# grep "Timed out" $(find -name *.out)
./nptl/tst-mutex10.out:Timed out: killed the child process
./nptl/tst-thread-affinity-sched.out:Timed out: killed the child process
./stdlib/test-cxa_atexit-race2.out:Timed out: killed the child process
./stdlib/test-bz22786.out:Timed out: killed the child process
(lfs chroot) root:/sources/glibc-2.42/build#
```

- j) Sacamos una lista de cuales son los 6 FAIL (sugerido por la IA)

```
grep '^FAIL:' $(find -name *.sum) | sort -u
```

```
(lfs chroot) root:/sources/glibc-2.42/build# grep "FAIL:" $(find -name *.sum) | sort -u
./io/subdir-tests.sum:FAIL: io/tst-lchmod
./nptl/subdir-tests.sum:FAIL: nptl/tst-mutex10
./nptl/subdir-tests.sum:FAIL: nptl/tst-thread-affinity-sched
./stdio-common/subdir-tests.sum:FAIL: stdio-common/test-popen
./stdlib/subdir-tests.sum:FAIL: stdlib/test-bz22706
./stdlib/subdir-tests.sum:FAIL: stdlib/test-cxa_atexit-race2
./tests.sum:FAIL: io/tst-lchmod
./tests.sum:FAIL: nptl/tst-mutex10
./tests.sum:FAIL: nptl/tst-thread-affinity-sched
./tests.sum:FAIL: stdio-common/test-popen
./tests.sum:FAIL: stdlib/test-bz22706
./tests.sum:FAIL: stdlib/test-cxa_atexit-race2
(lfs chroot) root:/sources/glibc-2.42/build#
```

- k) Reintentamos tests (elegimos 30)

MAKEFLAGS=

w) Eliminamos el directorio de Glibc-2.42

```
rm -rf glibc-2.42
```

```
(lfs chroot) root:/sources/glibc-2.42/build# cd ../../
(lfs chroot) root:/sources# rm -rf glibc-2.42
(lfs chroot) root:/sources#
```

#### Problemas encontrados

- Los tests arrojaban el siguiente error: make: /bin/sh: No such file or directory, esto debido a que /bin ya estaba como symlink a /usr/bin, pero no existía /usr/bin/sh, así que tampoco /bin/sh.
  - Solución encontrada (sugerido por la IA)
    - Se creó correctamente el enlace con el comando `ln -sv bash /usr/bin/sh`
- Los tests también arrojaban el siguiente error:

```
/bin/cat: No such file or directory
```

```
FAIL: stdio-common/test-popen
```

Esto debido a que /bin y /sbin eran directorios reales creados en el pasado con `mkdir` por error, con dueño 1001:1001, cuando deberían ser symlinks a /usr/bin y /usr/sbin. Por eso /bin/cat no existía, aunque sí existía /usr/bin/cat.

- Solución encontrada (sugerido por la IA)
    - Convertimos /bin y /sbin a symlinks a los directorios correspondientes
- ```
/bin -> usr/bin
```
- ```
/sbin -> usr/sbin
```
- Al ejecutar `make check` salían como FAIL los siguientes procesos
- ```
stdlib/test-bz22786
```
- ```
stdlib/test-cxa_atexit-race2
```
- ```
nptl/tst-mutex10
```
- ```
nptl/tst-thread-affinity-sched
```
- Solución encontrada
    - Re-ajustamos los tests individuales con más margen como sugiere el libro

## 6. Zlib-1.3.1: suite de tests (make check)

Fecha: 1/01/2026   Páginas: 105

**Resumen:** Ejecutar la batería de pruebas del paquete para validar build/instalación.

**Comandos (tal como aparecen):**

`make check`

Captura de la página 105 del documento fuente.

#### c) Compilamos el paquete

make

```

(life check) root@source:zlib-1.3.1# make
gcc -D _LARGEFILE64_SOURCE=1 -D_WIDECHAR -I. -c -o example.o test/example.c
gcc -D _LARGEFILE64_SOURCE=1 -D_WIDECHAR -c -o adler32.o adler32.c
gcc -D _LARGEFILE64_SOURCE=1 -D_WIDECHAR -c -o crc32.o crc32.c
gcc -D _LARGEFILE64_SOURCE=1 -D_WIDECHAR -c -o deflate.o deflate.c
gcc -D _LARGEFILE64_SOURCE=1 -D_WIDECHAR -c -o infback.o infback.c
gcc -D _LARGEFILE64_SOURCE=1 -D_WIDECHAR -c -o inffast.o inffast.c
gcc -D _LARGEFILE64_SOURCE=1 -D_WIDECHAR -c -o inflate.o inflate.c
gcc -D _LARGEFILE64_SOURCE=1 -D_WIDECHAR -c -o inftrns.o inftrns.c
gcc -D _LARGEFILE64_SOURCE=1 -D_WIDECHAR -c -o trees.o trees.c
gcc -D _LARGEFILE64_SOURCE=1 -D_WIDECHAR -c -o zutil.o zutil.c
gcc -D _LARGEFILE64_SOURCE=1 -D_WIDECHAR -c -o compress.o compress.c
gcc -D _LARGEFILE64_SOURCE=1 -D_WIDECHAR -c -o uncompress.o uncompress.c
gcc -D _LARGEFILE64_SOURCE=1 -D_WIDECHAR -c -o gzclose.o gzclose.c
gcc -D _LARGEFILE64_SOURCE=1 -D_WIDECHAR -c -o gzlib.o gzlib.c
gcc -D _LARGEFILE64_SOURCE=1 -D_WIDECHAR -c -o gzread.o gzread.c
gcc -D _LARGEFILE64_SOURCE=1 -D_WIDECHAR -c -o gzwrite.o gzwrite.c
ar rc libz.a adler32.o crc32.o deflate.o infback.o inffast.o inflate.o inftrns.o trees.o zutil.o compress.o uncompress.o gzclose.o gzlib.o gzread.o gzwrite.o
gcc -D _LARGEFILE64_SOURCE=1 -D_WIDECHAR -o example example.o -L. libz.a
gcc -D _LARGEFILE64_SOURCE=1 -D_WIDECHAR -I. -c -o minigzip.o test/minigzip.c
gcc -D _LARGEFILE64_SOURCE=1 -D_WIDECHAR -D_FPIC -c -o obj.o adler32.o adler32.c
gcc -D _LARGEFILE64_SOURCE=1 -D_WIDECHAR -D_FPIC -c -o obj.o crc32.o crc32.c
gcc -D _LARGEFILE64_SOURCE=1 -D_WIDECHAR -D_FPIC -c -o obj.o deflate.o deflate.c
gcc -D _LARGEFILE64_SOURCE=1 -D_WIDECHAR -D_FPIC -c -o obj.o infback.o infback.c
gcc -D _LARGEFILE64_SOURCE=1 -D_WIDECHAR -D_FPIC -c -o obj.o inffast.o inffast.c
gcc -D _LARGEFILE64_SOURCE=1 -D_WIDECHAR -D_FPIC -c -o obj.o inflate.o inflate.c
gcc -D _LARGEFILE64_SOURCE=1 -D_WIDECHAR -D_FPIC -c -o obj.o inftrns.o inftrns.c
gcc -D _LARGEFILE64_SOURCE=1 -D_WIDECHAR -D_FPIC -c -o obj.o trees.o trees.c
gcc -D _LARGEFILE64_SOURCE=1 -D_WIDECHAR -D_FPIC -c -o obj.o zutil.o zutil.c
gcc -D _LARGEFILE64_SOURCE=1 -D_WIDECHAR -D_FPIC -c -o obj.o compress.o compress.c
gcc -D _LARGEFILE64_SOURCE=1 -D_WIDECHAR -D_FPIC -c -o obj.o uncompress.o uncompress.c
gcc -D _LARGEFILE64_SOURCE=1 -D_WIDECHAR -D_FPIC -c -o obj.o gzclose.o gzclose.c
gcc -D _LARGEFILE64_SOURCE=1 -D_WIDECHAR -D_FPIC -c -o obj.o gzlib.o gzlib.c
gcc -D _LARGEFILE64_SOURCE=1 -D_WIDECHAR -D_FPIC -c -o obj.o gzread.o gzread.c
gcc -D _LARGEFILE64_SOURCE=1 -D_WIDECHAR -D_FPIC -c -o obj.o gzwrite.o gzwrite.c
gcc -shared -Wl,-soname,libz.so.1,-version-script,libz.map -D_FPIC -o libz.so.1 obj.o adler32.o adler32.c crc32.o crc32.c deflate.o deflate.c infback.o infback.c inftrns.o inftrns.c trees.o trees.c zutil.o zutil.c compress.o compress.c uncompress.o uncompress.c gzclose.o gzclose.c gzlib.o gzlib.c gzread.o gzread.c gzwrite.o gzwrite.c
ln -s libz.so.1.3.1 libz.so.1
ln -s libz.so.1.3.1 libz.so
gcc -D _LARGEFILE64_SOURCE=1 -D_WIDECHAR -o examplex example.o -L. libz.so.1.3.1
gcc -D _LARGEFILE64_SOURCE=1 -D_WIDECHAR -o minigzipx minigzip.o -L. libz.so.1.3.1
gcc -D _LARGEFILE64_SOURCE=1 -D_WIDECHAR -I. -D_FILE_OFFSET_BITS=64 -c -o example64.o test/example.c
gcc -D _LARGEFILE64_SOURCE=1 -D_WIDECHAR -o example64 example64.o -L. libz.a
gcc -D _LARGEFILE64_SOURCE=1 -D_WIDECHAR -I. -D_FILE_OFFSET_BITS=64 -c -o minigzip64.o test/minigzip.c
gcc -D _LARGEFILE64_SOURCE=1 -D_WIDECHAR -o minigzip64 minigzip64.o -L. libz.a
(life check) root@source:zlib-1.3.1#

```

#### d) Realizamos test de los resultados

make check

```

(life check) root@source:zlib-1.3.1# make check
hello world
zlib version 1.3.1 - 0x1310, compile flags - 0xa9
uncompress(): hello, hello!
gzread(): hello, hello!
gzwrite(): after gzseek: hello!
inflate(): hello, hello!
large_inflate(): OK
after inflateSync(): hello, hello!
inflate with dictionary: hello, hello!
*** zlib test OK ***

hello world
zlib version 1.3.1 - 0x1310, compile flags - 0xa9
uncompress(): hello, hello!
gzread(): hello, hello!
gzwrite(): after gzseek: hello!
inflate(): hello, hello!
large_inflate(): OK
after inflateSync(): hello, hello!
inflate with dictionary: hello, hello!
*** zlib shared test OK ***

hello world
zlib version 1.3.1 - 0x1310, compile flags - 0xa9
uncompress(): hello, hello!
gzread(): hello, hello!
gzwrite(): after gzseek: hello!
inflate(): hello, hello!
large_inflate(): OK
after inflateSync(): hello, hello!
inflate with dictionary: hello, hello!
*** zlib 64-bit test OK ***
(life check) root@source:zlib-1.3.1#

```

#### e) Instalamos el paquete

make install



## 7. Xz-5.8.1: suite de tests (make check)

Fecha: 1/01/2026 Páginas: 111

**Resumen:** Ejecutar la batería de pruebas del paquete para validar build/instalación.

**Comandos (tal como aparecen):**

`make check`

Captura de la página 111 del documento fuente.

[illegible]

- c) Compilamos el paquete

make

```
(lfs chroot) root:/sources/xz-5.8.1# make
g.o lzmainfo-tuklib_exit.o ../src/liblzma/liblzma_la -lpthread
libtool: link: gcc -fvisibility=hidden -Wall -Wextra -Wvla -Wformat=2 -Winit-self -Wmissing-include-dirs -Wshift-overlo
w2 -Wstrict-overflow=3 -Wllocc-zero -Wduplicated-cond -Wfloat-equal -Wundef -Wshadow -Wpointer-arith -Wbad-function-cas
t -Wwrite-strings -Wdate-time -Wsign-conversion -Wfloat-conversion -Wlogical-op -Waggregate-return -Wstrict-prototypes -
Wold-style-definition -Wmissing-prototypes -Wmissing-declarations -Wredundant-decls -Wimplicit-fallthrough -Wimplicit-fa
llthrough=5 -Wmissing-variable-declarations -g -O2 -o .libs/liblzmainfo lzmainfo.o lzmainfo.o lzmainfo-tuklib_programme.o lzma
info-tuklib_mbst_r_nonprint.o lzmainfo-tuklib_mbst_r_width.o lzmainfo-tuklib_mbst_r_wrap.o lzmainfo-tuklib_exit.o ../src
c/liblzma/.libs/liblzma.so -lpthread -pthread
make(3): Leaving directory '/sources/xz-5.8.1/src/lzmainfo'
making all in scripts
make(3): Entering directory '/sources/xz-5.8.1/src/scripts'
make(3): Nothing to be done for 'all'.
make(3): Leaving directory '/sources/xz-5.8.1/src/scripts'
make(3): Entering directory '/sources/xz-5.8.1/src'
make(3): Nothing to be done for 'all-am'.
make(3): Leaving directory '/sources/xz-5.8.1/src'
make(2): Leaving directory '/sources/xz-5.8.1/src'
making all in po
make(2): Entering directory '/sources/xz-5.8.1/po'
make(2): Nothing to be done for 'all'.
make(2): Leaving directory '/sources/xz-5.8.1/po'
making all in tests
make(2): Entering directory '/sources/xz-5.8.1/tests'
make(2): Nothing to be done for 'all'.
make(2): Leaving directory '/sources/xz-5.8.1/tests'
make(2): Entering directory '/sources/xz-5.8.1'
make(2): Leaving directory '/sources/xz-5.8.1'
make(1): Leaving directory '/sources/xz-5.8.1'
(lfs chroot) root:/sources/xz-5.8.1#
```

- d) Ejecutamos el siguiente comando para probar los resultados

make check

## 8. Lz4-1.10: suite de tests (make check)

Fecha: 1/01/2026   Páginas: 114

**Resumen:** Ejecutar la batería de pruebas del paquete para validar build/instalación.

**Comandos (tal como aparecen):**

```
make -j1 check
```

Captura de la página 114 del documento fuente.

```
(lfs chroot) root:/sources# make BUILD_STATIC=no PREFIX=/usr
(lfs chroot) root:/sources# cd lz4-1.10.0
(lfs chroot) root:/sources/lz4-1.10.0# make BUILD_STATIC=no PREFIX=/usr
lz4-1.10.0-tests/encode/DictLists.tst
lz4-1.10.0-tests/datagen.c
lz4-1.10.0-tests/datagen.h
lz4-1.10.0-tests/datagen.c.c
lz4-1.10.0-tests/decompress-partial-stdoutDict.c
lz4-1.10.0-tests/decompress-partial.c
lz4-1.10.0-tests/frameTest.c
lz4-1.10.0-tests/fullbench.c
lz4-1.10.0-tests/fuzzer.c
lz4-1.10.0-tests/goldenSamples/
lz4-1.10.0-tests/goldenSamples-skip.bis
lz4-1.10.0-tests/knownDict.c
lz4-1.10.0-tests/knownDict.h
lz4-1.10.0-tests/roundTripTest.c
lz4-1.10.0-tests/test-lz4-sh1.py
lz4-1.10.0-tests/test-lz4-basic.sh
lz4-1.10.0-tests/test-lz4-contentSize.sh
lz4-1.10.0-tests/test-lz4-dict.sh
lz4-1.10.0-tests/test-lz4-fast-hupfile.sh
lz4-1.10.0-tests/test-lz4-frame-concatenation.sh
lz4-1.10.0-tests/test-lz4-list.py
lz4-1.10.0-tests/test-lz4-multiple-legacy.sh
lz4-1.10.0-tests/test-lz4-multiple.sh
lz4-1.10.0-tests/test-lz4-opt-parser.sh
lz4-1.10.0-tests/test-lz4-skipable.sh
lz4-1.10.0-tests/test-lz4-specs.sh
lz4-1.10.0-tests/test-lz4-speed.py
lz4-1.10.0-tests/test-lz4-testmode.sh
lz4-1.10.0-tests/test-lz4-versions.py
lz4-1.10.0-tests/test-lz4c-hupfile.sh
lz4-1.10.0-tests/test_custom_block_sizes.sh
lz4-1.10.0-tests/test_install.sh
lz4-1.10.0-tests/unicode_list.sh
(lfs chroot) root:/sources# make BUILD_STATIC=no PREFIX=/usr
make: *** No targets specified and no makefile found. Stop.
(lfs chroot) root:/sources# cd lz4-1.10.0
(lfs chroot) root:/sources/lz4-1.10.0# make BUILD_STATIC=no PREFIX=/usr
make[1]: Entering directory '/sources/lz4-1.10.0/lib'
compiling dynamic library 1.10.0
creating versioned links
creating phony file
make[1]: Leaving directory '/sources/lz4-1.10.0/lib'
make[1]: Entering directory '/sources/lz4-1.10.0/program'
cc -o building with multithreading support
make[1]: Leaving directory '/sources/lz4-1.10.0/program'
lz4 build completed
```

c) Ejecutamos el siguiente comando para probar los resultados

make -j1 check

```
(lfs chroot) root:/sources/lz4-1.10.0# make -j1 check
datagen (size) (args)
Arguments :
 -s# : generate s data (default:45536)
 -s# : Select seed (default:0)
 -P# : Select compressibility in % (range [0-100])
 -h : display help and exit
Special swines :
 -P0 : generate incompressible noise
 -P100 : generate sparse files
+ dd if=tmp-dict-20614061 of=tmp-dict-20614061-tail bs=1 count=45536 skip=45536
0+0 records in
0+0 records out
0 bytes copied, 0.000290715 s, 0.0 kB/s
+ lz4 -B stdin tmp-dict-data-12000 -c
+ lz4 -d tmp-dict-20614061-tail
+ diff - tmp-dict-data-12000
+ lz4 -B stdin tmp-dict-data-12000 -c
+ diff - tmp-dict-data-12000
+ lz4 -d tmp-dict-20614061
+ for i in 0 1 4 120 32767 32768 32769 65536 65537 90303 90304 90305 131071 131072 131073
+ datagen -p20614061
Compressible data generator
Usage :
 datagen (size) (args)
Arguments :
 -s# : generate s data (default:45536)
 -s# : Select seed (default:0)
 -P# : Select compressibility in % (range [0-100])
 -h : display help and exit
Special swines :
 -P0 : generate incompressible noise
 -P100 : generate sparse files
+ dd if=tmp-dict-20614061 of=tmp-dict-20614061-tail bs=1 count=45536 skip=45537
0+0 records in
0+0 records out
0 bytes copied, 0.000294623 s, 0.0 kB/s
+ lz4 -B stdin tmp-dict-data-12000 -c
+ lz4 -d tmp-dict-20614061-tail
+ diff - tmp-dict-data-12000
+ lz4 -B stdin tmp-dict-data-12000 -c
+ lz4 -d tmp-dict-20614061
+ diff - tmp-dict-data-12000
+ rm tmp-dict tmp-dict-20614061 tmp-dict-20614061-tail tmp-dict-data-12000 tmp-dict-sample-0 tmp-dict-sample-10a tmp-dict-sample-32a
make[1]: Leaving directory '/sources/lz4-1.10.0-tests'
(lfs chroot) root:/sources/lz4-1.10.0#
```

d) Instalamos el paquete

make BUILD\_STATIC=no PREFIX=/usr install

## 9. Zstd-1.5.7: suite de tests (make check)

Fecha: 1/01/2026 Páginas: 117

**Resumen:** Ejecutar la batería de pruebas del paquete para validar build/instalación.

**Comandos (tal como aparecen):**

`make check`

Captura de la página 117 del documento fuente.

- c) Ejecutamos el siguiente comando para probar los resultados

make check

```
(lfs chroot) root:/sources/zstd-1.5.7# make check
roundTripTest: Datagen -g2M 1 zstd -d2 --single-thread --long 1 zstd -d2 --single-thread --long
*** Zstdand CLI (64-bit) v1.5.7, by Yann Collet ***
/testbed: (9.00 MiB => 2.02 MiB, /stdout%)
roundTripTest: Datagen -g1M -F5B 1 zstd -v1 --single-thread --long-29 1 zstd -d --memory-512MB
*** Zstdand CLI (64-bit) v1.5.7, by Yann Collet ***
/testbed: (1.000 MiB => 320 KiB, /stdout%)
roundTripTest: Datagen -g1M -F5B 1 zstd -v1 --single-thread --long-29 --zstd-ulog-2B 1 zstd -d --memory-256MB
*** Zstdand CLI (64-bit) v1.5.7, by Yann Collet ***
/testbed: (1.000 MiB => 320 KiB, /stdout%)
roundTripTest: Datagen -g1M -F5B 1 zstd -v1 --single-thread --long-29 1 zstd -d --zstd-ulog-2B --memory-512MB
*** Zstdand CLI (64-bit) v1.5.7, by Yann Collet ***
/testbed: (1.000 MiB => 320 KiB, /stdout%)
./playTests.sh: line 1652: 1: integer expected

====> zstd aspic tests
roundTripTest: Datagen -g2M 1 zstd -d3 --aspicio --format-zstd 1 zstd -d3 --aspicio --format-zstd
*** Zstdand CLI (64-bit) v1.5.7, by Yann Collet ***
/testbed: (2.00 MiB => 613 KiB, /stdout%)
roundTripTest: Datagen -g2M 1 zstd -d3 --no-aspicio --format-zstd 1 zstd -d3 --no-aspicio --format-zstd
*** Zstdand CLI (64-bit) v1.5.7, by Yann Collet ***
/testbed: (2.00 MiB => 613 KiB, /stdout%)
roundTripTest: Datagen -g2M 1 zstd -d3 --aspicio --format-gzip 1 zstd -d3 --aspicio --format-gzip
*** Zstdand CLI (64-bit) v1.5.7, by Yann Collet ***
/testbed: (2.00 MiB => 616 KiB, /stdout%)
roundTripTest: Datagen -g2M 1 zstd -d3 --no-aspicio --format-gzip 1 zstd -d3 --no-aspicio --format-gzip
*** Zstdand CLI (64-bit) v1.5.7, by Yann Collet ***
/testbed: (2.00 MiB => 616 KiB, /stdout%)
roundTripTest: Datagen -g2M 1 zstd -d3 --aspicio --format-lzma 1 zstd -d3 --aspicio --format-lzma
*** Zstdand CLI (64-bit) v1.5.7, by Yann Collet ***
/testbed: (2.00 MiB => 613 KiB, /stdout%)
roundTripTest: Datagen -g2M 1 zstd -d3 --no-aspicio --format-lzma 1 zstd -d3 --no-aspicio --format-lzma
*** Zstdand CLI (64-bit) v1.5.7, by Yann Collet ***
/testbed: (2.00 MiB => 613 KiB, /stdout%)
roundTripTest: Datagen -g2M 1 zstd -d3 --aspicio --format-lz4 1 zstd -d3 --aspicio --format-lz4
*** Zstdand CLI (64-bit) v1.5.7, by Yann Collet ***
/testbed: (2.00 MiB => 612 KiB, /stdout%)
roundTripTest: Datagen -g2M 1 zstd -d3 --no-aspicio --format-lz4 1 zstd -d3 --no-aspicio --format-lz4
*** Zstdand CLI (64-bit) v1.5.7, by Yann Collet ***
/testbed: (2.00 MiB => 612 KiB, /stdout%)
Shipping large data tests

All tests completed successfully
=====
make[1]: Leaving directory '/sources/zstd-1.5.7/tests'
(lfs chroot) root:/sources/zstd-1.5.7#
```

- d) Instalamos el paquete

make prefix=/usr install

```
(lfs chroot) root:/sources/zstd-1.5.7# make prefix=/usr install
make[1]: Entering directory '/sources/zstd-1.5.7/lib'
creating pkgconfig
Installing static library
Installing shared library
Installing includes
zstd static and shared library installed
make[1]: Leaving directory '/sources/zstd-1.5.7/lib'
make[1]: Entering directory '/sources/zstd-1.5.7/programs'
Installing binaries
Installing man pages
zstd installation completed
make[1]: Leaving directory '/sources/zstd-1.5.7/programs'
(lfs chroot) root:/sources/zstd-1.5.7#
```

- e) Removemos la librería estática

rm -v /usr/lib/libzstd.a

```
(lfs chroot) root:/sources/zstd-1.5.7# rm -v /usr/lib/libzstd.a
removed '/usr/lib/libzstd.a'
(lfs chroot) root:/sources/zstd-1.5.7#
```

- f) Eliminamos el directorio zstd-1.5.7

## 10. File-5.46: suite de tests (make check)

Fecha: 2/01/2025 Páginas: 119

**Resumen:** Ejecutar la batería de pruebas del paquete para validar build/instalación.

**Comandos (tal como aparecen):**

`make check`

Captura de la página 119 del documento fuente.





## **11. M4-1.4.20: suite de tests (make check)**

**Fecha:** 2/01/2025   **Páginas:** 125

**Resumen:** Ejecutar la batería de pruebas del paquete para validar build/instalación.

**Comandos (tal como aparecen):**

`make check`

Captura de la página 125 del documento fuente.

```
(lfs chroot) root:/sources# cd m4-1.4.20
(lfs chroot) root:/sources/m4-1.4.20# ./configure --prefix=/usr
checking whether select supports a B argument... yes
checking whether select detects invalid fd... yes
checking whether select validates arguments... yes
checking whether sleep is declared... yes
checking for working sleep... yes
checking for sockets... yes
checking for catgets... yes
checking whether signal handles trailing slash correctly... yes
checking for IPv6 sockets... (cached) yes
checking for IPv6 sockets... (cached) yes
checking for UNIX domain sockets... yes
checking whether time() works... guessing no
checking for localtime... yes
checking for gettimeofday return type... int
checking whether localtime strips TIME... yes
checking whether utime works... guessing yes
checking whether utime is declared... yes
checking whether an open file can be renamed... yes
checking if changedir is tested... no
checking which shell to use for shopt... /bin/sh
checking if malloc debugging is tested... no
checking whether RL3 is required... yes
checking for realpath... /usr/bin/realpath
checking for realpath... /usr/bin/realpath
checking for getcwd... /usr/bin/getcwd
checking for mkdir... /usr/bin/mkdir
checking for CXXFLAGS_Cppgchdir... (cached) no
checking for CXXFLAGS_PreferenceLanguage... (cached) no
checking for GNU gettext in libc... yes
checking whether to use RL3... yes
checking where the gettext function comes from... libc
checking that generated files are newer than configure... done
configure: creating config.status
config.status: creating Makefile
config.status: creating doc-Makefile
config.status: creating lib-Makefile
config.status: creating po-Makefile.in
config.status: creating src-Makefile
config.status: creating tests-Makefile
config.status: creating checks-Makefile
config.status: creating examples-Makefile
config.status: creating libconf.m4
config.status: executing default commands
config.status: executing stamp-h commands
config.status: executing po-directories commands
config.status: creating po-POTFILES
config.status: creating po-Makefile
(lfs chroot) root:/sources/m4-1.4.20
```

c) Compilamos el paquete

make

```
(lfs chroot) root:/sources/m4-1.4.20# make
CC obj.o
CC gnu99.o
CC GnuLib tests
CC You can ignore compiler warnings in this directory.
make all-recursive
make[1]: Entering directory '/sources/m4-1.4.20-tests'
Building all in .
make[1]: Entering directory '/sources/m4-1.4.20-tests'
CC locale.o
CC args_init.o
CC gl_array_list.o
CC gl_array_sort.o
CC htoab.o
CC C-strcatstr.o
CC C-strncatcmp.o
CC CStrtok.o
CC findprog.o
CC lexchar.o
CC listintr.o
CC offintr.o
CC uftintr.o
CC uniointr.o
CC iact1.o
CC memnt_explicit.o
CC memint.o
CC pthread_rwlock.o
CC pthread_sigmask.o
CC read_file.o
CC sockets.o
CC str_endswith.o
CC str_startswith.o
CC sys_socket.o
CC glthread_thread.o
CC time.o
CC use_iter.o
CC memcat_filenames.o
CC getopt.o
CC streamer_F.o
CC libtests.o
CCLD current-localc
CC test-localcharset.o
CCLD test-localcharset
make[1]: Leaving directory '/sources/m4-1.4.20-tests'
make[1]: Leaving directory '/sources/m4-1.4.20-tests'
make[1]: Leaving directory '/sources/m4-1.4.20'
(lfs chroot) root:/sources/m4-1.4.20#
```

d) Ejecutamos el siguiente comando para probar los resultados

make check

## 12. Flex-2.6.4: suite de tests (make check)

Fecha: 2/01/2025   Páginas: 131

**Resumen:** Ejecutar la batería de pruebas del paquete para validar build/instalación.

**Comandos (tal como aparecen):**

`make check`

Captura de la página 131 del documento fuente.



### 13. DejaGNU-1.6.3: suite de tests (make check)

Fecha: 2/01/2025   Páginas: 143

**Resumen:** Ejecutar la batería de pruebas del paquete para validar build/instalación.

**Comandos (tal como aparecen):**

`make check`

Captura de la página 143 del documento fuente.

```
(lfs chroot) root:/sources/dejagnu-1.6.3/build# ./configure --prefix=/usr
checking for a BSD-compatible install... /usr/bin/install -c
checking whether build environment is sane... yes
checking for a thread-safe mkdir -p... /usr/bin/mkdir -p
checking for gawk... gawk
checking whether make sets $(MAKE)... yes
checking whether make supports nested variables... yes
checking whether to enable maintainer-specific portions of Makefiles... no
checking whether make sets $(MAKE)... (cached) yes
checking for gawk... (cached) gawk
checking for gcc... gcc
checking whether the C compiler works... yes
checking for C compiler default output file name... a.out
checking for suffix of executables...
checking whether we are cross compiling... no
checking for suffix of object files... o
checking whether we are using the GNU C compiler... yes
checking whether gcc accepts -g... yes
checking for gcc option to accept ISO C99... none needed
checking whether gcc understands -c and -o together... yes
checking for style of include used by make... GNU
checking dependency style of gcc... gcc3
checking for g++... g++
checking whether we are using the GNU C++ compiler... yes
checking whether g++ accepts -g... yes
checking dependency style of g++... gcc3
checking that generated files are newer than configure... done
configure: creating ./config.status
config.status: creating Makefile
config.status: executing depfiles commands
(lfs chroot) root:/sources/dejagnu-1.6.3/build# makeinfo --html --no-split -o doc/dejagnu.html ../doc/dejagnu.texi
dejagnu.texi:42: warning: no htmlexref.cnf entry found for `dir'
(lfs chroot) root:/sources/dejagnu-1.6.3/build# makeinfo --plaintext -o doc/dejagnu.txt ../doc/dejagnu.texi
(lfs chroot) root:/sources/dejagnu-1.6.3/build# make check
```

- d) Ejecutamos el siguiente comando para probar los resultados

make check

```
(lfs chroot) root:/sources/dejagnu-1.6.3/build# make check
```

```
Running target unix
Using ../baseboards/unix.exp as board description file for target.
Using ../config/unix.exp as generic interface file for target.
Using ../testsuite/./config/unix.exp as tool-and-target-specific interface file.
Running ../testsuite/runtest.lib/libc.exp ...
Running ../testsuite/runtest.lib/clone_output.test ...
Running ../testsuite/runtest.lib/config.test ...
Running ../testsuite/runtest.lib/remote.test ...
Running ../testsuite/runtest.lib/target.test ...
Running ../testsuite/runtest.lib/testcase_group.test ...
Running ../testsuite/runtest.lib/testsuite_can.test ...
Running ../testsuite/runtest.lib/testsuite_file.test ...
Running ../testsuite/runtest.lib/utls.test ...
Running ../testsuite/runtest.main/error.exp ...
Running ../testsuite/runtest.main/options.exp ...
Running ../testsuite/runtest.main/pr42399.exp ...
Running ../testsuite/runtest.main/pr48155.exp ...
Running ../testsuite/runtest.main/stats.exp ...

=== runtest Summary ===
of expected passes 308
DejaGnu version 1.6.3
Expect version 5.45.4
Tcl version 8.6

make[1]: Leaving directory '/sources/dejagnu-1.6.3/build'
(lfs chroot) root:/sources/dejagnu-1.6.3/build#
```

- e) Instalamos el paquete

make install

install -v -dm755 /usr/share/doc/dejagnu-1.6.3

install -v -m644 doc/dejagnu.{html,txt} /usr/share/doc/dejagnu-1.6.3

## 14. Binutils-2.45: suite de tests (make check)

Fecha: 5/01/2026   Páginas: 148

**Resumen:** Ejecutar la batería de pruebas del paquete para validar build/instalación. Se listan FAILs desde archivos \*.sum.

**Comandos (tal como aparecen):**

```
make -k check
grep '^FAIL:' $(find -name '*.log')
```

Captura de la página 148 del documento fuente.

```
checking for windres... no
checking for windmc... no
checking where to find the target ar... just compiled
checking where to find the target as... just compiled
checking where to find the target cc... host tool
checking where to find the target c++... host tool
checking where to find the target c++ for libstdc++... host tool
checking where to find the target dlltool... just compiled
checking where to find the target dsymutil... host tool
checking where to find the target gcc... host tool
checking where to find the target gfortran... host tool
checking where to find the target gcgc... host tool
checking where to find the target gdc... host tool
checking where to find the target gnu2... host tool
checking where to find the target ld... just compiled
checking where to find the target lipo... host tool
checking where to find the target nm... just compiled
checking where to find the target objcopy... just compiled
checking where to find the target objdump... just compiled
checking where to find the target otol... host tool
checking where to find the target ranlib... just compiled
checking where to find the target readelf... just compiled
checking where to find the target strip... just compiled
checking where to find the target windres... just compiled
checking where to find the target windmc... just compiled
checking whether to enable maintainer-specific portions of Makefiles... no
configure: creating ./config.status
config.status: creating Makefile
(lfs chroot) root:/sources/binutils-2.45/build#
```

d) Compilamos el paquete

```
make tooldir=/usr
```

```
(if $chroot) root:/sources/binutils-2.45/build# make tooldir=/usr
```

```
make[1]: Nothing to be done for 'all'.
make[1]: Leaving directory '/sources/binutils-2.45/build-id-gpr'
make[1]: Entering directory '/sources/binutils-2.45/build/id'
CC libidplug.o
GEN libidplug.so
libtool: link warning: ignoring multiple '-rpath's for a shared library
CC libidtestplug_la-testplug.lo
CCLD libidtestplug.so
CC libidtestplug2_la-testplug2.lo
CCLD libidtestplug2.so
CC libidtestplug3_la-testplug3.lo
CCLD libidtestplug3.so
CC libidtestplug4_la-testplug4.lo
CCLD libidtestplug4.so
CGenran.o
CC ldnew-wrapper.a
CC ldsnap.o
CC ldlang.o
CC mcl.o
CC mdcr.o
CC mmio.o
CC msasite.o
CC mspg.o
CC mtcmpl.o
CC mvacr.o
CC mwinc.o
CC mfile.o
CC mlocrf.o
CC plugin.o
CC sha1util.o
GEn Mucript/xstamp
GEn crlf_sdb_64.c
CC crlf_sdb_64.o
GEn crlf32_sdb_64.c
CC crlf32_sdb_64.o
GEn crlf_1380.c
CC crlf_1380.o
GEn crlf_lamcu.c
CC crlf_lamcu.o
CC href.o
CC McIfges.o
CCLD id-new

make[1]: Leaving directory '/sources/binutils-2.45/build-id'
make[1]: Leaving directory '/sources/binutils-2.45/build-id'
make[2]: Leaving directory '/sources/binutils-2.45/build-id'
make[1]: Nothing to be done for 'all-target'.
make[1]: Leaving directory '/sources/binutils-2.45/build'
(if $chroot) root:/sources/binutils-2.45/build#
```

e) Ejecutamos el siguiente comando para probar los resultados

```
make -k check
```

```
(lfs chroot) root:/sources/binutils-2.45/build# make -k check
```

f) Obtenemos una lista de los tests fallidos

```
grep '^FAIL:' $(find -name '*.log')
```



## 15. GMP: suite de tests (make check)

Fecha: 5/01/2026   Páginas: 152

**Resumen:** Ejecutar la batería de pruebas del paquete para validar build/instalación.

**Comandos (tal como aparecen):**

```
make check 2>&1 | tee gmp-check-log
```

Captura de la página 152 del documento fuente.

- e) Probamos los resultados

```
make check 2>&1 | tee gmp-check-log
```

```
Making check in demos
make[2]: Entering directory '/sources/gmp-6.3.0/demos'
Making check in calc
make[3]: Entering directory '/sources/gmp-6.3.0/demos/calc'
make check-am
make[4]: Entering directory '/sources/gmp-6.3.0/demos/calc'
make[4]: Nothing to be done for 'check-am'.
make[4]: Leaving directory '/sources/gmp-6.3.0/demos/calc'
make[3]: Leaving directory '/sources/gmp-6.3.0/demos/calc'
Making check in expr
make[3]: Entering directory '/sources/gmp-6.3.0/demos/expr'
make[3]: Nothing to be done for 'check'.
make[3]: Leaving directory '/sources/gmp-6.3.0/demos/expr'
make[3]: Entering directory '/sources/gmp-6.3.0/demos'
make[3]: Nothing to be done for 'check-am'.
make[3]: Leaving directory '/sources/gmp-6.3.0/demos'
make[2]: Leaving directory '/sources/gmp-6.3.0/demos'
Making check in tune
make[2]: Entering directory '/sources/gmp-6.3.0/tune'
make[2]: Nothing to be done for 'check'.
make[2]: Leaving directory '/sources/gmp-6.3.0/tune'
Making check in doc
make[2]: Entering directory '/sources/gmp-6.3.0/doc'
make[2]: Nothing to be done for 'check'.
make[2]: Leaving directory '/sources/gmp-6.3.0/doc'
make[2]: Entering directory '/sources/gmp-6.3.0'
make[2]: Leaving directory '/sources/gmp-6.3.0'
make[1]: Leaving directory '/sources/gmp-6.3.0'
(Ifs chroot) root:/sources/gmp-6.3.0#
```

- f) Verificamos los resultados con el siguiente comando

```
awk '/# PASS:/{total+= $3} ; END{print total}' gmp-check-log
```

```
(Ifs chroot) root:/sources/gmp-6.3.0# awk '/# PASS:/{total+= $3} ; END{print total}' gmp-check-log
199
(Ifs chroot) root:/sources/gmp-6.3.0#
```

- g) Instalamos el paquete y su documentación

```
make install
```

```
make install-html
```

## 16. MPFR: suite de tests (make check)

**Fecha:** 5/01/2026   **Páginas:** 155

**Resumen:** Ejecutar la batería de pruebas del paquete para validar build/instalación. El documento indica que pasaron 198 tests.

**Comandos (tal como aparecen):**

`make check`

Captura de la página 155 del documento fuente.

```
(lfs chroot) root:/sources/mpfr-4.2.2# make html
```

```
make[1]: Entering directory '/sources/mpfr-4.2.2/tests'
make[1]: Nothing to be done for 'all'.
make[1]: Leaving directory '/sources/mpfr-4.2.2/tests'
Making all in tunc.
make[1]: Entering directory '/sources/mpfr-4.2.2/tunc'
make[1]: Nothing to be done for 'all'.
make[1]: Leaving directory '/sources/mpfr-4.2.2/tunc'
Making all in tools/bench.
make[1]: Entering directory '/sources/mpfr-4.2.2/tools/bench'
make[1]: Nothing to be done for 'all'.
make[1]: Leaving directory '/sources/mpfr-4.2.2/tools/bench'
make[1]: Entering directory '/sources/mpfr-4.2.2'
make[1]: Nothing to be done for 'all-am'.
make[1]: Leaving directory '/sources/mpfr-4.2.2'
(lfs chroot) root:/sources/mpfr-4.2.2# make html
Making html in doc.
make[1]: Entering directory '/sources/mpfr-4.2.2/doc'
if /bin/sh './sources/mpfr-4.2.2/missing' makeinfo --html --enable-encoding -I . \
 -o mpfr.html mpfr.texi: \
then \
 rm -f mpfr.html && no mpfr.html mpfr.html: \
else \
 rm -f mpfr.html: exit 1: \
fi
mpfr.texi: warning: %index should only appear at the beginning of a line
mpfr.texi:53: warning: no @index entry found for 'dir'
make[1]: Leaving directory '/sources/mpfr-4.2.2/doc'
Making html in src.
make[1]: Entering directory '/sources/mpfr-4.2.2/src'
make[1]: Nothing to be done for 'html'.
make[1]: Leaving directory '/sources/mpfr-4.2.2/src'
Making html in tests.
make[1]: Entering directory '/sources/mpfr-4.2.2/tests'
make[1]: Nothing to be done for 'html'.
make[1]: Leaving directory '/sources/mpfr-4.2.2/tests'
Making html in tunc.
make[1]: Entering directory '/sources/mpfr-4.2.2/tunc'
make[1]: Nothing to be done for 'html'.
make[1]: Leaving directory '/sources/mpfr-4.2.2/tunc'
Making html in tools/bench.
make[1]: Entering directory '/sources/mpfr-4.2.2/tools/bench'
make[1]: Nothing to be done for 'html'.
make[1]: Leaving directory '/sources/mpfr-4.2.2/tools/bench'
make[1]: Entering directory '/sources/mpfr-4.2.2'
make[1]: Nothing to be done for 'html-am'.
make[1]: Leaving directory '/sources/mpfr-4.2.2'
(lfs chroot) root:/sources/mpfr-4.2.2#
```

- d) Probamos los resultados y nos aseguramos que todos los 198 tests hayan pasado

make check

```
(lfs chroot) root:/sources/mpfr-4.2.2# make check
```

```

2017-08-01
mpfr-4.2.2
mpfr-4.2.2
mpfr-4.2.2
mpfr-4.2.2

make[1]: Entering directory '/sources/mpfr-4.2.2/tests'
make[1]: Leaving directory '/sources/mpfr-4.2.2/tests'
(lfs chroot) root:/sources/mpfr-4.2.2# make check
make[1]: Entering directory '/sources/mpfr-4.2.2'
make[1]: Nothing to be done for 'check'.
make[1]: Leaving directory '/sources/mpfr-4.2.2'
Making check in tools/bench.
make[1]: Entering directory '/sources/mpfr-4.2.2/tools/bench'
make[1]: Nothing to be done for 'check'.
make[1]: Leaving directory '/sources/mpfr-4.2.2/tools/bench'
make[1]: Entering directory '/sources/mpfr-4.2.2'
make[1]: Nothing to be done for 'check-am'.
make[1]: Leaving directory '/sources/mpfr-4.2.2'
(lfs chroot) root:/sources/mpfr-4.2.2#
```

## 17. MPC-1.3.1: suite de tests (make check)

Fecha: 5/01/2026   Páginas: 159

**Resumen:** Ejecutar la batería de pruebas del paquete para validar build/instalación.

**Comandos (tal como aparecen):**

`make check`

Captura de la página 159 del documento fuente.

```
(lfs chroot) root:/sources/mpc-1.3.1# make html
```

```
Making html in doc
make[1]: Entering directory '/sources/mpc-1.3.1/doc'
rm -rf mpc.htm
if /bin/sh '/sources/mpc-1.3.1/build-aux/missing' makeinfo --html -I . \
-o mpc.htm mpc.texi: \
then \
 rm -rf mpc.html && mv mpc.htm mpc.html: \
else \
 rm -rf mpc.htm: exit 1: \
fi
make[1]: Leaving directory '/sources/mpc-1.3.1/doc'
Making html in tools
make[1]: Entering directory '/sources/mpc-1.3.1/tools'
Making html in bench
make[2]: Entering directory '/sources/mpc-1.3.1/tools/bench'
make[2]: Nothing to be done for 'html'.
make[2]: Leaving directory '/sources/mpc-1.3.1/tools/bench'
Making html in mpcheck
make[2]: Entering directory '/sources/mpc-1.3.1/tools/mpcheck'
make[2]: Nothing to be done for 'html'.
make[2]: Leaving directory '/sources/mpc-1.3.1/tools/mpcheck'
make[2]: Entering directory '/sources/mpc-1.3.1/tools'
make[2]: Nothing to be done for 'html-am'.
make[2]: Leaving directory '/sources/mpc-1.3.1/tools'
make[1]: Leaving directory '/sources/mpc-1.3.1/tools'
make[1]: Entering directory '/sources/mpc-1.3.1'
make[1]: Nothing to be done for 'html-am'.
make[1]: Leaving directory '/sources/mpc-1.3.1'
(lfs chroot) root:/sources/mpc-1.3.1#
```

- d) Ejecutamos el siguiente comando para probar los resultados

make check

```
(lfs chroot) root:/sources/mpc-1.3.1# make check
```

```
PASS: testvec
PASS: testb
PASS: testfr
PASS: testai
PASS: testm
PASS: testmp
PASS: testn
PASS: testh
PASS: testdiv
PASS: testai_sub
PASS: test_serie
PASS: testexp1000
PASS: testomp

Test suite summary for mpc 1.3.1

TOTAL: 24
PASS: 24
SKIP: 0
FAIL: 0
XFAIL: 0
FAIL: 0
XFAIL: 0
ERROR: 0

make[2]: Leaving directory '/sources/mpc-1.3.1/tests'
make[1]: Leaving directory '/sources/mpc-1.3.1/tests'
Making check in doc
make[1]: Entering directory '/sources/mpc-1.3.1/doc'
make[1]: Nothing to be done for 'check'.
make[1]: Leaving directory '/sources/mpc-1.3.1/doc'
Making check in tools
make[1]: Entering directory '/sources/mpc-1.3.1/tools'
Making check in bench
make[2]: Entering directory '/sources/mpc-1.3.1/tools/bench'
make[2]: Nothing to be done for 'check'.
make[2]: Leaving directory '/sources/mpc-1.3.1/tools/bench'
Making check in mpcheck
make[2]: Entering directory '/sources/mpc-1.3.1/tools/mpcheck'
make[2]: Nothing to be done for 'check'.
make[2]: Leaving directory '/sources/mpc-1.3.1/tools/mpcheck'
make[2]: Entering directory '/sources/mpc-1.3.1/tools'
make[2]: Nothing to be done for 'check-am'.
make[2]: Leaving directory '/sources/mpc-1.3.1/tools'
make[1]: Leaving directory '/sources/mpc-1.3.1/tools'
make[1]: Entering directory '/sources/mpc-1.3.1'
make[1]: Leaving directory '/sources/mpc-1.3.1'
(lfs chroot) root:/sources/mpc-1.3.1#
```

- e) Instalamos el paquete y su documentación

make install

make install-html

## 18. Attr-2.5.2: suite de tests (make check)

Fecha: 5/01/2026 Páginas: 162

**Resumen:** Ejecutar la batería de pruebas del paquete para validar build/instalación. Se indica FAIL asociado a SELinux (seclabel/security.selinux).

**Comandos (tal como aparecen):**

```
make check
```

Captura de la página 162 del documento fuente.

- c) Compilamos el paquete

make

```
(lfs chroot) root:/sources/attr-2.5.2# make
Making all in po
make[1]: Entering directory '/sources/attr-2.5.2/po'
make[1]: Nothing to be done for 'all'.
make[1]: Leaving directory '/sources/attr-2.5.2/po'
make[1]: Entering directory '/sources/attr-2.5.2'
CC tools/attr.o
CC libattr/la-attr.cmp_action.lo
CC libattr/la-attr.cmp_check.lo
CC libattr/la-attr.cmp_fd.lo
CC libattr/la-attr.cmp_file.lo
CC libattr/la-libattr.lo
CC libattr/la-synccall.lo
CCLD libattr.la
CC libmisc/ahp_attr_attr.lo
CC libmisc/sect_list.lo
CC libmisc/quote.lo
CC libmisc/unquote.lo
CC libmisc/walk_tree.lo
CCLD libmisc.la
CCLD attr
CC tools/getattr.o
CCLD getattr
CC tools/setattr.o
CCLD setattr
make[1]: Leaving directory '/sources/attr-2.5.2'
(lfs chroot) root:/sources/attr-2.5.2#
```

- d) Ejecutamos el siguiente comando para probar los resultados

make check

```
(lfs chroot) root:/sources/attr-2.5.2# make check
make[1]: Leaving directory '/sources/attr-2.5.2/po'
make[1]: Entering directory '/sources/attr-2.5.2'
make check-TESTS
make[2]: Entering directory '/sources/attr-2.5.2'
make[3]: Entering directory '/sources/attr-2.5.2'
PASS: test-root-getattr.test
PASS: test-attr.test

Test suite summary for attr 2.5.2

TOTAL: 2
PASS: 1
SKIP: 0
XFAIL: 0
FAIL: 1
XPASS: 0
ERROR: 0

See ./test-suite.log
Please report to bug-attr@sourceware.org

make[3]: *** [Makefile:1395: test-suite.log] Error 1
make[2]: Leaving directory '/sources/attr-2.5.2'
make[1]: *** [Makefile:1401: check-TESTS] Error 2
make[1]: Leaving directory '/sources/attr-2.5.2'
make: *** [Makefile:1294: check-recursive] Error 1
(lfs chroot) root:/sources/attr-2.5.2#
```

- e) Instalamos el paquete

make install

```
1.2582 libattr.so: 1:))
libtool: install: /usr/bin/install -c .libs/libattr.lai /usr/lib/libattr.la
libtool: finish: PATH="/usr/bin:/usr/sbin:/sbin" ldconfig -n /usr/lib

Libraries have been installed in:
 /usr/lib

If you ever happen to want to link against installed libraries
in a given directory, LIBDIR, you must either use libtool, and
specify the full pathname of the library, or use the '-LLIBDIR'
flag during linking and do at least one of the following:
- add LIBDIR to the 'LD_LIBRARY_PATH' environment variable
 during execution
- add LIBDIR to the 'LD_RUN_PATH' environment variable
 during linking
- use the '-Wl,-rpath -Wl,LIBDIR' linker flag
- have your system administrator add LIBDIR to '/etc/ld.so.conf'

See any operating system documentation about shared libraries for
more information, such as the ld(1) and ld.so(8) manual pages.

/usr/bin/mkdir -p '/usr/bin'
/bin/sh ./libtool --mode=install /usr/bin/install -c attr getattr setattr '/usr/bin'
libtool: install: /usr/bin/install -c .libs/attr /usr/bin/attr
libtool: install: /usr/bin/install -c .libs/getattr /usr/bin/getattr
libtool: install: /usr/bin/install -c .libs/setattr /usr/bin/setattr
make[2]: Leaving directory '/sources/attr-2.5.2'
make[1]: Leaving directory '/sources/attr-2.5.2'
(lfs chroot) root:/sources/attr-2.5.2#
```



f) Eliminamos el directorio attr-2.5.2

```
rm -rf attr-2.5.2
```

```
(lfs chroot) root:/sources/attr-2.5.2# cd ..
(lfs chroot) root:/sources# rm -rf attr-2.5.2
(lfs chroot) root:/sources#
```

## Problemas encontrados

```

nshel[1]: Entering directory '/sources/str-2.5.2g'
nshel[2]: Entering directory '/sources/str-2.5.2'
make check-TESTS
nshel[2]: Entering directory '/sources/str-2.5.2'
nshel[3]: Entering directory '/sources/str-2.5.2'
nshel[4]: test/mem-mgmt-test
INFO: test/str-test
=====
Warning: memory for str 2.5.2
=====
TOTAL: Z
PASS: 1
SKIP: 0
FAIL: 0
XFAIL: 1
XPASS: 0
ERROR: 0
=====
see /test-suite.log
Please report to sci-dev@sourceware.org
=====
nshel[3]: *** [Makefile:1395: test-suite.log] Error 1
nshel[2]: Leaving directory '/sources/str-2.5.2'
nshel[2]: *** [Makefile:1663: check-TESTS] Error 2
nshel[2]: Leaving directory '/sources/str-2.5.2'
nshel[1]: *** [Makefile:1631: check-am] Error 2
nshel[1]: Leaving directory '/sources/str-2.5.2'
Error see [Makefile:1298: check-miscall Error 1
(If a chroot root/sources/str-2.5.2)

```

- El paquete `attr` compiló bien y los atributos extendidos funcionan (probaste `user.*` y `trusted.*`).
- El `make check` falló solo en `test/root/getfattr.test` porque tu entorno tiene SELinux/etiquetado activado (se ve por el montaje con `seclabel` y porque aparece `security.selinux=...` en la salida de `getfattr`).
- Ese atributo extra cambia la salida esperada del test, entonces el script lo marca como FAIL, aunque la funcionalidad real esté OK.
- Solución práctica: ignorar ese FAIL único, hacer `make install` y seguir con el libro.

5/01/2026 18:52

### 1. Instalación de Acl-2.3.2

a) Desempaquetamos el archivo

```
tar -xvf acl-2.3.2
```

```
(lfs chroot) root:/sources# tar -xvf acl-2.3.2.tar.xz
acl-2.3.2/acl/
acl-2.3.2/acl/TODO
acl-2.3.2/acl/CHANGELOG
acl-2.3.2/acl/Makemodule.aw
acl-2.3.2/acl/COPYING.LGPL
acl-2.3.2/acl/INSTALL
acl-2.3.2/acl/COPYING
acl-2.3.2/acl/libacl.txt
acl-2.3.2/acl/extensions.txt
acl-2.3.2/libacl/
acl-2.3.2/libacl/high_water_allocator.c
acl-2.3.2/libacl/sgsort.c
acl-2.3.2/libacl/sgsort.h
acl-2.3.2/libacl/Makemodule.aw
acl-2.3.2/libacl/sgsort.c
acl-2.3.2/libacl/sgsort.h
acl-2.3.2/libacl/walk_tree.c
acl-2.3.2/localized/
acl-2.3.2/libacl/posix/
acl-2.3.2/Makefile.in
acl-2.3.2/README
acl-2.3.2/include/Makemodule.aw
acl-2.3.2/include/walk_tree.h
acl-2.3.2/include/sgsort.h
acl-2.3.2/include/sgsort.h.in
acl-2.3.2/include/libacl.h
acl-2.3.2/include/acl.h
acl-2.3.2/include/acl_g.h
acl-2.3.2/include/acl_g.h.in
```

## 19. Acl-2.3.2: suite de tests (make check)

Fecha: 5/01/2026 Páginas: 165

**Resumen:** Ejecutar la batería de pruebas del paquete para validar build/instalación.

**Comandos (tal como aparecen):**

`make check`

Captura de la página 165 del documento fuente.

- make check

```

make[1]: Leaving directory '/sources/sc1-2.3.2'
make[1]: Entering directory '/sources/sc1-2.3.2'
make[1]: libtest_lookup_la
make[2]: Entering directory '/sources/sc1-2.3.2'
CC test/libtest_lookup_la-test_group.lo
CC test/libtest_lookup_la
make[2]: Leaving directory '/sources/sc1-2.3.2'
make check-TESTS
make[2]: Entering directory '/sources/sc1-2.3.2'
make[3]: Entering directory '/sources/sc1-2.3.2'
PASS: test/getfac1-lfs-test
FAIL: test/cp-test
PASS: test/getfac1-recursive-test
PASS: test/malformed-restore-test
PASS: test/getfac1-misc1-test
PASS: test/xbits-restore-test
SKIP: test/rootgetfac1-test
PASS: test/effs-filenamg-test
SKIP: test/restore-permissions-test
SKIP: test/restore-test
SKIP: test/rootgetfac1-test
PASS: test/getfac1-x-test
XPASS: test/mfs/mfsacl-test
PASS: test/wisc-test
XPASS: test/mfs/mfs-dir-test

Test suite summary for sc1-2.3.2
=====
TOTAL: 15
PASS: 9
SKIP: 4
XPASS: 2
FAIL: 0
XFAIL: 0
ERROR: 0
=====

rm -f test-suite.log
ln -s report to sc1-down000.org
=====
make[3]: *** [Makefile:2073: test-suite.log] Error 1
make[3]: Leaving directory '/sources/sc1-2.3.2'
make[2]: *** [Makefile:2401: check-TESTS] Error 2
make[2]: Leaving directory '/sources/sc1-2.3.2'
make[1]: *** [Makefile:2418: check-mel] Error 2
make[1]: Leaving directory '/sources/sc1-2.3.2'
make: *** [Makefile:1950: check-recursive] Error 1
(lfs chroot) root:/sources/sc1-2.3.2#

```

- ```
make install
```

[illegible]

20. Libxcrypt-4.4.38: suite de tests (make check)

Fecha: 5/01/2026 Páginas: 170

Resumen: Ejecutar la batería de pruebas del paquete para validar build/instalación.

Comandos (tal como aparecen):

`make check`

Captura de la página 170 del documento fuente.

- make check

```

9935: test/ke-encrypt
9935: test/ke-gost-encrypt
9935: test/ke-memdb
9935: test/ke-encrypt
9935: test/alg-dss
9935: test/alg-gost3411-2012
9935: test/alg-gost3411-2012-hmac
9935: test/alg-hmac-sha1
9935: test/alg-md4
9935: test/alg-md5
9935: test/alg-pkdf-hmac-sha256
9935: test/alg-sha1
9935: test/alg-sha256
9935: test/alg-sha512
9935: test/ke-sha256crypt
9935: test/ke-sha512crypt
9935: test/hdmnttting
9935: test/legnarrider
9935: test/ke-gcrypt
9935: test/compile-strong-align
9935: test/crypt-balangs
9935: test/checksalt
9935: test/openssl-horo
9935: test/openssl
9935: test/gensalt-metadate
9935: test/gensalt-nbush
9935: test/getrandom-fallback
9935: test/getrandom-interfaces
9935: test/crypt-gost-gcrypt
9935: test-preferred-method
9935: test-short-output
9935: test/openssl-char-salt
9935: test/gensalt
9935: test/alg-gcrypt
=====
test/ke-memdb for script 4.4.30
=====
# TOTOL: 43
# PASS: 0
# SKIP: 11
# FAIL: 0
# XFAIL: 0
# XFAIL: 0
=====
make[2]: Leaving directory '/usr/src/libcrypt-4.4.30'
make[1]: Leaving directory '/usr/src/libcrypt-4.4.30'
Makefile not removed.
Makefile not removed.

```

- ```
make install
```

[illegible]

## 21. GCC-15.2.0: suite de tests (make check)

Fecha: 6/01/2026 Páginas: 177, 178, 180, 181

**Resumen:** Ejecutar la batería de pruebas del paquete para validar build/instalación. Ejecutado como usuario no privilegiado (tester). Se genera un resumen de resultados con test\_summary.

**Comandos (tal como aparecen):**

```
su tester -c "PATH=$PATH make -k check"
../contrib/test_summary | grep -A7 Summ
echo 'int main(){}' | cc -x c - -v -Wl,--verbose &> dummy.log readelf -l a.out |
grep -E -o '/usr/lib.*S?crt[1in].*succeeded' dummy.log
grep -B4 '^ /usr/include' dummy.log
grep 'SEARCH.*usr/lib' dummy.log | sed 's|; |\n|g'
grep "/lib.*libc.so.6 " dummy.log
grep found dummy.log
rm -v a.out dummy.log
```

Captura de la página 177 del documento fuente.

make

[illegible]

```
(lfs chroot) root:/sources/gcc-15.2.0/build# ulimit -s -H unlimited
(lfs chroot) root:/sources/gcc-15.2.0/build#
```

```
sed -e 'cpython/d' -i ../gcc/testsuite/gcc.dg/plugin/plugin.exp
```

```
(lfs chroot) root:/sources/gcc-15.2.8/build# sed -e 'cpython/d' -i ../gcc/testsuite/gcc.dg/plugin/plugin.exp
(lfs chroot) root:/sources/gcc-15.2.8/build#
```

chown -R tester .

```
su tester -c "PATH=$PATH make -k check"
```

```
(lfs chroot) root:/sources/gcc-15.2.0/build# chown -R tester .
(lfs chroot) root:/sources/gcc-15.2.0/build# su tester -c "PATH=$PATH make -k -j4 check"
```

## 22. Sed-4.9: suite de tests (make check)

Fecha: 6/01/2026   Páginas: 186

**Resumen:** Ejecutar la batería de pruebas del paquete para validar build/instalación. Ejecutado como usuario no privilegiado (tester).

**Comandos (tal como aparecen):**

```
su tester -c "PATH=$PATH make check"
```

Captura de la página 186 del documento fuente.





## 23. Psmisc-23.7: suite de tests (make check)

Fecha: 6/01/2026   Páginas: 190

**Resumen:** Ejecutar la batería de pruebas del paquete para validar build/instalación.

**Comandos (tal como aparecen):**

`make check`

Captura de la página 190 del documento fuente.

- make check

```

Active configuration is s06,04-pc-lima-gsm

--- ping tests ---

Schedule of variations:
unix

Running target unix
Using /usr/share/doc/gnssm/benchmark/unix.ssg as board description file for target.
Using /usr/share/doc/gnssm/conf/gnssm.ssg as generic interface file for target.
Using /usr/src/gnssm-23.7/testsuite/conf/gnssm.ssg as link-and-target-specific interface file.
Running /usr/src/gnssm-23.7/testsuite/ping_test/ping.ssg ...

--- ping Summary ---

of expected passes: 2
/usr/src/gnssm-23.7/src/ping version 23.7

WARNING: Guide's find tool left file
Test run by root on Wed Oct 22 16:46:48 2025
Active configuration is s06,04-pc-lima-gsm

--- fuser tests ---

Schedule of variations:
unix

Running target unix
Using /usr/share/doc/gnssm/benchmark/unix.ssg as board description file for target.
Using /usr/share/doc/gnssm/conf/gnssm.ssg as generic interface file for target.
Using /usr/share/doc/gnssm-23.7/testsuite/conf/gnssm.ssg as link-and-target-specific interface file.
Running /usr/src/gnssm-23.7/testsuite/fuser_test/fuser.ssg ...

--- fuser Summary ---

of expected passes: 9
/usr/src/gnssm-23.7/src/fuser version 23.7

s06t[1]: Loading directory "/usr/src/gnssm-23.7/testsuite"
s06t[2]: Loading directory "/usr/src/gnssm-23.7/testsuite"
s06t[2]: Entering directory "/usr/src/gnssm-23.7"
s06t[2]: src/s06t_test
s06t[2]: Entering directory "/usr/src/gnssm-23.7"
s06t[1]: "src/s06t_test" is up to date.
s06t[3]: Loading directory "/usr/src/gnssm-23.7"
s06t[2]: Loading directory "/usr/src/gnssm-23.7"
s06t[1]: Loading directory "/usr/src/gnssm-23.7"
s06t[1]: (Ifs checked) root /usr/src/gnssm-23.7

```

- ```
make install
```

[illegible]

24. Gettext-0.26: suite de tests (make check)

Fecha: 7/01/2026 Páginas: 193

Resumen: Ejecutar la batería de pruebas del paquete para validar build/instalación.

Comandos (tal como aparecen):

`make check`

Captura de la página 193 del documento fuente.

- make check

```
# test-wait-for-dir.sh  
# test-wait-for-dns.sh  
# test-syslogtestf  
# test-ssping  
# test-verifyp.sh  
# test-netstat.sh
```

```
-----  
Testcase summary for get-test-tools & .sh
```

```
# TOTAL: 960  
# PASS: 780  
# SKIP: 0  
# FAIL: 0  
# XPASS: 0  
# XFAIL: 0
```

```
naked(7): Leaving directory "/sources/gettext-@.26/gettext-tools/gnulib-tests"  
naked(6): Leaving directory "/sources/gettext-@.26/gettext-tools/gnulib-tests"  
naked(5): Leaving directory "/sources/gettext-@.26/gettext-tools/gnulib-tests"  
naked(4): Leaving directory "/sources/gettext-@.26/gettext-tools/gnulib-tests"  
naked(3): Leaving directory "/sources/gettext-@.26/gettext-tools/gnulib-tests"  
Poking check to install tests  
naked(3): Entering directory "/sources-gettext-@.26/gettext-tools/install-tests"  
naked(3): Nothing to be done for "check"  
naked(3): Leaving directory "/sources-gettext-@.26/gettext-tools/install-tests"  
Poking check to examples  
naked(3): Entering directory "/sources-gettext-@.26/gettext-tools/examples"  
Poking check to po  
naked(4): Entering directory "/sources-gettext-@.26/gettext-tools/compiler/po"  
for "check"  
naked(4): Leaving directory "/sources-gettext-@.26/gettext-tools/compiler/po"  
naked(4): Entering directory "/sources-gettext-@.26/gettext-tools/compiler/"  
for "check-on"  
naked(4): Nothing to be done for "check-on"  
naked(4): Leaving directory "/sources-gettext-@.26/gettext-tools/compiler"  
naked(3): Leaving directory "/sources-gettext-@.26/gettext-tools/examples"  
Poking check to doc  
naked(3): Entering directory "/sources-gettext-@.26/gettext-tools/doc"  
for "check"  
naked(3): Leaving directory "/sources-gettext-@.26/gettext-tools/doc"  
naked(3): Entering directory "/sources-gettext-@.26/gettext-tools/  
Leaving directory "/sources-gettext-@.26/gettext-tools/  
Entering directory "/sources-gettext-@.26/  
Nothing to be done for "check-on"  
Leaving directory "/sources-gettext-@.26/  
Leaving directory "/sources-gettext-@.26/  
(If's checked) root="/sources-gettext-@.26"
```

- ```
make install
```

[illegible]

## 25. Bison-3.8.2: suite de tests (make check)

Fecha: 7/01/2026   Páginas: 196

**Resumen:** Ejecutar la batería de pruebas del paquete para validar build/instalación.

**Comandos (tal como aparecen):**

`make check`

Captura de la página 196 del documento fuente.

- make check

```

792: Duplicate user destructors for lookahead: glr2.cc ok
793: Corrupted semantic options if user action cuts parse: glr.c ok
794: No users destructors if stack 0 deleted: glr.cc ok
795: Incorrectly initialized location for empty right hand side in GLR: glr2.cc ok
796: Corrupted semantic options if user action cuts parse: glr.c ok
797: Undesirable destructors if user action cuts parse: glr.c ok
798: No users destructors if stack 0 deleted: glr2.cc ok
799: Undesirable destructors if user action cuts parse: glr.cc ok
800: Corrupted semantic options if user action cuts parse: glr2.cc ok
801: Leaked semantic values if user action cuts parse: glr.c ok
802: Leaked semantic values if user action cuts parse: glr.cc ok
803: Incorrect lookahead during deterministic GLR: glr.c ok
804: Undesirable destructors if user action cuts parse: glr2.cc ok
805: Incorrect lookahead during deterministic GLR: glr.c ok
806: Incorrect lookahead during deterministic GLR: glr.cc ok
807: Leaked semantic values if user action cuts parse: glr2.cc ok
808: Incorrect lookahead during nondeterministic GLR: glr.cc ok
809: Incorrect lookahead during deterministic GLR: glr2.cc ok
810: Leaked semantic values when reporting ambiguity: glr.c ok
811: Leaked semantic values when reporting ambiguity: glr.cc ok
812: Incorrect lookahead during nondeterministic GLR: glr2.cc ok
813: Leaked lookahead after nondeterministic parse syntax error: glr.c ok
814: Leaked lookahead after nondeterministic parse syntax error: glr.cc ok
815: Uninitialized location when reporting ambiguity: glr.c api pure ok
816: Leaked semantic values when reporting ambiguity: glr2.cc ok
817: Missed merge type warnings when LHS type is declared later: glr.c ok
818: Missed merge type warnings when LHS type is declared later: glr.cc ok
819: Missed merge type warnings when LHS type is declared later: glr2.cc ok
820: Uninitialized location when reporting ambiguity: glr.c ok
821: Ambiguity reports: glr.c ok
822: Leaked lookahead after nondeterministic parse syntax error: glr2.cc ok
823: Ambiguity reports: glr.c ok
824: Uninitialized location when reporting ambiguity: glr2.cc ok
825: Predicates: glr.c ok
826: Predicates: glr.cc ok
827: Ambiguity reports: glr2.cc ok
828: Predicates: glr2.cc ok
829:
830:
831:
832: Tests were successful.
833: 64 tests were skipped.
make(3): Leaving directory `./sources-atom-3.0.2'
make(3): Leaving directory `./sources-atom-3.0.2'
make(3): Leaving directory `./sources-atom-3.0.2'
make(3): Leaving directory `./sources-atom-3.0.2'

```

- ```
make install
```

[illegible]

26. Grep-312: suite de tests (make check)

Fecha: 7/01/2026 Páginas: 199

Resumen: Ejecutar la batería de pruebas del paquete para validar build/instalación.

Comandos (tal como aparecen):

`make check`

Captura de la página 199 del documento fuente.

- make

Ejecutamos el siguiente comando para probar los resultados

make check

```
(lfs chroot) root:/sources/grep-3.12# make check
PASS: test-usage1.sh
SKIP: test-c-list-files-git.sh
SKIP: test-c-list-files-cvs.sh
PASS: test-verify
PASS: test-version-etc.sh
PASS: test-wchar.h
PASS: test-wctomb.h
SKIP: test-wctomb-w32-2.sh
SKIP: test-wctomb-w32-3.sh
SKIP: test-wctomb-w32-4.sh
SKIP: test-wctomb-w32-5.sh
SKIP: test-wctomb-w32-6.sh
SKIP: test-wctomb-w32-7.sh
SKIP: test-wctomb-w32-8.sh
PASS: test-wctype.h
PASS: test-wctype
SKIP: test-windows-mutex-type
SKIP: test-windows-regex-type
SKIP: test-windows-timedatex-type
SKIP: test-windows-timedatex-type
PASS: test-wcschr
PASS: test-wcrtol-dle.sh
PASS: test-wcrtolmax.sh
PASS: test-verify.sh
PASS: test-year2038
PASS: test-wcrtol.sh
PASS: test-phread-oncc2
PASS: test-regex
=====
Test suite summary for GNU grep 3.12
=====
# TOTAL: 315
# PASS: 252
# SKIP: 63
# FAIL: 0
# XPASS: 0
# ERROR: 0
=====
make[1]: Leaving directory '/sources/grep-3.12/gnulib-tests'
make[4]: Leaving directory '/sources/grep-3.12/gnulib-tests'
make[3]: Leaving directory '/sources/grep-3.12/gnulib-tests'
make[2]: Leaving directory '/sources/grep-3.12/gnulib-tests'
make[1]: Leaving directory '/sources/grep-3.12/gnulib-tests'
make[1]: Entering directory '/sources/grep-3.12'
make[1]: Leaving directory '/sources/grep-3.12'
(lfs chroot) root:/sources/grep-3.12#
```

27. Bash-5.3: suite de tests (make tests)

Fecha: 7/01/2026 Páginas: 203

Resumen: Ejecutar la batería de pruebas del paquete para validar build/instalación.

Comandos (tal como aparecen):

spawn make tests

Captura de la página 203 del documento fuente.

28. Libtool-2.5.4: suite de tests (make check)

Fecha: 7/01/2026 Páginas: 207

Resumen: Ejecutar la batería de pruebas del paquete para validar build/instalación.

Comandos (tal como aparecen):

`make check`

Captura de la página 207 del documento fuente.

make check

```
(lfs chroot) root:/sources/libtool-2.5.4# make check_
```

[illegible]

e) Instalamos el paquete

```
make install
```

```
(lfs chroot) root:/sources/libtool-2.5.4# make install
```

[illegible]

f) Eliminamos una librería estática utilizada únicamente para las pruebas

```
rm -fv /usr/lib/libltdl.a
```

```
(lfs chroot) root:/sources/libtool-2.5.4# rm -fv /usr/lib/libltdl.a
removed '/usr/lib/libltdl.a'
(lfs chroot) root:/sources/libtool-2.5.4#
```

29. GDBM-1.26: suite de tests (make check)

Fecha: 7/01/2026 Páginas: 210, 212

Resumen: Ejecutar la batería de pruebas del paquete para validar build/instalación.

Comandos (tal como aparecen):

```
make check  
make check
```

Captura de la página 210 del documento fuente.

- d) Ejecutamos el siguiente comando para probar los resultados

make check

```
(lfs chroot) root:/sources/qdbm-1.26# make check
```

```
21) delete a record          ok
22) delete: non existing record      ok
23) delete: all records            ok

DB options
24) setopt                  ok
25) setopt: map options      ok
26) DBM_SETOPENSIZE/DBM_SETOPENSIZE ok

Classes
27) classnc: qdbm_open       ok
28) classnc: qdbm_reorganize ok
29) classnc: dbm_open        ok
30) classnc: dbm_open -creat ok

Synchronap
31) synchronap              ok

qdbmtool
32) Input from file         ok
33) Input from stdin        ok
34) Input from command line ok
35) Initialization file     ok
36) Pipe                    ok

Database formats
37) Database format conversion ok

Free space management
38) Coalesce                ok

## ----- ##
## Test results: ##
## ----- ##

all 38 tests were successful.
make[1]: Leaving directory '/sources/qdbm-1.26-tests'
make[2]: Leaving directory '/sources/qdbm-1.26-tests'
make[1]: Leaving directory '/sources/qdbm-1.26-tests'
make[1]: Entering directory '/sources/qdbm-1.26'
make[1]: Leaving directory '/sources/qdbm-1.26'
(lfs chroot) root:/sources/qdbm-1.26#
```

- e) Instalamos el paquete

make install

```
(lfs chroot) root:/sources/qdbm-1.26# make install
```

```
compiling... 2/ 2 ?
libtool: install: cd /usr/lib && ( ls -s -f libqdbm_compat.so.4.8.8 libqdbm_compat.so.11 ( rm -f libqdbm_compat.so.4.8.8 libqdbm_compat.so.11 ) )
libtool: install: /usr/bin/install -c libqdbm_compat.lai /usr/lib/libqdbm_compat.la
libtool: finish: PATH="/usr/bin:/usr/sbin:/sbin" ldconfig -s /usr/lib

Libraries have been installed in:
  /usr/lib

If you ever happen to want to link against installed libraries
in a given directory, LIBDIR, you must either use libtool, and
specify the full path of the library, or use the "-LLIBDIR"
flag during linking and do at least one of the following:
- add LIBDIR to the 'LD_LIBRARY_PATH' environment variable
  during execution
- add LIBDIR to the 'LD_RUN_PATH' environment variable
  during linking
- use the '-Wl,-rpath -Wl,LIBDIR' linker flag
- have your system administrator add LIBDIR to '/etc/ld.so.conf'

See any operating system documentation about shared libraries for
more information, such as the ld(1) and ld.so(8) manual pages.

make[2]: Leaving directory '/sources/qdbm-1.26/compat'
make[1]: Leaving directory '/sources/qdbm-1.26/compat'
Making install in tests
make[1]: Entering directory '/sources/qdbm-1.26-tests'
Making install in de.jpwn
make[2]: Entering directory '/sources/qdbm-1.26-tests/de.jpwn'
make[2]: Entering directory '/sources/qdbm-1.26-tests/de.jpwn'
make[2]: Nothing to be done for 'install-exec-am'.
make[2]: Nothing to be done for 'install-data-am'.
make[2]: Leaving directory '/sources/qdbm-1.26-tests/de.jpwn'
make[2]: Entering directory '/sources/qdbm-1.26-tests/de.jpwn'
make[2]: Nothing to be done for 'install-exec-am'.
make[2]: Nothing to be done for 'install-data-am'.
make[2]: Leaving directory '/sources/qdbm-1.26-tests/de.jpwn'
make[2]: Entering directory '/sources/qdbm-1.26-tests'
make[2]: Nothing to be done for 'install-exec-am'.
make[2]: Nothing to be done for 'install-data-am'.
make[2]: Leaving directory '/sources/qdbm-1.26-tests'
make[1]: Leaving directory '/sources/qdbm-1.26'
make[1]: Entering directory '/sources/qdbm-1.26'
make[1]: Leaving directory '/sources/qdbm-1.26'
(lfs chroot) root:/sources/qdbm-1.26#
```

30. GDBM-1.26: suite de tests (make check)

Fecha: 8/01/2026 **Páginas:** 215, 218

Resumen: Ejecutar la batería de pruebas del paquete para validar build/instalación.

Comandos (tal como aparecen):

```
make check  
make check
```

Captura de la página 215 del documento fuente.

- make check

e) Instalamos el paquete

```
(lfs chroot) root:/sources/expat-2.7.1# make install
make[1]: Leaving directory '/sources/expat-2.7.1/samples'
making install in tests
make[2]: Entering directory '/sources/expat-2.7.1/tests'
making install in .
make[2]: Entering directory '/sources/expat-2.7.1/tests'
make[2]: Entering directory '/sources/expat-2.7.1/tests'
make[2]: Nothing to be done for 'install-exec-am'.
make[2]: Nothing to be done for 'install-data-am'.
make[2]: Leaving directory '/sources/expat-2.7.1/tests'
make[2]: Leaving directory '/sources/expat-2.7.1/tests'
making install in benchmark
make[2]: Entering directory '/sources/expat-2.7.1/tests/benchmark'
make[2]: Entering directory '/sources/expat-2.7.1/tests/benchmark'
make[2]: Nothing to be done for 'install-exec-am'.
make[2]: Nothing to be done for 'install-data-am'.
make[2]: Leaving directory '/sources/expat-2.7.1/tests/benchmark'
make[2]: Leaving directory '/sources/expat-2.7.1/tests/benchmark'
make[1]: Leaving directory '/sources/expat-2.7.1/tests'
making install in src
make[2]: Entering directory '/sources/expat-2.7.1/src'
make[2]: Entering directory '/sources/expat-2.7.1/src'
make[2]: Nothing to be done for 'install-data-am'.
/usr/bin/mkdir -p '/usr/lib'
/bin/sh ./libtool --mode=install /usr/bin/install -c srcf '/usr/lib'
libtool: install: /usr/bin/install -c .libs/srcf /usr/bin/mkdir
make[2]: Leaving directory '/sources/expat-2.7.1/srcf'
make[1]: Leaving directory '/sources/expat-2.7.1/srcf'
making install in doc
make[2]: Entering directory '/sources/expat-2.7.1/doc'
make[2]: Entering directory '/sources/expat-2.7.1/doc'
make[2]: Nothing to be done for 'install-exec-am'.
/usr/bin/mkdir -p '/usr/share/xml/xml'
/usr/bin/install -c -s 644 srcf.1 '/usr/share/xml/xml'
make[2]: Leaving directory '/sources/expat-2.7.1/doc'
make[1]: Leaving directory '/sources/expat-2.7.1/doc'
make[1]: Entering directory '/sources/expat-2.7.1'
make[2]: Entering directory '/sources/expat-2.7.1'
make[2]: Nothing to be done for 'install-exec-am'.
/usr/bin/mkdir -p '/usr/lib/cmake/expat-2.7.1'
/usr/bin/mkdir -p '/usr/lib/cmake/expat-2.7.1'
/usr/bin/mkdir -p '/usr/lib/pkgconfig'
/usr/bin/install -c -s 644 cmake/autotools/expat.cmake '/usr/lib/cmake/expat-2.7.1'
/usr/bin/install -c -s 644 expat.pc '/usr/lib/pkgconfig'
/usr/bin/install -c -s 644 cmake/autotools/expat-config-version.cmake cmake/autotools/expat-macros.cmake cmake/expat-config.cmake '/usr/lib/cmake/expat-2.7.1'
make[2]: Leaving directory '/sources/expat-2.7.1'
make[1]: Leaving directory '/sources/expat-2.7.1'
(lfs chroot) root:/sources/expat-2.7.1#
```

31. Less-679: suite de tests (make check)

Fecha: 8/01/2026 Páginas: 221

Resumen: Ejecutar la batería de pruebas del paquete para validar build/instalación.

Comandos (tal como aparecen):

`make check`

Captura de la página 221 del documento fuente.

- make check

[illegible]

- ```
make install
```

```
rm -rf les-679
```

```
(lfs chroot) root:/sources/less-679# cd ..
(lfs chroot) root:/sources# rm -rf less-679
(lfs chroot) root:/sources#
```

## 32. Intltool-0.51.0: suite de tests (make check)

Fecha: 8/01/2026   Páginas: 229

**Resumen:** Ejecutar la batería de pruebas del paquete para validar build/instalación.

**Comandos (tal como aparecen):**

`make check`

Captura de la página 229 del documento fuente.

- d) Compilamos el paquete

make

```
(lfs chroot) root:/sources/intltool-0.51.0# make
ife chroot: root:/sources/intltool-0.51.0# make
Picking all to tests
make[1]: Entering directory '/sources/intltool-0.51.0/tests'
Picking all to tests
make[2]: Entering directory '/sources/intltool-0.51.0/tests/conv'
make[2]: Nothing to be done for 'all'.
make[2]: Leaving directory '/sources/intltool-0.51.0/tests/conv'
Picking all to results
make[2]: Entering directory '/sources/intltool-0.51.0/tests/results'
make[2]: Nothing to be done for 'all'.
make[2]: Leaving directory '/sources/intltool-0.51.0/tests/results'
make[2]: Entering directory '/sources/intltool-0.51.0/tests'
make[2]: Nothing to be done for 'all-ov'.
make[2]: Leaving directory '/sources/intltool-0.51.0/tests'
make[1]: Leaving directory '/sources/intltool-0.51.0/tests'
Picking all to doc
make[1]: Entering directory '/sources/intltool-0.51.0/doc'
make[1]: Nothing to be done for 'all'.
make[1]: Leaving directory '/sources/intltool-0.51.0/doc'
make[1]: Entering directory '/sources/intltool-0.51.0'
sed -e 's|@PREFIX@|/usr|g' -e 's|@LIBDIR@|/usr/lib|g' -e 's|@LIBTOOL_SUFFIX@|_lib|g' < intltool-extract.in > intltool-extract
sed -e 's|@PREFIX@|/usr|g' -e 's|@LIBDIR@|/usr/lib|g' -e 's|@LIBTOOL_SUFFIX@|_lib|g' < intltool-merge.in > intltool-merge
sed -e 's|@PREFIX@|/usr|g' -e 's|@LIBDIR@|/usr/lib|g' -e 's|@LIBTOOL_SUFFIX@|_lib|g' < intltool-update.in > intltool-update
sed -e 's|@PREFIX@|/usr|g' -e 's|@LIBDIR@|/usr/lib|g' -e 's|@LIBTOOL_SUFFIX@|_lib|g' < intltool-prepare.in > intltool-prepare
make[1]: Leaving directory '/sources/intltool-0.51.0'
ife chroot: root:/sources/intltool-0.51.0#
```

- e) Ejecutamos el siguiente comando para probar los resultados

make check

```
(lfs chroot) root:/sources/intltool-0.51.0# make check
make[2]: Nothing to be done for 'check'.
make[2]: Leaving directory '/sources/intltool-0.51.0/tests/conv'
make[2]: Entering directory '/sources/intltool-0.51.0/tests/results'
make[2]: Nothing to be done for 'check'.
make[2]: Leaving directory '/sources/intltool-0.51.0/tests/results'
make[2]: Entering directory '/sources/intltool-0.51.0/tests'
make check-TESTS
make[3]: Entering directory '/sources/intltool-0.51.0/tests'
make[4]: Entering directory '/sources/intltool-0.51.0/tests'
cp selftest.pl selftest.sh chmod -x selftest
chmod -x selftest
make[5]: Entering directory '/sources/intltool-0.51.0/tests'
Picking all to conv
make[6]: Entering directory '/sources/intltool-0.51.0/tests/conv'
make[6]: Nothing to be done for 'all'.
make[6]: Leaving directory '/sources/intltool-0.51.0/tests/conv'
Picking all to results
make[6]: Entering directory '/sources/intltool-0.51.0/tests/results'
make[6]: Nothing to be done for 'all'.
make[6]: Leaving directory '/sources/intltool-0.51.0/tests/results'
make[5]: Leaving directory '/sources/intltool-0.51.0/tests'
.....
Test suite summary for intltool 0.51.0
.....
TOTAL: 1
PASS: 1
SKIP: 0
XFAIL: 0
FAIL: 0
DEPEND: 0
ERROR: 0
.....
make[4]: Leaving directory '/sources/intltool-0.51.0/tests'
make[3]: Leaving directory '/sources/intltool-0.51.0/tests'
make[2]: Leaving directory '/sources/intltool-0.51.0'
Picking check to doc
make[2]: Entering directory '/sources/intltool-0.51.0/doc'
make[2]: Nothing to be done for 'check'.
make[2]: Leaving directory '/sources/intltool-0.51.0/doc'
make[2]: Entering directory '/sources/intltool-0.51.0'
make[2]: Nothing to be done for 'check-ov'.
make[2]: Leaving directory '/sources/intltool-0.51.0'
ife chroot: root:/sources/intltool-0.51.0#
```

- f) Instalamos el paquete

make install

install -v -Dm644 doc/I18N-HOWTO /usr/share/doc/intltool-0.51.0/I18N-HOWTO

### **33. Autoconf-2.72: suite de tests (make check)**

**Fecha:** 8/01/2026    **Páginas:** 232

**Resumen:** Ejecutar la batería de pruebas del paquete para validar build/instalación.

**Comandos (tal como aparecen):**

`make check`

Captura de la página 232 del documento fuente.



## 34. Automake-1.18.1: suite de tests (make check)

Fecha: 8/01/2026   Páginas: 234

**Resumen:** Ejecutar la batería de pruebas del paquete para validar build/instalación.

**Comandos (tal como aparecen):**

```
make -j$(($(nproc)>4?$(nproc):4)) check
```

Captura de la página 234 del documento fuente.



make

```
(lfs chroot) root:/sources/automake-1.18.1# make
GEN bin/aclocal
GEN bin/automake
GEN t/ax/shell-no-trail-bslash
GEN t/ax/cc-no-c-o
GEN doc/aclocal.1
GEN runtest
GEN doc/automake.1
GEN lib/Automake/Config.pm
GEN bin/aclocal-1.18
GEN t/ax/test-defs.sh
GEN bin/automake-1.18
GEN doc/aclocal-1.18.1
GEN doc/automake-1.18.1
(lfs chroot) root:/sources/automake-1.18.1#
```

d) Ejecutamos el siguiente comando para probar los resultados

```
make -j$(($(nproc)>4?$(nproc):4)) check
```

```
(chroot) root:/sources/automake-1.18.1# make -j$(($(nproc)>4?$(nproc):4)) check
INFO: C-tap without-number.sh
INFO: C-tap-with-and-without-number.sh
INFO: C-tap-unplanned.sh
make-header: skipped test: required program 'gnuc' not available
SKIP: C-test-header.sh
INFO: C-tap-fail-tests.sh
make-libc: skipped test: required program 'gnuc' not available
SKIP: C-test-libc.sh
make-libc-dispatch: skipped test: required program 'gnuc' not available
make-libc-spath: skipped test: required program 'gnuc' not available
SKIP: C-test-libc-spath.sh
make-wild: skipped test: required program 'gnuc' not available
SKIP: C-test-wild.sh
make-wild: skipped test: required program 'gnuc' not available
SKIP: C-test-wild2.sh
make-non-recursive-setup: skipped test: required program 'gnuc' not available
SKIP: C-test-non-recursive-setup.sh
m-pasallel: skipped test: required program 'gnuc' not available
SKIP: C-test-pasallel.sh
INFO: C-tap-recheck-tags.sh
make-per-target-flags: skipped test: required program 'gnuc' not available
SKIP: C-test-per-target-flags.sh
make-recursive-setup: skipped test: required program 'gnuc' not available
SKIP: C-test-recursive-setup.sh
make-sort: skipped test: required program 'gnuc' not available
SKIP: C-test-sort.sh
make-spath: skipped test: required program 'gnuc' not available
SKIP: C-test-spath.sh
INFO: C-tap-stdev-preif.ty 14 ~~~~~stdev-preif "g" ~~~~~stdev-stdev ordering: make check passes
INFO: C-tap-stdev-preif.ty 15 ~~~~~stdev-preif "g" ~~~~~stdev-stdev ordering: result counts are correct
INFO: C-tap-stdev-preif.ty 16 ~~~~~stdev-preif "g" ~~~~~stdev-stdev ordering: '1.' before 'stdev 1'
INFO: C-tap-stdev-preif.ty 17 ~~~~~stdev-preif "g" ~~~~~stdev-stdev ordering: 'stdev 1' before 'ak 1'
INFO: C-tap-stdev-preif.ty 18 ~~~~~stdev-preif "g" ~~~~~stdev-stdev ordering: 'ak 1' before 'stdev 2'

Instructions summary for GNU Automake 1.18.1

TOTAL: 2940
PASS: 2761
SKIP: 178
FAIL: 0
WARN: 0
ERROR: 0

make[2]: Leaving directory '/sources/automake-1.18.1'
make[1]: Leaving directory '/sources/automake-1.18.1'
(chroot) root:/sources/automake-1.18.1#
```

e) Instalamos el paquete

```
make install
```

## 35. Libelf: suite de tests (make check)

Fecha: 9/01/2026   Páginas: 241, 243

**Resumen:** Ejecutar la batería de pruebas del paquete para validar build/instalación.

**Comandos (tal como aparecen):**

```
make check
make check
```

Captura de la página 241 del documento fuente.

- d) Ejecutamos el siguiente comando para probar los resultados  
(dwarf\_srclang\_check y run-backtrace-native-core.sh son conocidos por fallar)

make check

```
(lfs chroot) root:/sources/elfutils-0.193# make check_
```

```
make[1]: Nothing to be done for 'all-am'.
(lfs chroot) root:/sources/elfutils-0.193# make check
Making check in config
sed -i 's:/usr/bin:/usr/sbin:' profile.fish
Making check in lib
make[1]: Nothing to be done for 'check'.
Making check in libelf
make[1]: Nothing to be done for 'check'.
Making check in libdw
make[1]: Nothing to be done for 'check'.
Making check in libdwelf
make[1]: Nothing to be done for 'check'.
Making check in libdwfl
make[1]: Nothing to be done for 'check'.
Making check in libdwfltest
make[1]: Nothing to be done for 'check'.
Making check in libdwfltest
make[1]: Nothing to be done for 'check'.
make check-cc
make dwarf_srclang_check
CC dwarf_srclang_check.o
make check-cc
make dwarf_srclang_check
make[1]: Nothing to be done for 'check'.
(lfs chroot) root:/sources/elfutils-0.193#
```

- e) Instalamos solamente Libelf

make -C libelf install

install -vm644 config/libelf.pc /usr/lib/pkgconfig

rm /usr/lib/libelf.a

```
(lfs chroot) root:/sources/elfutils-0.193# make -C libelf install
make: Entering directory '/sources/elfutils-0.193/libelf'
make[1]: Entering directory '/sources/elfutils-0.193/libelf'
/usr/bin/mkdir -p /usr/include
/usr/bin/mkdir -p /usr/include/elfutils
/usr/bin/mkdir -p /usr/lib
/usr/bin/install -c -m 644 libelf.h gelf.h alist.h /usr/include
/usr/bin/install -c -m 644 libelf.a /usr/lib
/usr/bin/install -c -m 644 elf-knowledge.h /usr/include/elfutils
(cd /usr/lib && ranlib libelf.a)
make[1]: Leaving directory '/sources/elfutils-0.193/libelf'
/bin/sh /sources/elfutils-0.193/config/install-sh -d /usr/lib
/usr/bin/install -c libelf.so /usr/lib/libelf-0.193.so
ln -fs libelf-0.193.so /usr/lib/libelf.so.1
make: Leaving directory '/sources/elfutils-0.193/libelf'
(lfs chroot) root:/sources/elfutils-0.193# install -vm644 config/libelf.pc /usr/lib/pkgconfig
'config/libelf.pc' -> '/usr/lib/pkgconfig/libelf.pc'
(lfs chroot) root:/sources/elfutils-0.193# rm /usr/lib/libelf.a
(lfs chroot) root:/sources/elfutils-0.193#
```

- f) Eliminamos el directorio

rm -rf elfutils-0.193

```
(lfs chroot) root:/sources/elfutils-0.193# cd ..
(lfs chroot) root:/sources# rm -rf elfutils-0.193
(lfs chroot) root:/sources#
```

## 36. Coreutils-9.7: suite de tests (make check)

Fecha: 9/01/2026 Páginas: 259

**Resumen:** Ejecutar la batería de pruebas del paquete para validar build/instalación. Ejecutado como usuario no privilegiado (tester). Incluye tests costosos (RUN\_EXPENSIVE\_TESTS=yes). Incluye tests que requieren root y/o división root/no-root.

**Comandos (tal como aparecen):**

```
make NON_ROOT_USERNAME=tester check-root
su tester -c "PATH=$PATH make -k RUN_EXPENSIVE_TESTS=yes check" \
```

Captura de la página 259 del documento fuente.

f) Ejecutamos el siguiente comando para ejecutar el conjunto de pruebas

[illegible]

g) Añadimos un grupo temporal y hacemos que el usuario tester sea parte del grupo

```
(lfs chroot) root:/sources/coreutils-9.7# groupadd -g 182 dummy -U tester
(lfs chroot) root:/sources/coreutils-9.7#
```

h) Arreglamos algunos permisos que permitirán a los usuarios no-root compilar y ejecutar las pruebas

```
(lfs chroot) root:/sources/coreutils-9.7# chown -R tester .
(lfs chroot) root:/sources/coreutils-9.7#
```

i) Ejecutamos las pruebas

## 37. Diffutils-3.12: suite de tests (make check)

Fecha: 9/01/2026   Páginas: 262

**Resumen:** Ejecutar la batería de pruebas del paquete para validar build/instalación.

**Comandos (tal como aparecen):**

`make check`

Captura de la página 262 del documento fuente.



## 38. Gawk-5.3.2: suite de tests (make check)

Fecha: 9/01/2026   Páginas: 265

**Resumen:** Ejecutar la batería de pruebas del paquete para validar build/instalación. Ejecutado como usuario no privilegiado (tester).

**Comandos (tal como aparecen):**

```
su tester -c "PATH=$PATH make check"
```

Captura de la página 265 del documento fuente.



- make

e) Ejecutamos el siguiente comando para probar los resultados

chown -R tester .

```
su tester -c "PATH=$PATH make check"
```

```
(ifls chroot) root:/sources/gawk-5.3.2# chown -R tester .
(ifls chroot) root:/sources/gawk-5.3.2# su tester -c "PATH=$PATH make check"
ifls field
ifls loc1
ifls loc2
ifls rmain1
----- Starting machine-specific tests -----
if any of these tests fail, don't worry too much.
double1
ifls loc2
ifls registers
double2
ifls registers2
ifls nan-torture
ifls rmain
ifls testset
ifls rnr
ifls loc2bcwp
ifls rvec
ifls read
ifls rmainval
ifls rsort
ifls loc3
ifls rsort
ifls rstosum
ifls replas
ifls rcorsum
ifls loc2bcwp
make[3]: Leaving directory '/sources/gawk-5.3.2-test'
----- Done with machine-specific tests -----
ifls dir
ifls chr2
ifls all
ifls dir
ifls mkdir_test
ifls mkdir_test
ifls file
ifls ifac
ifls cast
ifls vtabsum
ifls rcrcat
ifls testset
ifls
make[3]: Leaving directory '/sources/gawk-5.3.2-test'
make[3]: Leaving directory '/sources/gawk-5.3.2-test'
ALL TESTS PASSED
make[3]: Leaving directory '/sources/gawk-5.3.2-test'
make[2]: Leaving directory '/sources/gawk-5.3.2-test'
make[1]: Leaving directory '/sources/gawk-5.3.2'
(ifls chroot) root:/sources/gawk-5.3.2#
```

## 39. Findutils-4.10.0: suite de tests (make check)

Fecha: 10/01/2026 Páginas: 269

**Resumen:** Ejecutar la batería de pruebas del paquete para validar build/instalación. Ejecutado como usuario no privilegiado (tester).

**Comandos (tal como aparecen):**

```
su tester -c "PATH=$PATH make check"
```

Captura de la página 269 del documento fuente.

- ```
su tester -c "PATH=$PATH make check"
```

```
make install
```

```
rm -rf findutils-4.10.0
```

```
(lfs chroot) root:/sources/findutils-4.10.0# cd ..
(lfs chroot) root:/sources# rm -rf findutils-4.10.0
(lfs chroot) root:/sources#
```

40. Groff-1.23.0: suite de tests (make check)

Fecha: 10/01/2026 **Páginas:** 271

Resumen: Ejecutar la batería de pruebas del paquete para validar build/instalación.

Comandos (tal como aparecen):

`make check`

Captura de la página 271 del documento fuente.

make check

```
(lfs chroot) root:/sources/groff-1.23.0# make check
```

[illegible]

e) Instalamos el paquete

```
make install
```

```
(lfs chroot) root:/sources/groff-1.23.0# make install
```

[illegible]

f) Eliminamos el directorio groff-1.23.0

```
rm -rf groff-1.23.0
```

```
(lfs chroot) root:/sources/groff-1.23.0# cd ..
(lfs chroot) root:/sources# rm -rf groff-1.23.0
(lfs chroot) root:/sources#
```

41. Gzip-1.14: suite de tests (make check)

Fecha: 10/01/2026 Páginas: 275

Resumen: Ejecutar la batería de pruebas del paquete para validar build/instalación.

Comandos (tal como aparecen):

`make check`

Captura de la página 275 del documento fuente.

42. Make-4.4.1: suite de tests (make check)

Fecha: 10/01/2026 Páginas: 285

Resumen: Ejecutar la batería de pruebas del paquete para validar build/instalación. Ejecutado como usuario no privilegiado (tester).

Comandos (tal como aparecen):

```
su tester -c "PATH=$PATH make check"
```

Captura de la página 285 del documento fuente.

c) Compilamos el paquete

make

[illegible]

d) Ejecutamos el siguiente comando para probar los resultados

chown -R tester .

```
su tester -c "PATH=$PATH make check"
```

```
(Ifs chroot) root:/sources/make-4.4.1# chown -R tester .
(Ifs chroot) root:/sources/make-4.4.1# su tester -c "PATH=$PATH make check"
options/shuffle ..... ok (12 passed)
options/gnulib ..... ok (16 passed)
options/args-defined-variables ..... ok (4 passed)
targets/default ..... ok (1 passed)
targets-select-on-error ..... ok (2 passed)
targets/race ..... ok (1 passed)
targets/immediate ..... ok (10 passed)
targets-not-implemented ..... ok (12 passed)
targets-unhandled ..... ok (11 passed)
targets/pdov ..... ok (1 passed)
targets-pdovx ..... ok (9 passed)
targets-skip-build ..... ok (12 passed)
targets-silent ..... ok (3 passed)
targets-unit ..... ok (14 passed)
targets-test ..... ok (2 passed)
variables/cross ..... ok (1 passed)
variables/default-only ..... ok (5 passed)
variables-cross-flags ..... ok (13 passed)
variables-object-files ..... ok (5 passed)
variables/include-dirs ..... ok (6 passed)
variables/libpatterns ..... ok (2 passed)
variables-path ..... ok (1 passed)
variables/prog-defaults ..... ok (3 passed)
variables-prog-libs ..... ok (2 passed)
variables-prog-libs ..... ok (222 passed)
variables-prog-lib ..... ok (1 passed)
variables/prog-no-targets ..... ok (3 passed)
variables/path-list ..... ok (2 passed)
variables-shell ..... ok (8 passed)
variables-tomfile ..... ok (9 passed)
variables-defline ..... ok (17 passed)
variables/headers ..... ok (15 passed)
variables-special ..... ok (7 passed)
variables-speciate ..... ok (16 passed)
variables-special ..... ok (5 passed)
variables-underline ..... ok (3 passed)
lib/library ..... N/A

[43] Tests in 133 Categories Complete ... No Failures :-)
```

```
Regression PASSED: GNU Make 4.4.1 (GNU_64-bit-linux-gnu) built with gcc.
```

```
make[2]: Leaving directory '/sources/make-4.4.1'
make[1]: Leaving directory '/sources/make-4.4.1'
(Ifs chroot) root:/sources/make-4.4.1#
```

43. Patch-2.8: suite de tests (make check)

Fecha: 10/01/2026 Páginas: 288

Resumen: Ejecutar la batería de pruebas del paquete para validar build/instalación.

Comandos (tal como aparecen):

`make check`

Captura de la página 288 del documento fuente.

- d) Ejecutamos el siguiente comando para probar los resultados

make check

```
(lfs chroot) root:/sources/patch-2.8# make check
```

```
make[1]: ctrl-handling
make[1]: file-modes
make[1]: filename-choice
make[1]: git-binary-diff
make[1]: git-clamp
make[1]: garbage
make[1]: hardlinks
make[1]: global-reject-files
make[1]: ignore
make[1]: line-modes
make[1]: mingled-modes-short
make[1]: no-out-patch-tapes
make[1]: noout-context-format
make[1]: no-backup
make[1]: no-mailin-triggers-assert
make[1]: no-mode-change-git-diff
make[1]: noout-filename
make[1]: preserve-c-function-names
make[1]: quoted-filenames
SKIP: read-only-files
make[1]: regression-abc123456789
make[1]: preserve-mode-and-timestamp
make[1]: remove-reject-files
make[1]: remove-backup-files
make[1]: reject-format
make[1]: remove-directories
make[1]: success-blanks
make[1]: unsatisfiable-files
make[1]: uplinks
make[1]: merge
=====
Test suite summary for GNU patch 2.8
=====
# TOTAL: 49
# PASS: 45
# SKIP: 2
# FAIL: 0
# XFAIL: 0
# XFAIL: 0
# XFAIL: 0
=====
make[1]: Leaving directory '/sources/patch-2.8/tests'
make[1]: Leaving directory '/sources/patch-2.8/tests'
make[1]: Leaving directory '/sources/patch-2.8'
make[1]: Leaving directory '/sources/patch-2.8'
make[1]: Leaving directory '/sources/patch-2.8'
(lfs chroot) root:/sources/patch-2.8#
```

- e) Instalamos el paquete

make install

```
(lfs chroot) root:/sources/patch-2.8# make install
make[1]: Entering directory '/sources/patch-2.8'
Packing install in lib
make[2]: Entering directory '/sources/patch-2.8/lib'
make[1]: Leaving directory '/sources/patch-2.8/lib'
make[1]: Entering directory '/sources/patch-2.8/lib'
make[2]: Entering directory '/sources/patch-2.8/lib'
make[3]: Entering directory '/sources/patch-2.8/lib'
make[4]: Entering directory '/sources/patch-2.8/lib'
make[5]: Nothing to be done for 'install-etc-ss'.
make[5]: Leaving directory '/sources/patch-2.8/lib'
make[4]: Leaving directory '/sources/patch-2.8/lib'
make[3]: Leaving directory '/sources/patch-2.8/lib'
make[2]: Leaving directory '/sources/patch-2.8/lib'
Packing install in src
make[2]: Entering directory '/sources/patch-2.8/src'
make[3]: Entering directory '/sources/patch-2.8/src'
make[4]: Nothing to be done for 'install-data-ss'.
./usr/bin/mkdir -p ./usr/bin
./usr/bin/install -c patch ./usr/bin
make[3]: Leaving directory '/sources/patch-2.8/src'
make[2]: Leaving directory '/sources/patch-2.8/src'
Packing install in tests
make[2]: Entering directory '/sources/patch-2.8/tests'
make[3]: Entering directory '/sources/patch-2.8/tests'
make[4]: Nothing to be done for 'install-etc-ss'.
make[4]: Leaving directory '/sources/patch-2.8/tests'
make[3]: Leaving directory '/sources/patch-2.8/tests'
make[2]: Leaving directory '/sources/patch-2.8'
make[1]: Leaving directory '/sources/patch-2.8'
make[1]: Nothing to be done for 'install-etc-ss'.
./usr/bin/mkdir -p ./usr/share/man/man1
./usr/bin/install -c -m 644 'patch.man' ./usr/share/man/man1/patch.1
make[1]: Leaving directory '/sources/patch-2.8'
make[1]: Leaving directory '/sources/patch-2.8'
make[1]: Leaving directory '/sources/patch-2.8'
(lfs chroot) root:/sources/patch-2.8#
```

- f) Eliminamos el directorio patch-2.8

rm -rf patch-2.8

```
(lfs chroot) root:/sources/patch-2.8# cd ..
(lfs chroot) root:/sources# rm -rf patch-2.8
(lfs chroot) root:/sources#
```

44. Tar-1.35: suite de tests (make check)

Fecha: 10/01/2026 Páginas: 290

Resumen: Ejecutar la batería de pruebas del paquete para validar build/instalación.

Comandos (tal como aparecen):

`make check`

Captura de la página 290 del documento fuente.

c) Compilamos el paquete

make

```
(lfs chroot) root:/sources/tar-1.35# make_
```

```

n0ke[2]: Entering directory '/sources/tar-1.35/src'
CC      rot.o
CC      rot.o
n0ke[2]: Leaving directory '/sources/tar-1.35/src'
Poking all in src
n0ke[2]: Entering directory '/sources/tar-1.35/src'
CC      compare.o
CC      checkpoint.o
CC      create.o
CC      delete.o
CC      exit.o
CC      exclud.o
CC      extract.o
CC      header.o
CC      incrsn.o
CC      link.o
CC      map.o
CC      nls.o
CC      remove.o
CC      sparse.o
CC      suffix.o
CC      system.o
CC      tar.o
CC      transform.o
CC      unlink.o
CC      update.o
CC      utf8.o
CC      unware.o
CC      utime.o
CC      utime.o
CClib tar.o
n0ke[2]: Leaving directory '/sources/tar-1.35/src'
Poking all in scripts
n0ke[2]: Entering directory '/sources/tar-1.35/scripts'
n0ke[2]: Nothing to be done for 'all'.
n0ke[2]: Leaving directory '/sources/tar-1.35/scripts'
n0ke[2]: Entering directory '/sources/tar-1.35pe'
n0ke[2]: Nothing to be done for 'all'.
n0ke[2]: Leaving directory '/sources/tar-1.35pe'
Poking all in tests
n0ke[2]: Entering directory '/sources/tar-1.35tests'
n0ke[2]: Nothing to be done for 'all'.
n0ke[2]: Leaving directory '/sources/tar-1.35tests'
n0ke[2]: Entering directory '/sources/tar-1.35'
n0ke[2]: Leaving directory '/sources/tar-1.35'
n0ke[2]: Leaving directory '/sources/tar-1.35'
(life client) root:/sources/tar-1.35#

```

d) Ejecutamos el siguiente comando para probar los resultados (binary store/restore es un fallo conocido)

make check

```
(lfs chroot) root:/sources/tar-1.35# make check
```

```

227: settime: settime and read-only files ok
228: settime: settime and skip-old-files ok
229: cfs: user with +C ok
230: cfs: basic functionality ok
231: settime: basic store/restore skipped (tstfail.at.20)
232: acl: acl:nonempty special files & files skipped (tstfail.001.at.20)
233: capabilities: binary store/restore PhilB (capabilities.at.20)
234: tar --use-tap-level ok
235: tar --use-tap-level --show-transformed ok
236: tar --use-tap-level --transform ok
237: cfs: default 0634 ok
238: tar --use-tap-level --transform skipped (tstfail.at.26)
239: gltarall ok
240: gltarall skipped (tstfail.at.28)
241: multi-fail ok
242: multi-fail skipped (multi-fail.at.20)
243: xstar-big-2g ok
244: xstar-big-2g skipped (xstar-big-2g.at.20)
245: xstar-big-8g ok
246: xstar-big-8g skipped (xstar-big-8g.at.26)
247: pax-big-10g --use-tap-level restoring-permissions ok
248: pax-big-10g ok
249: gnu ok
250: gnu skipped (pax-big-10g.at.26)
251: Having sparse files bigger than 2^23 B ok

## ##
## Test results. ##
##
252 tests were run.
1 failed unexpectedly.
21 tests were skipped.
## ##
##

Please send 'test@tuxsuite.org' and all information you think might help:
To: Chay-Larkyou.org
Subject: [GNU tar 1.33] tuxsuite: 233 failed

You may investigate any problem if you're not able to do so, in which
case the test suite provides a good starting point. Its output may
be found here 'test@tuxsuite.org':

make[2]: *** [libarchive-2.9.7: check-local] Error 1
make[2]: Leaving directory '/sources/tar-1.35-test'
make[1]: *** [libarchive-2.9.7: check-local] Error 2
make[1]: Leaving directory '/sources/tar-1.35-test'
make: *** [libarchive-2.9.7: check-local] Error 1
(Ifs check) root:/sources/tar-1.35


```

e) Instalamos el paquete

45. Texinfo-7.2: suite de tests (make check)

Fecha: 10/01/2026 Páginas: 293

Resumen: Ejecutar la batería de pruebas del paquete para validar build/instalación.

Comandos (tal como aparecen):

`make check`

Captura de la página 293 del documento fuente.

- d) Compilamos el paquete

make

```
(lfs chroot) root:/sources/texinfo-7.2# make
fi: N
rm -rf $backdir; exit 0;
restore: AS backdir:"." AS N
rm -rf $backdir AS mkdir $backdir AS N
if TESTINFO_DEV_SOURCE=1 top_srcdir="." top_builddir="." /usr/bin/perl ./tp/test2ang --version >/dev/null 2>&1; then N
  for f in tex2ang_api.info tex2ang_api.info-10-91 tex2ang_api.info-10-910-91 tex2ang_api.info-110-91 tex2ang_api.info-910-91; do N
    if test -f $f; then mv $f $backdir; restore-mo else : fi; N
  done: N
else : fi AS N
if TESTINFO_DEV_SOURCE=1 top_srcdir="." top_builddir="." /usr/bin/perl ./tp/test2ang --c INFO_SPECIAL_CHARS_WARNING=0 -1 . N
  > tex2ang_api.info 'test -f 'tex2ang_api.texi' || echo './'tex2ang_api.texi: N
then N
  ec=0: N
else N
  ec=0? : N
  restore $backdir="echo './tex2ang_api.info' 1 and 'all'/'b011': N
fi: N
rm -rf $backdir; exit 0;
restore: AS backdir:"." AS N
rm -rf $backdir AS mkdir $backdir AS N
if TESTINFO_DEV_SOURCE=1 top_srcdir="." top_builddir="." /usr/bin/perl ./tp/test2ang --version >/dev/null 2>&1; then N
  for f in texinfo.info texinfo.info-10-91 texinfo.info-10-910-91 texinfo.info-110-91 texinfo.info-910-91; do N
    if test -f $f; then mv $f $backdir; restore-mo else : fi; N
  done: N
else : fi AS N
if TESTINFO_DEV_SOURCE=1 top_srcdir="." top_builddir="." /usr/bin/perl ./tp/test2ang --c INFO_SPECIAL_CHARS_WARNING=0 -1 . N
  > texinfo.info 'test -f 'texinfo.texi' || echo './'texinfo.texi: N
then N
  ec=0: N
else N
  ec=0? : N
  restore $backdir="echo './texinfo.info' 1 and 'all'/'b011': N
fi: N
rm -rf $backdir; exit 0;
make[1]: Leaving directory '/sources/texinfo-7.2/doc'
make[2]: Leaving directory '/sources/texinfo-7.2/doc'
Packing all in man
make[2]: Entering directory '/sources/texinfo-7.2/man'
make[2]: Nothing to be done for 'all'.
make[2]: Leaving directory '/sources/texinfo-7.2/man'
Packing all in js
make[2]: Entering directory '/sources/texinfo-7.2/js'
make[2]: Nothing to be done for 'all'.
make[2]: Leaving directory '/sources/texinfo-7.2/js'
make[2]: Entering directory '/sources/texinfo-7.2'
make[2]: Leaving directory '/sources/texinfo-7.2'
make[1]: Leaving directory '/sources/texinfo-7.2'
(lfs chroot) root:/sources/texinfo-7.2#
```

- e) Ejecutamos el siguiente comando para ejecutar los resultados

make check

```
(lfs chroot) root:/sources/texinfo-7.2# make check
make[2]: Entering directory '/sources/texinfo-7.2/util'
make check-TGTS
make[3]: Entering directory '/sources/texinfo-7.2/util'
make[4]: Entering directory '/sources/texinfo-7.2/util'
GMS: tests-texinfo_36.powershell.sh
-----
Test suite summary for GNU Texinfo 7.2
-----
# TOTAL: 1
# PASS: 1
# SKIP: 0
# XFAIL: 0
# FAIL: 0
# XFAILS: 0
# ERROR: 0
-----
make[4]: Leaving directory '/sources/texinfo-7.2/util'
make[3]: Leaving directory '/sources/texinfo-7.2/util'
make[2]: Leaving directory '/sources/texinfo-7.2/util'
Packing check in doc
make[2]: Entering directory '/sources/texinfo-7.2/doc'
Packing check in tp_api
make[3]: Entering directory '/sources/texinfo-7.2/doc/tp_api'
make check-an
make[4]: Entering directory '/sources/texinfo-7.2/doc/tp_api'
make[4]: Nothing to be done for 'check-an'
make[4]: Leaving directory '/sources/texinfo-7.2/doc/tp_api'
make[3]: Leaving directory '/sources/texinfo-7.2/doc/tp_api'
Packing check in refcard
make[3]: Entering directory '/sources/texinfo-7.2/doc/refcard'
make[3]: Nothing to be done for 'check'
make[3]: Leaving directory '/sources/texinfo-7.2/doc/refcard'
make[3]: Entering directory '/sources/texinfo-7.2/doc'
make[3]: Nothing to be done for 'check-an'
make[3]: Leaving directory '/sources/texinfo-7.2/doc'
make[2]: Leaving directory '/sources/texinfo-7.2/doc'
Packing check in man
make[2]: Entering directory '/sources/texinfo-7.2/man'
make[2]: Nothing to be done for 'check'
make[2]: Leaving directory '/sources/texinfo-7.2/man'
Packing check in js
make[2]: Entering directory '/sources/texinfo-7.2/js'
make[2]: Nothing to be done for 'check'
make[2]: Leaving directory '/sources/texinfo-7.2/js'
make[2]: Entering directory '/sources/texinfo-7.2'
make[2]: Leaving directory '/sources/texinfo-7.2'
make[1]: Leaving directory '/sources/texinfo-7.2'
(lfs chroot) root:/sources/texinfo-7.2#
```

46. Man-DB-2.13.1: suite de tests (make check)

Fecha: 11/01/2026 Páginas: 309

Resumen: Ejecutar la batería de pruebas del paquete para validar build/instalación.

Comandos (tal como aparecen):

`make check`

Captura de la página 309 del documento fuente.

- c) Compilamos el paquete

make

[illegible]

- d) Ejecutamos el siguiente comando para probar los resultados

make check

```
(Ifs chroot) root:/sources/man-db-2.13.1# make check_
```

```
index[3]: Loading directory '/sources/man-db-2.13.1/man/1/'
index[2]: Loading directory '/sources/man-db-2.13.1/man/1/'
index[2]: Entering directory '/sources/man-db-2.13.1/man/'
make check TESTS
index[3]: Entering directory '/sources/man-db-2.13.1/man/'
index[4]: Entering directory '/sources/man-db-2.13.1/man/'
INFO: multi/argpar.1
multi-man-recurs.1
INFO: multi/argpar.1
multi-man.1
multi-man-misc.1
multi-man-walk.1
multi-subst.1
INFO: multi/range.1
multi-man-walk.5
INFO: multi/man-walk.5
multi-man-walk.8
INFO: multi-man-walk.8
INFO: multi-man-walk.8
-----
Detailed summary for man-db-2.13.1
# TOTAL: 12
# PASS: 12
# SKIP: 0
# FAIL: 0
# XFAIL: 0
# ERROR: 0
index[4]: Loading directory '/sources/man-db-2.13.1/man/'
index[3]: Loading directory '/sources/man-db-2.13.1/man/'
index[2]: Loading directory '/sources/man-db-2.13.1/man/'
index[1]: Loading directory '/sources/man-db-2.13.1/man/'
Poling check in normal
index[3]: Entering directory '/sources/man-db-2.13.1/man/1/'
index[2]: Nothing to be done for 'check'.
index[1]: Loading directory '/sources/man-db-2.13.1/man/1/'
Poling check in ps
index[3]: Entering directory '/sources/man-db-2.13.1/man/'
index[2]: Nothing to be done for 'check'.
index[1]: Loading directory '/sources/man-db-2.13.1/man/'
Poling check in tman
index[3]: Entering directory '/sources/man-db-2.13.1/tman/'
index[2]: Nothing to be done for 'check'.
index[1]: Loading directory '/sources/man-db-2.13.1/tman/'
index[3]: Entering directory '/sources/man-db-2.13.1/'
index[2]: Loading directory '/sources/man-db-2.13.1/'
index[1]: Loading directory '/sources/man-db-2.13.1/'
```

- e) Instalamos el paquete

```
make install
```

47. Procps-ng-4.0.5: suite de tests (make check)

Fecha: 11/01/2026 Páginas: 312

Resumen: Ejecutar la batería de pruebas del paquete para validar build/instalación. Ejecutado como usuario no privilegiado (tester).

Comandos (tal como aparecen):

```
su tester -c "PATH=$PATH make check"
```

Captura de la página 312 del documento fuente.

- ```
chown -R tester .
su tester -c "PATH=$PATH make check"
```

e) Instalamos el paquete

[illegible]

- ```
rm -rf procps-ng-4.0.5
```

```
(lfs chroot) root:/sources# rm -rf procps-ng-4.0.5
(lfs chroot) root:/sources#
```

48. Util-linux-2.41.1: suite de tests (make check)

Fecha: 11/01/2026 **Páginas:** 314

Resumen: Ejecutar la batería de pruebas del paquete para validar build/instalación. Ejecutado como usuario no privilegiado (tester).

Comandos (tal como aparecen):

```
su tester -c "make -k check"
```

Captura de la página 314 del documento fuente.

49. E2fsprogs-1.47.3: suite de tests (make check)

Fecha: 11/01/2026 Páginas: 317

Resumen: Ejecutar la batería de pruebas del paquete para validar build/instalación.

Comandos (tal como aparecen):

`make check`

Captura de la página 317 del documento fuente.

d) Compilamos el paquete

make

[illegible]

e) Ejecutamos el siguiente comando para probar los resultados (m assume storage_prezeroed es un fallo conocido)

make check

```
(lfs chroot) root:/sources/e2fssprogs-1.47.3/build# make check
./project_0off: Attributable project using time2fs: ok
./project_3m: enable project using time2fs -q option: ok
./quota_0off: Attributable quota using time2fs: -q option: ok
./quota_2off: Attributable quota using time2fs: ok
./quota_hm: enable quota using time2fs: ok
./quota_off: all several quotas types using time2fs and check computed mgroup: ok
./util by rw remove miscit by shipped for Linux
./replay_and_opt: recover journal and clear features: ok
./util subdirectory: debug's write creation file in subdirectory: ok
./xsource_in: source I/O in unix io: ok
./compand_bad_replayck: e2fsd with meta2+time2fs+reintime2fs+e2fsck -: ok
./compand_replayck: e2fsd with meta2+time2fs+reintime2fs+e2fsck -: ok
./corrupt_bib_kcm: corrupt e2fsd block data: ok
./corrupt_bib_kcm_force: force replay of corrupt e2fsd block data: ok
./corrupt_md_kcm: corrupt e2fsd header: ok
./corrupt_mjg_kcm: corrupt e2fsd key data: ok
./debug's_opt: corrupt with debug's -: ok
./dryrun: e2fsd dry run: ok
./direct_io: direct I/O in unix io: ok
./e2fsck_opt: e2fsd with e2fsck -: ok
./current: e2fsd a failed command: ok
./force: e2fsd force: ok
./force_dryrun: force dry-run replay of corrupt e2fsd block data: ok
./meta2: e2fsd with meta2: ok
./incomplete: e2fsd with incomplete undo file: ok
./meta2_opt: e2fsd with meta2 -: ok
./meta2_opt_offset: e2fsd with meta2 -: and non-SZ-aligned bdev sizes: ok
./set_undo: e2fsd a new-undo file: ok
./meta2_opt_offset: e2fsd with meta2 with offset option: ok
./offset: e2fsd with the offset option (-o offset): ok
./metafile_bad: check that we can't append a bad undo file: ok
./reintime2fs_opt: e2fsd with reintime2fs -: ok
./reintime2fs_minmax_metafile_convert_fr: 64bit.minmax and revert undo file: ok
./revert_all_metafile: convert 64bit.minmax and revert undo file: ok
./time2fs: e2fsd with time2fs: ok
./time2fs_opt: e2fsd with time2fs -: ok
./undo_undo: undo e2fsd: ok
./revert_upgrade_to_64bitminmax: convert 64bit.minmax and revert both: ok
./writing_test_scripts
./stray_fr: e2fsd on the wrong fr: ok
./ung_lsm: enable lsm using time2fs: ok
./ung_2off: Attributable lsm using time2fs: ok
309 tests succeeded / 1 tests failed
Tests failed: a missing strategy perceived
make[1]: *** [Makefile:803: test_post] Error 1
make[1]: Leaving directory '/sources/e2fssprogs-1.47.3/build-tests'
make[1]: *** [Makefile:830: check_recursion] Error 1
(lfs chroot) root:/sources/e2fssprogs-1.47.3/build#
```

50. OpenSSH: tests y validaciones de servicio

Fecha: 14/01/2026 **Páginas:** 351, 353

Resumen: Ejecutar tests del paquete y verificar configuración/estado del servicio SSH. Validación sintáctica de sshd_config (sshd -t). Verificación de estado del servicio con systemctl.

Comandos (tal como aparecen):

```
make -j1 tests
systemctl status sshd --no-pager
sshd -t -f /etc/ssh/sshd_config
```

Captura de la página 351 del documento fuente.

- d) Instalamos OpenSSH ejecutando los siguientes comandos

```
./configure --prefix=/usr \
--sysconfdir=/etc/ssh \
--with-privsep-path=/var/lib/ssh \
--with-default-path=/usr/bin \
--with-superuser-path=/usr/sbin:/usr/bin \
--with-pid-dir=/run &&
```

make

```
-bash-5.3# ./configure --prefix=/usr \
> --sysconfdir=/etc/ssh \
> --with-privsep-path=/var/lib/ssh \
> --with-default-path=/usr/bin \
> --with-superuser-path=/usr/sbin:/usr/bin \
> --with-pid-dir=/run &&
> make
OGRAM="/usr/bin/ssh" -D_PATH_SSH_ASKPASS_DEFAULT="/usr/libexec/ssh-askpass"
-D_PATH_SFTP_SERVER="/usr/libexec/sftp-server" -D_PATH_SSH_KEY_SIGN="/usr/lib
exec/ssh-keysign" -D_PATH_SSHD_SESSION="/usr/libexec/sshd-session" -D_PATH_SS
HD_AUTH="/usr/libexec/sshd-auth" -D_PATH_SSH_PKCS11_HELPER="/usr/libexec/ssh-
pkcs11-helper" -D_PATH_SSH_SK_HELPER="/usr/libexec/ssh-sk-helper" -D_PATH_SSH
_PIDDIR="/run" -D_PATH_PRIVSEP_CHROOT_DIR="/var/lib/ssh" -DHAVE_CONFIG_H -c
ssh-sk.c -o ssh-sk.o
cc -g -O2 -pipe -Wno-error=format-truncation -Wall -Wextra -Wpointer-arith -Wuni
initialized -Wsign-compare -Wformat-security -Wsizeof-pointer-memaccess -Wno-poin
ter-sign -Wno-unused-parameter -Wno-unused-result -Wimplicit-fallthrough -Wmisle
ading-indentation -fno-strict-aliasing -D_FORTIFY_SOURCE=2 -ftrapv -fzero-call-u
sed-regs=used -ftrivial-auto-var-init=zero -fno-builtin-memset -fstack-protector
-strong -fPIE -I. -I. -D_XOPEN_SOURCE=600 -D_BSD_SOURCE -D_DEFAULT_SOURCE -D_
GNU_SOURCE -DOPENSSL_API_COMPAT=0x10100000L -DSSHDIR="/etc/ssh" -D_PATH_SSH_PR
OGRAM="/usr/bin/ssh" -D_PATH_SSH_ASKPASS_DEFAULT="/usr/libexec/ssh-askpass"
-D_PATH_SFTP_SERVER="/usr/libexec/sftp-server" -D_PATH_SSH_KEY_SIGN="/usr/lib
exec/ssh-keysign" -D_PATH_SSHD_SESSION="/usr/libexec/sshd-session" -D_PATH_SS
HD_AUTH="/usr/libexec/sshd-auth" -D_PATH_SSH_PKCS11_HELPER="/usr/libexec/ssh-
pkcs11-helper" -D_PATH_SSH_SK_HELPER="/usr/libexec/ssh-sk-helper" -D_PATH_SSH
_PIDDIR="/run" -D_PATH_PRIVSEP_CHROOT_DIR="/var/lib/ssh" -DHAVE_CONFIG_H -c
sk-usbhid.c -o sk-usbhid.o
cc -o ssh-sk-helper ssh-sk-helper.o ssh-sk.o sk-usbhid.o -L. -lopenbsd-compat/
-Wl,-z,relro -Wl,-z,now -Wl,-z,noexecstack -fstack-protector-strong -pie -lssh
-llopenbsd-compat -lssh -lopenbsd-compat -lcrypto -lz
-bash-5.3# _
```

- e) Ejecutamos el siguiente comando para probar los resultados

make -j1 tests